NOT MEASUREMENT SENSITIVE

MIL-L-11484/52D
9 June 1992
SUPERSEDING
MIL-L-11484/52C
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, RETIRED PERSONNEL, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Gilding Metal

DASH NO:
-1: Under 30 Years Service (Gold)
-2: 30 Years Service or Over (Silver)

DIMENSIONS:
DIAMETER: 19/32 inch (1.51 cm) (REF)
THICKNESS (At edge): 0.048 inch ± .005 inch (0.122 cm ± 0.012 cm)

FINISH:
-1: Hard Enameled, Dull Black Lacquered, Gold Plated, Matte Finish, Highlighted
-2: Hard Enameled, Dull Black Lacquered, Nickel Plated, Mirror-like Polished

NOTES:
1. Enameled or lacquered areas shall be as indicated.

2. White enamel shall conform to TIOH Color Chip No. 28.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T16:21Z
Check the source to verify that this is the current version before use.

3. Black lacquer shall approximate TIOH Color Chip No. 26.

4. Enamel and lacquer colors shall match the enamel and lacquer colors of the standard sample.

5. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85 and incorporate an ultraviolet inhibitor.

6. The term (REF) refers to measurements taken from the Government furnished hub or die.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0671)

Source: https://assist.dla.mil -- Downloaded: 202640-17T16:21Z
Check the source to verify that this is the current version before use.