MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M752A1 PARTS FOR

This Amendment forms a part of Military Specification MIL-C-48396A (AR), dated 30 June 1986, and is approved for use by the U.S. Army Armament,Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, Change "M853" to "M853A1"

2.1.1, Add "MIL-STD-810 Environmental Test Methods"

PAGE 2

3.2, Add the following paragraph:

"3.2.1 Corrosion resistance (salt spray). Parts selected for the salt spray test shall show no evidence of pitting or mottling when tested in accordance with 4.5.2."

PAGE 9

4.4.2.2, Under Major category, add the following:

"129 Salt spray test ... (a) ...3.2.1 ... Visual/4.5.2

Note (a) See sampling plans described in paragraph 4.4.3.2"

PAGE 13

4.4.2.5, Under Major category, add the following:

"114 Salt spray test ... (a) ... 3.2.1 ... Visual/4.5.2

Note (a) See sampling plans described in 4.4.3.2"

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:24Z
Check the source to verify that this is the currentversion before use.

4.4.3, Add the following paragraph:

"4.4.3.2 Salt spray test (3.2.1)

4.4.3.2.1 Sampling plan. Each batch of parts anodized at the same time with the same equipment shall be considered as an anodizing lot. For the first three (3) batches, the sampling plan for this test shall be in accordance with MIL-STD-105, Table IIA, inspection level II at AQL of 0.25%. Successive lots shall be sampled as above except that level I shall apply. If a continuous anodizing process is used, the engineering activity shall provide an alternate sampling plan after details of the process are provided by the contractor. The test shall be performed as specified in 4.5.2."

4.5, Add the following paragraph:

"4.5.2 Salt spray test. Samples selected shall be tested using equipment and procedures in accordance with MIL-STD-810, Method 509.2, Salt Fog. Parts shall be tested with the black powder pellet end up and the pellet cavity or contact surface inclined approximately six degrees from the vertical in fixturing which does not obstruct the longitudinal flashole. Parts shall be tested for 336 hours minimum. After testing, parts shall be rinsed, dried and examined for evidence of pitting or mottling of the finish. Particular attention shall be paid to the black powder pellet cavity inside the body. The technique used to inspect the cavity must be capable of thoroughly inspecting all surfaces of the cavity (face, walls, inside and outside corners), otherwise the body shall be transversely sectioned approximately 1.75 inches from the front face in order to facilitate visual inspection. The cutting tool (if used) must not remove any part of the pellet cavity. One or more pits or mottling shall be cause for rejection of all anodized parts represented by the sample. Parts subjected to salt shall not be returned to the lot."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A970)

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:24Z
Check the source to verify that this is the current version before use.