MILITARY SPECIFICATION

CHARGE ASSEMBLY FOR M207E5 OR M207E6 WARHEADS
INERT PARTS, FOR

This Amendment forms a part of Military Specification MIL-C-48670 (AR), dated 21 March 1986 and is approved for use within U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

In the specification wherever "M207E5" appears add "or M207E6".

PAGES 7 & 8

Delete 4.4.2.1 in its entirety and substitute included revised 4.4.2.1.

PAGE 9

Delete 4.4.2.2 in its entirety and substitute included revised 4.4.2.2.

PAGE 10

Delete 4.4.2.3 in its entirety and substitute included revised 4.4.2.3.

PAGE 11

Delete 4.4.2.4 in its entirety and substitute included revised 4.4.2.4.

PAGE 12

Delete 4.4.2.5 in its entirety and substitute included revised 4.4.2.5.

AMSC N/A FSC 1336
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1	Liner				9387148
					NEXT HIGHER ASSEMBLY 9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter (O.D.)		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Runout of O.D. with datums A and B		0.40%	3.2	Gage
104	Depth of datum A from base		0.40%	3.2	Gage
105	Length of datum A to datum B		0.40%	3.2	Gage
106	Inside spherical radius		0.40%	3.2	Gage
107	Wall thickness at apex end (See note 7 on dwg.)		0.40%	3.2	Gage
108	Wall thickness between datum A and datum B		0.40%	3.2	Gage
109	Perpendicularity of base of liner with datums A and B		0.40%	3.2	Gage
110	Straightness between datum A and datum B (See note 5 on dwg.)		0.40%	3.2	Gage
111	Length from datum A to inside spherical radius		0.40%	3.2	Gage
112	Wall thickness variation between datum A and datum B (See note 4 on dwg.)		0.40%	3.2	Gage
113	Hardness of starting stock (See note 1)	Mat'l Sample		3.2	4.6.1
114	Chemical compostion of starting stock (See note 1)	Mat'l Sample		3.2	4.6.2
115	Grain size of starting stock (See note 1)	Mat'l Sample		3.2	4.6.3

NOTES:

Note 1: Starting stock - See note 2 of drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48670 (AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET 2 OF 2			DRAWING NUMBER
4.4.2.1	Liner (Continued)				9387148
					NEXT HIGHER ASSEMBLY 9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MAJOR					
116	Hardness of finished liner (See note 11B on dwg.)	4.4.3.1.1		3.2	4.6.4
117	Grain size of finished liner (See note 11A on dwg.)	4.4.3.1.1		3.2	4.6.5
118	Evidence of discontinuity of machined surface (See note 10 on dwg.)		0.40%	3.2	Visual
MINOR					
201	63 Finish (See note 6 on dwg.)		0.65%	3.2	Gage
202	Workmanship		0.65%	3.6	Visual

NOTES:

(8)

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48670 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9387149
4.4.2.2	Body				NEXT HIGHER ASSEMBLY 9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Wall thickness		0.40%	3.2	Gage
102	Total length		0.40%	3.2	Gage
103	Large inside diameter (I.D.)		0.40%	3.2	Gage
104	Middle I.D.		0.40%	3.2	Gage
105	True position middle I.D.		0.40%	3.2	Gage
106	Small I.D.		0.40%	3.2	Gage
107	Total runout of small I.D.		0.40%	3.2	Gage
108	Depth of middle I.D. to small I.D.		0.40%	3.2	Gage
109	Small outside diameter (O.D.)		0.40%	3.2	Gage
110	Runout small O.D.		0.40%	3.2	Gage
111	Large O.D.		0.40%	3.2	Gage
112	Runout large O.D.		0.40%	3.2	Gage
113	Parallelism of small face to datum B		0.40%	3.2	Gage
114	Perpendicularity of datum B to datum A		0.40%	3.2	Gage
MINOR					
201	125 Finish (see note 3 on dwg.)		0.65%	3.2	Gage
202	Protective finish (see note 4 on dwg.)		0.65%	3.2	Visual
203	Workmanship		0.65%	3.6	Visual

NOTES:

(6)

4

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48670 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9387158
4.4.2.3	Plate				NEXT HIGHER ASSEMBLY 9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Inside diameter		0.40%	3.2	Gage
102	True position of inside diameter		0.40%	3.2	Gage
103	Large outside diameter		0.40%	3.2	Gage
104	Depth, inside diameter		0.40%	3.2	Gage
MINOR					
201	Overall thickness		0.65%	3.2	Gage
202	Presence of chamfer		0.65%	3.2	Gage/Visual
203	Thickness of outside diameter		0.65%	3.2	Gage
204	125 ✓ Finish (see note 4 on dwg.)		0.65%	3.2	Gage
205	Protective finish (see note 5 on dwg.)		0.65%	3.2	Visual
206	Workmanship		0.65%	3.6	Visual

NOTES:

(10)

5

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399691
4.4.2.4	Body, PIC				NEXT HIGHER ASSEMBLY 9399689
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Large inside diameter		0.40%	3.2	Gage
102	Small inside diameter		0.40%	3.2	Gage
103	Length large inside diameter		0.40%	3.2	Gage
104	True position large inside diameter		0.40%	3.2	Gage
105	Outside diameter		0.40%	3.2	Gage
106	True position, outside diameter		0.40%	3.2	Gage
MINOR					
201	Overall length		0.65%	3.2	Gage
202	Protective finish (see note 4 on dwg.)		0.65%	3.2	Visual
203	Workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9387189
4.4.2.5	Pad, Compression				NEXT HIGHER ASSEMBLY 9399687
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Material (see note 2 on dwg.)				Certification
MINOR					
201	Inside diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Workmanship		0.65%	3.6	Visual

NOTES:

(12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 14

4.6.4: Delete "The Rockwell F" and substitute "The Rockwell 15T".

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1336-A561)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.