MIL-C-48881B(AR)
AMENDMENT 2
19 JULY 1985
SUPERSEDING
AMENDMENT 1
17 September 1984

MILITARY SPECIFICATION

CHARGE, PROPELLING, M205
LOADING, ASSEMBLING, AND PACKING

This Amendment forms a part of Military Specification MIL-C-48881B (AR), dated 11 March 1983, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.2, Delete: "9378773 - Container Assembly"

PAGE 3

* 3.6.1, Delete in its entirety and substitute:

"3.6.1 Propelling charge. The propelling charge shall be free of dirt, grease, cracks, splits, cuts, tears, rips, holes, soft spots, seam separations or foreign material."

PAGE 7

* 4.4.2.1, under Critical category, Delete Critical 3 and substitute the following:

Critical		AQL	Reg. Para.	Para. Ref.
"3	Container assembly or seal between top, bottom and closure damaged or unbonded to the extent that propellant can escape	100%	3.2	Visual (4.5.5)"

FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

* 4.4.2.1, under Major category Delete "Major 105" and substitute the following:

		AQL	Reg. Para.	Para. Ref.
Major "105	Container assembly or seal between top, bottom and closure damaged or unbonded but not to the extent that propellant can escape	100%	3.2	Visual (4.5.5)"

4.5.1.2, Delete in its entirety and substitute the following:

"4.5.1.2 Automated method.

4.5.1.2.1 Method 1. The contractor may elect to perform this operation with automated equipment and mandatory process controls. The automated equipment shall weigh the container and place this weight in memory and then weigh/check weight the propellant before loading. After loading, the total weight of the container/propellant combination shall be weighted to verify complete loading by subtracting the increment weight (from memory) from the total loaded propellant weight. In such cases, process control plans in accordance with Data Item DI-P-1604 must be submitted to the Technical Agency (see 6.6) for review of the automated operation.

4.5.1.2.2 Method 2. The empty increments shall be sorted into discreet weight groups with a minimum group range of 0.6 grains to minimize container weight variance. After the empty increments are sorted, they will be loaded by groups. The automated equipment shall weigh and check weigh the propellant before loading. After loading, the total weight of the container and propellant combination shall be weighed to verify complete loading by subtracting the increment group weight from the total weight to obtain the loaded propellant weight."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A742)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.