MILITARY SPECIFICATION SHEET

CABLE ASSEMBLY W41-1(A)DM-E1

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-50288(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly W41-1(A)DM-E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-50288(MU) - Cable Assemblies for War Reserve Atomic Demolition Charges, General Specification for

STANDARDS

MILITARY

NAS-1081C02D2 - Set screw
NAS1455B0-5 - Chain, Weldless, Flat, Type, Link
MS20450C8AD12 - Rivet
MS25281-3 - Clamp
MS27183-4 - Washer
MS87006-33 - Hook "S"

DRAWINGS

ORDNANCE CORPS

8800545 - Bag, Packing, Ammunition, for Cable Assembly
8808362 - Packing and Marking for Storage and Shipments
8838900 - Connector, Plug, Electrical
8838904 - Cap, Dust
9216278 - Coupling Ring Extension

FSC 1125

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

9216402 - Cable Assembly W41-1(A)DM-E1
9217617 - Glyptal Adhesive
9217618 - Chemotec, Plastic-Sealer
ET-9216402 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-50288(MU) and as specified herein.

3.2 Circuit resistance (see Environmental testing, section 3, MIL-C-50288(MU)). Circuit resistance test shall not be performed before, during or after any environmental test.

3.3 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 9216402)

From Connector P5-2	To Field wire	Ohms max
Pin	either end	0.2
Shell	other end	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-C-50288(MU) and as specified herein.

4.1.1 Quality assurance provisions not applicable. The following quality assurance provisions in MIL-C-50288(MU) are not applicable.

a. Inspections and testing to be performed in first article testing.
b. Circuit resistance (see Testing).
c. Circuit resistance (see Test Methods).

4.2 Inspections and testing to be performed. The first article inspection sample shall be subjected to inspections and tests specified in Table II. Tests shall be conducted in the order specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table II

First article inspections and tests

Examination or test	Contractor's inspection permissable before submission	Non-Dest.	Dest.	Sub-Assemb.	Assemb.
1. Classification of characteristics (see 4.3 and Classification of Characteristics, MIL-C-50288(MU).	X	X		X	X
2. Insulation resistance (see 4.6.2 and Insulation resistance, section 3, MIL-C-50288(MU).	X	X			X
3. Low temperature (see Low temperature, section 3, MIL-C-50288(MU).	X	X			X
4. High temperature (see High temperature, section 3, MIL-C-50288(MU).	X	X			X
5. Vibration (see Vibration, section 3, MIL-C-50288(MU).	X	X			X
6. Humidity (see Humidity, section 3, MIL-C-50288(MU).			X		X
7. Circuit resistance (see 3.2 and Circuit resistance, section 3, MIL-C-50288(MU).			X		X

Note: Circuit resistance test shall not be performed before, during or after High and Low Temperature, Vibration and Humidity Tests.

4.3 Classification of characteristics.

4.3.1 Connector, plug, electrical (see dwg 8838900); cap with chain, dust (see dwg 8838904); glyptal adhesive (see dwg 9217617); chemotec, plastic sealer (see dwg 9217618); set screw (see NAS1081C02D2); chain, weldless, flat, type, link (see NAS1455B0-5); rivet (see MS20450C8AD12); clamp (see MS25281-3); washer (see MS27183-4); hook "S" (see MS87006-33) covering details of dwg 9216402.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for component in accordance with applicable standard or drawing.....Visual

Minor: None defined.

4.3.2 Coupling ring, extension (see dwg 9216278) covering a detail of dwg 9216402.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Inside diameter, max.....Gage
102. Pitch diameter of threads, max.....Gage
103. Minor diameter of threads, max.....Gage
104. Diameter of holes.....Gage
105. Knurl present.....Visual
106. Material (see Material, section 3, MIL-C-50288(MU).....Visual
107. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for finish in accordance with dwg 9216278.....Visual

Minor: None defined.

4.3.3 Cable assembly W41-1(A)DM-E1 (see dwg 9216402) before molding.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length of chain.....*Measure
102. Length from connector to sleeve.....*Measure
103. Length of sleeve.....*Measure
104. Length of wire.....*Measure
105. Cable folded and taped properly.....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

106. Marking.....Visual
107. Torque on connector nut before sealing.....Gage
108. Connector nut sealed.....Visual
109. Torque on set screws.....Gage

* Measure with suitable scale.

Minor:
201. Serialization (see Serialization, section 3, MIL-C-50288(MU).....Visual

4.3.4 Cable Assembly W41-1(A)DM-E1 (see dwg 9216402).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Total length.....*Measure
102. Length of mold around cable and wire.....*Measure

* Measure with suitable scale.

Minor: None defined.

4.4 Testing.

4.4.1 Circuit resistance (see Circuit resistance, section 3, MIL-C-50288(MU). Each cable assembly, before molding ends of wire, shall be tested in accordance with 4.6.1. If any cable assembly fails to comply with circuit resistance, section 3, MIL-C-50288(MU), the cable assembly shall be rejected and removed from the lot.

4.5 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-C-50288(MU) and ET-9216402.

4.6 Test methods.

4.6.1 Circuit resistance (see Circuit resistance, section 3, MIL-C-50288(MU). Remove molded ends of wire when necessary. The circuit resistance shall be measured with approved resistance equipment in accordance with Table I (see 3.2). In addition, while making each circuit resistance test, the cable shall be gripped at a point not greater than 6 inches from the face of the connector and wiggled back and forth for more than 30° of arc on each side of the axis of the cable.

4.6.2 Insulation resistance (see Insulation resistance, section 3 and 4, MIL-C-50288(MU). The insulation resistance shall be tested in accordance with Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table II

Insulation resistance (see dwg 9216402)

Positive potential applied to connector P5-2 Pin	Minus potential to shell

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-50288(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-50288(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800545 and 8808362 and as specified in MIL-C-50288(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-50288(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8800545 and 8808362 and MIL-C-50288(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8800545 and 8808362 and MIL-C-50288(MU).

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-50288(MU).

Custodian:
Army - MU

Preparing Agency
Army - MU

Project No. - 1125-A048

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-C-50288/10(MU) Cable Assembly W41-1(A)DM-E1

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*	DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.