INCH-POUND

MIL-F-50945D (AR)
AMENDMENT 5
13 February 1992
SUPERSEDING
AMENDMENT 4
27 AUGUST 1990

MILITARY SPECIFICATION

FUZE, PD, M567/XM935 (M935) LESS BOOSTER

This Amendment forms a part of Military specification MIL-F-50945D (AR), dated 8 September 1982 and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Add "(M935)" after "M567/XM935"; and wherever it appears in the specification.

Title: Add "/M936" after "(M935)"; and where applicable.

PAGE 2

2.1.2, Add to title of 9272193, "or Body Assembly, Front, M935."
Add to title of 9272194, "or Body Assembly, Front, M935."

PAGE 10

4.3.1.2: Delete "Cap, Shipping... 9255255...10."

PAGE 18

TABLE I, First article inspection: delete "Cap, Shipping Dwg. 9255255, Examination for defects."

PAGE 23

* 4.4.2.1, Delete major 112 in its entirety

PAGE 33

4.4.2.6 And 4.4.2.6.1, Add Major 113 which reads as follows:

"113 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

PAGE 35

* 4.4.2.7, MAJOR 101 and 102, delete 0.40% AQL and substitute "Note (a)".

Add Note (a) which reads as follows:

"(a) Sample per paragraph 4.5.18.1."

PAGE 43

4.4.2.13, Add Major 106 which reads as follows:

"106 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

PAGE 44

4.4.2.14, Add Major 109 which reads as follows:

"109 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

PAGE 45

4.4.2.15, Delete Major 104 in its entirety.

PAGE 62

4.4.2.26, Add Major 105 which reads as follows:

"105 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

PAGE 72

4.4.2.35, delete major 105 in its entirety and substitute the following:

"Major 105 Tensile test...(b)...3.1...Gage."

Major 106 Add new CD as follows:

"Major 106 Wrap test...(b)...3.1...Gage"

Note (b): Add at end of note the following:

"Test per MIL-STD-105D, inspection level S-4, AQL 1.0 percent for wrap test and level S-1, AQL 1.5 percent for the tension test. Examination of wrap test samples shall utilize 4 X magnification"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

PAGE 74

* 4.4.2.37, Critical 2, change inspection method form "visual" to "gage".

PAGE 82

* 4.4.2.41, Critical 2, change "Critical 2" to "Special A".

PAGE 83

* 4.4.2.42, Critical 2, change inspection method from "visual" to "gage"

"109 Presence of tape over rear face of body assembly... 0.40%..3.2...Visual."

Major 106: Delete in its entirety.

PAGE 85

4.4.2.44: Delete in its entirety.

PAGE 86

* 4.4.2.45, Critical 2, change "Critical 2" to "Special A".

PAGE 87

4.4.2.46, Add Major 103 and Note (h) which reads as follows:

"103 Lubrication missing or improperly applied...12...(h) ...3.2...Visual.

(h) Same 12 samples after being used for the Jolt and Jumble Test shall be disassembled to examine for missing or improperly applied lubrication/grease (components to be checked are striker, setback pin, setback spring, slider detent, safety latch and selector cap O-ring). If one or more samples are classed defective, the lot shall be rejected."

PAGE 88

4.4.2.46, Major 102 and Major 104, Delete "15" sample size and substitute "5."

4.4.2.46, Under sample units, Delete "166" and substitute "146."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

PAGE 89

4.4.2.47, Add Major 103 and Note (h) which reads as follows:

"103 Lubrication missing or improperly applied...12...(h) ...3.2...Visual.

(h) Same 12 samples after being used for the Jolt and Jumble Test shall be disassembled to examine for missing or improperly applied lubrication/grease (components to be checked are striker, setback pin, setback spring, slider detent, safety latch and selector cap O-ring). If one or more samples are classed defective, the lot shall be rejected.

PAGE 90

4.4.2.47 Major 102 and Major 104, delete "15" sample size and substitute "5."

Under sampling units, delete "166" and substitute "146."

PAGE 91

4.4.2.48, Add to title: "or Body Assembly, Front, M935."

PAGE 92

4.4.2.49, Add to title: "or Body Assembly, Front, M935."

PAGE 93

4.4.2.50, Delete Major 101 in its entirety.

PAGE 96

* 4.5.6, change line 1 to read as follows:
"The assembly shall be hand-held or placed in"

PAGE 98

4.5.10, Delete "the shipping cap (dwg. 9255255) shall be removed and"

PAGE 100

* Change the following to read:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

4.5.18.1 Examination for location and depth of spring pin cavity. The location and depth of the spring pin cavity shall be inspected in the following manner.

4.5.18.1.1 Initial production examination - Beginning with the first production shift, ten (10) consecutive drilled units shall be inspected and found defect free prior to rate production. Then inspect five (5) units every two (2) hours until the end of the shift. Five (5) units shall be inspected at the end of the shift. If a defect is found in any of the five (5) units, the production represented by the units shall be rejected and the machine set-up shall be adjusted until ten (10) consecutive units are defect free.

4.5.18.1.2 Second production interval - After successfully completing the sampling of 4.5.18.1.1 for three consecutive eight hour production shifts with no defects, the sampling plan may be reduced to five (5) drilled units being inspected every four (4) hours and at the beginning and at the end of the shift. If a defect is found, the production represented by the sample shall be rejected and the sampling plan of 4.5.18.1.1 shall be reinstated.

4.5.18.1.3 Third production interval - After successfully completing the sampling of 4.5.18.1.2 for five consecutive eight hour shifts, the sampling plan may be reduced to three (3) drilled units being inspected every four (4) hours and at the beginning and at the end of the shift. If a defect is found, the production represented by the sample shall be rejected and the sampling plan of 4.5.18.1.1 shall be reinstated.

4.5.18.1.4 Tooling change. A change of tooling will require a first piece inspection prior to continuing production. The sampling plan will be the same as that prior to the tooling change. The above plan shall be applicable to each drilling machine equipment set up.

4.5.18.1.5 Production lapse. A stop in production of over one month will require starting the inspection at the initial production shift plan.

PAGE 104

6.7.2, Under quantity column, delete "15" and substitute "5."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

* 6.9, Add new paragraph as follows:

"6.9 Special defect. A defect, other than critical, that judgement and experience indicate may, depending upon the degree of variance from the design requirement:

a. Result in hazardous or unsafe conditions for individuals using, maintaining or depending upon the product or

b. Prevent performance of the tactical function of a major end item."

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendmemt were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A763)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.