MIL-I-48779A(PA)
7 April 1975
SUPERSEDING
MIL-I-48779 (PA)
13 January 1975

MILITARY SPECIFICATION

IGNITER, INERT, TRAINING FOR PROJECTILE TRAINING, 8 INCH

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of igniter, inert, used on the M423 Loading Assembly, 8 inch, training.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification for.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1167	- Ammunition Data Card
MIL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

PICATINNY ARSENAL

PRODUCT DRAWING

8787133	- Igniter, Training

FSC: NUOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Materials. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Igniter. - The igniters shall comply with all requirements specified on drawing 8787133 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 First article inspection. - Not applicable.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. - All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.4.2 Threads. - Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. - Parts shall be free from burrs.

3.4.4 Foreign matter. - Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.5 Cleaning. - The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. - The inspection requirements specified herein are classified as Quality Conformance Inspections.

4.3 First article inspection. - Not applicable.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078.

a. Major B defects sampling plan. - Unless otherwise specified, major defects shall be sampled in accordance with Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

Table I
Major Defects

LQ = .05 Acceptance No = 0 Consumers Risk = .10

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

b. Minor defects sampling plan. - Unless otherwise specified, minor defects shall be sampled in accordance with Table II.

Table II
Minor Defects

LQ = .10 Acceptance No = 0 Consumers Risk = .10

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.4.2.1	TITLE Igniter, Inert, Training		SHEET 1 OF 1		DRAWING NUMBER 8787133
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Special	None defined.				
Major B					
131.	Major diameter of thread, max		Table I	3.2	Gage
132.	Total length, max		Table I	3.2	Gage
133.	Pitch diameter of thread, max		Table I	3.2	Gage
134.	Outside diameter of tube section, max		Table I	3.2	Gage
135.	External diameter of thread pilot, max		Table I	3.2	Gage
136.	Location of wrench holes in flange (functional)		Table I	3.2	Gage
137.	Thickness of flange, max		Table I	3.2	Gage
138.	Diameter of wrench holes min		Table I	3.2	Gage
139.	Chamfer present		Table I	3.2	Visual
Minor					
201.	Surface finish damaged		Table II	3.4	Visual
202.	Stamping not visible		Table II	3.2	Visual
203.	Workmanship unsatisfactory		Table II	3.4	Visual/Manual

NOTES

SARPA QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Not applicable.

4.4.4 Inspection equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the table starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking. The igniter shall be preserved, packaged, packed and marked in accordance with MIL-STD-1169, Level C.

6. NOTES

6.1 Intended use. - The component covered by this specification is intended for use on a breech training device.

6.2 Ordering data. - See MIL-A-48078.

6.2.1 Procurement requirements. - See MIL-A-48078.

6.2.2 Contract data requirements. - See MIL-A-48078.

6.3 Inspection equipment designs. - See MIL-A-48078.

6.3.1 SIE designs. - Not applicable, none furnished.

6.3.2 Contractor designs. - See MIL-A-48078.

6.3.3 Submission of designs for approval. - See MIL-A-48078.

6.4 Identification of changes. - Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensive changes.

6.5 Supersession data. - This specification supersedes the requirements of MIL-B-48779(PA), dated 13 January 1975.

Custodian:
Army - PA

Preparing Activity:
Army - PA

Project Number: NUOR-A034

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING.

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1426 (JAN 72)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.