MIL-T-52452B(ME)
24 August 1981
SUPERSEDING
MIL-T-52452A
2 December 1975

MILITARY SPECIFICATION

TRAINING AID, MODEL COMPASSES, PLANE-SURFACE AND LENSATIC

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers plane surface and lensatic model compasses.

1.2 Classification. Model compasses shall be the following types, as specified (see 6.2):

Type I - Plane surface.
Type II - Lensatic.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.

FSC 6910

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

DRAWINGS

ME

TA13211E7404	- Training Aid, Model Compass, Plane Surface.
TA13211E7382	- Training Aid, Model Compass, Lensatic.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The compasses shall be in accordance with Top Assemblies TA13211E7404 and TA13211E7382 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the compasses. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made availabe, upon request, for inspection by the contracting officer or his designated representative.

3.2 Material. Material shall be as specified herein and on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the current version before use.

3.3 Type I model compass. The Type I model compass shall conform to TA13211E7404.

3.4 Type II model compass. The Type II model compass shall conform to TA13211E7382.

3.5 Workmanship. Wood components shall be free of sharp or splintered edges. Metal components shall be free of sharp edges and burrs. Plastic components shall be free of pits, cracks, or sharp edges. Corners, edges, and adjacent surfaces of components fabricated of building board shall be free of loose or peeled fibers.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that the materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.2 Classification of inspection. Inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of packaging (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1. AQL shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

4.4 Inspection procedure.

4.4.1 Examination. The compasses shall be examined as specified herein for the following major defects:

101. Dimensions not as specified.
102. Components missing or not as specified.
103. Materials not as specified.
104. Welded or brazed joints not as specified.
105. Treatment and painting not as specified.
106. Marking not as specified.
107. Plating not as specified.
108. Workmanship not as specified.

4.5 Inspection of packaging.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

109. Materials, methods, and containers not as specified for Level A or Level B. Each incorrect material, method, or container shall constitute one defect.
110. Box not closed and sealed as specified for Level A.
111. Compasses of unlike description packed together for Level A or Level B.
112. Gross weight or size exceeds the limitation of the box specification for Level A or Level B.
113. Strapping not as specified for Level A.
114. Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or Commercial, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each compass, in collapsed position, shall be placed in a close-fitting box conforming to PPP-B-636, W5c or W6c, style optional. The box shall be closed and sealed as specified for Method V in the appendix to the box specification.

5.1.2 Commercial. Commercial preservation shall be in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.2.1 Level A. Compasses of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, style optional, in quantities not to exceed the weight limitation of the box specification. The boxes shall be closed and strapped in accordance with the appendix to the applicable box specification except that strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable; and, unless otherwise specified herein, shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.2.2 Level B. Compasses of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-636, V3c, style optional or PPP-B-640, Class 2, style optional. The gross weight or size shall not exceed the limitation of the box specification.

5.2.3 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.3 Marking. Marking for military levels of protection shall be in accordance with MIL-STD-129. Commercial marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The model compasses are components of a map reading set. The Type I compass is used to illustrate map orientation and to find azimuths. The Type II compass is used to illustrate direction and azimuths. The set is used as an aid in teaching basic map reading.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).

Source: https://assist.dla.mil - Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

(c) Degree of preservation and degree of packing required (see 5.1 and 5.2).
(d) When strapping shall be Finish A (see 5.2.1).

6.3 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).

Custodians:
Army - ME

Preparing activity:
Army - ME

Project 6910-0410

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DS
Fort Belvoir, VA 22060

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/6539 2-1

Source: https://assist.dla.mil -- Downloaded: 20261 0-22T21:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-52452B(ME) Training Aid, Model Compasses, Plane-Surface and Lemniatic

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:18Z
Check the source to verify that this is the current version before use.