MIL-W-50550A (MU)
26 April 1973
SUPERSEDES
MIL-W-50550 (MU)
10 July 1970

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, FLECHETTE, WITH FUZE WDU-4A/A, WDU-13/A LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for Warhead, 2.75 Inch Rocket, Flechette, With Fuze WDU-4A/A, WDU-13/A.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date pf invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL- STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ARMY

66C10121 - Container, Packaging
66B10122 - Box, Packing
67D9700 - Warhead, 2.75 Inch Rocket, Flechette, WDU-4A/A
9242056 - Carton, Packing, Ammunition for Warhead, 2.75 Inch Rocket; Flechette, WDU-4A/A
9242057 - Box, Wirebound, Packaging, Ammunition for; Warhead, 2.75 Inch Rocket, Flechette, WDU-4A/A
9259095 - Warhead, 2.75 Inch Rocket, Flechette, 60 Grain

FSC: 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

ET 67D9700 - Equipment Tabulation Number (for 20 Grain Flechette)
ET 9259995 - Equipment Tabulation Number (for 60 Grain Flechette)

(Copies of specifications, standards, drawings and publications required by suppliers In connection with a specific procurement function should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Material shall be In accordance with applicable drawings and specifications.

3.2 Loaded Assemblies.-The loaded assemblies shall comply with all of the requirements specified on dwg. 67D9700 (For 20 Grain Flechettes) and dwg. 9259995 (For 60 Grain Flechettes) and with all requirements specified in applicable specifications.

3.3 Workmanship.-Loading and assembling shall be accomplished in accordance with best practices. All parts shall be free of any foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few slight scratches not exposing base material. All required markings shall be neat and sharply defined.

3.4 Performance.-Performance features defined herein are specified at environmental conditions normal to the place of acceptance testing unless otherwise noted.

3.4.1 Non-Arming.-The warhead shall not arm when subjected to a forward axial acceleration of 11+2 gravities (G's) for a period of not less than 3 seconds.

3.4.2 Arming.-The warhead shall arm when subjected to a forward axial acceleration of 31 ± 2 gravities (G's) for a period of 1.50 seconds minimum.

3.4.3 Firing.-Subsequent to arming In accordance with paragraph 3.4.2, the warhead shall fire upon a decrease in acceleration to 15 G's or lower.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

3.4.4 Flechette Expulsion.- Upon firing, the warhead shall expel the flechettes, as evidenced by expulsion of the pusher plate, without rupture of the munition case.

3.5 Leak Test .-The loaded warhead in the final assembled configuration shall be subjected to a leak test. Each loaded warhead shall be capable of withstanding an applied external pressure of ten (10) psi without exceeding a leakage rate of ten (10) to the minus fourth cubic centimeter per second (10-4 cc./sec.).

3.6 First Article Inspection. -This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified In the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.- Unless otherwise specified, In the contract or purchase order, the supplier Is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the Inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein.

4.1.1 Submission of Product .-At the time each completed lot of Items deliverable under the contract Is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the Information provided is correct and applicable to the product being submitted:

A statement that the lot complies with all of the quality assurance provisions specified In this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material Is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review,

d. Number of items In the lot.

Date submitted.

The certificate shall be signed by a responsible agent of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

certifying organization. The Initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority Is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission. -The contractor shall submit a sample consisting of 29 finished assemblies to the Government for testing in accordance with the provisions of 4.2.2. All parts and materials shall be the same as will be used in production and shall be obtained from the same source of supply. Prior to submission the sample shall be inspected by the contractor to the degree necessary to assure that it conforms to the requirements of the contract. A first article sample or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be Performed .-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in section 4.3.2, 4.3.3 and 4.3.4 of this specification and any or all of the applicable drawings. Five (5) warheads shall be used for the Leak Test. In addition 24 warheads shall be utilized for the Centrifuge (4.3.4.1) and Leak (4.3.4.2) test.

4.2.3 Rejection. -If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly or components In the sample to comply with any of the stated require-ments.

4.3 Inspection Provisions for Production

4.3.1 Lot Formation.-The term "Inspection lot" as used In this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

as specified in MIL-STD-105. Chances to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an Inspection lot. All material submitted for Inspection In accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which Is being applied to determine conformance with requirements. Lot numbering, as required, shall be In accordance with MIL-STD-1168. Lot size shall be 20,000 ± 500 or one months production; whichever Is smaller. Individual shipments from a supplier can be sub-lots. The maximum number of lots of components and the source of each component lot which can be assembled Into one loaded warhead lot is as follows:

a. Metal parts from lots bearing same lot interfix number from one manufacturer.

b. Fuzes from no more than two (2) lots bearing the same Interfix lot number from one manufacturer.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used If approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to Individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of' the contractor's Inspection system. Equipment necessary for the performance of the inspections listed shall be In accordance with 4.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.3.2.1 Warhead, prior to Insertion of Flechette Assembly and attachment of Nose Cone Assembly (see dwg. 67D9700 or dwg. 9259995).

Categories	Defects	Method of Inspection	Code No.
Critical:	100 percent		
1.	Evidence of unsafe fuze	Visual	01001
Major:	AQL 0.65 percent		
101.	Fuze type improper	Visual	01002
102.	Fuze not seated properly	Visual	01003
103.	Plate, pusher missing	Visual	01004
Minor:	AQL 1.00 percent		
201.	Spacer, Fuze missing	Visual	01005
202.	Spacer missing	Visual	01006
203.	Evidence of poor workmanship(see3.3)	Visual	01007

4.3.2.2 Warhead, prior to attachment of Nose Cone Assembly (see dwg. 67D9700 or dwg. 9259995).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Weight of flechette payload incorrect	Test	02001
102.	Flechette payload missing or seated improperly	Visual	02002
103.	Packing missing	Visual	02003
Minor:	AQL 1.00 percent		
201.	Sleeve not properly seated	Visual	02004
202.	Pigment missing (red dye)	Visual	02005
203.	Packing lubrication missing	Visual	02006
204.	Evidence of poor workmanship, (see 3.3)	Visual	02007

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.3.2.3 Warhead, loaded (see dwg. 67D9700 or dwg. 9259995)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Thread damaged or burres	Visual	03001
102.	Nose cone not seated properly	Visual	03002
103.	Pins not flush or below or loose or missing	Visual/Manual	03003
istance pin hole to forward			
104.	Distance pin hole to forward end of case	Gage	03004
Minor:	AQL 1.00 percent		
201.	Protective coating inadequate or damaged	Visual	03005
202.	Marking missing, incorrect, or illegible	Visual	03006
203.	Evidence of poor workmanship(see3.3)	Visual	03007

4.3.2.4 Container, Packaging, sealed (see dwg. 66C10121). (Applies if shipping to other than load plant).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Tape incomplete or badly wrinkled	Visual	04001
102.	Cuts, scuffs, gouges, or checks which penetrate outer layer	Visual	04002
103.	Metal end loose or distorted	Visual/ Manual	04003
104.	Overall length, max	Gage	04004
Minor:	AQL 1.50 percent		
201.	Marking missing, misleading or unidentifiable	Visual	04005
202.	Contents loose	Manual	04006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4 .3.2.5 Box, packing (see dwg. 66 B10122). (Applies if shipping to other than load plant).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Contents exposed	Visual	05001
102.	Board broken	Visual	05002
103.	Hardware missing, broken or loose	Visual/ Manual	05003
104.	Strapping missing, broken or loose	Visual/ Manual	05004
Minor:	AQL 1.50 percent		
201.	Marking, misleading or unidentifiable	Visual	05005
202.	Hardware improperly engaged	Visual	05006

4.3.3 Inspection

4.3.3.1 Outside diameter - Major Defect - Code No. 03008.-Each finished warhead shall be inserted through a ring gage of 2.792 Inch diameter. Any warhead that does not pass freely through the gage shall be rejected and removed from the lot. The test shall be performed with equipment in accordance with 4.3.5.

4.3.4 Testing

4.3.4.1 Centrifuge Test (see 3.4) - Non-Arming Critical Defect 03009.-Arming & Firing Major Defect 03010.-The twenty-four (24) warheads used In the leak test (see 4.3.4.2) shall be used for this test. The 2" warhead samples shall be tested at three temperatures: 8 warheads at -65 degrees F, 8 warheads at +115 degrees F and 8 warheads at +150 degrees F. This test shall be performed as specified In 4.4.1 using equipment in accordance with 4.3.5. Any warhead that arms during the non-arm test or fails to fire within the specified “g” loads and expel the flechette charge shall be considered a defective. One or more defective during the non-arm test shall reject the lot. Two or more defective during the arming and firing test shall reject the lot. If one defective occurs during the arming and firing test, the lot represented by the sample shall be placed in a referred status and a retest shall be conducted. The retest sample shall consist of forth-eight (48)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

randomly selected warheads from the referred lot. The retest procedure shall be as specified In 4.4.1 with sixteen (16) warheads at each temperature. If one or more defectives are found during the non-arm test or the arm and firing test, the lot shall be rejected.

4.3.4.2 Leak Test (see 3.5) Major defect Code No. 03011.-A sample of twenty-four (24 loaded warheads from each lot shall be subjected to the leak test as specified in 4.4.2 using equipment In accordance with 4.3.5. Any warhead that leaks in excess of the requirements shall be considered a defective. Two or more defectives shall reject the lot. If one defective occurs during test, the lot represented by the sample shall be placed In a referred status and a retest shall be conducted. The retest sample shall consist of forty-eight (48) randomly selected warheads from the referred lot. The retest procedure shall be as specified in 4.4 .2. If one or more defective are found during the leak retest, the lot shall be rejected. The warheads used for the centrifuge test shall be selected from warheads used In the leak test.

4.3.5 Inspection Equipment .-Equipment Tabulation Number ET-67D9700 (For 20 Grain Flechette) or ET-9259995 (For 60 Grain Flechette) identifies the inspection equipment required to perform the examination and tests prescribed In this section. The contractor shall design inspection equipment in accordance with the Instructions in paragraph 6.3.

4.3.5.1 Government Rights to Documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey whenever Inspection equipment drawings are needed.

4.4 Test Methods and Procedures.

4.4.1 Centrifuge Testing (see 4.3.4.1).-Each warhead selected shall be conditioned to assure a uniform temperature throughout its entire mass at the time of firing for at least two (2) hours. Each firing shall occur within 5 minutes from the time the rocket Is removed from the temperature conditioning cabinet. A warhead left out of the conditioning cabinet over five minutes prior to firing shall be placed at ambient temperature for not less

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

than 4 hours and then reconditioned to the applicable temperature. Utilizing a customer-approved centrifuge device, warheads shall be subjected to an axial acceleration force of 11+2 gravities (g's) for a period of at least 3 seconds. Centrifuge power shall then br turned off and the centrifuge arm shall be slowed to slow down at a natural rate to a full stop. If the round does not function, it shall be considered acceptable and the round again subjected to an axial acceleration force of 31 ± 2G's for a period Of at least 1.5 seconds. Centrifuge shall then be turned off, and the centrifuge arm shall be allowed to slow down at a natural rate. Warheads shall fire when acceleration decreased to 15G's or less. Warhead firing (flechette expulsion) shall verify the firing requirements established in paragraph 3.4 of this specification.

4.4.2 Leak Test (see 4.3.4.2).-The warheads selected for this test shall be subjected to a leak test. The loaded warhead, when subjected to a pressure differential of ten PSI at room temperature shall not leak at a rate exceeding 1 x 10-4 cc/see for 10 seconds minimum after stabilization.

5. PREPARATION FOR DELIVERY

5.1 Packaging

5.1.1 Level C .-(For shipment to load plants for further processing). (see dwg. 9242056).

5 .1.2 Level A. -The warheads, with Fuzes, shall be packaged In accordance with dwg. 66C10121. (If shipped to other than load plants).

5.2 Packing

5.2.1 Level C.-(For shipment to load plants for further processing). (see dwg. 9242057).

5.2.2 Level A.-The packaged assemblies shall be packed and marked In accordance with dwg. 66B10122. (If shopped to other than load plants).

6, NOTES

6.1 Ordering Data.- Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.- Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Provisions for submission of first article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

6.2 Inspection Code Numbers. -The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed In this specification. In addition, they should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.5).

6.3 Inspection Equipment.-The contractor shall design Inspection equipment as required by the Inspection Equipment Lists (EL) referenced on the applicable ET In accordance with the instruction of paragraphs 6.3.1 through 6.3.2.

6.3.1 Inspection Equipment Lists (EL).-Inspectlon equipment lists indicate the availability of Inspection equipment designs by showing In the “number” column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock Numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as “Contractor Design” In the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection Equipment List Codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army Designs .-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the Item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of Inspection equipment. Army designs fall into two basic classifications : mandatory (designated “MU”) and non-mandatory (indicated by drawing or Federal Stock Number). When an Inspection equipment list references mandatory Army designs, the contractor shall comply with, and use, these designs accordingly. The contractor may, however, In connection with non-mandatory designs, design alternate Inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of’ the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

6.3.4 Contractor Designs,-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed designs which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000. Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of Contractor Designs. -All submitted designs shall contain a reference to the applicable five digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-R. All other designs of Inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by tile contracting officer. Partial submission of Inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Submission of First Article Samples .-Instructions as to the location for the evaluation of the First Article sample shall be obtained from the contracting officer. Upon receipt of such request, the contracting officer shall advise Picatinny Arsenal and instruction will be issued accordingly All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA- A-I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

6.5 Defect Reporting -For every lot produced and submitted to the Government, the contractor shall submit a defect report to the Commanding Officer, Picatinny Arsenal, Dover, New Jersey, ATTN: SMUPA-QA-A-R. The defect report shall contain the results of the inspections and tests as per paragraphs 4.3.4.1 and 4.3.4.2 In addition, the contractor shall perform a study to determine the cause of any defects found in paragraphs 4.3.4.1 and 4.3.4.2 and the corrective action instituted.

NOTICE: When Government drawing, specifications, or other data are used for any purpose other than In connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may have In any way related thereto.

CUSTODIAN:

ARMY - MU

PROJECT NUMBER: 1340-A-396

PREPARING ACTIVITY:

ARMY - MU

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS. This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:29Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Picatinny Arsenal
Dover, New Jersey 07801

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD 314

OFFICIAL BUSINESS

Commander
Picatinny Arsenal
ATTN: SMUPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:29Z
Check the source to verify that this is the current version before use.