FEDERAL SPECIFICATION SHEET

FEDERAL SPECIFICATION

DRYING AND CONDITIONING TUMBLERS, LAUNDRY, COMMERCIAL:

CYLINDER TYPE, END LOADING STYLE, REVERSIBLE AND NON-REVERSIBLE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

(This specification forms a part of the latest issue of Federal Specification 00-D-1297).

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for end loading, twin cylinder tumblers with steam heating coils of one tumbler size.

1.2 Classification. The tumblers shall be reversible or non-reversible, as specified (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 Specifications. The following Federal Specification of the issue in effect on date of invitation for bids or request for proposal, forms a part of the specification to the extent specified herein:

00-D-1297 - Drying and Conditioning Tumblers, Laundry, Commercial: General Specification For

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers, at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specification and Standards from established distribution points in their agencies.)

3. REQUIREMENTS

3.1 Design and construction. The tumblers shall be in accordance with table I and the two cylinders shall be vertical double deck mounted with an arrangement for non-recirculation of the heated air.

TABLE I - Design requirements

Size	Reversibility	Evaporation	Cylinder size	
Minimum dry weight capacity (pounds)		Water evaporated per minute, minimum (pounds)	Approximate interior dimensions (inches) Diameter	Length
30 (15 per cylinder)	reversible	0.65	26	24
30 (15 per cylinder)	non-reversible	0.72	26	24

3.1.1 Cylinder. The cylinders shall be of open-end construction without a door and shall consist of a circular solid back sheet and a front sheet (with an approximately 16-1/4 inches in diameter) and a perforated side sheet. The front and back sheets shall be not less than 0.0324 inches thick, and the side sheet shall be not less than 0.0214 inches thick. The cylinder shall be fitted with not less than three tumbling ribs with through tie rods to increase cylinder rigidity. The circular back sheet of the cylinder shall be securely fastened to a substantial ferrous metal transmitter and trunnions. The trunnions shall rotate in suitable ball or roller bearings.

3.1.2 Door. The housing shall have a door for each cylinder located at readily accessible heights and shall be suitably hinged with a heavy duty latch and door handle. Each door shall have a window fabricated from a commercial grade of shock and heat-resistant glass.

3.1.3 Heat conditioning system. For the cooling cycle, means shall be provided for the admission of air by-passing the heater.

3.1.4 Optional equipment. When specified (see 6.2), the tumbler shall be equipped with a solenoid operated valve on the steam line and an automatic

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

temperature control with a visual signal light and settings graduated from 100 to 200 F. The timing device shall be provided with a minimum drying cycle of 30 minutes, adjustable to a cool-down cycle. During the cool-down cycle, means shall be provided for ducting the entering air to by-pass the heater. When specified (see 6.2), the tumbler shall be furnished with durable press controls.

3.1.5 Lint screen. A lint screen of adequate size, fitted with screens of corrosion-resistant metal, brass wire mesh, or metal painted with heat-resistant enamel, heat-resistant treated synthetic fibers, through which all of the air shall be exhausted, shall be provided. Means shall be provided for cleaning the lint screens without removing the collector from the unit.

4. QUALITY ASSURANCE PROVISIONS

4.1 Test items, functional testing. During functional testing, the following items shall be checked for compliance with the specified requirements:

(a) Operation of the air heater by-pass system.
(b) Operation of the automatic temperature control.

5. PREPARATION FOR DELIVERY (see 00-D-1297)

6. NOTES

6.1 General notes. In addition to the notes contained in the general specification, the following ordering data peculiar to these tumblers are specified.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) The reversibility (see 1.2).
(b) When a solenoid operated temperature valve is required (see 3.1.4).
(c) When durable press controls are required (see 3.1.4).

Custodians:

Army - GL
Navy - YD
Air Force - 84

User activities:

Army - ME, CE
Navy - MC

Preparing activity:

Army - GL

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

Project No. 3510-0201-2

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE Drying and Conditioning Tumblers, Laundry, Commercial: Cylinder Type, End Loading Style, Reversible and Non-Reversible 00-D-1297/2

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

STSNLT-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



Commander
US Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.