00-D-735C
January 11, 1973
SUPERSEDING
Fed. Spec. 00-D-735B
July 12, 1971 and
Fed. Spec. 00-D-730A (In Part)
November 15, 1966
(See 6.5)

FEDERAL SPECIFICATION

DRYCLEANING FINISHING EQUIPMENT, MISCELLANEOUS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers commercial miscellaneous drycleaning finishing equipment which can be safely used in nonhazardous locations only (see 6.1).

1.2 Classification. The miscellaneous drycleaning finishing equipment covered by this specification shall be of the following items, classes, and sizes as specified (see 6.2 and 6.5):

Item:

1 - Air vacuum unit (see 3.7.1).
  Class 1 - Horizontal type.
  Class 2 - Vertical type.
2 - Bag, sleever (see 3.7.2).
3 - Finishing board (see 3.7.3).
  Class 1 - With flatiron.
  Class 2 - Without flatiron.
4 - Garment finisher (see 3.7.4).
5 - Flatiron, electric, steam (see 3.7.5).
  Size - 3 to 4 pounds.
  Size - 5-1/2 to 6-1/2 pounds.
7 - Spotting board (see 3.7.6).
8 - Coat Finisher, Automatic (see 3.8).
9 - Cabinet, Drying and Deodorizing (see 3.9).
10 - Reel Sorting (see 3.10).

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

CC-M-636	-	Motor, Alternating-Current, (Fractional Horsepower).
CC-M-641	-	Motor, Alternating-Current, (Integral Horsepower, 200 HP and Smaller).
QQ-C-390	-	Copper Alloy Castings (Including Cast Bar).
QQ-N-281	-	Nickel-Copper-Alloy Bar, Plate, Rod, Sheet, Strip, Wire, Forgings, and Structural and Special Shaped Sections.
QQ-N-288	-	Nickel-Copper Alloy and Nickel-Copper-Silicon Alloy Castings.

Federal Standard:

FED-STD-123	-	Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-T-152	-	Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

MIL-L-3153 - Laundry and Dry-Cleaning Machinery and Equipment (For Fixed Installations), Preparation for Delivery for Domestic and Overseas Shipment.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirements for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement Of.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Underwriters' Laboratories (UL), Inc., Standards:

(Application for copies of applicable UL standards should be addressed to the Underwriters' Laboratories, Inc., 1285 Walt Whitman Road, Melville, Long Island, N.Y., 11746; 207 East Ohio St., Chicago, Ill., 60611; or 1655 Scott Blvd., Santa Clara, CA 95050.)

American Welding Society (AWS) Standard:

Qualification Procedures of the American Welding Society.

(Application for copies should be addressed to the American Welding Society, United Engineering Center, 345 East 47th St., New York, NY 10017.)

American Society of Mechanical Engineers (ASME) Standards:

ASME Boiler and Pressure Vessel Code, Section VIII - Unfired Pressure Vessels.

Welding Qualifications of the American Society of Mechanical Engineers.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th St., New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM) Standards:

A167-70 - Corrosion-Resisting Chromium-Nickel Steel Plate, Sheet and Strip.
A176-71 - Corrosion-Resisting Chromium Steel, Plate, Sheet and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Fire Protection Association (NFPA) Standard:

No. 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch St., Boston, MA 02110.)

National Electrical Manufacturers' Association (NEMA) Standard:

ICS - Industrial Controls and Systems.

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 155 East 44th Street, New York, NY 10017.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the item to be procured under this specification for first article inspection and approval (see 4.3 and 6.4).

3.2 Standard product. The item(s) delivered under this specification shall be the manufacturer's commercial product, except for any changes necessary to comply with specification requirements. All like items furnished on any one contract, including parts and subassemblies thereof shall be new and interchangeable.

3.3 Codes and standards. The item(s) shall comply with the applicable requirements of UL Standards, NEMA Publication ICS 1970, NFPA Standard No. 70 and ASME Code for Unfired PRESSURE Vessels, when applicable.

3.4 Compliance. Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the current version before use.

the contracting officer or his authorized representative satisfactory evidence that the item(s) that he proposes to furnish under this specification meet the applicable requirements of UL Standards, NEMA ICS, NFPA No. 70, and ASME Standard for Unfired Pressure Vessels, when applicable.

3.4.1 NFPA. Acceptable evidence of meeting requirements of NFPA shall be the manufacturer's certified statement that the drycleaning finishing equipment is wired in accordance with NFPA No. 70, when applicable.

3.4.2 UL. Acceptable evidence of meeting requirements of UL shall be the UL label or a UL listing mark or a certification from an independent testing laboratory acceptable to the contracting officer or his authorized representative that the wiring, fittings, and conduit conform to applicable UL standards, when applicable.

3.4.3 NEMA. Acceptable evidence of meeting the requirements of NEMA shall be the manufacturer's certified statement that the motor controllers, switches, relays, time delays, and solenoids conform to performance requirements of NEMA ICS. A tag or label attached to these components stating they conform to this standard is acceptable evidence.

3.4.4 ASME. Acceptable evidence of meeting the requirements of ASME, when applicable, shall be the manufacturers' certified statement that the chests, chambets and cylinders are in compliance with the ASME Standard for Unfired Pressure Vessels.

3.5 Materials and components. Materials and components shall be as specified herein (and on applicable drawings). Materials not definitely specified shall be of the quality normally used by the manufacturer in the standard commercial items(s) provided that the completed items(s) comply with all provisions of this specification.

3.5.1 Corrosion-resistant metal. Corrosion-resistant metal used in the fabrication of the finishing equipment shall be corrosion-resisting steel conforming to the requirements of ASTM A167-70 or A176-71, as applicable; nickel-copper-alloy conforming to QQ-N-281 or composition A of QQ-N-288; or copper alloy castings conforming to alloy numbers G1 through G8 of QQ-C-390.

3.5.2 Materials for fasteners. Threaded fasteners and rivets shall be of carbon or alloy steel, except where brass or corrosion-resistant metal is to be fastened, in which case they shall be of brass or corrosion-resistant metal respectively (see 3.5.1). Where dissimilar metals are fastened, bolts, rivets, screws, and nuts shall be of corrosion-resistant metal (see 3.5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

3.5.3 Pipe, tube, fittings, and valves. Pipe, tube, fittings, and valves used for water, steam, and condensate lines shall comply with accepted plumbing practice.

3.5.4 Electrical conduit, fittings, and wire. Electrical conduit shall be rigid, electrical metallic tube or liquid-tight flexible conduit. All electrical wire shall be stranded copper, heat-resistant grade, thermoplastic insulated. Solid (nonstranded) wire shall not be used.

3.5.5 Motors. Motors shall be drip proof for operation in a 40° Centigrade (C) ambient temperature. Motors shall conform to the requirements of CC-M-636 or CC-M-641, as applicable, and to the following requirements:

(a) All motors shall have windings impregnated to resist moisture.

(b) Each motor of 1/8 horsepower rating or larger shall be provided with manually reset thermal-overload protection incorporated as a part of the motor or installed in the controller.

(c) Motors shall be equipped with ball bearings, except that motors of 1/2 horsepower or less when used in a horizontal application may have sleeve bearings.

(d) Motor bearings shall be a permanently lubricated type or shall have adequate and accessible means for lubrication.

3.6 Design and construction. The drycleaning finishing equipment shall be designed for use in a nonhazardous area. The completely assembled items when tested as specified in 4.6.4 shall show that assembly of components has:

(a) Complete and proper interrelationship.
(b) No leaks.
(c) No undue vibration or noise.
(d) No overheating of parts (e.g., bearings).
(e) Starting and stopping devices operate smoothly and positively.
(f) No structural failures.

3.6.1 Wiring. Wiring shall be provided between motors, controllers, and switches installed on the equipment with materials specified in 3.5.4 as applicable. All wiring shall terminate in connection boxes with provisions for connections beyond the item of equipment. Each conductor shall be identified by a different color or shall be clearly labeled. Wiring and connection diagrams showing any necessary connections required beyond the equipment shall be furnished with each item of equipment using electric power.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

3.6.2 Steam pressures. Assemblies of pipes, fittings, coils, cylinders, chests, and chambers using steam except for item 8 shall be designed for 100 pounds per square inch gage (psig) working pressure and shall be capable of withstanding a 200 psig hydrostatic pressure without leaks when tested as specified in 4.6.1.

3.6.3 Lubrication. Lubrication fittings for force-type systems shall be provided and accessibly located for lubricating bearings (see 3.5.5 (d) for motor exception).

3.6.4 Current characteristics. The electrical parts of machines shall be designed for the voltage, frequency, and number of phases specified (see 6.2). Operational and functional testing shall be performed at the voltage, frequency and number of phases specified.

3.6.5 Electromagnetic compatibility. When specified (see 6.2), equipment shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.6.7).

3.6.6 Finish. Unless otherwise specified (see 6.2), items of equipment shall be finished according to the manufacturer's standard practice except emergency stop and normal stop pushbuttons shall be red and this color shall be limited to pushbuttons.

3.6.7 Moisture and fungus-resistant treatment. When specified (see 6.2), electrical components of equipment covered by this specification shall be moisture and fungus-resistant treated with material conforming to and applied as specified in MIL-T-152.

3.6.8 Identification marking. For military procurements, each end item shall be marked in accordance with MIL-STD-130. For civil agency procurement, marking shall be in accordance with the manufacturer's standard practice.

3.7 Detail requirements.

3.7.1 Item 1 - air vacuum unit (for air vacuum presses). The vacuum system shall be the horizontal type (class 1) or the vertical type, (class 2) as stated in 1.2. Each class 1 and 2 unit shall consist of an electric-motor-driven (see 3.5.5) multistage centrifugal-type exhauster and a condenser tank. The number of presses that the air vacuum unit is to service shall be as specified (see 6.2). The exhauster shall be capable of maintaining a vacuum at sea level equivalent to 3/4-inch water column on 40 percent of the presses to be serviced and with these presses operating. This requirement shall be determined when tested as specified in 4.6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

3.7.1.1 Exhausters. The heads and intermediate sections of the class 1 and 2 exhausters shall be of ferrous metal, aluminum alloy, or aluminum. Sections shall be designed and fitted so as to minimize leakage and reduce air friction between stages.

3.7.1.1.1 Impellers. An aluminum impeller shall be furnished for each stage of exhauster and shall be mounted and keyed to a ferrous-metal shaft rotating in ball bearings provided on the head or heads. Bearings shall be of the permanently lubricated type or shall have adequate and accessible means for lubrication. Impeller sets and shaft shall be dynamically balanced.

3.7.1.1.2 Couplings. The impeller shaft of class 1 and class 2 units shall be connected to the motor by means of a flexible coupling, V-belt, or direct drive.

3.7.1.2 Base. The exhauster and motor for the class 1 units shall be properly aligned and bolted to a ferrous-metal base. The base shall be provided with anchor bolt holes and strips of sound absorbing material for isolation of the base from the floor. The base for class 2 units shall be equipped with dampening devices for isolation of the base from the floor and to minimize vibration.

3.7.1.3 Condenser tank. The condenser tank shall be of a size to match the exhauster furnished. The tank shall be constructed of ferrous metal of a thickness to withstand the necessary vacuum to be produced. Connections shall be provided on the tank for receiving air and condensate withdrawn from presses and for the outlet from the tank to the exhauster. A connection with a valve shall be fitted at a low level in the tank for draining the condensate.

3.7.1.4 Isolation. Two rubber sleeves of a size equal to the vacuum connections on the exhauster shall be furnished to isolate the piping from the exhauster vibration. Sleeves shall be reinforced to withstand the suction pressure developed by the exhauster and shall be of heat-resistant material.

3.7.2 Item 2 - bag, sleever. The bag sleever shall be a machine designed to finish sleeves of jackets, coats, and dresses by steam and warm air.

3.7.2.1 Description. The machine shall consist of a ferrous-metal base provided with anchor boltholes, supporting a sheet-steel cabinet that encloses an electric-motor driven fan and blower assembly, and provided with a steam-heated copper coil for heating the air as it is drawn into the fan and blower assembly. Approximately 36 inches from the floor, a U-shaped copper pipe shall extend from the side of the cabinet to allow for the emission of steam for conditioning sleeves. A canvas-type garment support, stretched on a metal frame, shall be affixed to the cabinet between the floorline and the copper arm. Foot pedals shall be provided to operate valves for controlling

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

the steam and air required for conditioning the sleeves. The steampipes extending from the cabinet into the sleeve assembly shall have a combination asbestos-flannel protective pad and be provided with a nylon sleeve-shaping bag and a nylon overbag to control the expansion of those portions of the shaping bag not utilized for any particular sleeve.

3.7.2.2 Cabinet. The cabinet shall be supplied with removable panels for inspection and maintenance of the assemblies enclosed therein. Cabinet shell shall further be provided with a grille positioned in the area of the enclosed copper steam coil.

3.7.3 Item 3 - finishing board class 1 and class 2. The finishing boards shall be a device for the hand finishing of garments using an electric steam iron on a board provided with facilities for the application of dry steam and vacuum through the top. The finishing boards shall have a metal top with openings or screen surface arranged for application of dry steam or vacuum by footcontrolled valves. The vacuum shall be induced by either air or steam, as specified (see 6.2). A canvas-type garment support, hung on a ferrous-metal frame, shall be provided between the board and the floor. An electric steam flatiron conforming to 3.7.5 shall be furnished with the class 1 board. The board garment support, foot pedals, and support for the electric and steam connections to the iron shall be supported by a cast iron stand or cast ferrous-metal stand that is provided with anchor bolt holes. The board shall be a minimum of 45 inches long and 35 inches above the floorline. The board shall be provided with padding, a cover cloth, an 18 and 12 inch pleat setter, pleat setter rack, and a hand pad. When specified (see 6.2), the manufacturer's standard swinging sleeve board shall be furnished.

3.7.4 Item 4 - garment finisher. The garment finisher shall be a machine which shall impart final finish to dresses, coats, jackets, and other similar garments after the drycleaning process. Garments to be finished shall be arranged over a collapsible bag-type form which shall expand by application of forced air or air and steam to fill out the garment being finished. The machine shall be capable of emitting steam at the will of the operator into the bag form and thence through both the bag and garment.

3.7.4.1 Frame. The frame shall be constructed of ferrous metal to support controls, bag frame, support column, steamer, and blower assemblies. The frame, with the exception of a housing for the motor, if used, and a housing for the blower fan, shall be covered with metal panels provided with sufficient readily removable smaller panels for inspection and maintenance of inclosed mechanisms. The frame shall be provided with anchor bolt holes.

3.7.4.2 Controls. The garment finisher shall be furnished with levers for manually regulating the size of the form at waist, hip, and lower positions to accommodate various sizes of garments, or size of form may be regulated by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

force of air and steam thru the bag to the garment. The finisher shall also be equipped with a timer or timers and pedals or other devices for automatic control of the flow of steam and hot air into the bag form.

3.7.4.3 Steam. The garment finisher shall be provided with steam accessories that are capable of handling steam at 100 psig (see 3.6.2). The machine shall be equipped with a steam coil, fabricated of copper, for heating the air that is forced into the garment bag, and with a steaming device for the emission of live steam into the garment bag.

3.7.4.4 Finishing bag. The machine shall be furnished with a nylon garment bag that is capable of adjustment in width at the waist, hip, and bottom to provide for necessary adjustments to handle various type garments or the manufacturer may furnish his standard type finishing bag. In lieu of adjustable bags, the machine may be equipped with different sizes of removable bags or forms for the various sized garments or equipped with controls which automatically size the bag upon contact of the bag with the garment.

3.7.4.4.1 Bag support. Unless otherwise specified (see 6.2), a standard height support shall be furnished for the bag.

3.7.4.5 Blower. The machine shall be equipped with an electric-motor-driven fan (see 3.5.5) to provide for the forcing of air through the steam heating coil and into the interior of the garment bag.

3.7.4.6 Warning marking. Each garment finisher shall have a warning plate of noncorrodible metal or a decalcomania permanently affixed in a conspicuous place. The warning marking shall bear the following in red letters not less than 1/4-inch high:

"WARNING - This machine is not intended for use in a HAZARDOUS AREA."

3.7.4.7 Accessories. The machine shall be equipped with assemblies at both the front and the back to provide for the securing of the garment being finished to the inflated bag without the necessity of buttoning or otherwise fastening the garment. In addition, a set of adjustable sleeve formers or built-in sleeve formers shall be provided.

3.7.5 Item 5 - flatiron, electric, steam. The steam flatiron shall be electrically heated and designed for supplying dry steam through perforations in the bottom of the shoe, at the option of the operator. Flatirons shall be size 3 to 4 pounds and 5-1/2 to 6-1/2 pounds as stated in 1.2.

3.7.5.1 Shoe. The shoe of the flatiron shall be cast corrosion-resisting metal, aluminum, or bronze arranged so that any entrained moisture entering with the steam shall be evaporated, thus providing dry steam through the shoe. The casting shall be free of blowholes and shall have exposed surfaces finished smooth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

3.7.5.2 Upper body. The upper part of the flatiron shall consist of a cover for the shoe and heating element, a thermosetting plastic or cork grip handle or knob, and an adjustable thermostat for the electric-heating element. The shoe cover shall be chromium-plated and finished with a mirror surface. The handle shall be adapted to the operator's hand and the thermostatic controls arranged for fingertip operation. Not less than five feet electric heating cord and rubber steam hose shall be supplied with each flatiron. Electric cord and steam hose shall be replaceable for maintenance purposes.

3.7.5.3 Steam. The flatiron shall be capable of utilizing steam at 100 psig (see 3.6.2).

3.7.5.4 Header assembly. When required and specified (see 6.2), the steam iron shall be furnished with a header assembly which contains a solenoid valve, pilot light, switch, support for cord and hose and header adapter.

3.7.6 Item 7 - spotting board. The steam spotting board shall be designed for removing spots. The unit shall consist of a spotting board, steam spotting gun, stand, spotting and tamping arm, controls, and garment tray, and shall have space for storing spotting compounds. The board shall be not more than 60 nor less than 48 inches long, not less than 12-1/2 inches wide at the widest point, and approximately 37 inches high.

3.7.6.1 Fabrication. The top of the spotting board shall be fabricated from corrosion-resistant metal, the narrow end of which shall be screened or the top may be screened the entire length or perforated for use with a steam spotting gun. In lieu of a complete corrosion-resistant metal top, the non-perforated portion may be of ceramic or similar hard material.

3.7.6.2 Steam spotting gun. The steam spotting gun shall consist of a steam separator, valve and control, spring arm, gun, steam hose, and fittings. The steam gun shall be arranged for ready use on any part of the board and shall be equipped for supplying either dry or wet steam, or compressed air at the will of the operator by means of a foot treadle. The gun shall be constructed of brass or corrosion-resistant metal throughout, except for the handgrip which shall be material conforming to the manufacturer's commercial practice.

3.7.6.3 Stand. The stand shall be the support for the board, the spotting and tamping arm, the spotting gun, controls, garment tray, and spotting compounds. The stand shall be constructed of ferrous metal and provided with anchor bolt holes.

3.7.6.4 Spotting and tamping arm. Each board shall be supplied with a small swivel arm fabricated from corrosion-resistant metal and designed for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

tamping and spotting. The swivel shall be arranged to permit swinging the arm out of the operator's way when not in use.

3.7.6.5 Controls. The controls shall be operated by pedals, and shall provide steam or compressed air at the will of the operator (see 3.7.6.2).

3.7.6.6 Garment tray. A garment tray shall be provided under the spotting board for supporting the garments being processed. This support shall consist of a ferrous-metal frame attached to one end of the stand and a canvas attached to the frame. The garment tray size shall be not less than the spotting board size.

3.7.6.7 Storage space. Storage space shall be located at the wide end of the board for storing special spotting chemical compounds.

3.8 Item 8 - coat finisher. The coat finisher shall be a machine capable of automatic presteaming and manual presteaming and automatically forming and air drying men's dry-cleaned suit coats, uniform coats, overcoats and topcoats. The machine shall be designed for fully-automatic operation with an adjustable timer to control the steam and air cycle. The machine shall be equipped with a pressing plate or shape-conforming device to impart a press finish to the collar and lapels; front and rear clamps; pressure regulators, gauges, and controls. The machine shall also be equipped with a hand operated steam spray gun for touching up wrinkles, and sleeves.

3.8.1 Frame. The unit shall have a steel frame welded to form a rigid structure to support controls, air form, steamer, and blower assemblies. Frame shall be covered with metal panels provided with sufficient removable smaller panels for inspection and maintenance of inclosed mechanisms or the frame may be covered with fiberglass panels which are removable for inspection and maintenance. The frame shall be provided with anchor bolt holes and anchor bolts.

3.8.2 Air expanding form. The form shall be a nylon or dacron bag that is capable of automatic expanding to conform to the exact size of coat (see 4.6.5) and to shape coat body. The bag shall inclose a padded buck that is perforated for rapid transfer of steam and air through buck padding or the bag shall inclose a steam heated tubular support.

3.8.3 Collar shaper. The collar shaper or steam head shall be self-forming to fit the tailored cut of the collar and lapels (see 4.6.5). An air pressure regulator and gauge shall be furnished for collar shapers which are air actuated.

3.8.4 Shoulder expanders. The form shall have air operated shoulder expanders that automatically adjust to coats of all sizes, and retract after each operation (see 4.6.5). When specified (see 6.2), the shoulder expanders shall also be capable of being manually operated.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:00Z
Check the source to verify that this is the current version before use.

3.8.5 Front and rear clamps. The machine shall be equipped with front and rear clamps which hold the coat while the expandable bag shapes and forms the coat (see 4.6.5).

3.8.6 Blower. The machine shall be equipped with an electric motor driven fan to provide for forcing of air across the steam coil and into the interior of the air expanding bag (see 4.6.5).

3.8.7 Controls. The machine shall be equipped with timers adjustable from 0 to a minimum of 55 seconds for automatic control of the flow of steam and hot air into the bag form and shall have pedal(s) or other devices for presteaming of coats. The controls shall also automatically release the shoulder expander (see 4.6.5).

3.8.8 Sleeve forms. Unless otherwise specified (see 6.2), sleeve forms in the quantity normally furnished commercially shall be supplied. On machines which employ automatic sleeve forms, the operation shall also be performed manually.

3.8.9 Working pressures. Assembly of pipe, tube, fittings, coils, cylinders, chests and chambers (except spray chambers) using steam shall be designed for a working steam pressure of 65 psig minimum and shall be capable of withstanding a hydrostatic pressure established in accordance with the provisions of the ASME Code for Unfired Pressure Vessels without any leaks. Air lines and cylinders shall be designed for a working pressure of 70 psig minimum without any leaks when tested as specified in 4.6.2.

3.9 Item 9, cabinet, drying and deodorizing. The cabinet shall be designed to hold garments on hangers for drying and deodorizing purposes.

3.9.1 Cabinet. The cabinet shall be fabricated of galvanized or enameled ferrous metal and shall be 74 inches high, 40 inches wide, and 40 inches in depth, with a hinge-type controlled damper. There shall be a hinged and latched full-length door or doors in the front panel to allow for the placing of garments on hangers into the cabinet. The inside of the front, back, and side walls shall be insulated. A rust proof hanger rod, extending the full width or depth of the inside of the cabinet shall be mounted in the center of the depth or width of the cabinet not more than 5 inches below the top of the cabinet. The cabinet shall be provided with a false top, false bottom, and 4 ferrous metal feet approximately 2 inches high. The feet shall be provided with anchor boltholes.

3.9.2 Heating. The cabinet shall be provided with steam coils of copper or copper and aluminum construction and shall be of extended surface fin and tube type, designed for a working pressure of 100 pounds per square inch gage (psig), and capable of withstanding the 200 psig hydrostatic pressure test specified in 4.6.1 without any leaks. The coils shall be of sufficient size

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

to provide for the drying of freshly drycleaned light-weight garments in a maximum of 15 minutes to not more than 115 percent of their bone-dry weight (see 4.6.6).

3.9.3 Fan. The cabinet shall be provided with an exhaust fan located on top of the cabinet to circulate heated air through the cabinet. The fan shall be driven by a motor conforming to 3.5.5.

3.10 Item 10 - reel, sorting. The sorting reel shall be of ferrous metal, galvanized or enameled and designed for supporting sorted finished drycleaning on coathangers hung on a revolving reel mounted on a pedestal.

3.10.1 Reel. The reel shall be 48 inches in diameter and shall be mounted on the pedestal with either ball or tapered roller bearings to allow free and positive revolving. The rail of the reel shall be provided with not less than 50 slots for receiving coathangers. Each slot shall be provided with a hanger suitable for supporting belts and neckties.

3.10.2 Pedestal. The pedestal shall be of such construction that the mounted reel can be adjusted to be from 62 to 80-inches from the floor. The base of the pedestal shall be round and of such diameter and weight to support the reel without tipping under any unbalanced load of garments hanging on the reel by coathangers.

3.11 Workmanship. The finished end items shall be free from defects such as fractures, splits, punctures, tears, dents, creases, bows, miscasts, deteriorations, or malformations. There shall be no sharp edges, burrs, or slivers.

3.11.1 Application of finish. The finish applied to the end items shall be continuous, smooth, adherent, without discolorations or foreign material imbedded, and contain no sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, cracks, scratches, pores, pits, lumps, flux, or orange peel. No rust, rough grinds, or toolmarks shall show through the coating.

3.11.2 Welders. The welders performing the welding on pressure vessels shall be certified welders and have passed the qualification test as prescribed by either the "Standard Qualification Procedures of the American Welding Society" or "Welding Qualification of the American Society of Mechanical Engineers" code. The supplier will furnish the Government with a list of names of his welders who are certified and have passed the test of either referenced codes and he shall certify that the welding of this equipment was performed by welders on the list.

3.11.3 Welding. The surface of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be continuous (on structural supports) sound, smooth, and free from porosity,

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the current version before use.

cracks, incomplete fusion, and deformation of material. All scale and flux (when flux is used) shall be removed from the finished welds.

3.11.4 Soldering. Soldering shall be complete and adherent with all flux and residue removed and shall contain no pinholes.

3.11.5 Threaded fasteners. Threaded fasteners shall not be broken, stripped, fractured, or loose.

3.11.6 Rivets. Rivets shall be driven to completely fill the holes, with full size heads neatly finished and in full contact with the surfaces of the riveted members.

3.11.7 Electrical wiring. Wiring shall not be cut, abraded, or have excessive insulation stripped, and shall be properly and tightly joined at terminals. Wiring shall have adequate slack to provide strain relief.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchse order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier shall insure that all components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards unless excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article. When a first article is required, the item(s) shall be tested as specified in 4.6.1 through 4.6.6 and when applicable, 4.6.7. Failure of any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the current version before use.

4.4.1 Component and material inspection. In accordance with 4.1.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 End item inspection. The inspection lot shall be all item(s) of the same class or size as applicable, offered for inspection at one time.

4.4.2.1 Visual examination. Examination of the end item shall be made for the defects in table I. The inspection level shall be level II and the acceptable quality level (AQL), expressed in terms of defects per hundred units shall be 2.5 for major defects and 6.5 for total defects.

TABLE I. Classification of defects

Examine	Defect	Classification	
		Major	Minor
Finish	Type of finish not as specified.	X	
	Blistered, peeled, chipped, or area of no film.		X
Construction and workmanship general (applicable to all components and assemblies)	Part missing.	X	
	Fractured, split, punctured, dented, deteriorated, bowed, malformed.	X	
	Not in proper alignment.	X	
	Sharp burr, edge, sliver, or splinter.	X	
	Component loose.		X
	Not connected or joined as specified.	X	
	Any adjustable assembly that cannot be adjusted to perform the function intended.	X	
	Any component not readily accessible for servicing where required.		X
	Anchor bolt holes not provided (where applicable).	X	
Welding and brazing (where required)	Missing, incomplete, burn holes, cracked, fractured, or otherwise not fused.	X	
	Slag inclusion, slight undercut, not smooth and uniform, scale or flux deposits not removed.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification	
		Major	Minor
Soldering (when applicable)	Missing, not adherent, or incomplete.	X	
	Not clean (flux or flux residue not removed), not smooth (surface not finished neatly) or pinholes in solder.		X
Threaded fasteners	Missing, broken, stripped, or fractured.	X	
	Loose.		X
Rivets (when applicable)	Broken, loose, not peened, or insufficiently peened.	X	
Electrical assembly	Wiring cut, abraded, not properly joined, loose at terminal, or not inclosed in specified conduit where required.	X	
	Adequate slack not provided for wiring to relieve strain or insulation stripped from wiring.		X
	Conductors not identified.	X	
Gages and instruments	Not properly mounted.	X	
Lubrication (where applicable)	Not lubricated where required.	X	
	Not specified type lubrication fitting.	X	
	Lubrication fitting not accessible for servicing.		X
Marking for identification	Missing, incomplete, not legible.		X
Warning plate	Missing, incomplete, not legible.	X	

4.4.2.2 Dimensional examination. The item(s) shall be examined for compliance with dimensions specified. Any dimension not within this specification tolerance shall be a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the current version before use.

4.4.2.3 End item testing. When a first article is not required, the first produced item(s) shall be examined and tested as specified in 4.6.1 through 4.6.6, as applicable and when applicable, 4.6.7. Each item(s) or each sample item(s) shall be tested as specified in 4.6.1 through 4.6.4, as applicable. Failure to pass a test shall be cause for rejection of the inspection lot or failure to pass a test shall be a defect. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed as defects per hundred units. The operational test in 4.6.4 and, when applicable, 4.6.5 and 4.6.6 shall be performed and shall be witnessed by a representative of the Government prior to acceptance unless satisfactory evidence is produced that this item has previously satisfactorily passed this test either in the manufacturer's plant or in a commercial application (see 6.4). The Government reserves the right to check-test such items to determine validity of the evidence produced. Operational and functional tests shall be performed at the specified voltage, frequency, and number of phases specified.

4.5 Code and standard examination. Certificate of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with specification requirements shall be examined and validated. When moisture and fungus treatment is specified, the supplier shall furnish proof that electrical components comply with 3.6.7.

4.6 Test methods.

4.6.1 Hydrostatic pressure test. All assemblies of pipes, fittings, coils, cylinders, chests, and chambers, using steam, of each item of equipment covered by this specification shall be tested with 200 psig hydrostatic pressure by the supplier to determine compliance with 3.6.2 and 3.9.2. The test pressure shall be maintained a sufficient length of time to determine that no leaks are present. Any nonconformance shall constitute failure of this test.

4.6.2 Air pressure tests. All air lines and cylinders shall be tested at manufacturers' operating pressure. The test pressure shall be maintained for ten (10) minutes to determine that no leaks are present. Noncompliance shall constitute failure of this test.

4.6.3 Vacuum test. Vacuum units shall be tested for compliance with the requirements of 3.7.1 by measuring with a 3-inch diameter cup and manometer, the vacuum produced on the padded surface of any one of the number of presses to be serviced. Any nonconformance shall constitute failure of this test.

4.6.4 Operational testing. Each power-operated item covered by this specification shall be connected to electric power, air, and steam (as applicable for operation), and operationally tested by the supplier. The test shall be maintained a sufficient length of time to determine that all performance requirements specified in 3.6 have been met. Any nonconformance shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T12:00Z
Check the source to verify that this is the currentversion before use.

4.6.5 Functional coat finisher testing. Each coat finisher shall be connected to electric power, steam, and compressed air and tested with coats. The following items and operations shall be checked to determine compliance with the following:

a. Complete and proper interrelationship to assembled components (see 3.6).
b. Starting and stopping devices operate smoothly and positively (see 3.6).
c. No structural failures (see 3.6).
d. Air expanding bag expands to size of coat (see 3.8.2).
e. Collar shaper operates (see 3.8.3).
f. Shoulder expander expands and retracts (see 3.8.4).
g. Front and rear clamps operate (see 3.8.5).
h. Blower operates (see 3.8.6).
i. Controls and timer operate (see 3.8.7).

Any noncompliance constitutes failure of this test.

4.6.6 Functional drying and cabinet drying tests. The drying cabinet shall be connected to a source of steam and electricity and tested by using not less than four freshly drycleaned lightweight garments that have not been dried in a tumbler, to determine compliance with the drying requirements of 3.9.2. Any nonconformance shall constitute failure of this test.

4.6.7 Electromagnetic compatibility. When electromagnetic compatibility is required, the first article or initial unit of production, as applicable, shall be tested by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or an independent testing agency. The supplier shall furnish the contracting office written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic test report and the requirements meet MIL-STD-461.

4.7 Examination of preparation for delivery. Examination shall be made to determine that preservation, packaging, packing, and marking are in accordance with MIL-L-3153.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Preservation, packaging, and packing shall be in accordance with the applicable level A, B, or C requirements of MIL-L-3153 (see 6.2).

5.2 Marking.

5.2.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

5.2.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Miscellaneous drycleaning finishing equipment covered by this specification is intended for use in fixed drycleaning establishments.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Item, class, and size required (see 1.2).
(c) When a first article is required (see 3.1, 4.2, and 6.3).
(d) Electrical characteristics: voltage, frequency, and number of phases (see 3.6.4).
(e) When electromagnetic compatibility is required (see 3.6.5).
(f) Finish, when other than manufacturer's standard is required (see 3.6.6).
(g) When moisture and fungus-resistant treatment is required (see 3.6.7).
(h) Number of presses the air vacuum unit is required to service (see 3.7.1).
(i) Type of vacuum system (air or steam induced) required for the finishing board (see 3.7.3).
(j) When bag support other than standard height is required for the garment finisher (see 3.7.4.4.1).
(k) When flatiron requires a header assembly (see 3.7.5.4).
(l) When shoulder expanders require manual operation (see 3.8.4).
(m) When sleeve forms are not required (see 3.8.8).
(n) Selection of applicable levels of preservation, packaging, and packing (see 5.1).

6.2.1 Contract data requirements. Any requirements for contract data items such as equipment manuals for the items covered by this specification should be included in DD Form 1423 Contract Data Requirements List, and cited in the contract.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Armed Services Procurement Regulations ASPR 7-104.55. The first article should be a preproduction sample, initial production item, or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the currentversion before use.

6.4 Successful commercial operation. Invitation for bids should specify that no item of equipment will be acceptable unless the manufacturer has had equipment of approximately the same type and design as that specified operating successfully in a commercial or institutional drycleaning plant or plants for at least one year. Equipment installed for test purposes in a manufacturer's plant or laboratory will not be considered as complying with this requirement.

6.5 Supersession data. This revision contains the requirements of IP/DES S-13-0 Coat Finisher, Automatic Drycleaning dated April 30, 1970, as item 8. Items 9 and 10 were formerly items 1 and 4 of OO-D-730A dated November 15, 1966.

MILITARY CUSTODIANS:

Army - GL
Air Force - 84

Review activities:

Army - MD
Air Force - 45

User activity:

Navy - SH

Preparing activity:

Army - GL

CIVIL AGENCIES COORDINATING ACTIVITIES:

DC GOVT - DCG
GSA-FSS
HEW - NIH
VA - DMS

Project No. 3510-0230

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 20 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
00-D-735C Drycleaning Finishing Equipment, Miscellaneous

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 54 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:00Z
Check the source to verify that this is the current version before use.