00-G-1513B
August 19, 1976
SUPERSEDING
Fed. Spec. 00-G-1513A
March 22, 1973

FEDERAL SPECIFICATION

GARBAGE DISPOSERS, HOUSEHOLD

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers garbage disposers for use in the home.

1.2 Classification. The disposers shall be of the following types and sizes:

Type I - Continuous Feed
Size 1 - 1/2 Horsepower
Size 2 - 1/3 Horsepower

Type 2 - Batch Feed
Size 1 - 1/2 Horsepower

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Association of Home Appliance Manufactures (AHAM) Standards:

AHAM No. FWD. 1 - Performance Evaluation for Household Food Waste Disposers.

(Application for copies should be addressed to the Association of Home Appliance Manufactures, 20 North Wacker Drive, Chicago, IL 60606.)

American National Standards Institute (ANSI) Standards:

C1 - National Electrical Code.
C52.1 - Motors and Generators.

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

Underwriters' Laboratories, Inc., (UL), Standards:

UL 430 - Waste Disposers.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio St., Chicago, IL 60611; 333 Pfingsten Rd., Northbrook, IL 606062; 1285 Walt Whitman Rd., Melville, L.I., NY 11746; 1655 Scott Blvd., Santa Clara, CA 95050.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Assication, Inc., Tariff Order Section, 1616 P Street, NW., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:01Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Preproduction sample. When specified in the procurement document (see 6.2), before production is commenced, a sample of the disposer ordered shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. Approval of the preproduction sample authorizes commencement of production, but does not relieve the supplier of responsibility for compliance with the detailed provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product. The disposer delivered under this specification shall be the manufacturer's current standard cataloged product. The manufacturer shall be regularly engaged in the manufacture of garbage disposers.

3.3 Fire and Casualty Hazards.

3.3.1 Each contractor shall submit to the contracting agency proof that the disposers he proposes to supply under this specification conform to the applicable requirements of the Underwriters' Laboratories, Inc., Standard UL 430, Waste Disposers. The label, or listing with re-examination, of the Underwriters' Laboratories, Inc., may be accepted as evidence that the disposers conform to this requirement.

3.3.2 In lieu of the label, or listing with re-examination, the contractor may submit independent proof, satisfactory to the contracting agency, that the disposer conforms to the applicable requirements of the published standards, including methods of test, of the Underwriters' Laboratories, Inc. Standard UL 430.

3.3.3 Compliance with the above preliminary requirements in regard to fire and casualty hazards does not absolve the contractor from complete compliance with the requirements of this specification in order to secure acceptance of his disposer.

3.4 Material. All material shall be of a quality suitable for the intended use of household garbage disposers. In all water contact areas, corrosion resistant metal or non corrosive material shall be used. The grinding chamber, the grinding wheel and the grinding ring shall be made of corrosion resistant steel (see 4.3.3).

3.5 Design. The design of the disposer shall be in accordance with the best engineering practice to grind garbage and wash it down the drain. The ground garbage shall not pack or adhere to any part of the disposer when water is flowing. The unit shall not leak. Ejection of garbage and water back into the sink during the operation of the disposer shall be minimized. It shall have easy accessibility for maintenance and service where installed. It will be either a continuous feed model or a batch feed model powered by either a 1/3 or a 1/2 horsepower electric motor (see 3.7.2) as specified in the procurement document.

3.5.1 Grinding wheel. The grinding wheel and all rotating parts shall be accurately balanced to insure a vibrationless, quiet running disposer.

3.5.2 Bearings. All bearings for rotating elements shall be of the permanently lubricated type.

3.6 Construction. Each disposer shall consist essentially of a grinding chamber containing the grinding ring, a grinding wheel with impellers, and the electric driving motor. The discharge outlet of each disposal shall be such that it can be connected to a standard pipe of not less than 1-1/2 inches ID. Disposers shall be designed for suspension mounting to a sink with a 3-1/2 inch drain opening and shall be suitable for either right or left hand "S" trap or "P" trap waste installation. The disposer shall be provided with a hopper opening cover which will also serve as a sink stopper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.7 Electrical requirements.

3.7.1 Wiring connections. Wiring connections for disposers shall be made at the manufacturer's plant, and shall be wired to provide for permanent connection to the house wiring system.

3.7.2 Motors. Motors shall be alternating current (ac) type conforming to the requirements of ANSI C52.1 and UL 430, and shall have the following characteristics:

Ambient Temperature	40°C.
Enclosure	Dripproof
Duty	Varying
Horsepower	1/3 or 1/2 horsepower (see 3.5)
Voltage	Nominal 115 volts
Bearings	Permanent Lubricated type
Overload Protection	Thermal Activated; Manual or automatic reset

3.7.3 Starting controls and wiring. Starting controls and wiring shall be in accordance with ANSI C1 and UL 430.

3.8 Finishing and painting. The equipment shall be finished and painted in accordance with the manufacturer's standard practice for this type of equipment.

3.9 Manuals. One copy of the manufacturer's instruction manual covering the use and care of the disposer shall be provided with each disposer. Installation, maintenance and parts list manuals shall be provided in the quantities specified in the contract or purchase order (see 6.2).

3.10 Identification plate. Each disposer shall be marked in accordance with UL 430.

3.11 Workmanship. The disposers shall be assembled and made free from blemishes, defects, burrs, and sharp edges (except for cutting edges); accuracy of dimensions and markings of parts and assemblies; thoroughness of soldering, welding, brazing, and painting; alignment of parts and tightness of assembly screws and bolts.

3.12 Performance requirements.

3.12.1 Fineness. When tested as in 4.5, 99% or more of the discharge shall pass through a 1/2" (12.7mm) sieve; 95% or more of the discharge shall pass through a 1/4" (6.3mm) sieve.

3.12.2 Grinding rate. When tested as in 4.5, 75% or more of the rib bone shall be ground in one minute. Within 150 seconds the rib bone shall be totally ground up. Within 70 seconds the citrus rinds shall be totally ground up. 98% or more of the mixed load shall be ground up in one minute.

3.12.3 Jamming. When tested as in 4.5, the disposer shall not have more than an average total of two running and starting jams.

3.12.4 Damage resistance. When tested as in 4.5, if damage results, repeat the Grinding Rate Tests (see 3.12.2). The results shall be within 10% of the original tests. After the damage resistance test, the disposer shall be operable and shall not leak.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure that supplies conform to prescribed requirements.

4.2 Preproduction sample inspection. When a preproduction sample is required it shall be examined for the visual defects in table I and tested as specified in 4.5.

Source: https://assist.dla.mil -- Downloaded: 20260410-26T12:01Z
Check the source to verify that this is the current version before use.

4.3 Sampling for inspection. Sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Visual examination. Examination shall be made of the end item for defects in table I. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5, for major defects and 6.5, for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defects	Classification	
		Major	Minor
Standard product	Not manufacturer's current standard cataloged product.	X	
Design	Disposer does not permit accessibility for maintenance and service.	X	
	Parts missing.	X	
	Parts deformed	X	
Materials	Not as specified.		X
Construction	Disposer not designed for suspension mounting.	X	
	Not wired for permanent connection to the house wiring system	X	
Finishing and Painting	Not uniformly applied		X
Manuals	User's manual missing	X	
	Less than the requested amount of the following manuals: Installation, maintenance, parts list	X	
Identification Plate	Does not meet UL 430.	X	
Workmanship	Welds not clean.		X
	Welds not smooth or uniform.	X	
	Poor fit due to poor faying surfaces.	X	
	Exterior surfaces of disposer not clean.		X

4.3.2 Dimensional examination. An examination shall be made of the disposers for dimensional defects. Any dimension not within specified requirements shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.3.3 Certification. The manufacturer, when requested shall certify in writing to the contracting officer or his representative that the steel used for the grinding components of the disposers offered to the government is corrosion resistant (see 3.5.3).

4.3.4 End product testing. Disposers shall be tested in accordance with 4.5. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units. Any test not within specified requirements shall be classified as a defect.

4.4 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5. Defects shall be scored in accordance with table II. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operation. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, inadequate stapling, loose strapping, or distortion of container.
Contents	Number per container is more or less than required. Contents exceeds weight limitation of the applicable box specification.

4.5 Tests. The disposers shall be tested for fineness, grinding rates, jamming and damage resistance in accordance with the test procedures set forth in AHAM Standard FWD.1 for compliance with paragraph 3.12. The final test results shall be available to the contracting official or his representative upon request.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Machines. Each complete machine with manuals shall be preserved in accordance with MIL-P-116, Method IA, submethod as applicable. The breaking, pulverizing, and expelling section of the machine shall be coated with type P-3 preservative.

5.1.2 Level B.

5.1.2.1 Machines. Each complete machine with manuals shall be preserved in accordance with MIL-P-116, method III.

5.1.3 Level C. Machines with applicable manuals shall be preserved and packaged in accordance with the manufacturer's commercial practice, providing that this insures protection for the contents during shipment and provides for safe delivery to its destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Each complete machine with applicable manuals packaged as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-621, class 2; PPP-B-601, overseas type or to PPP-B-640, class 2. Boxes shall be closed and strapped in accordance with the applicable box specification.

5.2.2 Level B. Each complete machine with applicable manuals, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-621, class 1; PPP-B-601, domestic type; or to PPP-B-640, class 1; or to PPP-B-636, class domestic, variety DW, grade 275 minimum.

5.2.3 Level C. Machines and applicable manuals packaged as specified in 5.1.3 shall be packed in a manner which will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply to the Uniform Freight Classification rules and the National Motor Freight Classification rules, as applicable.

5.3 Marking. In addition to any special markings required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. All marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. All marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The household garbage disposers are intended primarily for Department of Defense Military Family Housing installations. The disposers are for shredding foot waste into fine particles which are washed into a drain pipe.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a) Title, number and date of this specification.
b) Type and size required (see 1.2).
c) If a preproduction sample is required (see 3.1).
d) Manuals required and number (see 3.9).
e) Preservation and packaging (see 5.1).
f) Packing (see 5.2).
g) Marking (see 5.3).

MILITARY INTEREST:

Air Force - 84
DSA-CS

CIVIL AGENCY COORDINATING ACTIVITY:

HEW-FDA, FEC

Preparing Activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.