00-I-2100
March 30, 1979
SUPERSEDING
(See 6.6)

FEDERAL SPECIFICATION

IRONERS, FLATWORK, COMMERCIAL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers chest-type flatwork ironers.

1.2 Classification. The flatwork ironers shall be of the following sizes as specified (see 6.2).

Size 2 - 6 rolls
Size 3 - 8 rolls

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20202.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers, at the General Services Admininstration Regional Offices in Boston, New York, Philadelphia, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Houston, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-T-152	-	Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment.
MIL-L-3153	-	Laundry and Dry Cleaning Machinery and Equipment (For Fixed Installations), Preparation For Delivery Of.
MIL-P-43219	-	Paddings and Covers For Flatwork Ironer Roll.

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-461	-	Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-462	-	Electromagnetic Interference Characteristics, Measurement Of
MIL-STD-1474	-	Noise Limits for Army Material

(Copies of Military specifications, and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

29 CFR 1910 - Occupational Safety and Health Act (OSHA) Standards

(The code of Federal Regulations (CFR) and Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Electrical Manufacturers' Association (NEMA)

ICS - Industrial Controls and Systems

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 155 East 44th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

Underwriters Laboratories Inc. (UL) Standards

(Application for copies of applicable standards should be addressed to the Underwriters Laboratories Inc., 207 East Ohio Street, Chicago, IL 60611; 333 Pfingsten Road, Northbrook, IL 60062; 1285 Walt Whitman Road, Melville, L.I., NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050; or 2602 Tampa East Boulevard, Tampa, FL 33619.)

National Fire Protection Association (NFPA)

Standard No. 70 - The National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02210.)

American Society of Mechanical Engineers (ASME)

Boiler and Pressure Vessel Code, Section VIII, Pressure Vessels Welding Qualifications of the American Society of Mechanical Engineers

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The ironers delivered under this specification shall be the manufacturer's commercial product, except for any changes necessary to comply with specification requirements.

3.2 Codes and standards. The ironers shall comply with the applicable requirements of NEMA ICS, UL, NFPA No. 70, and OSHA 29 CFR 1910.

3.2.1 Compliance. Prior to commencing production, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the ironers that he proposes to furnish under this specification meet the applicable requirements of NEMA ICS, UL, NFPA No. 70 and OSHA.

3.2.2 NEMA. Acceptable evidence of meeting the requirements of NEMA shall be a certificate of compliance certifying that motor controllers, switches, relay and time delays conform to ICS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.2.3 UL. Acceptable evidence of meeting the requirements of UL shall be a certificate of compliance certifying that the wiring, fittings and conduit conform to the applicable UL standard.

3.2.4 NFPA. Acceptable evidence of meeting the requirements of NFPA shall be a certificate of compliance certifying that the ironer's wiring conforms to NFPA No. 70.

3.2.5 OSHA. Acceptable evidence of meeting the applicable safety and health standards of OSHA shall be a certificate of compliance certifying that the ironers furnished conform to OSHA Standards 29 CFR 1910. (c) (3) (ii) (a), 29 CFR 1910.264e (1) and (2), and 29 CFR 1910.212 (b).

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for ironers provided the completed items comply with all provision of this specification (see 6.3).

3.3.1 Conduit, fittings, and electric wire. Electrical conduit shall be electrical metallic tubing or flexible metallic conduit. All electric wire shall be stranded copper, heat-resistant grade, thermoplastic insulated. Solid (nonstranded) wire shall not be used.

3.3.2 Motors. Motors shall conform to the requirements of CC-M-1807 and the following:

(a) All motors shall have windings impregnated to resist moisture.

(b) Each motor shall have the proper starting characteristics and ample power, and adequate thermal dissipation capacity to comply with requirements specified herein, with a reasonable factor of safety, commensurate with the application and expected duty cycle to which each motor might be subjected under normal operating conditions.

(c) Motors shall be equipped with ball bearings, except that motors of 1/2 horsepower (hp) (373W) or less when used in horizontal applications may have sleeve bearings.

(d) Motor bearings shall be of the permanently lubricated type or shall have adequate and accessible means for lubrication.

(e) Each motor of 1/8 hp (93W) rating or larger shall be provided with thermal-overload protection incorporated as a part of the motor or installed in the controller.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

3.3.3 Motor control circuit. Each motor on the ironers shall be provided with a controller of the magnetic across-the-line type having a separate pole for each ungrounded conductor. Controllers for direct current motors of more than 1/2 hp (373W) shall be of the reduced voltage type having one or more steps of armature resistance for smooth acceleration. Pushbutton control stations shall be mounted at points convenient to the operator. Pushbuttons shall be protected or recessed to prevent accidental operation. Timers, limit switches, remote control pushbutton switches, signals, and indicating lights shall be provided to perform the intended functions.

3.3.4 Belts and pulleys. V-belts shall be of the grade commercially known as multiple-drive type for a fractional horsepower motor where a single belt is used, a V-belt commercially known as a fractional-horsepower belt may be supplied. Pulleys for V-belts shall be suitably grooved and shall not be of a die cast type when used in powered drive. Chain type belts shall be of the silent or roller-chain type. Belt and chain tension shall be adjustable.

3.4 Design and construction.

3.4.1 Ironers. The ironers shall be of the chest-type. The size 2 ironers shall be provided with six rolls not less than 13-1/4 inches (337 mm) in diameter and 120 inches (3048 mm) long. The size 3 ironers shall be provided with eight rolls not less than 13-1/4 inches (337 mm) in diameter and 120 inches (3048 mm) long. The ironer shall operate on the electrical characteristics as specified (see 6.2).

3.4.2 Wiring. Wiring shall be provided in rigid conduit. Where belt or drive adjustment is required, flexible metallic conduit shall be provided. All wiring shall terminate in a connection box with provisions for connections beyond the ironer.

3.4.3 Safety devices. Belt, chains, shafts, pulleys, and gears shall be enclosed or guarded. Guards shall be cast iron or sheet metal. All parts of the guard shall be removable without disassembling pipes or fittings on the ironer. There shall be access openings with covers over parts requiring adjustment or lubrication.

3.4.4 Equipment base. When specified (see 6.2), the equipment base shall be provided with a leveling device. There shall be provisions for anchoring the base to the floor, and anchor bolts shall be furnished.

3.4.5 Working pressure. Cylinders, chests, and chambers using steam shall be designed for a working pressure of 125 pounds per square inch (psi) (862 kPa) gage and shall be capable of withstanding a hydrostatic pressure specified in the ASME Boiler and Pressure Vessel Code (see 4.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.4.6 Gears and sprockets. Gears and sprockets shall have machined teeth. The use of die-cast gears or sprockets shall not be permitted on any powered drive. Gears shall be of ferrous or aluminum bronze material and sprockets shall be of ferrous metal. Noise reducing material of phenolic laminate may be used for drive and intermediate pinions. All pinions shall have faces at least as wide as the mating gears.

3.4.7 Bearings and lubrication. Removable, aluminum bronze sleeve, ball, or roller bearings shall be provided for all shafts, rolls, and studs. Bearings shall be replaceable and shall be permanently lubricated unless oil cups or pressure grease fittings are provided. Gears and chains shall be oil or grease lubricated. Seals shall be provided to prevent the lubricant from entering parts of the machines where clothes are handled. Lubrication instructions including location, type of lubricant, and time intervals shall be indented or embossed on a noncorrodible metal plate and permanently affixed in accordance with the manufacturer's practice.

3.4.8 Piping. Integral piping, fittings, condensate traps, pressure reducing valves for air and steam, and drains shall be installed or furnished as complete assemblies suitable for installation with unions or other standard fittings. Each condensate trap shall be provided with a valve and by-pass.

3.4.9 Valves. Inlet steam and air supply connections shall be provided with valves. Condensate traps (with valve and by-pass) and steam, air drain, and other operational valves shall be accessible for operation and maintenance.

3.4.10 Spacing and extent of fasteners. The spacing and extent of welds, rivets, bolts, and screws shall insure fastening and prevent bulging of fastened metals.

3.4.11 Frames. Two ferrous metal frames with legs shall support the padded rolls, steam chests, and control mechanism at the operating level. The frame shall be connected with rods or structural shapes to support the ironing components and prevent distortion of support members.

3.4.11.1 Rolls. The rolls shall be padded ferrous tube or pipe with ferrous metal heads and shall be driven through gears or sprockets and roller chains. The rolls shall operate in bearing mounts with springs or pneumatic or hydraulic cylinders arranged to exert the ironing pressure.

3.4.11.2 Padding and covering. Padding shall conform to the requirements of MIL-P-43219. When specified (see 6.2), spring padding shall be furnished. When flatwork ironer rolls are equipped with spring padding, there shall be a vacuum attachment for exhausting moisture from the padded rolls.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.4.11.3 Chests, steam. Steam chests shall be ferrous metal. Chests shall have a smooth machine finish with ground and polished ironing surfaces. For each padded roll, the ironer shall have one steam chest anchored to the frame. The chests shall be concave on top to suit the padded rolls, and flat or convex on the bottom. The last chest shall have a continuous radius rear section over which the items shall pass to reach the bottom side of the chests on return type ironers. When specified (see 6.2), the underside of the chest shall be insulated.

3.4.11.4 Shafts. Ferrous metal shafts shall be provided for mounting of pulleys, gears, and rolls.

3.4.11.5 Feed. The feed shall consist of ribbons traveling over a power driven roll and a stationary plate member fitted with guiding pins or metal fingers. The ribbons shall be endless, 2-1/2 to 3 inches (64 to 76 mm) wide, made of heavy feed ribbon stock. The ribbons shall be arranged to carry the items to be ironed to the first padded roll. There shall be a padded finger roll placed on the feeder ribbons to carry the items to be ironed to the first padded ironing roll, when a vacuum type spreader, or automatic feeder spreader is being used. The finger roll shall rest on the feed ribbons and be powered by the motion of the feed ribbons. Means shall be provided for tightening the ribbons, and the drive chain, if used. The feed device shall be supported by ferrous metal brackets bolted to the front of the machine.

3.4.11.6 Guard, finger. A metal finger guard shall be fitted across the entire width of the ribbons, ahead of the first padded roll and the steam chest. Movement of the guard in the direction of feeding, as a result of the operator's finger or fingers passing between the guard and the ribbon feed, or bulging of material shall automatically stop the machine (see 4.4.2). The guard shall be located so the operator's fingers cannot pass between the guard and the ribbon feed. The height of the guard shall be sufficient to prevent the operator reaching over it and getting his fingers caught between the chest and the first padded roll.

3.4.11.7 Guard, roll. When specified (see 6.2), the padded rolls shall be guarded so that the operator or any other person cannot reach into the rolls without removing the guard. This may be either a vertical guard on all sides or a complete cover. If a vertical guard is used, the distance from the floor or working platform to the top of the guard shall be not less than 6 feet (1.8 m).

3.4.11.8 Apron or ribbons. The apron shall be No. 5 standard duck or heavier. The upper and lower metallic-laced duck aprons or ribbons operate over a series of rotating rolls. The aprons or ribbons shall receive the items being ironed after leaving the last roll and carry them against the bottom of the chests to the feed side where the lower apron or ribbons shall convey them back to the delivery side. Ribbons shall be 2-1/2 to 3 inches (64 to 76 mm) wide and in sufficient number to suit the width of their respective rolls.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

3.4.11.8.1 Rolls. The rolls, whether for drive or support purposes, shall rotate in bearings. The rolls shall be turned from sturdy steel tubing, be equipped with secured heads having trunnions of high grade steel and be capable of maintaining permanent alignment. The rolls shall produce a uniformly distributed pressure over their entire length.

3.4.11.8.2 Release. Means shall be provided for simultaneously releasing both upper and lower aprons or ribbons from the ironing position without changing the initial tension. Aprons shall be automatically released with a roll pressure release (see 4.4.2).

3.4.11.8.3 Adjustment, tension. Ironers shall have individual takeup devices for controlling the tension of each apron or ribbons. Each takeup device shall have a visible graduated scale so that the amount of adjustment may be determined and thus prevent the possibility of uneven stretching of the apron or ribbons.

3.4.11.8.4 Rolls, tension and guide. Tension rolls shall be provided with a raised track in the form of a double spiral, arranged to prevent buckling and to keep the apron taut sidewise. Guide rolls shall be arranged to keep the aprons or ribbons aligned automatically.

3.4.11.9 Device, pressure. The pressure device shall exert uniform pressure on the springs at both ends of the padded rolls and operate in conjunction with means for applying or releasing the tension on the aprons or ribbons on ironers, as applicable. Application and release of pressure shall be through mechanical, pneumatic, or hydraulic devices. Devices shall operate manually when power is not available. A pressure indicator for indicating the relative amount of pressure and a speed indicator showing the approximate peripheral speed of the rolls in feet (m) per minute shall be mounted so they are readable from the feed side of the ironer.

3.4.11.10 Guides. Heat-resisting strings or tapes operating over spools shall be provided for guiding the laundry under the rolls. A string or tape rod, or other suitable and equivalent means, shall be fitted at the rear of the machine and shall be adjustable as to its location with respect to the last chest or padded rolls. Means shall be provided for automatically tightening the strings or tapes.

3.4.11.11 Motors, controls, and operating speeds. The motor shall be started by a push button located at the front of the ironer and stopped by push button located both at the front and rear of the ironer. Motors shall be furnished with a mechanical speed changer to provide infinite delivery speed ranges from 1/3 to full speed. Means shall be provided wherein the mechanical speed changer can be changed from full speed to 1/3 speed (without stopping the ironer) (see 4.4.2). Provisions shall be made so that the speed changer may be set at low speed prior to starting the ironer. The mechanical speed changer controls shall be mounted on a metal bracket on the ironer or on a metal floor stand at operating level at the feed end of the ironer. A detachable hand crank shall be provided for operating the drive in the reverse direction. Means shall be provided for operating the machine forward at a slower speed for repadding purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.4.11.12 Moisture and fungus-resistant treatment. When specified (see 6.2), electrical components of equipment covered herein shall be moisture and fungus-resistant treated with material conforming to and applied as required by MIL-T-152.

3.4.11.13 Contract data requirements. The contract data requirements shall be as specified (see 6.2 and 6.4).

3.5 Performance.

3.5.1 Ironer. The ironers shall be capable of ironing sheets dry (not more than 7 percent moisture content) with the design steam pressure of 125 psi (362 kPa) gage and temperature of 345°F (174°C) within the operating speeds of 24-72 feet per minute (610-1830 mm/minute) for size 2, and 30-90 feet per minute (760-2290 mm/minute) for size 3, when tested as specified in 4.4.3.

3.5.2 Electromagnetic compatability. When specified (see 6.2), equipment shall be designed and equipped for electromagnetic compatibility in accordance with class II B of MIL-STD-461 (see 4.4.4).

3.5.3 Noise limits. The ironer shall meet the noise limits specified in MIL-STD-1474 and where applicable, shall not exceed 85 decibels A- weighted at the normal operating position when tested as specified in 4.4.5.

3.6 Finish and color. Unless otherwise specified (see 6.2), each ironer shall be finished in accordance with the manufacturer's commercial practice. The color of the emergency stop and normal push button and feed guard shall be red.

3.7 Marking for identification. Marking for identification of the ironers shall be in accordance with the manufacturer's commercial practice and shall include manufacturer's name, date of manufacture, model number and electrical characteristics.

3.8 Workmanship. The ironer shall be free from defects such as fractures, splits, punctures, tears, dents, creases, deteriorations, or malformations. There shall be no sharp edges, burrs, or slivers. Threaded fasteners shall not be broken, stripped, fractured or loose. Rivets shall completely fill the holes, with full size heads, finished and in full contact with the surface of the riveted members, and shall not be loose. Wiring shall not be cut, abraded, or have excessive insulation stripped, and shall be properly and tightly joined at terminals. Wiring shall have adequate slack to provide strain relief.

3.8.1 Application of finish. The finish applied to the ironer shall be continuous, smooth, adherent, have no imbedded foreign matter, and contain no sags, runs, drips, creeps, laps, bubbles, or streaks. No rust or tool marks shall show through the coating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.8.2 Welders and welding.

3.8.2.1 Welders. The welders performing the welding on subassemblies, and on the end item shall be certified welders and have passed the welding qualifications as prescribed by the American Society of Mechanical Engineers. The contractor will furnish the Government with a list of names of his welders who are certified and have passed the welding qualifications, and he shall certify that the welding of this equipment was performed by the welders listed.

3.8.2.2 Welding. The surfaces of parts to be welded shall be free from oxide, paint, grease, and other foreign matter. Welds shall be continuous, sound, smooth, and free from porosity, cracks, incomplete fusion, and deformation of materials. All scale and flux shall be removed from the finished welds. Soldering shall be complete and adherent, with all flux and residue removed and shall contain no pinholes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificates of compliance. Certificate of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with specification requirements shall be examined and validated.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall be all ironers of the specified size offered for inspection at one time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

4.2.2.1 Visual examination. The ironer shall be examined for the defects in table I. The inspection level shall be II and the acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Type of finish not as specified, or not in accordance with the manufacturer's standard commercial practice		X
	Area of no film	X	
	Not continuous, smooth and adherent	X	
	Discoloration or foreign material embedded in finish		X
	Sags, runs, drips, creeps, laps, flux or orange peel		X
	Rust or tool marks showing through the coating	X	
	Emergency stop and normal stop push buttons not red	X	
	Feed guards not red	X	
	Color red used on other than stop push buttons and feed guards	X	
Construction	Any component missing or not specified type	X	
	Any component split, puncture, tear, dent, crease, deteriorated, or malformed	X	
	Sharp burr, sliver, or sharp edge	X	
	Push button control stations not convenient to operator	X	
	Push button not protected or recessed	X	
	Exposed belts, chains, shafts, pulleys, or gears	X	
	Any functioning component that requires abnormal force to operate	X	
	Bearings not replaceable	X	
	Guards not removable without disassembling pipes or fitting	X	
	Base not in full contact with a level floor, (when applicable)	X	
	No provision for anchoring base to floor (when applicable)	X	
	Component not connected or joined as specified	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction (cont'd)	Pinion not as wide as meshing gear		X
	Seals not provided to prevent grease from entering parts of machine where flatwork is handled	X	
	No means to adjust belt and chain tension	X	
	Condensate trap without valve and by-pass	X	
	Not chest type	X	
	Control mechanism not at operating level	X	
	No leveling devices	X	
	No springs to exert ironing pressure	X	
	Not a steam chest for each padded roll	X	
	Chests not concave on top or flat or convex on bottom	X	
	Guard across line of feed missing or allows operator's fingers to pass through	X	
	No apron release device		X
Welding and brazing (where applicable)	Missing, incomplete, burn holes, fractured, or not fused	X	
	Slag inclusion, undercut, not smooth and uniform, or deposit of scale and flux not removed	X	
Soldering (where applicable)	Missing, incomplete, or not adherent	X	
	Not clean (flux or residue not removed) or contains pinholes		X
Bolts, nuts, screws, studs and other threaded fasteners	Broken, stripped, or fractured	X	
	Threaded fasteners loose		X
Rivets (when applicable)	Missing, broken, not peened, or not peened sufficiently	X	
	Rivets loose		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Electrical apparatus wiring	Wiring cut, abraded, excessive insulation stripped, not properly joined, or loose at terminal	X	
	Not inclosed in specified conduit, where required	X	
	Wiring not terminated in junction box	X	
	Adequate slack not provided for wiring to relieve strain		X
Piping, tubing, fittings and valves	Improperly connected or installed; will not provide a seal or threads stripped	X	
Lubrication	Not lubricated where required		X
	Excessive lubrications		X
	Fitting not accessible for lubrication		X
Marking for identification	Missing, incomplete, illegible		X

4.2.2.2 Dimensional examination. The ironer shall be examined for compliance with dimensions specified. Any dimension not within this specification tolerance shall be a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.2.2.3 End item testing. The first produced ironer shall be tested as specified in 4.4.3, 4.4.5 and when applicable. 4.4.4. Each sample shall be tested as specified in 4.4.1 and 4.4.2. Failure to pass the test shall be cause for rejection of the inspection lot. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed as defects per hundred units.

4.3 Packaging inspection. Preservation, packing and marking shall be inspected in accordance with the quality assurance provisions of MIL-L-3153.

4.4 Tests.

4.4.1 Hydrostatic pressure. Assemblies of cylinders and chambers that in operation contain steam shall be subjected to a hydrostatic pressure test determined in accordance with the provisions of the ASME Unfired Pressure Vessel based on a working pressure of 125 psi (862 kPa) gage. The pressure shall be maintained for 10 minutes. Inability of the cylinders and chambers to meet the requirements of 3.4.5 shall constitute failure of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

4.4.2 Operational testing. The ironers shall be tested for compliance with the following:

(a) Operation of the feed finger guard for compliance with 3.4.11.6.

(b) Operation of the apron or ribbon release for compliance with 3.4.11.8.2.

(c) Operation of the mechanical speed changer for compliance with 3.4.11.11.

Nonconformance shall constitute failure of the test.

4.4.3 Functional test. Connect the ironer to electrical power and to a steam line at 125 psi (862 kPa) gage and 345°F (174°C) and operate at speeds specified in 3.5.1 for the applicable size ironer. Ten sheets containing moisture not more than 1.45 times the dry weight shall be ironed. Examine the sheets to determine that moisture retention does not exceed 7 percent. Nonconformance to 3.5.1 shall constitute failure of this test.

4.4.4 Electromagnetic compatibility tests. When electromagnetic compatibility is required, the first unit of production shall be tested by the supplier in accordance with test method CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or an independent testing agency. The contractor shall furnish the contracting officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic test report and the requirements meet MIL-STD-461 (see 3.5.2).

4.4.5 Noise test. The ironer shall be tested for conformance with the noise limits of 3.5.3 in accordance with MIL-STD-1474.

5. PACKAGING

5.1 Preservation, packing. Preservation, packing, and marking shall be in accordance with levels A, B, and C requirements of MIL-L-3153 as specified (see 6.2).

6. NOTES

6.1 Intended use. The ironers are intended to be used in fixed laundry installations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should exercise options offered herein, and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size ironer required (see 1.2).
(c) Electrical characteristics (see 3.4.1).
(d) When a leveling device is required (see 3.4.4).
(e) When spring padding is required (see 3.4.11.2).
(f) When underside of chest is to be insulated (see 3.4.11.3).
(g) When padded rolls are to be guarded (see 3.4.11.7).
(h) When moisture and fungus resistant treatment is required (see 3.4.11.12).
(i) Contract data requirements (see 3.4.11.13 and 6.4).
(j) When electromagnetic compatibility is required (see 3.5.2).
(k) Finish when other than specified (see 3.6).
(l) Levels of preservation, packing, and marking required (see 5.1).

6.3 Recycled material. It is encouraged that recycled material be used when practical, as long as it meets the requirements of the specification (see 3.3).

6.4 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity (see 3.4.11.13).

6.5 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value in US customary units shall be controlling.

6.6 Supersession data. This specification replaces the size 1 and 2 ironers shown in 00-I-675F, dated November 20, 1973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD
DLA - GS

User activity:

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
VA - DMS

Preparing Activity:

Army - GL

Project No. 3510-0278

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.