00-L-90E
1 June 1988
SUPERSEDING
00-L-90D
12 February 1986

FEDERAL SPECIFICATION

LATHE, HEAVY DUTY, FOR BRAKE DRUM AND DISC BRAKE ROTOR TURNING AND TRUING

This specification is approved by the assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers a heavy duty truck brake drum and disc brake rotor lathe, pedestal base, floor mounted, with chip catcher and storage board, electrically powered, with equipment and accessories, for turning and truing brake drums and disc brake rotors of commercial and military passenger car and truck vehicles.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or solicitation for offers, shall apply.

Federal Specifications

W-C-596/13	-	Connector, Plug Electrical, General Purpose, Hospital Grade, Grounding 2 Pole, 3 Wire, 15 Amperes, 125 Volts 50/60 Hertz
FF-B-171	-	Bearings, Ball, Annular (General Purpose)
FF-B-185	-	Bearings, Roller, Cylindrical; and Bearings, Roller, Self-Aligning
FF-B-187	-	Bearing, Roller, Tapered
VV-L-800	-	Lubricating Oil, General Purpose, Preservative (Water-Displacing, Low Temperature)
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-T-60	-	Tape: Packaging, Waterproof

Beneficial comments (recommendations, additions, deletions) and pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research, Development and Engineering Center, ATTN: SMCAR-EST-S, Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

Federal Standards

FED-STD-H28 - Screw-Thread Standards for Federal Services

(Single copies of this specification, and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications

MIL-C-104	-	Crates, Wood: Lumber and Plywood Sheathed, Nailed and Bolted
MIL-T-152	-	Treatment, Moisture and Fungus-Resistant of Communications, Electronic and Associated Electrical Equipment
MIL-V-173	-	Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications Electronics, and Associated Equipment
MIL-G-10924	-	Grease, Automotive and Artillery
MIL-B-13501	-	Bearings and Bushings, Brass and Bronze, Machined and Formed
MIL-C-16173	-	Corrosion Preventive Compound, Solvent Cutback, Cold-Application
MIL-P-17667	-	Paper, Wrapping, Chemically Neutral (Non-Corrosive)
MIL-L-21260	-	Lubricating Oil, Internal Combustion Engine, Preservative and Break-In

Military Standards

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of US Military Property
MIL-STD-889	-	Dissimilar Metals
MIL-STD-1186	-	Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods
MS19081	-	Bearings, Roller, Tapered Single Row of Rollers, Normal Angle

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulation

Occupational Health and Safety Administration (OSHA)
29 CFR, Chapter XVII, Part 1910 - Occupational Safety and Health Standards

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following other Government documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Electrical Manufacturers Association (NEMA)

NEMA ICS 1 - General Standards for Industrial Controls and Systems
NEMA MG 1 - Motors and Generators

(Applications for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street N.W., Washington, DC 20037.)

National Fire Protection Association (NFPA)

NFPA 79 - Electrical Standard for Industrial Machinery and Plastics Machinery

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

American Gear Manufacturers Association (AGMA)

AGMA 360.2 - Manual for Machine Tool Gearing
AGMA 390.03-80 - Gear Handbook Volume I: Gear Classification, Materials and Measuring Methods for Unassembled Gears

(Application for copies should be addressed to the American Gear Manufacturers Association, Standards Dept., 1500 King Street, Suite 201, Alexandria, VA 22314.)

American Society for Testing and Materials (ASTM)

ASTM E380-86 - Standard for Metric Practice

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

International Organization for Standardization (ISO)

ISO 1122/1 - Glossary of Gear Terms - Part 1: Geometrical Definitions
ISO 54 - Cylindrical Gears for General Engineering and for Heavy Engineering - Modules and Diametral Pitches

(Application for copies of ISO documents should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.1 First article. When specified (see 4.2.1 and 6.2), the contractor shall furnish one or more complete lathe(s) for first article inspection. The first article may be either a preproduction model(s) or an initial production item(s) which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.1.1 Contractor furnished property. Brake drums, brake disc rotors, spindle assemblies, and bearing assemblies necessary to establish conformity with requirements herein shall be provided by the contractor. There will be no Government Furnished Property or Material (GFP/GFM) provided.

3.2 Design. The heavy duty brake drum and disc brake rotor lathe, pedestal base, floor mounted, with chip catcher and storage board, electrically powered, shall include all the features, components, and accessories necessary for turning and truing automotive brake drums and disc brake rotors as specified herein. The lathe shall be new and of the manufacturer's latest design capable of meeting the requirements specified herein. The lathe shall be electric motor driven, with automatic and hand feeds. The equipment shall be readily accessible from the operator's normal work station for operations such as feed selection, tool bar positioning, movement of all slides (carriage slides, cross slides, etc.). All parts subject to wear, breakage, or distortion shall be accessible for replacement, adjustment, and repair.

3.2.1 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any part of a particular type or model lathe may be replaced, interchanged, and adjusted without modification of the respective replacement part of any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

3.2.2 Fastening devices. All screws, pins, bolts, and similar fastening devices shall be installed with means for preventing loss of tightness and adjustment. All such parts, when subject to removal or adjustment, shall not be swaged, peened, staked, or otherwise permanently deformed.

3.2.2.1 Threads. Threads shall conform with FED-STD-H28 and the applicable detailed standards referenced therein.

3.2.3 Gears. All gears and pinion designs used in the lathe and its components shall be fabricated to either English (USA) standard inch diametral pitch per AGMA 390.03, AGMA 360.02 or Metric (SI) module ratio per ISP-1122, ISO-54, and ASTM E380.

3.2.4 Bearings. Spindle bearings shall be tapered roller bearings. When other than tapered roller bearings are used, suitable thrust bearings shall be provided. Ball and roller bearings shall be in accordance with the requirements of FF-B-171, FF-B-185, FF-B-187, or MIL-B-13501, as applicable. All bearings shall be protected from dust and chips.

3.2.5 Dials. Dials shall be provided and graduated in the U.S. customary inch or Metric (SI) system of measurement. Manufacturers are encouraged to provide dials graduated in the U.S. customary inch and Metric (SI) system of measurement. Dial graduations indicating stock removal or tool movement shall be in increments of not more than 0.001 inch or 0.02 millimeters (mm). Dials shall be such that the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

graduations may be easily read from the machine operator's normal working position. Dials shall be permanently and legibly etched or engraved on a non-glare background. The dials shall be accurate indicators for adjustment of machine of machine component movement.

3.2.6 Lubricating systems. All bearings (except sealed for life, permanently lubricated type), matching gears, and all other moving parts shall be provided means to assure adequate lubrication. Recirculating systems shall include cleanable or replaceable filters. Each lubricant reservoir shall have means for determining fluid levels. All oil holes, grease fittings, and filler caps shall be readily accessible. the contractor shall include and install all lubricants, fluids, greases and other compounds in the lathe, in accordance with the best commercial practices of the brake lathe industry.

3.2.7 Safety and health requirements. Each lathe shall be furnished with safety devices. Guards shall be installed on parts which are hazardous to the operator. Protection against electric shock shall be provided. The lathe shall comply with 29 CFR, Chapter XVII, Part 1910.

3.2.8 Surfaces. External surfaces of the lathe shall be clean and smooth and all edges shall be rounded or beveled. All bearing surfaces between matching parts shall be finished by machining, grinding, or scraping to necessary tolerances to provide the required accuracy. All castings, formings, molded parts, stampings, and welded parts shall be clean and free of sand, dirt, fins, sprues, scale, flux, and other harmful materials.

3.2.9 Materials. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the lathe industry, shall be suitable for the intended purpose in the design of the end item, and shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.2.10 Reclaimed materials. The manufacturer is encouraged to use reclaimed materials for fabricating new parts without jeopardizing the chemical and physical properties, design integrity, and intent of the materials originally selected of specified. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner that shall restore them to the same chemical composition and physical properties as the materials originally selected for use. It shall not be permissible to use reclaimed parts as is or rebuilt from scrap or other used equipment.

3.3 Construction. Construction shall be free from any characteristics or defects that may render the lathe unsuitable or inefficient for the intended purpose.

3.3.1 Castings and forgings. All castings and forgings shall be free from blow-holes, porosity, hard spots, cracks, scale, inclusions, cold shuts, mismatching, and other defects that may affect the structural strength of the castings or forgings. Strength and other physical and chemical properties of the castings and forgings shall be adequate to meet the performance requirements specified herein. Castings and forgings shall not be subjected to any reclaiming process without the authorization of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

3.3.2 Welding, brazing, and soldering. Welding, brazing, and soldering shall be of a quality which shall sustain all requirements of the welded, brazed, for soldered parts. These operations shall not be employed as repair measures for defective parts.

3.3.3 Electrical connections. Connections of conductors and terminal parts shall be of the screw, pressure or solder type. When soldered connections are used, the conductors and terminal parts shall be mechanically secured before soldering. Rosin base fluxes only shall be used in soldering operations. Connections to screw type terminals shall be mechanically secured with a means to prevent loss of tightness.

3.4 Performance and product characteristics. The lathe shall be capable of truing commercial and military passenger car and truck brake drums and disc brake rotors within the sizes specified herein with one initial machine setup for each drum and rotor. The entire friction surface of the drum or rotor on the spindle, relocate tool bar or holder or relocate carriage or cross slide. The lathe shall be capable of truing brake drums and disc brake rotors weighing up to and including 600 pounds, with the wheels removed, within the sizes and to the accuracies specified herein without the aid of an outboard support. Performance accuracy shall apply after turning/truing the brake drum or disc brake rotor in the lathe, and shall be unaffected by the mounting position of the brake drum or disc on the arbor. Performance accuracy shall also apply with the brake drum or disc brake rotor mounted on a vehicle spindle or on an arbor which duplicates the exact mounting of the drum or disc brake rotor on the vehicle. spindle. The drum or disc rotor shall be mounted with proper companion bearing assemblies (cups, cones, and ball or roller bearings) in place and torqued in accordance with bearing manufacturer's recommendations. Turning and truing of the drums and rotors shall be accomplished with out chatter. If a grinder or grinding attachment (see 3.5.10.2) is required to meet the required finishes specified in paragraph 3.4.3.c and 3.4.4.c, it shall be furnished with the lathe.

3.4.1 Lathe capacities, capabilities, and characteristics. Lathe capacities, capabilities, and characteristics shall be not less than those shown. Where a range is indicated, the required performance shall be from and including the smaller figure or less to and including the larger figure or more.

a. Drum diameter range - Six inch inside diameter to 24 inch inside diameter.

b. Drum width (friction surface) cutting range - 1 to 9 inches.

c. Drum machine powered (not hand powered) cutting feed rate range - 0.005 to 0.015 inches per revolution.

d. Number of machine powered (not hand powered) cutting feed rates for drums - Infinite or not less than 2.

e. Disc rotor friction surface cutting diameter range capacity - 4 inch inside diameter to 19-1/2 inch outside diameter.

f. Rotor width (face to face of friction surfaces) - 0.125 to 1.75 inches.

g. Disc rotor machine powered (not hand powered) cutting feed rate range 0.002 to 0.015 inches per revolution.

h. Number of machine powered (not hand powered) cutting feed rates for rotors - Infinite or not less than 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

For drums and disc rotors:

i. Spindle speed range - minimum speed no more than 60 revolutions per minute (rpm), maximum speed no less than 115 rpm.

j. Number of machine powered spindle speeds - Infinite or not less than 3 (low speed, mid-range speed and high speed).

3.4.2 Machine accuracy. The lathe and accessories shall not exceed the following tolerances:

a. Spindle taper run-out (concentricity) 0.0005 inch total indicator reading (TIR).

b. Arbor run-out (concentricity) 0.0005 inch TIR at all positions along its length up to 7 inches from the spindle nose and 0.001 TIR inch from 7 inches to 16 inches and .0015 TIR past 16 inches, if applicable.

c. Adapters such as short radius cones, taper cones, sleeves, bushings, and spacers; run-out and concentricity to their true axis .0005 inch TIR.

d. Carriage alignment 0.001 inch TIR with the true axis of the spindle, at any point up to and including the necessary travel to true a 9-inch face depth drum and 0.0015 inch TIR for the balance of the travel.

3.4.3 Performance accuracy for brake drums. The lathe shall be capable of truing all brake drums specified herein within the following tolerances:

a. Concentricity (turned surface to axis of hub). The turned surface of the brake drum shall be concentric with the axis of the bearing surfaces in the hub within 0.0015 inch TIR for brake drums up to 24 inches in diameter and friction surfaces up to 9 inches in depth. Applicable to rough cutting as well as finish cut.

b. Taper. The turned surface of the brake drum shall be true with the axis of the bearing surfaces of the hub within 0.0015 inch TIR per 9 inches of brake drum friction surface for brake drums up to 24 inches in diameter. applicable to rough cutting as well as finish cut.

c. Finished surface. The final turned surface finish of the brake drum shall not have a finish numerically greater than 40 micro-inches arithmetical average (AA).

3.4.3.1 Rough cutting for brake drums. The brake drum and disc lathe shall rough cut brake drums of at least 24 inches inside diameter. The brake drum lathe shall also rough cut brake drums of at least 9 inch depth. Rough cutting does not have to comply with finished requirements of para 3.4.3(c). These drums shall be rough cut as follows:

a. At not less than 60 rpm.

b. At not less than 0.025 inch deep cut (0.025 radius or 0.050 diameter).

c. At not less than 0.015 inch per revolution feed rate of the carriage tool bar and cutting tool.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.4 Performance accuracy for disc brake rotors. The lathe shall be capable of simultaneously truing both friction surfaces of disc brake rotors, from 4 inch inside diameter to 19-1/2 inch outside diameter, within the following tolerances:

a. Each finished trued surface of the rotor shall not deviate from the true plane of the rotor surface in excess of plus/minus 0.0005 inch or a TIR of 0.001 when measured face to face. The true plane of the rotor surface is a plane perpendicular to the axis of rotation which is established by the bearing surfaces of the hub and spindle assembly (see 3.4). Applicable to rough cutting as well as finish cut.

b. Thickness variations (parallelism) of the rotor between trued surfaces shall not exceed 0.001 inch. Applicable to rough cutting as well as finish cut.

c. The trued finished rotor surfaces shall not have a surface finish numerically greater than 40 micro-inches AA.

3.4.4.1 Rough cutting for disc brake rotors. The brake drum and disc lathe shall rough cut the friction surface of brake disc rotors from 4 inch inside diameter to 19-1/2 inch outside diameter:

a. At not less than 60 rpm.

b. At not less than 0.015 inch deep cut on both sides of the disc rotor simultaneously.

c. At not less than 0.015 inches per revolution (IPR) feed rate of cross slide tool holder and cutting tool.

3.5 Detail of components. The lathe shall consist of, but not be limited to, the following component parts.

3.5.1 Floor mounting base. The floor mounting base shall be cast iron or heavy steel fabrication to absorb and prevent resonant vibration and to assure strength, rigidity and zero deformation when the brake drum and disc rotor lathe is operated under full load. Welded base structures shall be stress relieved. The base shall provide for permanent floor mounting (see 1.1) of the brake lathe with the center line of the lathe spindle at operator working height of no less than 35 inches from the floor and no more than 42 inches from the floor. Compartments shall be provided in the base for the storage of short radius cones, arbors, adapters, and tools required in the resurfacing of brake drums and disc brake rotors.

3.5.2 Headstock housing. The headstock housing shall contain the main spindle assembly and the matching ways for the carriage. The headstock housing shall be of a cast iron or cast steel construction, stress relieved, and shall be of sufficient strength to assure rigidity and zero deformation while operating under full load. The headstock assembly shall consist of, but not be limited to, the main spindle, gears, gear change mechanisms, feed change mechanisms, a handwheel drive for manually positioning the cutting tool, and the headstock ways.

3.5.2.1 Headstock ways. The headstock ways provide the bearing surface for the tool travel (parallel to the spindle) for the operation of turning and truing brake drums. The headstock ways shall be finished to provide an accurate uniform bearing surface for the matching carriage ways. The headstock ways shall be of sufficient

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

length to maintain a full 100 percent load bearing contact, without any cantilever while machining all specified sizes of brake drums. The headstock ways shall also be of adequate size and strength to maintain the required accuracies as specified in 3.4.2, and 3.4.3, and 3.4.4.

3.5.3 Carriage. The carriage shall provide the matching bearing surface for carriage travel (parallel to the spindle) for the operation of turning and truing brake drums. If applicable, the carriage shall also provide the matching bearing surface for the cross slide travel (perpendicular to the spindle) for the operation of turning and truing disc brake rotors. The carriage shall be of a cast iron or cast steel construction, stress relieved, and shall be of sufficient strength to assure rigidity and zero deformation while operating under full load. The carriage shall consist of, but not be limited to the following:

a. A handwheel for manually positioning the cutting tool to the proximity of the work piece.

b. A feed dial graduated in increments to indicate 0.001-inch movements of the carriage.

c. Provisions for locking the carriage in all positions necessary for cutting.

d. A carriage adjustment gib to compensate for wear (see 3.5.3.2).

e. Carriage ways for the matching headstock and, if applicable, cross slide ways (see 3.5.3.1).

3.5.3.1 Carriage ways. The carriage ways shall be finished to provide an accurate uniform bearing surface for the matching ways. The carriage ways shall be of sufficient length to maintain a full 100 percent load bearing contact, without any cantilever effect with the matching set of ways, throughout the full carriage travel and, if applicable, cross slide travel, while machining all specified sizes of brake drums and disc brake rotors. An automatic shut off device shall be incorporated in the carriage ways that will either disable the motor, or disengage the machine powered cutting feed mechanism in the event of the ways lose the full 100 percent load bearing contact with the matching set of ways.

3.5.3.2 Carriage gib. The carriage gib shall provide for a fine, precision adjustment to compensate for wear in the carriage ways, throughout the life of the brake drum and disc brake rotor lathe. The carriage gib shall provide an even pressure along the surface area of the ways.

3.5.4 Cross slide. The cross slide shall provide the matching bearing surface for the carriage ways (perpendicular to the spindle) for the operation of turning and truing disc brake rotors. The cross slide shall also provide the movable tool support for the turning and truing of disc brake rotors and, if applicable, brake drums. The cross slide shall be of a cast iron or cast steel construction, stress relieved, and shall consist of, but not be limited to the following:

a. A hand wheel and feed dial, graduated in increments to indicate 0.001-inch movements of the cross slide.

b. Provisions for locking the cross slide in any position.

c. Cross slide adjustment gib to compensate for wear (see 3.5.4.1).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currenversion before use.

d. Provisions for mounting the tool holder rigidly in its proper position on the cross slide.

e. Cross slide ways (see 3.5.4.2).

3.5.4.1 Cross slide gib. The cross slide gib shall provide for a fine, precision adjustment to compensate for wear in the cross slide ways throughout the life of the brake drum and disc brake rotor lathe. The cross slide gib shall provide an even pressure along the surface area of the ways.

3.5.4.2 Cross slide ways. The cross slide ways shall provide the mating bearing surface for the carriage ways (perpendicular to the spindle) for the operation of turning and truing disc brake rotors. The cross slide ways shall be of sufficient length to maintain a full 100 percent load bearing contact, without any cantilever effect with the matching carriage ways, throughout the full cross slide travel range while machining all specified sizes of disc brake rotors.

3.5.5 Tool bar. The lathe tool bar shall be made from steel and shall be designed to hold the cutting tool rigidly and securely, and prevent change in the rake angle of the cutting tool. The tool bar shall be design so that it can be rotated 180 degrees in the clamp for turning drums with external braking surfaces.

3.5.6 Machine powered feed drive. There shall be two machine powered feed systems, one for machining brake drums and the other for machining disc brake rotors. Each of the machine powered feed systems shall have either an infinite feed rate or not less than two feed rates, as specified in 3.4.1, one for rough machining cuts, and the other for finish machining cuts. Each machine powered feed system shall be provided with a clutch lever or a means of engaging the machine powered feeds. All feed rate changes, clutch levers, and controls shall be easily accessible to the operator and shall be easily adjustable. All half nuts, gears, clutches, etc. required in conjunction with the machine powered feed systems shall be enclosed. Feed screws and/or feed rods may be exposed.

3.5.6.1 Handwheels for manual positioning. Handwheels shall be provided for manually positioning the cutting tool to the proximity of the surface to be machined, pick up the initial cut, set the depth of cut, etc. There shall be a handwheel to provide manual movement of the carriage and another to provide manual movement of the cross slide.

3.5.6.2 Automatic stops. Automatic stop devices, for the prevention of damage to the equipment, for both grinding and turning, shall be as follows:

a. An automatic stop device shall be provided that disengages the machine powered feed mechanism at a point that prevents any contact between the carriage and the headstock.

b. An automatic stop device shall be provided for the cross slide ways and the carriage ways, as specified in 3.5.3.1, that either shuts off the motor or disengages the machine powered feed mechanism, to prevent any overhang or cantilever effect in the event that the carriage or cross slide does not maintain the full 100 percent load bearing contact with the matching set of ways.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the currentversion before use.

3.5.7 Spindles and arbors. Spindles and arbors shall be alloy steel, heat treated and ground on all aligning surfaces. Spindles shall be heat treated to a surface hardness of Rockwell C40-45. Arbors shall be heat treated to a surface hardness of at least Rockwell C50. Spindles and arbors shall be of a size to ensure the accuracy required of this type of lathe and mounted to permit turning brake drums and disc brake rotors of the size specified. The arbors shall be mounted in the spindle by means of a suitable taper (from at least 0.5 inch per foot to not more than 6.5 inches per foot on diameter) with a positive lock and release system which prevents damage to spindle or arbor. The length of the arbor shall be adequate to mount and surface finish cut the entire friction surface of the sizes of brake drums, disc brake rotors, and hubs specified.

3.5.7.1 Spindle drive. A minimum of three spindle speeds or infinitely variable spindle speeds shall be provided. Gear drives shall be totally enclosed. Easily adjustable tensioning devices and guards shall be provided where belt or chain drives are employed. All necessary motor mounting brackets, pulleys, belts, chains, sprockets, gears, countershafts, and other parts required to successfully operate the lathe (as specified herein) shall be furnished. Visual means shall be provided to show spindle speeds throughout the entire speed range specified herein.

3.5.8 Electrical equipment.

3.5.8.1 Motors. The motors shall conform to the requirements of NEMA MG1, as applicable. The lathe shall be furnished with a continuous duty, induction squirrel-cage type, minimum 3 horsepower motor with a temperature rise of not more than 50 degrees Celsius (C) above ambient temperature, thermal overload protected. The motor shall function on 120 volts, single phase, 60 Hertz current. Mounting shall be in accordance with NEMA ICS 1. Motors shall be protected from dirt and grit and shall be accessible for lubrication and maintenance and shall be equipped with sealed-for-life, antifriction bearings. A start-stop switch shall be mounted and wired, convenient to the operator.

3.5.8.2 Electrical components. Electrical components of the lathe including starters, relays, switches, wiring, and their enclosures shall conform to and shall be located in accordance with NEMA ICS 1, except as specified herein. There shall be no component part used where the requirements exceed the electrical component manufacturer's rating for the part.

3.5.8.3 Light fixture. The lathe shall be provided with a work light located in a position which will not interfere with controls, yet will afford full illumination at the cutting tool area. The light shall be equipped with a separate switch that shall function independently of the motor switch.

3.5.8.4 Electric power supply cable. An electric power supply cable shall be installed on each lathe. The cable shall be not less than 10 feet in length and shall terminate with a three prong grounding plug complying with W-C-596/13 and NFPA 79. The three prong plug shall be furnished with a 3 to 2 prong outlet adapter, with a grounding lead. The cable shall include sheathing/covering in accordance with NFPA 79 and 29 CFR Chapter XVII, Part 1910. The cable shall have a voltage/potential and ampere/current carrying capacity exceeding that required by the electric power consuming devices, including electric motors, of the lathe in accordance with NFPA 79.

3.5.8.5 High voltage requirement. The entire electrical system of the brake lathe shall withstand, without damage malfunction, breakdown, arcing, surface or air discharge, at least 2500 volts Root Mean Square (RMS), 60 Hertz of electrical

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

energy, at room standard ambient temperature. The electrical energy shall be applied instantaneously at full voltage of at least 2500 volts, and shall be maintained for at least 15 seconds. Each circuit shall be isolated from other circuits, and all circuits shall be isolated from electrical ground. Solid state control components may be damaged as a result of high voltage and is not cause for rejection. Damage to solid state control components may be avoided by wiring around or by-passing them, terminal to terminal. No arcing or discharge from solid state control components is acceptable.

3.5.9 Accessories. All needed accessories for turning and truing brake drums and disc brake rotors of military and commercial vehicles shall be furnished. For commercial and military vehicles, such accessories shall be provided to fit all bearing cups from the minimum size bearing cup MS19081-18 thru the maximum size bearing cups MS19081-173 and from MS19081-184 thru MS19081-313. Hardened steel, ground, short radius cones shall be furnished to fit all sizes and configuration of bearing cups. Collets are not acceptable. Tapered cone adaptors shall be provided for all commercial and military brake drums and discs to fully cover the sizes specified herein. Truck drum and disc anti-chatter devices shall be provided to cover the range of sizes specified herein.

3.5.10 Optional equipment.

3.5.10.1 Case. When specified (see 6.20), a suitable sturdy case of sheet metal or wood shall be furnished to contain the grinding attachment, gages, and all accessories for transportation of the equipment.

3.5.10.2 Grinding attachment. When specified (see 6.2), a grinding attachment shall be furnished with each lathe with six grinding wheels suitable for grinding cast-iron and /or hardened-steel brake drums. A suitable guard, an abrasive-wheel dresser having a mounted octahedron diamond of 1/4-carat minimum size, feed mechanism, brackets, and necessary equipment to make a complete unit shall be included. The grinding attachment shall be capable of driving the abrasive wheel at a working surface speed of 3600 to 7000 feet per minute.

3.6 Fungus treatment. Components of electrical circuitry that are hermetically sealed or inherently resistant to fungus growth and moisture need not be treated. Components of electrical circuitry that are not inherently resistant to fungus growth or moisture shall be treated in accordance with MIL-T-152 and MIL-V-173.

3.7 Painting. Painting and finishing shall be in accordance with the best practices of the lathe industry. Immediately prior to painting, all surfaces shall be clean and dried and free of all foreign matter. The protecting paint coating shall be not less than 2.0 MIL in thickness. The paint adhesion shall be such that no paint shall be peeled by fiberglass tape when two intersecting cuts expose the base metal for a distance of not less than 2 inches. The surface hardness of the paint shall be between the industrial standards of H to HB pencil lead.

3.8 Identification marking. The lathe shall be marked for identification in accordance with MIL-STD-130 and shall include the National Stock Number.

3.9 Plates. All instruction plates and indicating dials shall be provided and shall be written in the English language and shall be clearly and legibly etched, stamped, embossed, or engraved in bold face on a contrasting background on a corrosion resistant metallic composition plate and shall be securely attached to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

each lathe in a location visually convenient to the machine operators normal work station. All plates shall be permanently secured to the lather with fasteners such as screws, bolts, and rivets.

3.10 Workmanship. Standards of workmanship shall be such as to assure equipment of a neat appearance, having the stability and efficient operating characteristics as found in commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All lathes shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that the products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2. Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).

b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. When specified, first article inspection shall be performed on the preproduction model(s) or initial production item(s) noted in 3.1 and 6.2. First article inspection shall consist of the examination in 4.3, all tests in 4.4, and the packaging inspection in 4.5. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.2.2 Quality conformance inspection.

4.2.2.1 Inspections and tests. Quality conformance inspection shall be applied to production units offered for acceptance under the contract. Quality conformance inspection shall consist of a. through j. as follows, and failure of any unit to pass an examination or test shall be cause for rejection of the unit.

a. Product examination (see 4.3).

b. Machine accuracy test (see 4.4.1).

c. Drum truing test (see 4.4.2).

d. Disc truing test (see 4.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

e. Automatic stop test (see 4.4.5).

f. High voltage requirement test (see 4.4.6).

g. Grinding wheel speed test (see 4.4.7).

h. Paint adhesion test (see 4.4.8).

i. Hardness tests (see 4.4.9).

j. Packaging inspection (see 4.5).

4.2.2.2 Sampling. Sampling for quality conformance inspection shall be performed in accordance with MIL-STD-105, using the following:

Inspection or test	Level	AQL
Product examination (4.3)	II	1.0
Machine accuracy test (4.4.1)	II	1.0
Drum turning test (4.4.2)	S-4	1.0
Disc truing test (4.4.3)	S-4	1.0
Automatic stop test (4.4.5)	S-4	1.0
High voltage req'm't test (4.4.6)	S-4	1.0
Grinding wheel speed test (4.4.7)	S-4	1.0
Paint adhesion test (4.4.8)	S-4	1.0
Hardness tests (4.4.9)	S-4	2.5
Packaging inspection (4.5)	S-4	4.0

4.3 Product examination. The lathes shall be visually, manually, and dimensionally examined to determine conformance with the requirements of 3.2 through 3.3.3, 3.4.1, 3.5 through 3.5.8.4, and 3.5.9 through 3.10 (including 3.5.10.1 and 3.5.10.2, if applicable). Visual examinations shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from the identified defects. Manual examinations shall include the operation of movable parts by hand to assure proper functioning. Dimensional examination shall verify size and weight conditions when specified. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the lathes and their components have passed the examinations prescribed for them by the contractor's inspection systems shall be cause for rejection. In addition, failure of the contractor to provide objective evidence that all parts are manufactured to definite standards, clearances, and tolerances so that no replacement part will degrade the form, fit, or function of the end item (see 3.2.1), shall be cause for rejection.

4.4 Tests. Measuring instruments used in performing the following tests shall be more accurate by a factor of ten than the specified limit, and shall be traceable to the National Bureau of Standards. Failure to pass any of the test requirements shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.4.1 Machine accuracy test. The spindle taper run-out, arbor run-out, adapter run-out and concentricity, and carriage alignment of the lathe shall be measured. Failure of the machine to comply with the requirements of 3.4.2 shall be cause for rejection.

4.4.2 Drum truing test. Three brake drums shall be set up and turned as a typical operation. A large brake drum (minimum diameter 24 inches) and a small brake drum (maximum diameter 6 inches) shall be turned, as well as a wide brake drum (minimum friction surface width 9 inches). The large brake drum shall weight at least 600 pounds and shall be trued without the aid of an outboard support. (At the contractor's option, weight may be attached to the brake drum as necessary to meet the weight requirement.) Performance accuracy of the lathe shall be determined by measuring the taper and concentricity of the turned surface to the spindle with dial indicators accurate within plus/minus 0.0001 inch, while the freshly turned drum is still mounted on the lathe. The drum shall then be loosened on the arbor, rotated to 120 and 240 degrees from its original position on stationary arbor and short radius cone, and measured for concentricity with the spindle in both positions in the same manner as above. For the first article test only, the turned drum shall then be mounted on a vehicle spindle with proper companion bearing assemblies (cups, cones, and ball or roller bearings) in place and torqued in accordance with the bearing manufacturer's recommendations, and re-measured for taper and concentricity with the vehicle spindle in both positions in the same manner as above. For the first article test only, the turned drum shall then be mounted on a vehicle spindle with proper companion bearing assemblies (cups, cones, and ball or roller bearings) in place and torqued in accordance with the bearing manufacturer's recommendations, and re-measured for taper and concentricity with the vehicle spindle. The final finish of the turned drum shall then be checked with a surface analyzer or profilometer. Failure of the lathe to attain the performance requirements of 3.4 and the rough cut, final finish, and accuracy requirements of 3.4.3 and 3.4.3.1 shall be cause for rejection.

4.4.3 Disc truing test. Two brake discs shall be set up and trued as a typical operation. A large brake disc (friction surface diameter no less than 19 inches) and a small brake disc (friction surface diameter of no more than 5 inches) shall be trued. The large brake disc shall weigh at least 600 pounds (At the contractor's option, weight may be attached to the disc as necessary to meet this requirement.) Performance accuracy of the lathe shall be determined by measuring the true plane of each rotor surface and the parallelism of the rotor surfaces with dial indicators accurate within plus/minus 0.0001 inch, while the freshly trued disc is still mounted on the lathe. The disc shall then be loosened on the arbor, rotated to 120 and 240 degrees from its original position on the stationary arbor and short radius cones, and the true planes and parallelism of the rotor surfaces re-measured in both positions in the same manner as above. For the first article test only, the trued disc shall then be mounted on a vehicle spindle with proper companion bearing assemblies (cups, cones, and ball or roller bearings) in place and torqued in accordance with the bearing manufacturer's recommendations, and the true planes and parallelism of the rotor surfaces re-measured. The final finish of the trued disc shall then be measured with a surface analyzer of profilometer. Failure of the lathe to attain the performance requirements of 3.4 and the rough cut, final finish, and accuracy requirements of 3.4.4 and 3.4.4.1 shall be cause for rejection.

4.4.4 Spindle speed test. The lathe shall be tested with a tachometer to determine speeds and speed ranges. Failure of the spindle speeds to comply with 3.4.1.(i) and 3.4.1.(j) shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.4.5 Automatic stop test. Without a brake disc or brake drum mounted on the lathe, the lathe shall be turned on and the carriage and cross-slide drives operated to the limits of their travel. Failure of the automatic stops to operate in accordance with 3.5.6.2 shall be cause for rejection.

4.4.6 High voltage requirement test. A test voltage of at lease 2500 volts rms, 60 Hz, shall be applied instantaneously between each and every isolated circuit in the unit. The voltage shall be supplied by a transformer having a volt-ampere capacity of at least 500. The voltage shall be applied to an uninsulated point in each circuit and between each circuit and frame or chassis ground. The voltage shall be maintained for at least 15 seconds. When test voltage is applied to the power input terminals the master switch and other involved switches shall be in the closed position. During this part of the test solid state components shall be replaced or repaired upon conclusion of the test. When testing internal circuits, solid state devices may be bridged or removed to prevent damage. Any damage to any part other than solid state components evidenced by manlfunction, breakdown, arcing, or other surface or air discharge shall be cause for rejection (see 3.5.8.5). CAUTION: Due to high voltage, extreme care should be taken during this test.

4.4.7 Grinding wheel speed test. When a grinding attachment is specified in the contract, the spindle speed of the grinding attachment shall be measured with a tachometer while performing grinding operations on the brake drums tested in 4.4.2. The test shall include use of each size and type of grinding wheel provided with the attachment. Failure of the attachment to maintain a calculated surface speed of 3600 to 7000 feed per minute for each wheel during the grinding operation shall be cause for rejection (see 3.5.10.2).

4.4.8 Paint test. The hardness, adhesion, and thickness of the paint used on the machine shall be checked as follows:

a. The graphite point of a sharpened HB lead pencil shall be pressed at a right angle into a painted area of the unit until the graphite crumbles. Failure of the surface to withstand the test, as evidenced by a pitting of the paint, shall be cause for rejection.

b. A test sample of the same metal, painted with the same process and at the same time as the unit, shall have a sharpened H lead pencil pressed into the paint as in a. Failure of the surface to pit (paint too hard) shall be cause for rejection.

c. Two, two-inch intersecting lines shall be cut through the paint to the base metal of the test sample. A strip of 1/2 inch wide fiberglass tape shall be firmly pressed over the intersection and then pulled from the surface. Adhesion of any paint to the tape shall be cause for rejection.

d. Using a paint thickness measuring instrument, or by masking a portion of the test sample during painting, measure the thickness of the paint. Failure of the paint to be at least 0.002 inch thick shall be cause for rejection.

4.4.9 Hardness tests. The lathe spindles and arbors shall be hardness tested to Rockwell C, or equivalent superficial scales may be used and converted to Rockwell C. Spindle hardness shall be in the Rockwell C40 to C50 range and arbor hardness shall be at least Rockwell C50 (see 3.5.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.5 Packaging inspection. The lathes shall be inspected before and after packaging to determine compliance with the preservation, packaging, packing, and marking requirements specified in Section D of the contract.

5. PACKAGING

5.1 First article. When specified (see 4.2), the contractor shall furnish one complete pack for first article packaging inspection. The first article may be either a preproduction pack or an initial production pack which conforms to the requirements stated herein. In either case, the approved first article and the production packs shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements stated herein.

5.2 Disassembly. When practical, for the protection of components, attachments, and accessories against damage, pilferage or to reduce cubage, items may be disassembled only to a necessary basic degree. Disassembled parts shall be preserved, anchored, braced, blocked, and cushioned to prevent damage. Disassembled parts shall be clearly and legibly marked as to identity and proper location on the assembled item. All fasteners removed during disassembly shall be secured in one of the mating parts. A part shall not be removed from an assembly unless it can be reassembled readily in the field without special skills or tools.

5.3 Disassembled parts marking. Disassembled parts shall be marked, when necessary with instructions, to facilitate reassembly. Removed parts and mating parts on the item shall be marked by stenciling, on the part, or by the use of tags. Tags shall be waterproofed and ink used (on parts or tags) shall be waterproof. Tags shall be firmly secured to each individual part.

5.4 General requirements. Component parts of machinery, accessories, and maintenance tools shall be cleaned, dried, preserved, packaged, and packed as specified herein. Parts and assemblies which are not covered herein shall be preserved and packaged utilizing the materials and methods specified for similar parts and assemblies described herein. Cleaning and drying procedures, and preservatives shall conform to the criteria and guidelines specified herein.

5.5 Level A preservation.

5.5.1 Cleaning and drying. Thorough cleaning and drying of all bare ferrous metal surfaces is essential before the application of a preservative. Care must be taken to limit the handling of cleaned parts prior to the assembly of new machinery. Where practicable, processors and assemblers shall wear rubber or plastic gloves while handling cleaned parts.

5.5.2 Internal surfaces. All ferrous metal surfaces of parts which will be utilized internally in the assembly of new machinery shall be solvent cleaned followed by fingerprint remover and wiped or drain dried. In the interim, to preclude contamination from forming on cleaned surfaces prior to the assembly operation, parts shall be coated with a light weight preservative oil conforming to P-9 (see VV-L-800). To prevent dust from accumulating on cleaned parts, cover with a sheet of chemically neutral paper conforming to MIL-P-17667.

5.5.3 External surfaces. All accessories and attachments such as chucks, faceplates, steady rests, toolholders, abrasive wheels, etc., shall be removed from the assembly prior to the external cleaning operation. All external, critical

Source: https://assist.dla.mil -- Downloaded: 20261O-26T11:58Z
Check the source to verify that this is the current version before use.

ferrous metal surfaces, fit or function, of the machine shall be solvent cleaned followed by fingerprint remover and wiped or drain dried. Noncritical ferrous metal surfaces shall be solvent cleaned and wiped or drain dried. Nonmetallic composites and painted metal surfaces shall be cleaned by wiping with a clean, dry cloth. Care must be taken to prevent cleaning solvents from coming in contact with nonmetallic components. When cleaned surfaces of the machine show signs of rusting before application of the final preservative, reprocessing the rusting surface shall be confined to that area of the assembly. The solvent used for the final wiping operation shall contain a small amount, approximately 5 percent by volume, preservative oil conforming to P-10, type 10, grade 30 (see MIL-L-21260). It is extremely important that elapsed time between these operations be held to an absolute minimum.

5.5.4 Disassembled components. Disassembled components detached from the basic machine shall be cleaned and dried a specified herein for like items.

5.5.5 Lathe and accessories. The lathe and its accessories shall be clean and free from contaminants. Preservatives shall be applied to provide protection from corrosion during shipment and storage. All preserved items shall be wrapped with greaseproof barrier material. Critical surface items, i.e., parallels, etc., shall also be wrapped with no less than 1/2 inch uncompressed cushioning material.

5.5.6 Electrical equipment. Electrical equipment shall be clean and dry. Preservatives shall be applied as required to prevent corrosion to moving or other ferrous metal parts, but shall not come into contact with electrical connections, windings, etc. Openings shall be sealed with cap-plugs or with waterproof, pressure sensitive tape conforming to PPP-T-60 to provide protection against entry of any foreign materials.

5.5.7 Lubricating systems. Vent openings in the lubrication systems shall be temporarily capped or plugged to prevent loss of lubricants during shipment. Tags, warning that "ALL TEMPORARY CAPS OR PLUGS MUST BE REMOVED BEFORE START-UP OR USE OF THE ITEM", shall be attached to all temporary caps or plugs intended to be vented to the atmosphere during operation. These warnings shall also be included in the instruction manual. In the event a lubricant reservoir cannot be covered and sealed, it shall be appropriately preserved and the lubricant shall be provided in a sealed container and shipped with each machine. A warning tag shall be placed in a conspicuous place near the filling area, warning the user to "INSTALL THE FURNISHED LUBRICANT BEFORE OPERATION OF THE EQUIPMENT". The operator's manual shall also reflect the above warning and procedure.

5.5.8 Maintenance and hand tools. Maintenance and hand tools such as screwdrivers, hammers, chisels, etc., shall be clean and free from contaminants. Sharp edges such as cutting edges shall be protected by a fiberboard shield placed on the edge and taped in place. Tools shall be placed in a fiberboard box and secured from movement so as to prevent damage to the tools or other items.

5.5.9 High-speed spindle bearings. The reservoir shall be filled to normal operating level with manufacturer's operating lubricant. If the system is of such design that the oil will leak out during shipment or storage, the system shall be preserved by filling with preservative oil P-10, type I, grade 30 (see MIL-L-21260), and drained. Operational lubricant shall be furnished.

5.5.10 Grease fittings. All grease fittings shall be charged with preservative compound conforming to P-11 (see MIL-G-10924).

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T11:58Z
Check the source to verify that this is the currentversion before use.

5.5.11 Nonlubricated interior surfaces. Surfaces of internal gears which do not run in lubricant shall be thoroughly coated with P-2 (see MIL-C-16173), grade 2 preservative.

5.5.12 Gear cases. The gear cases shall be filled with normal lubricating oil. Shift gears into all possible positions while operating the machine, then close and seal all openings.

5.5.13 Sliding or friction surfaces. Surfaces of ways, gibs, driving gears, traversing and adjusting screws, and other critical, exterior operating machined surfaces shall be coated with P-2 (see MIL-C-16173), grade 2 preservative compound and covered with greaseproof barrier material. Parts of the machine which are adjustable shall be locked into place.

5.5.14 Bearings and journals. Grease lubricated bearings shall be preserved with P-11 (see MIL-G-10924) preservative. Oil lubricated journals shall be filled with lubricating oil P-10, type I, grade optional (see MIL-L-21260).

5.5.15 Drive belts and pulleys. Drive belts shall either be removed from the machine or released from tension. Ferrous metal pulleys shall be coated with rust-inhibiting primer. Belts removed from the machine shall be packaged in a waterproof, greaseproof bag and sealed.

5.5.16 Electrical wiring system. Exposed ends of wires, plug openings, sockets, connector plugs, terminals, and openings into switches and junction boxes, etc., shall be sealed with waterproof tape conforming to PPP-T-60 or cap-plugs, respectively. Electric cable shall be coiled to a minimum safe diameter and secured with cotton tape or twine to prevent uncoiling.

5.5.17 Closed dial indicators. Closed dial indicators shall be covered with 1 inch thick uncompressed cushioning material and secured in place with waterproof, pressure sensitive tape conforming to PPP-T-60. Cushioning materials and tape used shall be water-resistant, non-dusting and non-corrosive.

5.5.18 Drawers and door assemblies. Sliding surfaces of drawer guides shall be coated with P-11 (See MIL-G-10924) preservative grease. Interior surfaces of door hinges shall be lubricated by application of P-10, grade 30 (see MIL-L-21260) preservative oil. In addition to mechanical locks or catches incorporated in the machine, secure doors and drawers with metal strapping or other devices which are suitable for the purpose intended. Fiberboard pads shall be placed under metal strapping to prevent marring the surfaces.

5.5.19 Closure of openings. Small openings, except vents and louvers installed for ventilation purposes, shall be sealed with waterproof, pressure sensitive tape conforming to PPP-T-60. Large openings shall be covered with waterproof barrier material. Secure materials in place with tape specified above. When very large openings are covered, or when location of openings render coverings vulnerable to puncture, coverings shall be protected by applying wood, plywood, sheet metal or fiberboard over the materials. Open ends of all piping and fittings shall be plugged to prevent the entrance of foreign materials, using pipe fittings, waterproof tape conforming to PPP-T-60 or plastic cap-plugs.

5.5.20 Technical data. Technical data furnished with the machine shall be packaged in a waterproof, greaseproof barrier material and sealed. The package shall be legibly and clearly marked "TECHNICAL DATA" in bold letters. The package shall be protected against puncture and abrasion. The data shall be either attached

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

to the machine with tape, placed in a stowage compartment of the machine, or positioned in a consolidated box containing accessories or disassembled components.

5.5.2.1 Consolidated packaging. Packaged accessories, maintenance tools, and small disassembled components shall be consolidated and placed in drawers and stowage compartments of the machine. When it is not feasible to stow parts as specified above, place parts in weather-resistant fiberboard box or boxes of sufficient strength to handle weight inside. Large bulky disassembled components shall be packed as specified (see 5.6.1).

5.5.22 Cushioniing. Cushioning materials shall be water resistant, non-dusting and non-corrosive and of sufficient thickness to prevent damage, not less than 1/2 inch thick wrap.

5.5.23 Protection of preservatives. All exposed preserved surfaces of machines which are subject to being disturbed during the packing operation shall be loosely covered with greaseproof barrier material. Not less than two layers of similar-type barrier material shall be used to separate wood or metal blocking and finished metal surfaces of the machine. Secure barrier in place with waterproof, pressure sensitive tape conforming to PPP-T-60.

5.5.24 Movable parts. Operating heads, sliding tables, rams, counter-balances, and other movable parts shall be secured by mechanical devices incorporated in the machine. The devices alone do not always provide adequate support to prevent movement in the handling and transporting of the item and therefore must be augmented with appropriate with appropriate wood blocking, metal tie rods used in conjunction with wood blocking, metal strapping, or other devices which will immobilize the part. Handwheels, cranks, levers, and similar controls shall be secured in position with common annealed wire or steel strapping.

5.5.25 Positioning assemblies. Assemblies having vertical movement shall be blocked and braced in a lowered position; those capable of moving traversely shall be centered, blocked and braced to prevent movement.

5.5.26 Tables. All tables and other components designed for movement shall be removed, or blocked, and all components treated in such a manner that neither the way(s), surface(s), nor the anti-friction devices will be subject to brinelling or other damage.

5.6 Level A packing.

5.6.1 Machinery. Machines shall be packed individually in crates conforming to MIL-C-104, type I, class 2, style A. Consolidated containers shall be packed with the machine in the specified crate. Arrangement of contents, anchoring, blocking, bracing, and cushioning shall be in accordance with the appendix to the crate specification, MIL-STD-1186, and as specified herein. Consolidated containers for large bulky disassembled items (see 5.5.25) shall conform to PPP-B-601, domestic, style optional.

5.6.2 Bolting. Machines shall be secured to the skid base by no less than four bolts. When sufficient bolting points are not available, J-clamps or tie rod assemblies, or other devices shall be used to provide the minimum of four holding points. Bolts shall pass completely through the skid runner or sleeper, as applicable, and the base flooring.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the currentversion before use.

5.6.3 Consolidated containers. Consolidated containers shall be placed inside the shipping container housing the machine. The boxes shall be restrained by use of metal strapping or tie rod assemblies.

5.6.4 Operational oils. Operational oils furnished with the machine, but not placed in the machine stowage receptacles, shall be stowed in metal drum(s). Drums shall be positioned upright inside the shipping container housing the machine. Blocking shall be applied to immobilize the drum(s) inside the shipping container.

5.7 Marking. Marking shall be in accordance with MIL-STD-129. Bar coding is also required in accordance with MIL-STD-129.

5.8 Workmanship. Workmanship shall be such that when proper procedure is followed, materials and equipment being processed will be provided the maximum protection against corrosion and deterioration consistent with the shipment hazards known or anticipated, and suitable for long term storage.

6. NOTES

6.1 Intended use. The floor mounted, with base, lathes covered by this specification are intended for use in truing brake drums and disc brake rotors of the commercial and military type.

6.2 Acquisition requirements. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number, and date of this specification.

b. First article, when required (see 3.1).

c. Case, when required (see 3.5.10.1).

d. Grinding attachment, when required (see 3.5.10.2).

e. First article inspection, if different (see 4.2.1).

f. Preservation-packaging and packing, if different (see 5.1).

g. First article packaging inspection, if required (see 5.1).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, wiring diagrams, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on DD Form 1423 incorporated into the contract.

6.4 Safety and health requirements. In order that equipment integrated into the user's operational environment will comply with OSHA limitations and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc., as applicable, specific requirements concerning such points of operation and other health and safety requirements should be specified by the user.

6.5 The values stated in US customary units are to be regarded as the standard. The metric equivalents of US customary units given in this specification may be approximate.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodian:

Army - AL
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS

Preparing activity:

Army - AL

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.