00-M-1724A
April 30, 1974
SUPERSEDING
Fed. Spec. 00-M-1724
January 12, 1972

# FEDERAL SPECIFICATION

# MARKING MACHINES, LAUNDRY

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

## 1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers marking machines used in fixed laundries and dry cleaning installations.

1.2 Classification. The marking machines shall be of the following styles, classes and sizes with applicable supports and support style as specified (see 6.2).

| | | |
|---|---|---|
| Style A | - | Electrically operated 18-point type, permanent marking |
| Class 1 | - | Keyboard operated |
| Size 1 | - | 16 character wheels |
| Class 2 | - | Lever operated |
| Size 1 | - | 6 character wheels |
| Style B | - | Pneumatically operated, 18-point type permanent marking |
| Class 1 | - | Keyboard operated |
| Size 1 | - | 8 character wheels |
| Size 2 | - | 16 character wheels |
| Class 2 | - | Lever operated |
| Size 1 | - | 6 character wheels |
| Style C | - | Manually operated, 18-point type, lever operated permanent marking |
| Size 1 | - | 6 character wheels |
| Style D | - | Electrically operated, temporary marking, not less than 15-point, or less than 5 character wheels, lever operated |

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

Style E - Pneumatically operated, temporary marking type, not less than 15-point, or less than 5 character wheels, lever operated

Style F - Pneumatically and/or electrically operated, temporary marking laundry, not less than 15-point or less than 5 character wheels and with pricing and listing console

Style G - Electrically operated, temporary marking, dry cleaning, not less than 15-point, or less than 6 character wheels

Support 1 - Table

Style A - One straight section

Style B - One long section and one short section (right angle forming)

Support 2 - Cabinet

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

CC-M-636 - Motor, Alternating-Current (Fractional Horsepower).
CC-M-641 - Motors, Alternating-Current (Integral Horsepower, 200 HP and smaller).

Federal Standard:

FED-STD-123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

| | | |
|---|---|---|
| MIL-T-152 | - | Treatment, Moisture and Fungus Resistant, of Communications, Electronic, and Associated Electrical Equipment. |
| MIL-L-3153 | - | Laundry and Dry-Cleaning Machinery and Equipment (For Fixed Installations), Preparation for Delivery for Domestic and Overseas Shipment. |

Military Standards:

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - | Marking for Shipment and Storage. |
| MIL-STD-130 | - | Identification Marking of U.S. Military Property. |
| MIL-STD-461 | - | Electromagnetic Interference Characteristics, Requirements For Equipment. |
| MIL-STD-462 | - | Electromagnetic Interference Characteristics, Measurement Of. |
| MIL-STD-1474 | - | Noise Limits For Army Material. |

(Copies of specifications, standards and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

29 CFR 1910 - OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA) STANDARDS

(The Code of Federal Regulations (CFR) and Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Underwriters' Laboratories, Inc., (UL)

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio St., Chicago, IL 60611; 1285 Walt Whitman Road, Melville, Long Island, NY 11746; or 1655 Scott Boulevard, Santa Clara, CA 95050.)

National Fire Protection Association (NFPA)

No. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

3.2 Standard product. The items delivered under this specification shall be the manufacturer's commercial product, except for any changes necessary to comply with specification requirements. All like items furnished on any one contract, including parts and subassemblies thereof shall be new and interchangeable.

3.3 Codes and standards. Marking machines shall comply with the applicable requirements of OSHA 29 CFR 1910 and NFPA No. 70.

3.3.1 Compliance. Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative satisfactory evidence that the marking machine that he proposes to furnish under this specification meet the applicable requirements of OSHA and NFPA No. 70.

3.3.1.1 OSHA. Acceptable evidence of meeting the applicable safety and health standards of OSHA shall be a certificate of compliance certifying that the marking machines furnished conforms to OSHA Standard 29 CFR 1910.264.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.3.1.2 NFPA. Acceptable evidence of meeting requirements of NFPA standard shall be a certificate of compliance that the marking machine when applicable is wired in accordance with NFPA Standard No. 70.

3.4 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial marking machine or support provided that the completed item complies with all provisions of this specification.

3.5 Design and construction (general). The marking machines including accessories covered by this specification shall conform to the requirements specified hereinafter.

3.5.1 Electrical systems and equipment.

3.5.1.1 Electrical characteristics. The electrical components of the equipment shall conform to the voltage, frequency, and number of phases specified (see 6.2).

3.5.1.2 Motors. Motors shall be supplied with inclosures in accordance with the manufacturer's standard practice. Motors shall conform to the applicable requirements of CC-M-636 or CC-M-641, as applicable, and to the following requirements:

(a) All motors shall have windings impregnated to resist moisture.
(b) Motors shall have the proper starting characteristics and power for their intended operation under full-load conditions without exceeding the permissible temperature rise.
(c) Motors shall be equipped with ball bearings, except that motors of less than 1/2 horsepower for horizontal applications may have sleeve bearings.
(d) Motor bearings shall be of the permanently lubricated type or shall have adequate and accessible means for lubrication.
(e) Each motor shall be provided with a manual reset and thermal overload protection.

3.5.2 Lubrication. Means shall be provided to insure proper lubrication of all moving parts. Equipment shall be designed to prevent lubricant from entering areas of the equipment where clothes are handled.

3.5.3 Electromagnetic compatibility. When specified (see 6.2), electrical equipment procured under this specification shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.5.3).



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:01Z
Check the source to verify that this is the current version before use.

3.6 Design and construction. The assembled marking machines shall have complete and proper interrelationship of components, no overheating of parts, starting and stopping devices shall operate smoothly and positively, and there shall be no structural failures. Conformance of the requirements for each style, class and size marking machine specified shall be determined when tested in accordance with 4.5.1. When tested as specified in 4.5.2, the marking machine noise limits shall conform to MIL-STD-1474.

3.6.1 Key operated machines. Key operated machines designated as class 1, for styles A and B marking machines shall be equipped with 18-point character type wheels and shall set up for printing the desired identification mark when selected keys are operated. The keyboard shall be of the typewriter adding machine principle and shall contain each letter of the alphabet; each numeral; a dash (-); and a blank for spacing. Each key shall control a designated character on each of the character wheels. A return character lever shall be provided to clear all characters wheels to the blank position at one time.

3.6.2 Character wheels. The styles A and B, class 1 machines shall have the following number of character wheels:

| | | | | |
|---|---|---|---|---|
| Style A | - | Size 1 | - | 16 wheels |
| Style B | - | Size 1 | - | 8 wheels |
| Style B | - | Size 2 | - | 16 wheels |

The character wheels shall be fabricated of metal and of a composition normally used by the manufacturer in his commercial product.

3.6.3 Lever operated machines. Lever operated marking machines designated as class 2, styles A and B, and styles C, D, E, F, and G machines shall place a selected character at the print position when the lever is moved to the selected character in an independent slot. Each slot shall have an indicator containing characters conforming to the character wheels. Each lever set up shall be positively connected to provide movement of the character wheel.

3.6.4 Character wheels. The character wheels shall be made of the same material as the character wheels of the key operated marking machines (see 3.6.2). Lever operated marking machines shall have character wheels as follows:

| | | | | | | |
|---|---|---|---|---|---|---|
| Style A | - | Class 2 | - | 6 character wheels | - | 18-point |
| Style B | - | Class 2 | - | 6 character wheels | - | 18-point |
| Style C | | | - | 6 character wheels | - | 18-point |
| Style D | | | - | 5 character wheels, min | - | 15-point, min |
| Style E | | | - | 5 character wheels, min | - | 15-point, min |
| Style F | | | - | 5 character wheels, min | - | 15-point, min |
| Style G | | | - | 6 character wheels, min | - | 15-point, min |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.6.5 Alignment. An alignment bar or other means shall be provided for easy alignment and maintaining the selected characters in the printing position for any desired marking.

3.6.6 Inking reservoirs or device. An ink reservoir or inking ribbon, as applicable, shall be provided with the marking mechanism. When an ink reservoir is provided, the capacity shall approximate a normal 8 hour work day. The construction of the inking device shall conform to the manufacturer's current commercial practice.

3.6.7 Electrically operated machines. All electrically operated marking machines shall be operated from an electrical source as specified (see 3.5.1.1 and 6.2). The machines shall be furnished complete with an electric motor conforming to 3.5.1.2, an "ON" and "OFF" switch, an electric cord and plug and a driving mechanism to operate the machine.

3.6.7.1 Machine construction. The electric marking machines shall include a metal base, metal housing including front, back and side covers. Character setting mechanism shall be either die-cast metal or steel. All parts shall be fully inclosed with the exception of such openings as are necessary for the operation of the machine.

3.6.8 Pneumatically operated machines. All pneumatically operated marking machines shall be designed to operate by pneumatic power, the mechanism for character printing in proper sequence. The general construction of the marking machine shall be the same as the electrically operated machine (see 3.6.7.1). The machine shall be provided with an air regulator valve and an air pressure gage in accordance with the manufacturer's current commercial practice.

3.6.9 Manually operated machine. The style C machine shall be designed to be operated by manually working a lever after all the required characters are aligned to produce the marking on a garment. All parts of the machine shall be fully inclosed with the exception of such openings as are necessary for the operation of the machine.

3.7 Style details.

3.7.1 Style A. Style A, class 1 and class 2 machines shall be electrically operated and all components, when operated, shall perform as specified in 3.6, when tested as specified in 4.5.1. Characters required shall conform to 3.6.1.

3.7.2 Style B. Style B, class 1 and class 2 machines shall be pneumatically operated, and when in operation, shall perform as specified in 3.6 when tested as specified in 4.5.1. Characters shall include all the letters of the alphabet; numeral 0 through 9; and a dash (-).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

3.7.3 Style C. The style C machine shall print the selected characters by manually operating a lever. Characters required are all the characters of the alphabet; numerals 0 through 9; a dash (-) and when specified (see 6.2) special character blanks and a blank space. The indicator shall contain characters conforming to the character wheels. When operated, the components shall perform as specified in 3.6 when tested in accordance with 4.5.1.

3.7.4 Style D. The style D marking machine shall be electrically operated, and the component shall perform as specified in 3.6 when tested in accordance with 4.5.1. The characters shall include 24 or more letters on the letter wheels; numerals 0 through 9 on the numeral wheel or the character wheels shall be provided with all the letters of the alphabet and numerals 0 through 9 on each character wheel. Two counters shall be provided to register each time a mark is made. One counter shall be nonsettable and one resettable. The style D machine shall feed at least 1/4 inch wide woven or pre-coated marking tag material; print the tag material; cut the tag material to produce at least a one inch long tag; and seal the tag to garments with or without the use of solvents. The performance shall be in a sequence of at least 4 basic steps. The mechanism shall be synchronized to operate in proper sequence, so that one movement of the operating handle shall produce a completely marked tag. Opening of an invoice clip shall either cause the machine to become inoperative until the bundle numbering lever has been advanced or automatically advances the number. Sealing shall be accomplished by a temperature controlled heating platen, applied pressure, and a dwell time governed by a timer or cam movement. When the sealing cycle is complete, the operating handle shall release from the sealing position. Tag removal shall not require the use of solvents nor shall there be any noticeable residue left on the marked garment when the tag is removed (see 4.5.1).

3.7.5 Style E. The style E machine shall be pneumatically operated. Operating characteristics and character wheels are otherwise the same as style D (see 3.7.4).

3.7.6 Style F. The style F machine shall be electrically or pneumatically operated and shall include character wheels as specified in 3.7.4 and a console containing a listing of pieces and prices and totals which are synchronized with the operation of the invoice printing and marking machines. The buttons on the console shall identify the names of items processed in laundries. The console shall provide for recording the total number of pieces and total price of the item. Performance shall be the same as 3.7.4 except that the invoice clip board is not employed.

3.7.7 Style G. The style G marking machine shall be electrically operated and when operated, the components shall perform as specified in 3.6 when tested in accordance with 4.5.1. Character wheels shall be as specified in 3.7.4. The top invoice clip, which is used to hold the invoice while the bundle



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

is being marked shall be wired to automatically inactivate the machine until the bundle numbering lever is advanced. The machine shall feed not less than 1/2 inch wide marking tag material; print the tag, cut the tag to produce a one inch long tag and staple the tag to the garment. The mechanism shall be synchronized to operate in proper sequence so that one movement of the operating handle shall produce a completely marked and stapled tag to the garment. When stapling is complete, the operating handle shall release the stapling device (see 4.5.1). The machine shall be provided with two rheostats, one for printing pressure and one for stapling control.

3.8 Accessories. Styles D, E, F and G marking machines shall be provided with an attached invoice listing board table, and tape roll storage rack. The tape roll storage rack shall provide a storage space for not less than ten rolls of tag material. The style G machine shall be provided with two invoice clips on the listing board, the tape roll storage rack and the flag tag holder.

3.9 Marking machine supports.

3.9.1 Support 1.

3.9.1.1 Style A table. When specified (see 6.2), the table shall be 2 feet 4 inches wide by 4 feet 4 inches long with a back wall 5 feet 8 inches high with a tolerance of ± 3 inches applicable to these dimensions. The height of the table (working area) shall be 2 feet 10 inches ± 2 inches above the floor (or the table shall be the manufacturer's standard table with a working height and other dimensions compatible with machine furnished). The entire framework of the table, including the four legs shall be fabricated of minimum 2- by 1-1/2 by 1/8 inch angle iron. The framework shall be braced and bolted. Each leg shall be adjustable for leveling the table. The back wall shall be made of ferrous sheet metal material, not less than 0.052 inch thick, bolted to the frame. The table top shall be provided with a recessed work bin of ferrous metal material, not less than 0.052 inch thick, the front side of which shall be tapered inward. The bin size shall conform to the manufacturer's commercial practice. A shelf of ferrous sheet metal material, not less than 0.052 inch thick shall be mounted on the back wall for storing marking supplies.

3.9.1.2 Table ends. The end of the table where the marking machine is mounted shall have a top of ferrous sheet metal material, not less than 0.092 inch thick, adequately braced and bolted to the frame to withstand the weight of the machine. Holes shall be provided for mounting the marking machine.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:01Z
Check the source to verify that this is the current version before use.

3.9.1.3 Net holder. An angle iron frame for the holding of two laundry nets shall be provided and mounted at the left end of the table.

3.9.1.4 List board. A wood list board with means for mounting and holding a laundry list shall be provided in accordance with the manufacturer's commercial practice.

3.9.1.5 Style B table. When specified (see 6.2), the style B table shall consist of a long table and a short table with a total of six legs, which can be assembled to form a 90° angle for right or left machine operation and having a common back upright fastened to legs and supports. Each table shall be equipped with one full shelf. The table height working area shall be 32 inches ± 1 inch above the floor when tables are assembled and all six legs setting on the floor. The frame for supporting table top and shelf shall be fabricated of channel shape cold rolled steel. The legs shall be heavy duty angle iron capable of supporting the marking machine, equipment and working materials for its intended use.

3.9.2 Support 2, cabinet. When specified (see 6.2), the cabinet furnished shall be of the type designed for use with a specified machine and normally supplied to commercial users for use with similar equipment.

3.9.2.1 Motor support and electrical accessories. Cabinets for electrically operated marking machines shall be provided with a motor support platform 11 inches below the cabinet top. In addition, these cabinets shall be provided with an electrical receptacle to which an 8 foot extension cord, with plug, is attached. The cabinet shall have a thermal overload switch that is wired to the receptacle.

3.9.2.2 Controls.

3.9.2.2.1 Electric controls. The drive mechanism of the electrically operated machines shall be controlled by a foot pedal so the operator may operate the machine by foot, leaving both hands free to handle the materials.

3.9.2.2.2 Pneumatic controls. The drive mechanism of pneumatically operated machines shall be controlled by either of the following methods for the operator's protection:

(a) Two trip knobs on either side of the platen.
(b) Twin lever type operation using operating handles. The moving member or members shall be designed so they cannot lock in the event an obstruction over 3/4 inch is between the platen and type.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the currentversion before use.

3.10 Name and data plates. Except on procurements for civil agencies, each item of equipment covered by this specification shall be marked for identification in accordance with MIL-STD-130. For procurements for civil agencies, the plates may be in accordance with the manufacturer's standard practice provided they are legibly and permanently marked with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined and shall contain the type, size, and the electrical characteristics of the item, as applicable.

3.11 Moisture and fungus resistant treatment. When specified (see 6.2), electrical components of equipment covered by this specification shall be moisture and fungus resistant treated with material conforming to and applied as required by MIL-T-152.

3.12 Finish. Unless otherwise specified (see 6.2), the marking machines shall be finished in accordance with the manufacturer's standard practice.

3.13 Workmanship. The items shall be free from defects such as fractures, splits, punctures, tears, dents, creases, miscasts, or deterioration. There shall be no sharp edges, burrs, or slivers.

3.13.1 Application of finish. The finish applied to the marking machine shall be continuous smooth, adherent, without discoloration or foreign material imbedded and contain no sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, cracks, scratches, pores, pits, lumps, flux, or orange peel. No rust, rough grinds, or toolmarks shall show through the coating.

3.13.2 Welding and brazing. Electrodes or welding rods shall deposit material compatible with the base metal. All surfaces of parts to be welded or brazed shall be clean. Welding and brazing shall be accomplished in a manner which will prevent the occurrence of burn holes, cracks, fractures or incomplete fusion. All scale and flux deposits shall be removed from finished welds.

3.13.3 Soldering. Soldering shall be complete and adherent with all flux and residue removed and shall contain no pinholes.

3.13.4 Threaded fasteners. Threaded fasteners shall not be broken, stripped, fractured, or loose.

3.13.5 Rivets. Rivets shall be driven to completely fill the holes, with full size heads neatly finished and in full contact with the surface of the riveted members.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:01Z
Check the source to verify that this is the currentversion before use.

3.13.6 Electrical wiring. Wiring shall not be cut, abraded, or have excessive insulation stripped, and shall be properly and tightly joined at terminals. Wiring shall have adequate slack to provide strain relief.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article. When a first article is required, the marking machines shall be tested as specified in 4.5.1, 4.5.2 and 4.5.3 when applicable.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 End item inspection. A lot shall consist of all units of the same style, class, size and support, when required, as applicable, offered for inspection at one time. The sample unit shall be one completely fabricated end item.

4.4.2.1 Visual examination. The completely assembled end item shall be examined for defects classified in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Finish | Not continuous, smooth, adherent. | | X |
| | Sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, cracks, scratches, pores, pits, lumps, flux, or orange peel. | | X |
| | Rust, rough grinds or toolmarks, foreign matter imbedded, and not adherent. | | X |
| Construction and workmanship | Fractured, split, punctured, dented, or deteriorated. | X | |
| | Sharp burr, edge sliver, or splinter. | X | |
| | Component loose. | | X |
| | Not connected or joined as specified. | X | |
| | Anchor boltholes not provided when required. | X | |
| | Any component not readily accessible for servicing where required. | | X |
| | Moving parts not guarded. | X | |
| Welding and brazing (where required) | Incomplete, burn holes, cracked, fractured, or otherwise not fused. | X | |
| | Scale or flux deposits not removed. | | X |
| Soldering (when applicable) | Not adherent or is incomplete. | X | |
| | Not clean (flux or flux residue not removed), not smooth (surface not finished neatly) or pinholes in solder. | | X |
| Threaded fasteners | Missing, broken, stripped, fractured. | X | |
| | Loose. | | X |
| Rivets (when applicable) | Broken, loose, not peened, or insufficiently peened. | X | |
| Electrical assembly | Wiring cut, abraded, not properly joined, loose at terminal or not inclosed in specified conduit where required. | X | |
| | Adequate slack not provided for wiring to relieve strain or insulation stripped from wiring. | X | |



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Lubrication (where applicable) | Not lubricated where required. | X | |
| | Lubrication fitting not accessible for servicing. | X | |
| Marking machines | Not type, class or size as specified. | X | |
| | Not number of character wheels specified. | X | |
| | Character wheel point type not as specified. | X | |
| | Return character lever not provided (when required). | X | |
| | Character aligning bar not provided (when required). | X | |
| | Ink reservoir or device missing. | X | |
| | Tension device for holding materials not provided (when required). | X | |
| | Indicator strips not provided on keyboard (when required). | X | |
| | Receptacle for ear muffs not provided (when required). | X | |
| | Tag-marking attachment and tag-marking paper not provided as specified (when required). | X | |
| Table or cabinet (as applicable) | Marking machine support not provided (when required). | X | |
| | Marking machine support not type specified (when required). | X | |
| | Thermal overload switches not provided on motors (when required). | X | |
| | Electric controls not provided (when required). | X | |
| | Pneumatic controls not provided (when required). | X | |
| Marking for identification | Missing, incomplete, not legible. | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

4.4.2.2 Dimensional examination. Inspection shall be made of the end item to determine compliance with dimensional requirements. Any dimension that is not within the specified requirements shall be classified a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.4.2.3 Testing of the end item. Each unit of production shall be tested as specified in 4.5.1. Any nonconformance shall be cause for rejection of the unit. When first article is not required, the initial unit of production shall be tested as specified in 4.5.1 and 4.5.2 as required, and, when applicable, 4.5.3. Any nonconformance shall be cause for rejection of the lot. The operational test in 4.5.1 shall be performed prior to acceptance unless satisfactory evidence is produced that the item has previously satisfactorily passed this test either in the manufacturer's plant or in a commercial application (see 6.4). The Government reserves the right to check test such items to determine validity of the evidence produced.

4.4.3 Code and standards compliance. Proof of compliance with the requirements of 3.3.1 shall be available to the Government representative.

4.5 Tests.

4.5.1 Operational testing. The applicable marking machines covered by this specification shall be operational tested by the supplier to determine compliance with the requirements specified below. Each power operated item shall be connected to electric power of the specified voltage, frequency, and number of phases, and air power, as required, and tested to determine that the applicable performance requirements have been met. Any nonconformance with requirements specified in 3.6, as applicable, shall constitute failure of the test.

Style A. The style A, class 1 and 2 machines shall be operated for a period of 15 minutes to determine that all parts including the keys, return type lever, character wheels, automatic ink feed, and aligning driver, function satisfactorily, that the assembled item complies with the requirements of 3.6 and the operational requirements of subsequent paragraphs applicable to the style machine.

Style B. The style B, class 1 and 2 machines shall be operated for a period of 15 minutes. The class 1 machine shall be checked to determine that all parts including the keys, return lever, character wheels, automatic ink feed, and aligning driver, function satisfactorily and that the assembled item complies with the requirements of 3.6. The class 2 machine shall be checked to determine that all parts including setup lever, character wheels, alignment machanism, tension device, and automatic inking device function satisfactorily and that the assembled item complies with the requirements of 3.6. The machine shall also be checked for the operational requirements applicable to the style B machine.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:01Z
Check the source to verify that this is the currentversion before use.

Style C. The style C machine shall be operated for 15 minutes to determine that all parts including setup levers, character wheels, automatic inking device, alignment mechanism, and tension device function satisfactorily and that the assembled item complies with the requirements of 3.6 and the operational requirements of subsequent paragraphs applicable to the style C machine.

Style D and E. The style D and E machines shall be operated with at least 1/4 inch wide woven or pre-coated tag material and garments to determine that all parts including feed assembly, spray assembly, marking assembly and sealing assembly are synchronized to operate in proper sequence to produce completely marked garments. One hour after the sealed tags have been applied to the garments, they shall be removed by hand without using solvents. The garments shall also be examined for any noticeable residue. During the test, the invoice clip shall be opened to determine that the machine either becomes inoperative or advances the number automatically. The bundle number lever shall be advanced either automatically or manually to determine that the machine again becomes operative. The tags shall be measured for length to determine compliance with 3.7.4 and 3.7.5.

Style F. The style F machine with listing, pricing and totalling equipment shall be operated with at least 1/4 inch wide pre-coated tag material and garments to determine that all parts including feed assembly, marking assembly, sealing assembly and listing pricing and totalling equipment are synchronized to operate in proper sequence to produce completely marked garments and a completed invoice. One hour after the sealed tags have been applied to the garments, they shall be removed by hand without using solvents. The garments shall also be examined for any noticeable residue. When the total button is pressed and completed invoice is removed the lever shall advance automatically to the next bundle number or the lever may be moved manually to the next bundle number. The tags shall be measured for length to determine compliance with 3.7.6.

Style G. The style G machine shall be operated with at least 1/2 inch wide tag material and garments to determine that all parts including feed assembly, marking assembly and stapling assembly are synchronized to operate in proper sequence to produce completely marked and stapled garments. During the test, the invoice clip shall be opened to determine that the machine becomes inoperative until a new number is introduced. The bundle number lever shall be advanced manually to determine that the machine again becomes operative. The tags shall be measured for length and staples examined for attachment to determine compliance with 3.7.7.

4.5.2 Noise level test. The noise level test shall be conducted as specified in MIL-STD-1474 to determine compliance with 3.6.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

4.5.3 Electromagnetic compatibility. When electromagnetic compatibility is required, the first article or initial unit of production, as applicable, shall be tested by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or an independent testing agency. The supplier shall furnish the contracting officer a written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic compatibility test report and the requirements meet MIL-STD-461.

4.6 Examination of preparation for delivery. Examination of preparation for delivery shall be in accordance with MIL-L-3153.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Laundry equipment shall be preserved, packaged, and packed in accordance with applicable level A, B, or C requirements of MIL-L-3153 (see 6.2).

5.2 Marking.

5.2.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.2.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The marking machines and supports, covered by this specification are intended for use in fixed laundry and dry cleaning installation

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in the procurement documents:

(a) Title, number, and date of this specification.
(b) Style, class, size and support and support style, if applicable, required (see 1.2).
(c) When a first article is required (see 3.1, 4.2 and 6.3).
(d) Electrical characteristics required (voltage, phase, and frequency) (see 3.5.1.1).
(e) When electromagnetic compatibility is required (see 3.5.3).
(f) When special characters and a blank space for the style C marking machine are required (see 3.7.3).



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:01Z
Check the source to verify that this is the current version before use.

(g) When a marking table is required (see 3.9.1.1 and 3.9.1.5).
(h) When a marking cabinet is required (see 3.9.2).
(i) When moisture and fungus-resistant treatment is required (see 3.11).
(j) Finish required if other than specified (see 3.12).
(k) Selection of applicable levels of preservation, packaging, and packing (see 5.1).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 Successful commercial operation. Invitation for bids should specify that no item of equipment will be acceptable (see 4.3.2.3) unless the manufacturer has had equipment of approximately the same style, class and size as that specified operating successfully in a commercial or institutional laundry or laundries for at least one year. Equipment installed for test purposes in a manufacturer's plant or laboratory shall not come within the category of successful commercial operation.

6.5 Style A, class 1, size 1 laundry marking machines only authorized for use by Veterans Administration.

6.6 Classification data. Classification changes between 00-L-131J, dated 6 November 1969, and Interim Amendment-1 (GL), dated 21 December 1970 and this specification, are as follows:

| 00-L-131J | 00-M-1724A |
|---|---|
| Style A | Style A |
| Size 1-8 character | Deleted |
| Size 2-16 character | Class 1 - keyboard operated<br>Size 1-16 character<br>Added style A, class 2 lever, size 1-6 character |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

Style B, class 1-keyboard

Size 1-8 character
2-16 character

Class 2 - lever

Size 1-6 character
2-8 character

Style D

Style E

Size 2-8 character

Style F - Pneumatically operated

15-point, 6-character

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activity:

Army - ME

User activity:

Navy - MC

Style B, class 1-keyboard

Size 1-8 character
2-16 character

Class 2 - lever

Size 1-6 character
Deleted

Deleted

Style C

Deleted
Added size 1-6 character

Style E - Pneumatically operated

Not less than 15-point or less than 5-character wheels

Preparing activity:

Army - GL

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS
HEW
VA

Project No. 3510-0245

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 20 cents each.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
00-M-1724A MARKING MACHINES, LAUNDRY

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314




STSNLT-EQS

Commander
US Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:01Z
Check the source to verify that this is the current version before use.