PROPOSED FEDERAL SPECIFICATION

SPRAY OUTFITS, UNDERCOATING, AUTOMOTIVE

This Federal specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

1 SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two types of pumps with spray gun and hose for use in applying motor-vehicle-type undercoating material and other materials of a similar nature.

1.2 Classification.

1.2.1 Types. Spray outfits shall be of the following types, as specified (see 6.2):

Type I - Low volume pump.
Type II - High volume pump.

2 APPLICABLE DOCUMENTS

2.1 Government publications. The issues of the following documents, in effect on date of invitation for bids or solicitation for offers, form a part of this specification to the extent specified herein.

Federal Specifications

QQ-B-626	- Brass, Leaded and Non-Leaded: Rod, Shapes, Forgings, and Flat Products With Finished Edges (Bar and Strip)
TT-C-520	- Coating Compound, Bituminous, Solvent Type, Underbody (For Motor Vehicles)
ZZ-H-521	- Hose and Hose Assemblies, Nonmetallic, Spray
PPP-D-729	- Drums, Shipping and Storage, Steel, 55-Gallon (208 Liters)

Federal Standards

FED-STD-123	- Marking for Shipment (Civil Agencies)
FED-STD-H28	- Screw-Thread Standard for Federal Services

FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

(Single copies of this specification and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specification

MIL-S-12651 - Sprayers, Packaging of

Military Standards

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-889 - Dissimilar Metals

Federal Regulation

Occupational Health and Safety Administration (OSHA) 29 CFR 1910.107, Spray finishing using flammable and combustible materials.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

(Copies of military specifications and standards, required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM):

ASTM D3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

3 REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish one or more spray outfits for first article inspection. The first article may be either a preproduction model(s) or an initial production item(s) which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The spray outfits shall be new and of the manufacturer's current model that will meet the performance requirements of this specification.

3.2.1 Maintainability. All parts subject to wear, deterioration, or distortion shall be easily accessible for adjustment, replacement, or repair. Those components specified to be guarded or totally enclosed shall provide access to their internal parts by removable panels or slide-out chassis. All parts shall be manufactured to such standards as will permit replacement without modification of the replacing parts or machine. All bearings (except sealed-for-life type) and moving parts shall be provided with means of lubrication. If used, grease fittings and oil fittings shall be accessible and have means for sealing the openings to prevent entrance of dirt and foreign matter. Recirculating systems, when provided, shall have filters which are cleanable. Each lubricant reservoir shall have means for determining fluid level.

3.3 Materials. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the spray outfit industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.4 Construction. Construction of the spray outfits shall be free from characteristics or defects which may render them unsuitable or inefficient for the purpose intended. The spray outfits and their equipment shall be complete so that when installed in their intended application and connected to the proper power source, they can be used for any operation for which they were designed.

3.4.1 Welding, brazing and soldering. Welding, brazing and soldering shall be of a quality which shall sustain all requirements of the welded, brazed, or soldered parts. These operations shall not be employed as repair measures for defective parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.4.2 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

3.4.3 Occupational safety standards. The product shall comply with OSHA standards set forth in 29 CFR 1910.107 with respect to spraying equipment (see 6.2).

3.4.4 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

3.4.5 Castings and forgings. All castings and forgings shall be free from defects, scale, and mismatching. In no event shall such processes as welding, peening, plugging, or filling with solders or metallic pastes be used for reclaiming any defective castings and forgings.

3.4.6 Surfaces. All surfaces of all castings, forgings, molded parts, stampings, and welded parts shall be cleaned and free of sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous materials. External surfaces shall be smoothed and all edges shall be rounded or beveled.

3.5 Performance and product characteristics. The spray outfits shall be capable of operating on air input pressure from 50 to 125 pounds per square inch gage (psig) with a continuous flow of material through the spray gun. The motor and pump assembly shall operate satisfactorily from a 55-gallon open top drum conforming to PPP-D-729, type III setting on end and pumping material conforming to TT-C-520 from the drum. The motor and pump assembly shall be so designed and constructed as to withstand at least a 200 psig air input pressure when stalled, on relief, on bypass, or when in any part of the operating cycle. Leakage of pressure from the motor shall not exceed 50 psig in 1 minute when stalled with 175 psig air input pressure in the motor with air inlet valve closed.

3.5.1 Performance at +72 degrees Fahrenheit (F) to +78 degrees F. At a coating material temperature and at an ambient temperature of +72 degrees F to +78 degrees F with spray gun attached to the pump by the hose assemblies specified in 3.7.4, and with the pump motor operating at not more than 65 psig, the pump shall be capable of delivering not less than 1 1/4 gallons per minute (gpm) for the type I and not less than 2 1/2 gpm for the type II pumps of the material conforming to TT-C-520. At the same coating material temperature and 65 psig air supply to the pump, with the atomizing pressure of the spray gun not exceeding 80 psig, the unit shall cover a surface area of 30 square feet for the type I and 50 square feet for the type II pumps, averaging 1/16 inch thick in 1 minute with the same material specified above while consuming not more than 30 cubic feet per minute (cfm) of free air.

3.6 Storage temperature. The spray outfits and all components thereof shall be able to withstand storage without damage at a temperature of -65 degrees F for periods of at least 72 hours, and a 24-hour cycle of temperature starting with 10 hours at +90 degrees F, followed by 5 hours of steady increase to +155 degrees F, 4 hours at +155 degrees F, and 5 hours steady decrease to +90 degrees F +5 degrees F. Following these extreme exposures and when stabilized at +72 degrees F to +78 degrees F, the spray outfits shall conform to the performance and product characteristics of 3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.7 Motor, pump, regulators, hose, and spray gun assemblies. The motor, pump, regulators, hose, and spray gun assemblies shall consist essentially of an air operated motor, a drum-type pump, two regulators with gages, three hoses, and a spray gun. Compressed air supply shall be through a manifold arrangement providing air for both motor and spray gun. The compressed air inlet shall be screened and provision made for easy cleaning. The air supply hose connection shall be a 1/2-inch size, quickly detachable air coupler with automatic shut-off valve on supply hose end. The motor and pump shall be industrial rated equipment. Working parts of the assembly coming in contact with the compressed air and spray material shall resist corrosion and abrasion, and shall provide a finished surface for travel of moving parts. The base and housing of motor and pump, and all connections shall be so arranged as to permit the assembly to be quickly and easily applied to the drum. An eyebolt, hook, or other arrangement for lifting the pump assembly from the drum shall be provided for the type I and type II pumps. The type I and type II pump assemblies shall weigh not more than 85 pounds each. The pump intake shall extend as near to the bottom of the drum as possible without imparing flow of the material and shall be so arranged that not more than 1 inch of spray material will be left in the bottom of the emptied drum when bottom of drum is horizontal.

3.7.1 Motor. The motor shall be a compressed-air-operated unit, and shall operate on air pressures specified in 3.5. The air valving mechanism shall be so designed as to insure that the motor will start in any position. When reciprocating-type motors are used, the valve action shall be full-floating, self-adjusting, and self-cleaning. An easily removable cover (hood) shall be provided for the motor if movable parts are not fully enclosed. All parts of the motor shall be fabricated from noncorrosion-type material or be fully protected from corrosion. The connection between the motor and pump shall be so designed so as not to permit any of the material being pumped to enter the inside of the motor. All packing and packing glands shall provide for means of adjustment. Lubrication shall be provided where necessary.

3.7.2 Pump. The pump shall deliver a continuous supply of the spray material as specified herein and a priming device shall be provided if the pump is not self-priming by design. Provision shall be made for easy dismantling for the purpose of cleaning operating parts.

3.7.2.1 Pump mountings. The motor and pump assembly shall be equipped with a clamping arrangement and with a drum lid adequate for holding the assembly at proper elevation and in pumping position on a 55-gallon, open top drum as specified in 3.5.

3.7.3 Regulators, air pressure. Two regulators shall be supplied; one for regulating air pressure to the motor and the other for regulating air pressure to the spray gun. Regulators shall be of the conventional hand-screw type for adjusting air and shall pass not less than 50 cfm of air at +72 degrees F to +78 degrees F and 80 psig intake pressure with a maximum pressure drop of 15 psig. The regulators shall operate over the range of 50 to 125 psig. Regulators shall be made of brass, zinc, or aluminum alloy as applicable and shall be able to withstand operation on air lines with pressure up to 200 psig. Regulators shall be adjustable for any pressure required for operations specified in 3.5 and shall hold the set pressure without creep until changed by the operator.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the currentversion before use.

3.7.3.1 Gages, pressure. Each regulator shall be supplied with a pressure gage of nonferrous construction, using a phosphor bronze Bourdon tube, equipped with a silver or white lacquered dial of not less than 2 inches in diameter, and protected in an enameled steel case. Gages shall be calibrated to commercial accuracy of 3 percent of the maximum pressure capacity in the middle portion of the scale. Pressure scale shall be 0 to 200 psig in 5-pound scale divisions.

3.7.4 Hose. Hose assemblies shall be furnished with each unit as follows: one 25-foot length of 3/4-inch inside diameter (id) material hose, one 25-foot length of 3/8-inch id air hose for spray gun connection, and one 15-foot length of 1/2-inch id air hose for air supply line. Couplings shall be securely attached to each end of the hose. The hose tube and cover shall be of material not adversely affected by petroleum-base products.

3.7.4.1 Material hose. The material hose assembly shall withstand a burst test pressure of not less than four times the maximum pressure developed by the pump at a stall or bypass pressure. The outer covering of the hose shall be abrasion- and oil-resistant, and the inside material of the hose shall be resistant to aromatic solvents. Each end of the material hose shall have a swivel female coupling, 3/4-inch standard straight pipe thread, and a 60 degree included bevel taper seat.

3.7.4.2 Air hose. The air hose assembly shall conform to ZZ-H-521 to safely perform its intended function for spray undercoating as specified herein for 3/8-inch and the 1/2-inch sizes. The air hose assemblies shall be capable of withstanding 200 psig working pressure and a burst pressure of at least 800 psig. Outer hose cover shall be abrasion- and oil-resistant. All couplings shall be swivel, female, standard straight pipe thread, and 60 degrees included bevel taper seat of the same size as the hose except that the air hose for air supply line shall have a 1/2-inch, quickly detachable, air coupler with automatic shut-off valve on one end.

3.7.5 Spray gun. The spray gun shall properly spray material conforming to TT-C-520, unless otherwise specified (see 6.2), on vertical, horizontal, overhead, or intermediate surfaces without undue fatigue to the operator. Parts of the spray gun subject to operating pressure of spray materials shall be of metal and shall withstand a pressure of 250 psig without injury and without more than 15 psig drop in pressure in 1 minute when supplied with air from a 100 psig air pressure line with trigger in closed position. The gun shall be suitable for volume production spraying and shall be designed for operation on 12 to 14 cfm at 50 to 60 psig air pressure. The nozzle provided shall be for pressure feed. Material and air hose connections shall be male, standard straight pipe thread, with 60 degrees included angle bevel taper seat. The air hose connection shall be 3/8-inch id. The material hose connection shall be size 3/4-inch id. The air hose connection shall be detachable connector fabricated from drawn brass rod conforming to composition 22 of QQ-B-626 and shall be located in the butt of the grip. The material hose connection shall be underneath the head.

3.8 Operation. The spray outfits shall have the capability of satisfactory operation in their intended application when connected to an air supply delivering not less than 50 cfm of air at 125 psig air input pressure with a spray gun atomizing pressure of not less than 80 psig and the pump motor pressure at not more than 65 psig. The spray outfits shall be capable of being operated at a rate of 10 cycles per minute (consisting of 4 seconds operation per cycle with depressed trigger and 2 seconds with trigger released) for 1,000 cycles at +72 degrees F to +78 degrees F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.9 Tools. If the unit is of such design as to require special tools (other than common), a complete set necessary for maintenance of equipment shall be furnished with each spray outfit.

3.10 Painting. Unless otherwise specified (see 6.2), painting and finishing shall be in accordance with the best commercial practice in the industry. Before painting, all surfaces to be painted shall be clean and free of all foreign matter detrimental to painting and at least one coat of primer (or a phosphate or chromate base) and one coat of enamel, or equivalent (i.e. epoxy enamel) is applied.

3.11 Lubrication instructions. Lubrication instructions shall be provided in the operation manual or permanently and securely attached to each spray outfit. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application
Service interval
Type of lubricant
Viscosity
Military or Federal Specification

3.12 Identification marking. The spray outfits shall be marked for identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2), shall include the National Stock Number. A noncorrosive metal nameplate securely attached to each pump shall be permanently marked with the name or trademark of the manufacturer.

3.13 Workmanship. The spray outfits, including all parts and accessories, shall be fabricated and finished in a workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp edges; accuracy of dimensions and markings of parts and assemblies; thoroughness of soldering, welding, brazing, and painting; alignment of parts and tightness of assembly screws and bolts.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production items (see 3.1). Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Unless otherwise specified (see 6.2), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2), quality conformance inspection shall consist of "a" through "c" below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.5).
(b) Tests (see 4.6).
(c) Packaging inspection (see 4.7).

4.4.1 Sampling. When required (see 6.2), sampling for quality conformance inspection shall be as specified in MIL-STD-105, using the following:

Inspection or Test	Inspection Level	AQL
Product examination (see 4.5)	II	1.0
Operational test (see 4.6.1)	II	1.0
Packaging inspection (see 4.7)	S-4	4.0

4.5 Product examination. Visually and manually examine the spray outfit to determine conformance with the requirements of 3.2 through 3.4.6, 3.7 through 3.7.5, and 3.9 through 3.13. Visual examinations shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from the identified defects. Manual examinations shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the spray outfit passed the examinations prescribed for them by the contractor's inspection system shall be cause for rejection.

4.6 Test methods.

4.6.1 Operational test. The spray outfits shall be placed in a pumping position on a 55-gallon drum in accordance with PPP-D-729, type III containing detergent oil of not less than SAE 40 weight and operated for 10 minutes in accordance with the manufacturer's instructions. The spray gun shall be set up to spray the oil back into the container. Proper operation of the motor, pump, regulators, and spray gun shall be verified (see 3.5).

4.6.2 Storage test. The spray outfits and their components as specified in 3.7 shall be tested at the following temperatures and hourly rates: -65 degrees F for a period of 72 hours, and a 24-hour cycle of temperature starting 10 hours at +90 degrees F, followed by 5 hours of steady increase to +155 degrees F, 4 hours at +155 degrees F, and 5 hours of steady decrease to +90 degrees F +5 degrees F (see 3.6). Following these extreme exposures and when stabilized at +72 degrees F to +78 degrees F, the spray outfits shall be subjected to the performance ambient temperature test of 4.6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.6.3 Spray gun air pressure test. Spray guns selected for testing shall be tested in accordance with 4.6.4 and shall spray material in accordance with 4.6.5 and 4.6.6.

4.6.4 Performance ambient temperature test. At a coating material temperature and at an ambient temperature of +72 degrees F as specified in 3.5.1, with the spray gun attached to the pump by the hose assemblies specified in 3.7.4, and the pump motors operating at not more than 65 psig, the pump shall deliver not less than 1 1/4 gpm for type I pump and not less than 2 1/2 gpm for the type II pump when fitted to a 55-gallon drum conforming to PPP-D-729, type III filled with material conforming to TT-C-520.

4.6.5 Endurance test. After completion of tests in 4.6.2 and 4.6.4, the spray outfits shall be placed in pumping position on a container of chassis-coating compound as specified in 4.6.4, with spray gun fixed so as to spray the material back into the drum. With the unit connected to an air supply delivering not less than 50 cfm of air at 125 psig air input pressure, with a spray gun atomizing pressure of not more than 80 psig, and the pump motor pressure at not more than 65 psig, the unit shall be operated at a rate of 10 cycles per minute (each cycle consisting of 4 seconds operation with depressed trigger and 2 seconds with trigger released) for 1,000 cycles at +72 degrees F to +78 degrees F as specified in 3.8. At the end of this period of tests, the unit shall be moved to a new container of chassis-coating compound and tested in accordance with 4.6.6.

4.6.6 Spray test. The spray outfits shall be lowered to operating position on a new drum of chassis-coating compound in accordance with 4.6.4 and connected to an air supply delivering not less than 50 cfm of free air at a temperature of +72 degrees F to +78 degrees F, a pressure of 125 psig and tested in accordance with 4.6.4. A 30-square foot panel shall be placed in a vertical position and coating applied to one side and then placed in a horizontal position and coating applied overhead to the uncoated surface.

4.7 Inspection of preparation for delivery. The preservation-packaging, packing, and marking of the spray outfits shall be inspected to determine conformance with the applicable requirements of section 5.

5 PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B or Commercial, as specified in the contract (see 6.2).

5.1.1 Level A or B. Level A or B preservation and packaging requirements shall be in accordance with MIL-S-12651, for applicable levels (see 6.2).

5.1.2 Commercial. Commercial preservation and packaging requirements shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B or Commercial, as specified in the contract (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

5.2.1 Level A or B. Level A or B packing requirements shall be in accordance with MIL-S-12651, for applicable levels (see 6.2).

5.2.2 Commercial. Commercial packing requirements shall be in accordance with ASTM D3951.

5.3 Marking. Marking shall be military, commercial, or civil, as specified in the contract (see 6.2).

5.3.1 Military. In addition to any special or other identification marking required by the contract (see 6.2), military marking shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be in accordance with ASTM D3951.

5.3.3 Civil agency. In addition to any special marking required by the contract (see 6.2), the packages and shipping containers shall be marked in accordance with FED-STD-123.

6 NOTES

6.1 Intended use. The spray outfits covered by this specification are primarily used in the application of undercoating material to the underside of automotive- or similar-type vehicles. It is also used in the application of other similar materials that are sprayable.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type (see 1.2.1).
(c) First article, if required (see 3.1).
(d) Special safety devices, when required (see 3.4.3).
(e) Sprayed surfaces, if different (see 3.7.5).
(f) Painting, if different (see 3.10).
(g) Identification marking, if different (see 3.12).
(h) First article inspection, if different (see 4.3).
(i) Quality conformance inspection, if different (see 4.4).
(j) Sampling, if required (see 4.4.1).
(k) Preservation-packaging, packing, and marking, if different (see 5.1).
(l) Specify level of packaging and packing required (see 5.1 and 5.2).
(m) Special marking, when required (see 5.3).

6.3 OSHA standards. Products which meet all requirements of this specification comply with the OSHA standards published prior to the date of this specification and identified in section 3 (see 3.4.3).

6.4 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - AL
Air Force - 99

Review Activities

Army - SM

User Activities

Army - ME
Marine Corps - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS

PREPARING ACTIVITY:

Army - AL

Project No. 4940-0441

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research
and Development Center
ATTN: SMCAR-ETS (R)
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
00-S-630D	Spray Outfits, Undercoating, Automotive

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.