MILITARY SPECIFICATION

COVER ASSEMBLY, WARHEAD

1. SCOPE

1.1 This specification covers special requirements, quality assurance provisions and the preparation for delivery criteria for Cover Assembly, Warhead for Repair Part procurement only.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY
MIL-C-14982/13 - Cable Assembly

STANDARDS

MILITARY
AN960-6L - Washer, Flat
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MS20365-632 - Nut, Self-Locking
MS24149D1 - Relay
MS25098-22 - Switch, Toggle, Single Pole
MS25281-4W - Clamp, Loop, Plastic
MS35206-231 and 232 - Screw, Machine, Pan Head
MS35489-94 - Grommet, Rubber
MS171494 - Pin Spring

DRAWINGS

ORDNANCE CORPS
197887 - Housing Lock
198146 - Dust Cap
311827 - Lock Assembly
39198 - Packing, Preformed
8808362 - Packing and Marking for Storage and Shipments
8852190 - Insert, Lock
8852191 - Nut

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

8852192 - Retainer, Nut
8852196 - Connector
8852203 - Cable Assembly for Unit Packages
8880602 - Marking and Sealing
9210066 - Wiring Diagram XM149E2 Auxillary Warhead
9210067 - Schematic Diagram XM149E2 Auxillary Warhead
9210069 - Cover, Assembly, Warhead
9210070 - Cover, Weldment
9210071 - Cover
9229000 - Carton, Packing, Ammunition for Cover Assembly, Warhead
ET-9210069 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publication required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The cover assembly shall comply with all requirements specified on Drawing (dwg.) 9210069, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.3 Circuit resistance. Circuit resistance shall comply with table I when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table I

Circuit Resistance (see dwg 9210067)

From Connector J1	To Connector J1	Relay Energized	Not Energized	To Connector Cable Assembly	Ohms Max
N	K		X		0.1
N	P		X		0.1
N	f		X		0.1
N	Chassis		X		0.1
A	B		X		0.1
A	g		X		0.1
A			X	C	0.1
A	A3		X		0.1
A	B3		X		0.1
A	B1	X			0.1
A		X		A	0.1
A	A1	X			0.1
J	X2		X		0.1
X1	Chassis		X		0.1
J	S		X		0.1
M	Chassis switch closed		X		0.1
M	Chassis switch open		X		Infinity
	Chassis		X	B	0.1

3.4 Insulation reistance. The insulation resistance shall not be less than 50 megohms when subjected to a potential of 500 volts direct current (vdc) with the current limited to 5 milliamperes (ma) when tested as specified in 4.4.2.

3.5 Workmanship.

3.5.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.5.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.5.3 Burrs. Parts shall be free from burrs.

3.5.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.5.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.5.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Product acceptance inspection.

4.3.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	2362- ∞	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table III

Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	1121-	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics. Critical, major, and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Washer, flat (see AN960-6L); nut self-locking (see MS20365-632); relay (see MS24149D1); switch, toggle, single pole (see MS25098-22); clamp, loop, plastic (see MS25281-4W); screw, machine (see MS35206-231 and 232); grommet, rubber (see MS35489-94); pin, spring (see MS171494); connector (see dwg 8852196) covering details of dwg 9210069.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for component in accordance with the applicable standard or drawing	Visual
Minor: None defined.		

4.3.2.1.2 Retainer, nut (see dwg 8852192) covering a detail of dwg 9210069.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Location of 3 projections	Gage
102.	Inside diameter, max	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

103. Outside diameter, min.....Gage
104. Height of projections, min.....Gage
105. Length of flat inside portion.....Gage
106. Thickness.....Gage
107. Material (see 3.1).....Visual
108. Objective evidence (see 6.2) for protective finish in accordance with dwg 8852192.....Visual

Minor:
201. Workmanship (see 3.5).....Visual-Manual

4.3.2.1.3 Nut (see dwg 8852191) covering a detail of dwg 9210069.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Width of slots.....Gage
102. Pitch diameter of thread, max.....Gage
103. Minor diameter of thread, max.....Gage
104. Width of key slot.....Gage
105. Location of key slot.....Gage
106. Depth of key slot.....Gage
107. Outside diameter, min.....Gage
108. Total thickness.....Gage
109. Thickness of material at bottom of slots.....Gage
110. Material (see 3.1).....Visual
111. Objective evidence (see 6.2) for finish in accordance with dwg 8852191.....Visual
112. Workmanship (see 3.5).....Visual-Manual

4.3.2.1.4 Cover (see dwg 9210071) covering a detail of dwg 9210070.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Location of large hole.....Gage
102. Location of small hole.....Gage
103. Depth of recess.....Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

104. Contour of recesses.....Gage
105. Location of recesses.....Gage
106. Thickness.....Gage
107. Outside diameter.....Gage
108. Inside diameter above thread.....Gage
109. Distance from bottom of recess to bottom of center projection.....Gage
110. Diameter of large hole.....Gage
111. Diameter of small hole.....Gage
112. Location of 4 small holes.....Gage
113. Diameter of 4 small holes.....Gage
114. Pitch diameter of thread.....Gage
115. Minor diameter of thread.....Gage
116. Depth of thread.....Gage
117. Total height.....Gage
118. Pitch diameter of small threaded hole.....Gage
119. Minor diameter of small threaded hole.....Gage
120. Location of small threaded hole.....Gage
121. Material (see 3.1).....Visual

Minor:
201. Workmanship (see 3.5).....Visual-Manual

4.3.2.1.5 Insert, lock (see dwg 8852190) covering a detail of dwg 9210070.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Outside diameter.....Gage
102. Concentricity of outside diameter.....Gage
103. Diameter of thread clearance.....Gage
104. Small diameter of outside taper.....Gage
105. Small outside diameter, min.....Gage
106. Bottom inside diameter.....Gage
107. Depth of taper.....Gage
108. Thickness of top inside flange.....Gage
109. Pitch diameter of outside thread.....Gage
110. Minor diameter of outside thread.....Gage
111. Width of 3 slots.....Gage
112. Distance from flat to small inside diameter.....Gage
113. Location of small hole.....Gage
114. Width of large slot.....Gage
115. Location of large slot.....Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

116. Smallest inside diameter.....Gage
117. Large inside diameter.....Gage
118. Middle size inside diameter.....Gage
119. Diameter of small hole.....Gage
120. Depth of small hole, min.....Gage
121. Width of thread clearance.....Gage
122. Depth of top of bottom inside flange.....Gage
123. Depth of slots.....Gage
124. Length of outside thread.....Gage
125. Length to outside taper shoulder.....Gage
126. Total length.....Gage
127. Material (see 3.1).....Visual
128. Radius missing.....Visual

Minor:
201. Workmanship (see 3.5).....Visual-Manual

4.3.2.1.6 Cover weldment (see dwg 9210070) covering a detail of 9210069.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Welding.....Visual-Manual
102. Objective evidence (see 6.2) for finish in accordance with dwg 9210070.....Visual
103. Marking.....Visual

Minor: None defined.

4.3.2.1.7 Cover assembly, warhead (see dwg 9210069).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Wiring in accordance with dwg 9210066 and dwg 9210067.....Visual
102. Marking.....Visual
103. Objective evidence (see 6.2) available for components in accordance with dwgs 197887, 198146, 311827 and 39198.....Visual
104. Objective evidence (see 6.2) available for cable assembly (see dwg 8852203) in accordance with MIL-C-14982/13(MU).....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

105. All components properly assembled.....Visual-Manual
106. Workmanship (see 3.5).....Visual-Manual

Minor: None defined.

4.3.2.1.8 Carton, packing, ammunition for cover assembly warhead (see dwg 9229000 and section 5).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Envelope over connector secured with tape.....Visual
102. Tape shall not contact cable.....Visual
103. Assembly with cable folds under wrapped.....Visual
104. Contents tight in carton.....Manual
105. Carton sealed in accordance with dwg 8880602.....Visual
106. Marking.....Visual

Minor: None defined.

4.3.2.1.9 Packing and marking for storage and shipments (see dwg 8808362 and section 5).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Gross load weight, max.....*Measure
102. Contents tight in package.....Manual
103. Correctly packed.....Visual-Manual
104. Package material (see 3.1).....Visual

*Determine weight with a suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.5).....Visual-Manual

4.3.3 Testing. All the tests specified shall be performed. Tests shall be performed in the order specified.

Test	Test Classification
a. Circuit resistance	Major
b. Insulation resistance	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.3.4 Circuit resistance (see 3.3) and insulation resistance (see 3.4). Each assembly shall be tested as specified in 4.4.1 or 4.4.2 as applicable. If any assembly fails to comply with 3.3 and 3.4, the assembly shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). EL's for assemblies are listed on the Equipment Tabulation, ET-9210069. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part of Identifying Number" column on the EL.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Circuit resistance (see 3.3). The circuit resistance shall be measured in accordance with table I (see 3.3) with approved resistance measuring equipment.

4.4.2 Insulation resistance (see 3.4). The insulation resistance shall be measured with approved insulation measuring equipment in accordance with table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table IV

Insulation resistance (see dwg 9210067)

Positive Potential to Connector	Negative Potential to
J1-M	J1-A, cable pin A, chassis with S1-1 off position and all unused pins
J1-A	Cable pin A, chassis and all unused pins
Cable Pin A	J1-A, chassis and all unused pins
All unused pins	J1-A, cable pin A, and chassis

5.0 PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The assembly shall be packaged in accordance with dwgs 9229000 and 8808362 using the specified moisture barrier.

5.1.2 Level C. The assembly shall be packaged in accordance with dwg 9229000 and 8808362 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The assembly shall be packed in accordance with dwg 9229000 and 8808362.

5.3 Marking. Marking shall be as specified in accordance with dwgs 9229000 and 8808362, as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1125-A050

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.