MIL-C-63189(AR)
26 February 1982
Superseding
(See 6.5)

MILITARY SPECIFICATION

CONTAINER, DUMMY
SHIPPING AND STORAGE, M622

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions and the preparation for delivery criteria for M622 Dummy Shipping and Storage Containers (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

| | |
|---|---|
| MIL-W-22248 | Weldment, Aluminum and Aluminum Alloy |
| MIL-A-48078 | Ammunition, Standard Quality Assurance Provisions, General Specification for |

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-1167 | Ammunition Data Cards |
| MIL-STD-1595 | Aerospace Welder Performance Qualification |

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS AND PACKAGING DATA SHEETS (see 6.6)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

| | |
|---|---|
| 9335737 | Retainer, Handle, Side |
| 9335740 | Tube |
| 9335747 | Cover, End, Forward Weldment |
| 9335748 | Cradle, Weldment |
| 9335749 | Container, Weldment |
| 9335750 | Dummy Shipping and Storage Container, M622 |

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials and components. The contractor shall provide objective evidence (see 6.4) that materials and components comply with specifications listed on the applicable drawing (dwg).

3.2 Assembly. The container shall comply with all requirements specified on dwg. 9335750, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the dwg. and herein.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

3.3 Welding. Unless otherwise specified on dwgs., welding shall be performed in accordance with the requirements of MIL-W-22248 by operators currently qualified in accordance with MIL-STD-1595. The contractors welding capability and facilities shall be evaluated and approved by the Government QAR prior to award of contract. Welds shall exhibit characteristics of fusion, penetration and soundness of weld deposit representative of good weld practice. Inspection shall be performed in accordance with 4.5.1.

3.4 Ammunition data cards. Ammunition data cards shall be provided for each assembly in accordance with MIL-STD-1167.

3.5 First article inspection. This specification contains technical provisions for first article inspection (see 4.3). Requirments for submission of first article samples shall be as specified in the contract.

3.6 Workmanship. Requirements for workmanship shall be as indicated on applicable dwgs., in applicable specifications and as specified herein.

3.6.1 Metal characteristics All parts and assemblies shall be free of burrs, cracks, and sharp edges. Threads shall be full and undamaged for the entire minimum length or depth as required by applicable dwgs.

3.6.2 Cleaning and surface preparation. All parts, surfaces and assemblies shall be free of dirt, grease, rust, corrosion, welding flux, scale, unacceptable weld spatter (see 4.5.1), metal filings or shavings or any other foreign matter prior to assembly or application of primers or finish. Cleaning methods shall not be injurious to any of the parts or assemblies, nor shall the parts or assemblies be contaminated by the cleaning agents.

3.6.3 Finish. Paint and finishes shall comply with all applicable dwg. requirements. Prior to the application of any finish, parts and assemblies shall be dry and thoroughly clean and free of dirt, dust or any other foreign material. Unless otherwise specified on dwgs., primary coats shall be thoroughly dry before application of any finished coat. Finish coats shall cover all required surfaces and be continuous with the possible exception of a few light scratches not exposing base metal. Paint shall not appear on any part or area where explicitly excluded by dwg. requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

3.6.4 Marking. Marking shall be as specified on dwgs. and shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract or purchase order, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First Article Inspection (see 4.3).

2. Quality Conformance Inspection (See 4.4).

4.3 First article inspection.

4.3.1 Submission. When the contract requires first article inspection (see 3.5), the contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

| Item Identification | Drawing No. | Quantity |
|---|---|---|
| Dummy Shipping and Storage Container, M622 | 9335750 | 2 |

4.3.2 Inspections to be performed. The first article quantity submitted in accordance with 4.3.1 shall be subjected to any or all of the requirements of the applicable dwgs. and to the inspections and tests specified in the first article table herein. All fabricated parts and assemblies shall have been manufactured using the same production processes, procedures and equipment which will be



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

used in fulfilling the contract. All procured parts and materials shall be obtained from the same source as will be used in regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

FIRST ARTICLE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63189(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.3.2.1 | Dummy Shipping and Storage Container, M622 | | | | 9335750 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | N.A. |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Classification of Defects and Tests | 2 | - | | 4.4.2.2 thru 4.4.2.4 |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection equipment. The inspections and tests specified in 4.3.2 shall be accomplished with the gages and test equipment specified in 4.4.4.

4.3.4 Rejection. See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078.

4.4.2 Examinations. See MIL-A-48078 and the Quality Conformance Inspection tables herein. Unless otherwise specified, inspection for major defects shall be sampled in accordance with Table I.

TABLE I. Sampling plan for major defects.

LQ = .05 Acceptance No. = 0 Consumers Risk = .10

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-16 | all | 28-29 | 23 | 52-56 | 31 | 132-156 | 39 |
| 17 | 16 | 30-31 | 24 | 57-62 | 32 | 157-191 | 40 |
| 18 | 17 | 32-34 | 25 | 63-69 | 33 | 192-244 | 41 |
| 19-20 | 18 | 35-36 | 26 | 70-76 | 34 | 245-334 | 42 |
| 21 | 19 | 37-40 | 27 | 77-86 | 35 | 335-519 | 43 |
| 22-23 | 20 | 41-43 | 28 | 87-97 | 36 | 520-1120 | 44 |
| 24-25 | 21 | 44-47 | 29 | 98-112 | 37 | over 1120 | 45 |
| 26-27 | 22 | 48-51 | 30 | 113-131 | 38 | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63189(AR)

| PARAGRAPH | TITLE | | | SHEET | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.1 | Commercial and MS Parts | | | 1 OF 1 | See Below |
| | | | | | NEXT HIGHER ASSEMBLY: N.A. |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Objective evidence (see 6.4) will be required for the following components:<br><br>Item — Ident. — Ref on Dwg.<br>Bolt — MS35764-1068 — 9335750<br>Screw — MS24630-10 — "<br>Washers, Flat — AN960-516 — "<br>Washers, Lock — MS35338-45 — "<br>Nut, Hexagon — MS35649-2314 — " | | - | 3.1 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63189(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 2 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.2 | Cover, End, Forward Weldment | | | | 9335747 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | 9335750 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Major | | | | | |
| 101. | Improper or incomplete assembly | | 100% | 3.2 | Visual |
| 102. | Location of forward handle retainer from side | | Table I | 3.2 | Gage |
| 103. | Spacing between forward handle retainers | | Table I | 3.2 | Gage |
| 104. | Location of top hole of end plate from side | | Table I | 3.2 | Gage |
| 105. | Pitch diameter of holes (see dwg. 9335744) (5) | | Table I | 3.2 | Gage |
| 106. | Minor diameter of holes (see dwg. 9335744) (5) | | Table I | 3.2 | Gage |
| 107. | Depth of holes (see dwg. 9335744) (5) | | Table I | 3.2 | Gage |
| 108. | Location of center of end plate from top of angle | | Table I | 3.2 | Gage |
| 109. | Location of spacer from center of forward end plate | | Table I | 3.2 | Gage |
| 110. | Outside diameter of forward end plate (see dwg. 9335744) | | 100% | 3.2 | Gage |
| 111. | Location of holes in forward end plate (see dwg. 9335744) | | 100% | 3.2 | Gage |
| 112. | Weld quality | | 100% | 3.3 | 4.5.1 |
| 113. | Weld present in bushing area | | 100% | 3.2 | Visual |
| 114. | Protective finish improper or missing | | 100% | 3.2 | Visual |

NOTES:



Source: Superintendent of Documents, Downloaded 2026-10-29 09:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63189(AR)

| PARAGRAPH | TITLE | | SHEET 2 OF 2 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.2 (cont.) | Cover, End, Forward Weldment | | | | 9335747 |
| | | | | | NEXT HIGHER ASSEMBLY 9335750 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Major | | | | | |
| *115. | Materials | | 100% | 3.6 | Visual (6.4) |
| 116. | Poor workmanship | | | | Visual |

NOTES: *Objective evidence shall be provided for all materials used in fabrication of parts and subassemblies for this weldment.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63189(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 2 | | DRAWING NUMBER 9335749 |
|---|---|---|---|---|---|
| 4.4.2.3 | Container Weldment | | | | NEXT HIGHER ASSEMBLY 9335750 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Major | | | | | |
| 101. | Improper or incomplete assembly | | 100% | 3.2 | Visual |
| 102. | Location of tie-down handle retainers from end (2 places) | | Table I | 3.2 | Gage |
| 103. | Spacing between tie-down handle retainers (4 places) | | Table I | 3.2 | Gage |
| 104. | Spacing between tie-down handle retainers (2 places) | | Table I | 3.2 | Gage |
| 105. | Location of 9335737-2 handle retainers from end (2 places) | | Table I | 3.2 | Gage |
| 106. | Spacing between side handle retainers (4 places) | | Table I | 3.2 | Gage |
| 107. | Spacing between 9335737-1 side handle retainers (2 places) | | Table I | 3.2 | Gage |
| 108. | Location of 9335733 skid gussets from end (2 places) | | Table I | 3.2 | Gage |
| 109. | Location of blocks (8 places) | | Table I | 3.2 | Gage |
| 110. | Height of flange | | Table I | 3.2 | Gage |
| 111. | Inside diameter of holes (see dwg. 9335740) | | 100% | 3.2 | Gage |
| 112. | Location of holes (see dwg. 9335740) | | 100% | 3.2 | Gage |
| 113. | Weld quality | | 100% | 3.3 | 4.5.1 |
| 114. | Weld present in bushing area | | 100% | 3.2 | Visual |
| 115. | Protective finish improper or missing | | 100% | 3.2 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET | DRAWING NUMBER |
|---|---|---|---|---|
| 4.4.2.3 (cont.) | Container Weldment | | 2 OF 2 | 9335749 |
| | | | | NEXT HIGHER ASSEMBLY 9335750 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Major | | | | | |
| *116. | Materials | | - | 3.1 | Visual (6.4) |
| 117. | Poor workmanship | | 100% | 3.6 | Visual |

NOTES:

*Objective evidence shall be provided for all materials used in fabrication of parts and subassemblies for this weldment.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-C-63189(AR)

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.4 | Dummy Shipping & Storage Container, M622 | 1 OF 1 | 9335750 |
| | | | NEXT HIGHER ASSEMBLY: N.A. |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Major | | | | | |
| 101. | Improper or incomplete assembly | | 100% | 3.2 | Visual |
| 102. | Overall length (max.) | | 100% | 3.2 | Gage |
| 103. | Overall height (max.) | | 100% | 3.2 | Gage |
| 104. | Overall width (max.) | | 100% | 3.2 | Gage |
| 105. | Any skid improperly assembled or missing (4 places) | | 100% | 3.2 | Visual |
| 106. | Improper torque of 9317872 screws | | 100% | 3.2 | Gage |
| 107. | Identification plate improperly assembled or missing | | 100% | 3.2 | Visual |
| 108. | Protective finish improper or missing | | 100% | 3.2 | Visual |
| 109. | Marking improper or missing | | 100% | 3.2 | Visual |
| 110. | Handles do not rotate freely (10) | | 100% | 3.2 | Manual |
| 111. | Poor workmanship | | 100% | 3.6 | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil- Downloaded: 2026-01-23T02:23Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63189(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.5 | Packaging | | | | See 5.0 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | N.A. |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Major | | | | | |
| 101. | Improper packing or packing materials | | 1 Assy. | 5.1 | Visual |
| 102. | Assembly not clean, dry and free of dirt and other foreign matter prior to packing | | 100% | 5.1 | Visual |
| 103. | Fiberboard container improperly or inadequately supported, packed and secured | | 100% | 5.1 | Visual |
| 104. | Wooden box missing, improperly packed or not secured (when required) | | 100% | 5.1 | Visual |
| 105. | Marking improper or missing | | 100% | 5.2 | Visual |
| 106. | Ammunition data cards not provided | | 100% | 3.4 | Visual |
| 107. | Poor workmanship | | 100% | -- | Visual |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the first article and quality conformance inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract (see MIL-A-48078 and 6.3).

4.5 Test Methods and Procedures.

4.5.1 Welding quality (see 3.3). Weld quality shall be visually inspected for the requirements of MIL-W-22248 (class 3) with particular attention to the following details.

(a) Surfaces to be welded shall be free of dirt, grease, oil, paint or other foreign material prior to welding.

(b) When multiple welds are deposited, each layer shall be thoroughly clean and free of slag and gas pits before deposit of another layer.

(c) Tack welds, when used, shall be deposited in such a manner as to assure their incorporation into the final weld without causing discontinuity in the deposit.

(d) Final welds shall be of the fillet size specified on the dwg. and shall be free of discontinuities, overlaps, gas holes, slag, flux, or any other obvious defects representative of poor weld practice. There shall be no weld spatter on functional or machined mating surfaces. Weld spatter, when present on other surfaces shall be removed by chipping, grinding or other commercial practice and the underlying surface refinished to the satisfaction of the Government QAR. Removal of weld spatter shall not puncture, tear or otherwise damage the underlying surface.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

(e) Dimensional characteristics on dwgs. shall apply after welding. The contractor shall provide all necessary shrinkage controls to assure the finished item complies with dwg. dimensional requirements.

5. PACKAGING

5.1 Packing and marking.

5.1.1 Normal packing. Unless ordered as a spare part, containers shall be prepared and packed in accordance with Packaging Data Sheet (PDS) 9335750, except that an outer wooden box shall not be required.

5.1.2 Spare part packing. When ordered as a spare part, containers shall be prepared and packed in accordance with Packaging Data Sheet (PDS) 9335750, including packing in an outer wooden box.

5.2 Marking. Inner containers and outer wooden boxes shall be marked with the following information.

a. Item nomenclature
b. Part or dwg. no.
c. Manufacturer
d. Quantity inclosed
e. Contract or purchase order no.
f. Date of acceptance

6. NOTES

6.1 Intended use. The item covered by this specification is intended for use as a training item for the M753 Projectile System.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification
b. First article inspection, when required (see 3.5).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD1423, Contract Data Requirements List (CDRL) the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs:

| Paragraph no. | | Data requirements | Applicable DID no. |
|---|---|---|---|
| (a) | 3.4 | Data cards | DI-L-1410 |
| (b) | 4.4.4 | Inspection equipment approval | DI-R-1714 (Tailored) |

(Copies of DID's required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Equipment design approval. Submit equipment designs, as required, to Commander US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 Objective evidence.

6.4.1 MS Components. A certificate of conformance from the supplier certifying that the item complies with applicable dwg. or specification requirements.

6.4.2 Materials. A statement (certification) supported by test data that all materials produced or purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in contractual documents.

6.5 Supersession data. This specification includes the requirements of AR-PD-34 dated 2 October, 1980.

6.6 Drawings and specifications. Drawings and specifications listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings and specifications prepared by and identified as Edgewood Arsenal,



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings and specifications. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:

Army-AR

Preparing activity:

Army-AR

(Project 8140-A547)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-63189 (AR) Container, Dummy Shipping and Storage, M622

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

**DD FORM 1 OCT 76 1426** EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

## BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAN-Q
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.