MIL-L-52008C(ME)
14 October 1971
SUPERSEDING
MIL-L-52008B(ME)
6 December 1966

MILITARY SPECIFICATION

LIGHT HOODS, AIRPORT AND HELIPORT MARKER

1. SCOPE

1.1 Scope. This specification covers two types of light hoods designed to provide narrow beams of light for landing, takeoff, and taxiing of aircraft.

1.2 Classification. Light hoods shall be of the following types, as specified:

Type I - For airport use.
Type II - For heliport use.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Box, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-F-320	- Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Military

MIL-P-116	- Preservation, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.

FSC 6210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED. TEST METHOD STD. No. 101	- Preservation, Packaging, and Packing Materials: Test Procedures.

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U. S. Military Property.

DRAWINGS

ME

DL13217E5605	- Light Hood, Airport Marker.
DL13216E8150	- Light Hood, Heliport Marker.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202, Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, D. C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

E308 Spectrophotometry and Description of Color in CIE 1931 System.

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The type I light hood shall be in accordance with Data List DL13217E5605 and as specified herein. The type II light hood and visor shall be in accordance with Data Lists DL13217E5605 and DL13216E8150 and as specified herein.

3.2 Drawings. The drawings forming a part of this specification are engineering design drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.3 Filter. The filter on the type I hood shall have a luminous transmittance of 10.5 percent plus or minus 0.5 percent.

3.4 Lenses. Lenses on the type I hood shall have a focal length of not less than 15 and not more than 16 diopters.

3.5 Treatment and painting. All components normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type A, lusterless.

3.6 Identification markings. The identification markings shall be in accordance with MIL-STD-130 and the Federal stock numbers shall be permanently stamped on the outside.

3.7 Workmanship. Lenses shall be clear and without blemishes. Edges of all metal parts shall be smoothly finished. Joints and seams shall have a tight fit.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:05Z
Check the source to verify that this is the current version before use.

INVITATION FOR

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of preparation for delivery (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, inspection level S4.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1. AQL shall be 1.5 percent defective.

4.3.3 Tests. Samples selected in accordance with 4.3.1 shall be tested as specified in 4.4.2. AQL shall be 1.5 percent defective.

4.4 Inspection procedures.

4.4.1 Examination. The light hoods shall be examined for the following defects:

101. Nonconformance to the dimensions shown on the drawings.
102. Parts or components missing.
103. Misalinement of parts or components.
104. Materials or components not as specified.
105. Treatment and painting not as specified.
106. Identification markings not as specified.
107. Workmanship not as specified.

4.4.2 Tests.

4.4.2.1 Selector knob (type I hood). Rotate the selector knob to each of the three positions shown on the dial. Misalinement of openings in the two

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:05Z
Check the source to verify that this is the currentversion before use.

cylinders that will restrict the light path or mechanical restrictions preventing the selector knob from remaining at the desired setting shall constitute failure of this test.

4.4.2.2 Filter (type I hood). Before assembly, test for luminous transmission in accordance with ASTM E308. Luminous transmittance of more than 11 percent or less than 10 percent shall constitute failure of this test.

4.4.2.3 Focal length of lens (type I hood). Before assembly, determine the focal length of the lens by imaging the filament of a lamp on a surface and measuring the distance in centimeters from the smallest image obtainable to the center of the lens. This distance in centimeters divided into 100 is the focal length. Less than 15 or more than 16 diopters shall constitute failure of this test.

4.5 Inspection of preparation for delivery.

4.5.1 Preproduction pack inspection.

4.5.1.1 Examination. The pack shall be examined for defects specified in 4.5.2.3. Presence of one or more defects shall be cause for rejection.

4.5.1.2 Test. The pack for levels A and B shall be subjected to the free fall drop test in accordance with FED. TEST METHOD STD. No. 101, method 5007. At the conclusion of the test, the pack and all contained packages shall be opened and the hoods shall be removed. The pack, packages, and hoods shall be examined. Rupture or deformation of the pack or packages or any visible damage to the hoods shall constitute failure of the test and shall be cause for rejection.

4.5.2 Quality conformance inspection of pack.

4.5.2.1 Unit of product. For the purpose of inspection, a completed pack of any level prepared for shipment shall be considered a unit of product.

4.5.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, inspection level S-2.

4.5.2.3 Examination. Samples selected in accordance with 4.5.2.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

108.	Materials, methods or containers not as specified for level A or B. Each incorrect material or container shall be considered one defect.
109.	Hoods not secured within the box as specified for level B.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:05Z
Check the source to verify that this is the current version before use.

110. Type II hoods not packaged in quantities of two.
111. Boxes not waterproof sealed with tape as specified for level A packaging.
112. Gross weight of wood boxes exceeds 200 pounds for level A or B.
113. Fiberboard boxes exceed the size or weight limitations for level B.
114. Boxes not waterproof sealed with tape as specified for level B packing.
115. Marking missing, illegible, incorrect or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Preproduction pack. The supplier shall furnish a preproduction pack for examination and test within the time frame specified to prove prior to starting production packaging, packing, and marking, that the applied preservation, packaging, packing, and marking comply with the preparation for delivery requirements of this specification. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

5.2 Preservation and packaging. Preservation and packaging shall be level A, B, or C, as specified.

5.2.1 Level A. The hoods shall be preserved in accordance with MIL-P-116, method III. Type I hoods shall be individually preserved and type II hoods shall be preserved in quantities of two. Containers shall be close-fitting boxes conforming to PPP-B-636, W6c, style optional. The boxes shall be waterproof sealed with tape in accordance with the appendix to the box specification.

5.2.2 Level B. The hoods shall be packaged in close-fitting boxes conforming to PPP-B-636, type CF, class domestic, variety SW, grade 125, style optional. Type I hoods shall be individually packaged and type II hoods shall be packaged in quantities of two. The hoods shall be secured within the boxes to prevent movement by use of fiberboard inserts. Fiberboard used for the inserts shall conform to PPP-F-320, type CF, class domestic, variety SW, grade 125. The boxes shall be closed in accordance with the appendix to the box specifications.

5.2.3 Level C. The hoods shall be packaged to afford protection against deterioration and damage from the supplier to the initial destination. Type I hoods shall be individually packaged and type II hoods shall be packaged in quantities of two.

5.3 Packing. Packing shall be level A, B, or C, as specified.

5.3.1 Level A. Hoods preserved and packaged as specified in 5.2 shall be packed in close-fitting boxes conforming to PPP-B-601, overseas

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.

type, style optional. The gross weight of each box shall not exceed 200 pounds. Closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall be zinc coated.

5.3.2 Level B. Hoods preserved or packaged as specified in 5.2 shall be packed in close-fitting boxes conforming to PPP-B-601, domestic type, style optional; PPP-B-640, class 2, style optional; or PPP-B-636, V3c, style optional. Plywood boxes shall be closed and strapped in accordance with the appendix to the box specification and shall not exceed 200 pounds gross weight. The gross weight and dimensional limitations of fiberboard boxes shall not exceed the limitations of the box specifications. The fiberboard boxes shall be closed, strapped, and waterproof sealed with tape in accordance with the appendix to the box specification. Strapping need not be zinc coated.

5.3.3 Level C. Hoods packaged as specified in 5.2 shall be packed to assure carrier acceptance and safe delivery to destination at lowest rating in containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.4 Marking. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The hoods are intended for use with the airport and heliport lighting sets in combat areas when maximum security is required.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of hood required (see 1.2).
(c) Time frame required for submission of preproduction pack (see 5.1).
(d) Level of preservation and packaging and level of packing required (see 5.2 and 5.3). Level B preservation and packaging is intended to provide economical but limited protection and should be specified only when it is determined the hoods will be held in covered storage.

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the light hoods in accordance with this specification.

Custodian:

Army - ME

User activity:

Army - AV

Preparing activity:

Army - ME

Project No. 6210-A414

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:05Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION **MIL-L-52008C(ME) Light Hoods, Airport & Heliport Marker**

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 20260-22T21:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. A. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

POSTAGE AND FEES PAID

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:05Z
Check the source to verify that this is the current version before use.