MILITARY SPECIFICATION

MINE, ANTIPERSONNEL, XM74
METAL PARTS FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 This specification contains requirements not normally covered by drawings and provides quality assurance provisions for the fabrication and packaging of the metal parts for the Mine, Antipersonnel, XM74.

2. APPLICABLE DOCUMENTS.

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169 - Packaging, Packing, and Marking for Shipment of Inert Ammunition Components

FSC: 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9292605 - Cover
9292639 - Case Assembly
9292645 - Lead, Retainer
9292673 - Sleeve
9292674 - Plug
9292677 - Plug, Closure

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

ASTM B 117 Standard Method of Salt Spray (Fog) Testing

3. REQUIREMENTS.

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawings 9292605, 9292639, 9292645, 9292673, 9292674, and 9292677 and associated drawings and with all requirements specified in applicable specifications and standards,

3.3 Salt spray. The Case Assembly, 9292639, shall pass a salt spray test (see Table I) and comply with the requirements on the applicable drawings and specifications.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as Specified in the contract.

3.5 Workmanship. All part and assemblies shall be fabricated, and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The First Article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Cover	9292605	10
Case Assembly (prior to primer coat)	9292639	15
Case Assembly (after painting)	9292639	15
Case	9292640	10
Ring, Liner	9292641	10
Liner and Booster cup Assembly	9292642	10
Cup, Booster	9292643	10
Liner	9292644	10
Lead , Retainer	9292645	10
Sleeve	9292673	10
Plug	9292674	10
Plug, Closure	9292677	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I specifed herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Mine, Antipersonnel, XM74 Metal Parts For				See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cover (Dwg. 9292605) Examination for defects	10		3.2	4.4.2.1
	Lead, Retainer (Dwg. 9292645) Examination for defects	10		3.2	4.4.2.2
	Liner (Dwg. 9292644) Examination for defects	10		3.2	4.4.2.3
	Cup, Booster (Dwg. 9292643) Examination for defects	10		3.2	4.4.2.4
	Liner and Booster Cup Assembly (Dwg. 9292642) Examination for defects	10		3.2	4.4.2.5
	Ring, Liner (Dwg. 9292641) Examination for Defects	10		3.2	4.4.2.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:32Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Mine, Antipersonnel, XM74 Metal Parts For				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Case (Dwg. 9292640)				
	Examination for defects	10		3.2	4.4.2.7
	Case Assembly (Dwg. 9292639)				
	Prior to primer coat				
	Examination for defects	15		3.2	4.4.2.8
	After painting				
	Examination for defects	15(a)		3.2	4.4.2.8
	Salt Spray Test	15(a)		3.2	ASTM B 117
	Sleeve (Dwg. 9292673)				
	Examination for defects	10		3.2	4.4.2.9
	Plug (Dwg. 9292674)				
	Examination for defects	10		3.2	4.4.2.10
	Plug, Closure (Dwg. 9292677)				
	Examination for defects	10		3.2	4.4.2.11

NOTES:

(a) These shall be the same 15 assemblies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination (See MIL-A-48078) Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Cover				9292605
					NEXT HIGHER ASSEMBLY 9292600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Length of oval holes (4)		0.40%	3.2	Gage
103	Width of oval holes (4)		0.40%	3.2	Gage
104	Thickness		0.40%	3.2	Gage
105	Height of tab		0.40%	3.2	Gage
106	Width of tab		0.40%	3.2	Gage
107	Depth of offset		0.40%	3.2	Gage
108	Distance from outside diameter to offset		0.40%	3.2	Gage
109	True position of oval holes (4)		0.40%	3.2	Gage
110	True position of tabs (4)		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

8

DRDAR-QA Form 160 Jul 77 Replaces SARFA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292645
4.4.2.2	Lead, Retainer				NEXT HIGHER ASSEMBLY 9292683
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
103	Height of clip offset, 3 places (0.020)		0.40%	3.2	Gage
104	Hardness	(a)	0.40%	3.2	SME
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

(a) A sample size of 15 per each batch hardened.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292644
4.4.2.3	Liner				NEXT HIGHER ASSEMBLY 9292642
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Length between flanges		0.40%	3.2	Gage
103	Flange thickness		0.40%	3.2	Gage
104	Largest hole diameter (4)		0.40%	3.2	Gage
105	True position of largest hole diameter (4)		0.40%	3.2	Gage
106	Flatness around largest hole diameter (4)		0.40%	3.2	Gage
107	Width of dimples (2)		0.40%	3.2	Gage
108	Location of dimples (2)		0.40%	3.2	Gage
109	Outisde diameter of largest flange		0.40%	3.2	Gage
110	True position of largest flange outside diameter		0.40%	3.2	Gage
111	Diameter of smallest holes (2)		0.40%	3.2	Gage
112	True position of smallest holes (2)		0.40%	3.2	Gage
Minor					
201	Outside diameter of smallest flange		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Cup, Booster				9292643
					NEXT HIGHER ASSEMBLY
					9292642
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None detined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Total depth		0.40%	3.2	Gage
103	Outside diameter of flange		0.40%	3.2	Gage
104	Flange thickness		0.40%	3.2	Gage
105	Wall thickness		0.40%	3.2	Gage
106	True position of flange outside diameter		0.40%	3.2	Gage
107	Flatness of flange		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Liner and Booster Cup Assembly				9292642
					NEXT HIGHER ASSEMBLY 9292639
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of booster cup		0.40%	3.2	Gage
102	Soldering missing or incorrect		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Ring, Liner				0202641
					NEXT HIGHER ASSEMBLY
					9292639
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Width of ring		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRSAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292640
4.4.2.7	Case				NEXT HIGHER ASSEMBLY 9292639
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Largest inside diameter		0.40%	3.2	Gage
103	Length from outer edge to shoulder (both ends)		0.40%	3.2	Gage
104	Length of smallest inside diameter		0.40%	3.2	Gage
105	Material thickness prior to fenn milling		0.40%	3.2	Gage
106	Thickness at grooves after fenn milling		0.40%	3.2	Gage
107	Length between grooves after fenn milling		0.40%	3.2	Gage
108	Length from shoulder to first groove		0.40%	3.2	Gage
109	Thickness of lip, 2 places		0.40%	3.2	Gage
110	Welding missing or incorrect		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292639
4.4.2.8	Case Assembly				NEXT HIGHER ASSEMBLY 9292638
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Leakage Test (a)		100%	3.2	4.5.1
Major					
101	Inside diameter of lip, min., after welding both ends (a)		0.40%	3.2	Gage
102	Weld spatter on inside of lip (a)		0.40%	3.2	Visual
103	Length from edge of liner to edge of liner ring, after welding (a)		0.40%	3.2	Gage
104	Welding missing or incorrect (a)		0.40%	3.2	Visual
105	Outside diameter, max (b)		0.40%	3.2	Gage
106	Primer coating on internal cavity missing or improper (b)		0.40%	3.2	Visual
Minor					
201	Protective finish on outside diameter missing or improper (b)		0.65%	3.2	Visual
202	Evidence of poor workmanship (b)		1.00%	3.5	Visual

NOTES:
(a) Prior to primer coat
(b) After painting

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292673
4.4.2.9	Sleeve				NEXT HIGHER ASSEMBLY 9292638
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Smallest outside diameter		0.40%	3.2	Gage
103	Height of flange		0.40%	3.2	Gage
104	Location of flange cutout from center		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292674
4.4.2.10	Plug				NEXT HIGHER ASSEMBLY 9292638
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest diameter		0.40%	3.2	Gage
102	Height of largest diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63287(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.11	Plug, Closure		1 OF 1	9292677
				NEXT HIGHER ASSEMBLY: 9292683

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height		0.40%	3.2	Gage
102	Largest diameter		0.40%	3.2	Gage
103	Height of angle (2 places)		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment (gage) require to perform the Inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Leakage test of case assembly. The leakage test shall be performed as specified on dwg. 9292639. Equipment used in performing the test shall be in accordance with 4.4.4.

5. PACKAGING

5.1 Preservation-packaging. Packaging shall be Level B in accordance with MIL-STD-1169.

5.2 Packing. Packing shall be Level B in accordance with MIL-STD-1169.

5.3 Marking. Marking shall be Level B in accordance with MIL-STD-1169.

6. NOTES .

6.1 Intended use. The metal parts covered by ths specification are intended for assembly of the XM74 antipersonnel mine.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number, and date of this specification.
b. Provisions of MIL-A-48078.
c. Provisions for submission of first article samples.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required, to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

6.4 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Commmand, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

6.5 Drawings. Drawings listed in Section 2 of this specification under the beading U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity
Army-AR

Project Number:1345-A211

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS. This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-M-63287 MINE, ANTIPERSONNEL, XM74 METAL PARTS FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED. ☆GPO 1980—603-121/692 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.