MIL-R-52475B(ME)
6 December 1982
SUPERSEDING
MIL-R-52475A(ME)
12 February 1976

MILITARY SPECIFICATION

ROLLERS, TOWED, SHEEPSFOOT, AIRMOBILE, SINGLE-DRUM

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers towed sheepsfoot rollers.

1.2 Classification. Rollers shall be one of the following types, as specified (see 6.2):

Type I - 40-inch drum diameter.
Type II - 60-inch drum diameter.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3895

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-R-196	- Repair Part, Accessories and Kits, Mechanical Packaging of.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-F-3541	- Fittings, Lubrication.
MIL-G-3859	- Grease Guns, Hand-Operated, Lever, Push and Screw Type.
MIL-G-10924	- Grease, Automotive and Artillery.
MIL-T-22085	- Tape, Adhesive, Preservation and Sealing.
MIL-C-46168	- Coating, Aliphatic Polyurethane Chemical Agent Resistant.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-209	- Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY, INC. (AWS)

D1.1 - Structural Welding Code, Section 5, Qualification.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 N.W. Seventh Street, Miami, FL 33125.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC. AGENT

National Motor Freight Classification Rules.

(Application for copies should be addressed to the National Motor Freight Traffic Agent, American Trucking Association, Inc., 1616 P Street, NW, Washington, DC 20036.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15086.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Blvd., Chicago, IL 60606.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The roller shall consist of a drum mounted in a frame, a drawbar with a front clevis, a rear clevis, replaceable drum cleaners, and tamping feet with replaceable tips. The roller shall withstand rough operation encountered over loose dirt fill or plowed ground, when towed at a speed of approximately 5 mph, without permanent deformation or damage.

3.1.1 Dimensions and weight. The rollers shall conform to the requirements listed in table I:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:20Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions, weight, and number of feet per drum.

Requirement	Type I	Type II
Overall length, maximum	15 ft.	18 ft.
Overall width, maximum	68 in.	80 in.
Weight, empty, maximum	4000 lb.	10,000 lb.
Drum length	48 in. ± 1/4 in.	60 in. ± 1/4 in.
Drum diameter	40 in. ± 1/4 in.	60 in. ± 1/4 in.
Drum thickness, minimum	1/2 in.	3/4 in.
Number of tamping feet per drum	112	120
Length of tamping feet	7 in. ± 1/2 in.	8 in. ± 1/2 in.
Area of tamping-foot face	7 sq. in. ± 1/2 sq. in.	21 sq. in. ± 1/2 sq. in.

3.2 First article. Unless otherwise specified (see 6.2), the contractor shall furnish one or more rollers for first article inspection within the time frame specified (see 6.2) to prove prior to starting production that his production methods and choice of design detail will produce rollers that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and unless otherwise specified herein, all examination and tests shall be conducted by the contractor subject to surveillance and approval by the Government (see 6.3). When specified (see 6.2), the Government will conduct any or all of the first article examination and tests, as specified (see 6.2). When specified (see 6.2), the contractor shall furnish one or more rollers for initial production inspection as specified in 4.3.2.

3.3 Initial production. When specified (see 6.2), the contractor shall furnish to the Government one or more rollers for inspection as specified in 4.4.

3.4 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.6). Materials and finishes selected shall be compatible and shall provide protection against the various forms of material deterioration in the applicable operating or storage environments to which the rollers may be exposed.

3.4.1 Dissimilar metals. All dissimilar metals throughout the rollers shall be insulated from one another to preclude galvanic or electrolytic action. Insulation shall be by a coat of epoxy, chromate or alkaline resistant primer, mylar barrier tapes, or other effective means that shall prevent direct contact.

3.5 Drawbar. The drawbar shall be removable and replaceable without cutting or welding and shall be constructed so as to permit pulling and pushing the roller. The drawbar shall be equipped with an adjustable, universal-type, front clevis which shall permit coupling to a standard SAE J749 drawbar, for a 40,000 pound vehicle except that the clevis shall contain a hole to accommodate a 2-inch pin.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:20Z
Check the source to verify that this is the currentversion before use.

3.6 Drum. The shell and heads of the drum shall be constructed of steel plates having the thickness specified in table I. The joints shall be welded and watertight. A drainage hole for a 2-inch pipe plug and a rectangular ballast hole having an area of not less than 100 square inches shall be provided. The holes shall be located on the end near the perimeter of the drum and shall be equipped with a removable watertight plug and cover.

3.7 Frame. The drum frame shall be constructed of structural steel or sheet plates and shall be rigidly braced. Type II rollers shall be furnished with beams and an independent frame for each roller.

3.8 Axles and bearings. The drum shall be equipped with its own axle extending entirely through the drum. The axle or drum shall be mounted on antifriction bearings having dusttight and watertight seals. Bearings shall be adjustable without removal of drum from axle or axle from frame.

3.9 Cleaners. Adjustable, replaceable cleaners shall be provided and shall prevent accumulation of dirt on the drum when the roller is towed in either the forward or reverse direction.

3.10 Tamping feet. Tamping feet shall be provided on the drum and shall be arranged in equally spaced staggered rows. The tamping-feet shanks shall be cast or forged from steel and shall be welded to the drum. The tamping tips shall be steel, heattreated to a Brinell hardness of not less than 250, and shall be replaceable without burning or welding.

3.11 Rear clevis. A clevis shall be provided at the rear of the roller and shall contain a hole to accommodate a 2-inch pin.

3.12 Lubrication. All surfaces requiring lubrication shall be provided with a means for lubricating.

3.12.1 Lubricants. The roller shall operate as specified herein when lubricated with grease conforming to MIL-G-10924.

3.12.2 Lubrication fittings. Lubrication fittings shall conform to MIL-F-3541, Type I, II, or III. Fittings shall be located in a protected position and shall be accessible to a grease gun conforming to MIL-G-3859. Accessibility to fittings shall be provided without the removal or adjustment of accessories or parts.

3.12.3 Pressure-release device. An automatic pressure-release device shall be provided where the use of pressure-lubricating equipment will damage grease seals or other parts.

3.12.4 Grease lubrication. Grease lubrication shall be with grease conforming to MIL-G-10924. The roller shall be assembled, run-in, tested, and delivered with this grease. Bearings shall be cleaned before lubrication because military grease is not compatible with other grease. The roller shall be tagged in a conspicuous place to indicate that military grease has been used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:20Z
Check the source to verify that this is the current version before use.

3.13 Lifting and tiedown attachments.

3.13.1 Lifting attachments. Permanently affixed attachments that enable the equipment to be lifted in its normal travel position shall be provided. The attachments shall meet the requirements specified in MIL-STD-209. Lifting attachments may also be used as tiedown attachments when such attachments meet the requirements specified in 3.14.

3.14 Tiedown attachments. Permanently affixed attachments that permit fastening the equipment to the floor or deck of a transportation medium shall be provided. The attachments shall meet the requirements specified in MIL-STD-209.

3.15 Treatment and painting. The portions of the roller normally painted shall be cleaned, treated, primed and painted in accordance with MIL-T-704, Type F. The finishing coat shall be in accordance with MIL-C-46168, forest green color.

3.16 Identification marking. The roller shall be identified in accordance with MIL-STD-130. The marking shall be applied to the roller on plates conforming to MIL-P-514, Type I, Style I, Composition C, of Type I, Grade A, Class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location. When specified (see 6.2), identification plates will be furnished by the Government.

3.17 Transportation data plate. The transportation data plate shall conform to MIL-P-514, Type III, Composition C, of Type I, Grade A, Class 1 material, and, in addition, shall show the silhouette of the roller in transport position indicating the center of gravity and the location and capacity of the lifting and the tiedown attachments. The plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.18 Stenciling. The gross weight of the roller shall be stenciled on each side so as to be discernible. The words "LIFT" and "TIEDOWN", as applicable, shall be stenciled adjacent to their respective attachments using block letters not less than 1 inch high. Stenciling shall conform to MIL-T-704.

3.19 Technical publications. Such technical publications as are specified shall be furnished (see 6.4).

3.20 Ground pressure.

3.20.1 Type I. The ground pressure of the tamping-foot face shall be not less than 250 pounds per square inch (psi) with the type I drum filled with wet sand. The ground pressure shall be based on having four tamping feet per drum on the ground.

3.20.2 Type II. The ground pressure of the tamping-foot face shall be not less than 250 psi with the type II drum filled with water. The ground pressure shall be based on having not less than two tamping feet per drum on the ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:20Z
Check the source to verify that this is the current version before use.

3.21 Workmanship.

3.21.1 Steel fabrication. Steel used in the fabrication of the rollers shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the metal. Shearing and chipping shall be done neatly and accurately. Corners shall be square and true. Flame-cutting may be employed instead of shearing or sawing. Re-entrant cuts shall be made in the best possible manner. All bends of a major character shall be made with controlled means to avoid overheating, and heated metal shall be allowed to cool slowly.

3.21.2 Bolted connection. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washer or lockwashers shall be provided for all threaded connections and all bolts, nuts, and screws shall be tight.

3.21.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of uniform size for the same diameter of the rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.21.4 Welders and welding.

3.21.4.1 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

Standard Qualification Procedure of the American Welding Society.
Welding Qualifications of the ASME.

3.21.4.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loading.

3.21.5 Castings. Castings shall be sound and free from patching, misplaced coring, warping, or other defects which might render the casting unsound for use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:20Z
Check the source to verify that this is the current version before use.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. Inspections shall be classified as follows:

a. First article inspection (see 4.3).
b. Initial production inspection (see 4.4).
c. Quality conformance inspection (see 4.5).
d. Inspection comparison (see 4.7).
e. Inspection of packaging (see 4.8).

4.3 First article inspection.

4.3.1 Examination. The roller shall be examined as specified in 4.6.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The roller shall be tested as specified in 4.6.2.2 through 4.6.2.5. Failure of any test shall be cause for rejection.

4.4 Initial production inspection. When specified (see 3.3), one or more initial production rollers will be selected at random by the Government from the rollers being produced from production tooling and will be examined as specified in 4.6.2.1 through 4.6.2.3 to determine conformance to the requirements of this specification. The inspection will be performed by the Government at a site selected by the Government. Acceptance of the initial production roller shall not exclude the remaining rollers from the quality conformance inspection and acceptance provisions specified in Section 4.

4.4.1 Inspection failure. Failure of the initial production roller to meet any requirement specified herein during and as a result of the examination and tests specified in 4.4 shall be cause for rejection of the initial production roller and shall be cause for refusal by the Government to continue acceptance of production rollers until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on rollers previously accepted and produced under the contract. Any deficiencies found as a result of the initial production testing will be considered prima facie evidence that all rollers accepted prior to the completion of initial production testing are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.5 Quality conformance inspection.

4.5.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the currentversion before use.

4.5.2 Examination. Samples selected in accordance with 4.5.1 shall be examined for the major and minor characteristics specified in 4.6.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5.3 Tests. Each sample roller selected in accordance with 4.5.1 shall be tested as specified in 4.6.2. AQL shall be 2.5 percent defective.

4.6 Inspection procedure.

4.6.1 Examination. The roller shall be examined as specified in 4.5.2 for the following characteristics:

Major

101. Dimensions or weight not as specified.
102. Components missing or do not function.
103. Material not as specified.
104. Drum not as specified.
105. Frame not as specified.
106. Tamping feet not as specified.
107. Axles not as specified.
108. Bearings not as specified.
109. Cleaners not as specified.
110. Drawbar or front clevis not as specified.
111. Rear clevis not as specified.
112. Lubrication fittings not as specified or not accessible.
113. Dissimilar metals not in compliance with MIL-STD-889.

Minor

201. Treatment, painting, or stenciling not as specified.
202. Identification marking or transportation data missing, not legible, or not as specified.
203. Technical publications missing or not as specified.
204. Workmanship not as specified.

4.6.2 Tests.

4.6.2.1 Test conditions. Prior to testing, the roller shall be lubricated as specified in 3.12.4. The type I roller shall be ballasted with sand and water. The type II roller shall be ballasted with water only. The ballasted roller shall be coupled to a tractor and towed at a speed of approximately 5 mph over loose dirt fill or earth having a plowed depth of not less than 6 inches.

4.6.2.2 Operations Test. Tow the ballasted roller with the tractor (see 4.6.2.1) for a period of 8 hours. Replace 10 percent of the tamping tips. Tow the ballasted roller for an additional 4-hour period. Any evidence of water leakage, inability of cleaners to prevent accumulation of dirt on the drums, inability to replace tamping tips, or any permanent deformation or damage shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the current version before use.

4.6.2.3 Ground pressure of tamping-foot face. The roller shall be weighed with drums empty, with drums full of water, and with drums full of sand and water. Based on having four tamping feet per drum on the ground, the ground pressure of the tamping foot face shall be determined for the roller with empty drums, for the roller with drums filled with water, and for the roller with drums filled with sand and water by the following formula:

Formula: $P = \frac{W}{FNA}$

Where P = ground pressure of each tamping foot face in psi.
W = weight of roller in pounds.
F = number of tamping feet per drum in contact with a hard-ground-surface.
N = number of drums on the roller.
A = area of tamping foot face in square inches.

Computed ground pressure of tamping foot not as specified in 3.1.1 shall constitute failure of this test.

4.6.2.4 Test procedures of lifting provisions. Test procedures of lifting provisions shall be as follows:

a. Lift the roller and hold in suspension in its normal travel position using slings that converge not more than 24 feet above the lowest extremity of the roller. Determine the forward angle of application for each provision. Measure the clearance between each sling and the roller. Measure eye openings and clearance dimensions of the provision. Measure the load carried by each provision.

b. Restrain the roller by anchoring the main frame and subject each provision to a force equal to the load factor specified in MIL-STD-209 times the load it carried in (a) above. An alternate method of test is to lift the roller as in (a) above and add weights to the main frame until the required force is obtained. Hold the roller under either of the above loading conditions for at least 90 seconds.

4.6.2.5 Failure criteria. Weld failure of permanent deformation caused by lifting or failure to meet the requirements of MIL-STD-209, shall constitute failure of this test.

4.6.2.6 Test procedures of tiedown provisions. With the roller anchored by means other than the provisions being tested, apply the proportion of the static loads as specified in MIL-STD-209 to each attachment. Measure dimensions of the tiedown.

4.6.2.7 Failure criteria. Failure to meet the requirements of MIL-STD-209 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:20Z
Check the source to verify that this is the currentversion before use.

4.7 Inspection comparison. The Government may select rollers at any time during the contract production period and subject these rollers to the examination specified in 4.6.1 and the tests specified in 4.6.2 to determine conformance to the requirements of this specification. The inspection will be performed by the Government, at a site selected by the Government, on rollers selected at random from those which have been accepted by the Government and will not include the previously inspected first article model and initial production rollers. In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison, and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.7.1 Inspection failure. Failure of an inspection comparison roller to meet any requirement specified herein during and as a result of the examination and tests specified in 4.7 shall be cause for rejection of the inspection comparison roller and shall be cause for refusal by the Government to continue acceptance of production roller until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on rollers previously accepted and produced under the contract. Any deficiencies found as a result of the inspection comparison will be considered prima facie evidence that all rollers accepted prior to the completion of inspection comparison are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.8 Inspection of packaging.

4.8.1 Quality conformance inspection of pack.

4.8.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.8.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.8.1.3 Examination. Samples selected in accordance with 4.8.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

NO.	Defect	A	COMM
113.	Disassembly not as specified.	5.1.1.1	
114.	Removed bolts, nuts, pins, and washers not placed and secured as specified.	5.1.1.1	
115.	Unprotected surfaces not preserved as specified.	5.1.1.2	5.1.2
116.	Technical publications, when required, not preserved as specified.	5.1.1.3	
117.	Repair parts, when required, not preserved as specified.	5.1.1.4	5.1.2

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the current version before use.

NO.	Defect	A	COMM
118	Consolidation container, when required, not as specified.	5.1.1.5	
119.	Cushioning not provided as specified within the consolidation container when required.	5.1.1.5	
120.	Securing of components and the consolidation container, when required, to the roller frame not as specified.	5.2.1	
121.	Strapping, when required, not finish B as specified.	5.2.1	
122.	Commercial packing not as specified.		5.2.2
123.	Marking not as specified.	5.3.1	5.3.2

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified.

5.1.1 Level A.

5.1.1.1 Disassembly. Disassembly shall be to the extent that economy in packing and shipping can be obtained, provided no special tools or skills are required for reassembly or the cost of assembly would be in excess compared to the economy of packing and shipping. Removed bolts, nuts, pins, and washers shall be placed in mating parts and secured to prevent their loss.

5.1.1.2 Unprotected surfaces. Unprotected exterior metal surfaces exposed by disassembly shall be coated with type P1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.1.1.3 Technical publications. When required (see 6.4), technical publications shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3, and secured to the roller frame in a protected location with tape conforming to MIL-T-22085, Type II, or placed in the consolidation container with the components specified in 5.1.1.5.

5.1.1.4 Repair parts. When required (see 6.5), repair parts shall be preserved in accordance with the level A requirements on MIL-R-196. Parts not specifically mentioned therein shall be preserved as specified for parts of similar design and construction.

5.1.1.5 Consolidation. Repair parts when required, technical publications when required (see 5.1.1.3), and any small parts removed for disassembly (see 5.1.1.1), shall be consolidated together in a close-fitting box conforming to PPP-B-601, domestic type, style optional. Strapping shall not be required. Cushioning shall be provided as required to protect and immobilize the contents within the container.

5.1.2 Commercial. Each complete roller shall be preserved in accordance with MIL-STD-1188 except unit packing shall not be required.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the currentversion before use.

5.2 Packing. Packing shall be level A or commercial as specified (see 6.2).

5.2.1 Level A. Each roller shall be shipped unboxed. The consolidation box and the drawbar, when an overall reduction in cubage can be accomplished (see 5.1.1.1), shall be secured to the roller frame in a manner that will not interfere with lifting or towing. Securing shall be accomplished with strapping conforming to QQ-S-781, Type I or IV, Class 1, finish B, size as applicable.

5.2.2 Commercial. Each complete roller shall be prepared for shipment in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings. Containers and packing shall comply with Uniform Freight Classification Rules or with National Motor Freight Classification Rules.

5.3 Marking.

5.3.1 Military. Marking for level A shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The sheepsfoot roller is capable of tandem compaction operation and is intended for use in compacting earth and rocky embankments and for localized breakup of existing earth or graveled roads and subgrade soil to increase the loadbearing capacity. The roller permits positive, solid compaction with a minimum of passes over surface areas, such as built-up solid fills for highways, airports, dams, bridge approaches, levees, and straits.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Type and class of roller required (see 1.2).
c. Date of issue of DoDISS applicable to this contract and exceptions thereto (see 2.1.1).
d. Time frame for submission of first article model and number of rollers to be furnished.
e. When the government will conduct any or all of the first article model examination and tests. When the Government will conduct some but not all of the first article examination and tests, the contracting officer should specify which examination and tests will be conducted by the Government and which examination and tests shall be conducted by the contractor (see 3.2).
f. When initial production testing is required and number of rollers to be furnished (see 3.3).
g. When the type II roller shall be furnished with a beam and an independent frame for the drum (see 3.7).
h. When identification plates will be furnished by the Government (see 3.16).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the currentversion before use.

i. When cleaning, treatment, and painting shall be as specified (see 3.15).
j. Color of finish coat if different from the forest green specified in 3.15.
k. Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 First article model. Any changes or deviations of production rollers from the approved first article model during production will be subject to the approval of the contracting officer. Approval of the first article model will not relieve the contractor of his obligation to furnish rollers conforming to this specification.

6.4 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's maintenance and operation manual to be furnished with each roller.

6.5 Provisioning. The contracting officer should include provisioning requirements for repair parts, as necessary, and instructions on shipment of rollers.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.4).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 3895-A193

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:20Z
Check the source to verify that this is the currentversion before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY MOBILITY EQUIPMENT RESEARCH
AND DEVELOPMENT COMMAND
ATTN: DRDME-DS
FORT BELVOIR, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-R-52475B(ME) Rollers, Towed, Sheepsfoot, Airmobile, Single-Drum

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:20Z
Check the source to verify that this is the current version before use.