MILITARY SPECIFICATION

CARTRIDGE, 40MM, HE, M384; BODY ASSEMBLY FOR METAL PARTS

This amendment forms a part of Military Specification MIL-C-60941A (MU), dated 12 January 1970, and is approved for use by the US Army Armament Research and Development Command and is available for se by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 7

4.3.2.3: Delete Major defect 108 in its entirety.

4.3.2.4: Add Major defect 102 as follows:

"102. Diameter of rotating bands Gage 02009."

PAGE 8

4.3.3.2: Delete in its entirety and substitute the following:

"4.3.3.2 Push test of rotating band on body assembly (See Dwg. 8889307), Major Defect, Code No. 05002. - Fifty (50) body assemblies shall be selected randomly from each lot and subjected to this test. Sampling selected shall be representative of each band setting machine used. If any assembly fails to comply with the applicable requirement, the lot shall be rejected.

NOTE: Movement as specified on Dwg. 8889307 is defined as movement of the back face of the rotating band relative to the body. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A279)

FSC 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:06Z
Check the source to verify that this is the current version before use.