INCH-POUND`

MIL-C-55302/55F
AMENDMENT 1
5 January 2000

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES,
PLUG, SOCKET CONTACTS, DECADE INCREMNTS 10 THRU 70 CONTACT POSITIONS AND
INTERMEDIATE POSITIONS OF 14, 24, 44, 54 AND 26, 36, 56, 66
FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This amendment forms a part of MIL-C-55302/55F, dated 23 September 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1, Details C and D: Delete “jackscrew” and substitute “jackset”.

PAGE 4

Requirements, mating and unmating, delete and substitute:

“Mating and unmating:

Standard insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.56 and the withdrawal force, in pounds, shall be a minimum of 0.08 times the number of contacts and shall not exceed the measured insertion force.

Low insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.25 and the withdrawal force, in pounds, shall be a minimum of 0.04 times the number of contacts and shall not exceed the maximum insertion force.

NOTE: Not applicable when mating and unmating is accomplished through the engaging of turning jacksets.”

Following mating and unmating, add:

“Jackscrew and jacksocket torque: 2 inch pounds max fully mated.”

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
Air Force – 11
NASA – NA
DLA - CC

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, TD
Air Force –19, 99

Preparing activity:
DLA - CC

(Project 5935-4201)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.