INCH-POUND`

MIL-C-55302/60H
AMENDMENT 1
5 January 2000

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE, SOCKET CONTACTS, DECADE INCREMNTS 90, 100 AND 120 CONTACT POSITIONS (.100 INCH SPACING)

This amendment forms a part of MIL-C-55302/60H, dated 31 December 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

FIGURE 1, Details D, E, and F: Delete “jackscrew” substitute “jackset”.

PAGE 6

Requirements, mating and unmating, delete and substitute:

“Mating and unmating:

Standard insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.56 and the withdrawal force, in pounds, shall be a minimum of 0.08 times the number of contacts and shall not exceed the measured insertion force.

Low insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.25 and the withdrawal force, in pounds, shall be a minimum of 0.04 times the number of contacts and shall not exceed the maximum insertion force.

NOTE: Not applicable when mating and unmating is accomplished through the engaging of turning jacksets.”

Following mating and unmating, add:

“Jackscrew and jacksocket torque: 2 inch pounds max fully mated.”

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
Air Force – 11
NASA – NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4201-02)

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, TD
Air Force – 19, 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:47Z
Check the source to verify that this is the current version before use.