INCH-POUND`

MIL-C-55302/66F
AMENDMENT 1
5 January 2000

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES,
RECEPTACLE, SOCKET CONTACTS, DECADE INCREMNTS 10 THRU 70 CONTACT POSITIONS AND
INTERMEDIATE POSITIONS OF 14, 24, 44, 54, AND 26, 36, 56 AND 66 FOR
PRINTED WIRING BOARDS (.100 INCH SPACING)

This amendment forms a part of MIL-C-55302/66F, dated 8 April 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1, Details A, B and C: Delete “jackscrews” and substitute “jackset”.

PAGE 4

Following mating and unmating, add:

“Jackscrew and jacksocket torque: Jackscrews and jacksockets require a torque of 2 inch pounds max fully mated.”

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
Air Force – 11
NASA – NA
DLA - CC

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, TD
Air Force –19, 99

Preparing activity:
DLA - CC

(Project 5935-4201-06)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.