INCH-POUND

MIL-DTL-55302/102E
22 May 2006
SUPERSEDING
MIL-C-55302/102D
4 April 1983

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, STRAIGHT-THRU, HERMAPHRODITIC CONTACT, CRIMP REMOVABLE, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

Inactive for new design after 24 October 1991

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.




FIGURE 1. Connectors, receptacle, .100 (2.54 mm) spacing.

AMSC N/A


FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.005	.13	.150	3.81
.007	.18	.156	3.96
.008	.20	.197	5.00
.010	.25	.246	6.25
.050	1.27	.273	6.93
.055	1.40	.294	7.47
.062	1.57	.312	7.92
.086	2.18	.477	12.12
.090	2.29	.550	13.97
.100	2.54		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm).
4. When keying, mounting bracket or mounting bracket and keying is required, refer to the applicable dash and figure number in table I.
5. Contacts (class A in accordance with MIL-DTL-55302/97-01) are shipped loose in a plastic bag with each connector unless otherwise specified. When contacts are furnished separately, the letters “WO” shall appear immediately after the Part or Identifying Number (PIN) marking on the connector (i.e., M55302/102-02 WO).
6. For direct government procurements connectors shall be furnished with contacts in a plastic bag with each connector.
7. With connectors fully engaged the mating contacts shall have a minimum overlap distance of .062. As a minimum the contacts shall exhibit a wiping action through this distance.

FIGURE 1. Connectors, receptacle, .100 (2.54 mm) spacing – Continued.




Inches	mm
.050	1.27
.072	1.83
.096	2.44
.130	3.30
.260	6.60
.360	9.14

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm).
4. When bracket assembly (see figure 3, 4, or 5) to chassis mounting is required, it is suggested that support pins be used.

FIGURE 2. Typical cutout for receptacle in nonconductive chassis.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.




Inches	mm
.015	.38
.050	1.27
.125	3.18
.250	6.35
.312	7.92
.350	8.89
1.000	25.40

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm).
4. Mounting brackets assembled with the insulator will have the clamping hardware shipped loose.

FIGURE 3. Mounting bracket assembly with small clamp.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.




Inches	mm
.015	.38
.125	3.18
.250	6.35
.294	7.47
.312	7.92
.700	17.78
1.000	25.40

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm).
4. Mounting brackets assembled with the insulator will have the clamping hardware shipped loose.

FIGURE 4. Mounting bracket assembly with large clamp.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.



Inches	mm
.062	1.57
.128	3.25
.250	.6.35
.312	7.92

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm).
4. Mounting brackets assembled with the insulator will have the clamping hardware shipped loose.

FIGURE 5. Mounting bracket assembly with self locking tie.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number and dimensions.

Dash number 1/	Number of contacts	Figure number	Dimensions 2/, 3/					
			A	B ±.010	C Ref.	D	E Ref.	F
01 02 03 04	18	1 3 4 5	8.50 (21.590	1.150 (29.21)	1.300 (33.02)	1.006 (25.55)	1.990 (50.55)	1.150 (29.221)
05 06 07 08	30	1 3 4 5	1.450 (36.83)	1.750 (44.45)	1.900 (48.26)	1.606 (40.79)	2.590 (65.79)	1.750 (44.45)
09 10 11 12	36	1 3 4 5	1.750 (44.45)	2.050 (52.07)	2.200 (55.88)	1.906 (48.41)	2.890 (73.41)	2.050 (52.07)
13 14 15 16	42	1 3 4 5	2.050 (52.07)	2.350 (59.69)	2.500 (63.50)	2.206 (56.03)	3.190 (81.03)	2.350 (59.69)
17 18 19 20	54	1 3 4 5	2.650 (67.31)	2.950 (74.93)	3.100 (78.740)	2.806 (71.27)	3.790 (96.27)	2.950 (74.93)
21 22 23 24	72	1 3 4 5	3.550 (90.17)	3.850 (97.79)	4.100 (104.14)	3.706 (94.13)	4.690 (119.13)	3.850 (97.79)

1/ See requirements for complete PIN when keying pin is required.
2/ Dimensions are in inches.
3/ Metric equivalents are given for information only.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figures 1 through 5.

Material:

Insulator: ASTM D5948, type SDG-F.

Bracket, mounting: Cold rolled steel, 1/4 HD, in accordance with QQ-S-698; plated in accordance with SAE-AMS-QQ-P-416, class 3, type II.

End guides: Left hand, sintered brass 90/10, clear chromate in accordance with MIL-C-5541, class 1A. Right hand, sintered brass 90/10, nickel plate 300 microinches in accordance with MIL-F-14072.

Clamps, large and small: Aluminum alloy 380, in accordance with SAE-AMS-QQ-A-591, cadmium plated in accordance with SAE-AMS-QQ-P-416, class 3, type II.

Keying pin: Aluminum alloy 2011-T3 with clear chromate in accordance with MIL-C-5541, class 1A.

Self locking tie: Nylon 6.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

Mounting screw: Brass, cadmium plated, gold chromate finish.

Flat washer: Stainless steel.

Contact identification: Contact locations are identified in numerical sequence (see figure 1).

Mating and unmating: The maximum insertion force in pounds, shall not exceed a value equal to .5 times the number of contacts, and the withdrawal force, in pounds shall be a minimum of .11 times the number of contacts and shall not exceed the measured insertion force.

Contact retention: 6.0 pounds minimum after 5 insertions and withdrawals from the same connector.

Contact resistance: The contact resistance shall not exceed 20 milliohms.

Dry circuit: Connectors shall be tested in accordance with test procedure EIA-364-23. The contact resistance shall not exceed 20 milliohms.

Dielectric withstanding voltage:

Sea level: 1,000 volts rms, 60 hertz.

High altitude: 300 volts rms, 60 hertz.

Current rating, maximum: 5 amperes.

Keying : When required, one of the following codes shall be added to the dash number:

"P" – Specifying location by contact number where keying pin shall be inserted; for example, M55302/102-01P17. (Keying pin inserted in place of contact number 17.)

"H" – Specifying location by contact number where contact shall be omitted for mating; for example, M55302/102-01H17. (Keying pin hole has contact number 17 omitted.)

Contact crimp removable (Class A or B): Shall conform to MIL-DTL-55302/97.

Contact removal tool: Shall conform to MIL-I-81969/4.

Contact insertion tool: Shall conform to MIL-I-81969/5.

Contract crimp tool: Shall conform to M22520/17-02.

Mating plug: Shall conform to MIL-DTL-55302/53 and MIL-DTL-55302/54.

PIN: M55302/102-(dash number from table I).

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/53	MIL-F-14072	ASTM D5948
MIL-DTL-55302/54	MIL-I-81969/4	EIA-364-23
MIL-DTL-55302/97	MIL-I-81969/5	SAE-AMS-QQ-P-416
MIL-C-5541	QQ-S-698	SAE-AMS-QQ-A-591

CONCLUDING MATERIAL

Custodians:
Army - CR
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4504-000)

Review activities:
Army – AR, AT, AV, CR4, MI

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.