MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PLUG, SOCKET CONTACTS, DECADE INCREMENTS 10 THRU 70 CONTACT POSITIONS AND INTERMEDIATE POSITIONS OF 14, 24, 44, 54 AND 26, 36, 56, 66 FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-55302.





FIGURE 1. Connector, plug .100 (2.54 mm) spacing.

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.




DIP TERMINAL

DETAIL A


FLEXIBLE CIRCUIT TERMINAL

DETAIL B



TYPE S SHORT TURNING JACKSCREW

DETAIL C



TYPE H SHORT TURNING HEX JACKSCREW

DETAIL D

Number of contacts	Dimensions		
	A ±.010	BSC B	REF C
10	.850 (21.59)	.650 (16.51)	.400 (10.16)
14	1.050 (26.67)	.850 (21.59)	.600 (15.24)
20	1.350 (34.29)	1.150 (29.21)	.900 (22.86)
24	1.550 (39.37)	1.350 (34.29)	1.100 (27.94)
26	1.650 (41.91)	1.450 (36.83)	1.200 (30.48)
30	1.850 (46.99)	1.650 (41.91)	1.400 (35.56)
36	2.150 (54.61)	1.950 (49.53)	1.700 (43.18)
40	2.350 (59.69)	2.150 (54.61)	1.900 (48.26)
44	2.550 (64.77)	2.350 (59.69)	2.100 (53.34)
50	2.850 (72.39)	2.650 (67.31)	2.400 (60.96)
54	3.050 (77.47)	2.850 (72.39)	2.600 (66.04)
56	3.150 (80.01)	2.950 (74.93)	2.700 (68.58)
60	3.350 (85.09)	3.150 (80.01)	2.900 (73.66)
66	3.650 (92.71)	3.450 (87.63)	3.200 (81.28)
70	3.850 (97.79)	3.650 (92.71)	3.400 (86.36)

FIGURE 1. Connector, plug .100 (2.54 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.

INCHES	MM	INCHES	MM	INCHES	MM
.001	.03	.051	1.30	.161	4.09
.005	.13	.058	1.47	.172	4.37
.006	.15	.075	1.91	.187	4.75
.008	.20	.07812	1.9842	.200	5.08
.010	.25	.086	2.18	.234	5.94
.017	.43	.100	2.54	.250	6.35
.025	.64	.108	2.74	.335	8.51
.027	.69	.130	3.30	.500	12.70
.030	.76	.140	3.56	.700	17.78
.035	.89	.150	3.81		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).
4. These connectors mate with connectors specified in MIL-C-55302/56.
5. Numbers indicating every fourth cavity are stamped on side with the exception of number one contact shall be marked.
6. Termination layout on .025 (0.64 mm) modular grid.
7. Metric equivalents are in parentheses.
8. Conformal coating clearances shall be .005 (0.13 mm) minimum (not required for optional design).
9. Optional design conformal coating clearance.

FIGURE 1. Connector, plug .100 (25.4 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Material: Jackscrews and jacksockets shall be of corrosion resisting stainless steel per ASTM-A582, passivated per QQ-P-35 or shall be corrosion resistant copper nickel alloy (61 ±2% copper, 25 ±2% nickel, 2.5% max. other, and the balance zinc) and shall have a brinell hardness of 145 to 175.

Plating: The contact plating shall be per MIL-C-55302 or gold per MIL-G-45204, type II, grade C, class 1, over nickel plating per QQ-N-290, class 2, 50 to 150 microinches in the engaging area and gold per MIL-G-45204, type II, grade C, class 00, over nickel plating per QQ-N-290, class 02, 50 to 150 microinches in the termination area.

Contact identification: See figure 1.

Contact engagement and separation forces (No. 22 contacts):
Minimum separation: 0.5 ounce.
Maximum engagement: 12.0 ounces.

Mating and unmating:
Standard insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.56 and the withdrawal force, in pounds, shall be a minimum of 0.08 times the number of contacts and shall not exceed the measured insertion force.

Low insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.25 and the withdrawal force, in pounds, shall be a minimum of 0.04 times the number of contacts and shall not exceed the measured insertion force.

Contact resistance: The average contact resistance of all contacts measured shall not exceed 0.010 ohm, and no individual contact pair shall have a resistance exceeding 0.020 ohm.

Dielectric withstanding voltage:
Sea level: 1,000 volts rms.
High altitude: 300 volts rms.

Current rating: 5.0 amperes maximum per contact.

Example of part number:

M55302/55	L -	A	10	L
Basic number of specification sheet	Type of contacts	Type of terminal (see figure 1)	Number of contacts (see figure 1)	Type of mounting hardward
	L = Low insertion force contacts S = Standard insertion force contacts	A = solder cup B = dip terminal .140 long C = dip terminal .172 long D = flexible circuit terminal .058 E = dip terminal .234 long F = flexible circuit terminal .100		L = .700 turning jackscrew slotted M = .500 turning jackscrew slotted S = .200 turning jackscrew slotted H = .200 turning jackscrew hex

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - AS, TD
Air Force - 11, 85, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - MC, CS
Air Force - 19

Agent :
DLA - ES

Preparing activity:
Army - CR

(Project 5935-3411-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.