MIL-C-62015E(AT)
AMENDMENT 3
3 April 1984
SUPERSEDING
AMENDMENT 2
11 March 1983

MILITARY SPECIFICATION

CARRIER, CARGO, FULL-TRACKED,
M548, PROCESSING FOR STORAGE AND
SHIPMENT OF

This amendment forms a part of Military Specification MIL-C-62015E(AT) dated 16 June 1978, and is approved for use by the US Army Tank-Automotive Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Line 1 - add "and M548A1;" after M548 (removing previous semi-colon).

Paragraph 1.1 Scope.

Line 1 - add "and M548A1;" after M548.

PAGE 2

Paragraph 2.1, "Issues of documents."

Under SPECIFICATIONS FEDERAL add "O-S-801 - Sulfuric Acid Electrolyte; for Storage Batteries."

Line 3 - add the above between O-S-576" and "P-D-220".

Line 6 - "QQ-S-781" - change title to read "Strapping, Steel, and Seals".

PAGE 3

Line 1 - delete "MIL-S-207" and title.

PAGE 5

Paragraph 3.1.7.1, delete paragraph in its entirety and substitute:

AREA-PACK

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:09Z
Check the source to verify that this is the current version before use.

"Interior of vehicle. Interior surfaces of vehicle shall be cleaned with solution of detergent conforming to P-D-220 or type I of MIL-D-16791 and water. Solution temperature shall not exceed 210°F and pressure shall not exceed 5 psi measured 4 inches from the nozzle. After cleaning, cleaned surfaces shall be rinsed with clean water and dried. Care shall be taken during cleaning and rinsing operations to assure that no solution or water enters instruments, connections, or other components susceptible to water damage. Solution or water shall not accumulate and remain in cavities that cannot be drained. Vehicles with decals, markers, straps, and floor plates installed shall only be hand-cleaned with solution of P-D-220 or type I of MIL-D-16791 and water to prevent damage to these components. Cleaned surfaces shall be hand-rinsed and dried."

PAGE 6

Paragraph 3.1.8.1, "Relubrication."

Delete "50 miles" and substitute "75 miles".

PAGE 11

Paragraph 3.1.8.11.1 - delete entire paragraph and substitute:

3.1.8.11.1 "Engine compartment access plate and drain plugs. Engine compartment access plate, gasket, and attaching hardware shall be removed for ventilation. A screen conforming to figure 4 shall be installed in the access plate opening and secured with four (4) of the existing mounting screws and washers. The two (2) forward MS drain plugs (MS49005-14) shall be removed for drainage. Bare metal surfaces of drain plugs shall be preserved with compound conforming to grade 4 of MIL-C-16173. Plate, gasket, preserved drain plugs, and four (4) access plate mounting screws and washers shall be packaged as specified in 3.1.9.6. The information "Remove screen, install access plate, gasket, and front drain plugs before vehicle operation" shall be stenciled on the exterior of the vehicle using white or yellow paint conforming to MIL-P-13983. Stenciling shall be in characters not less than 3/4-inch high."

Paragraph 3.1.9.2 "Electrolyte" - delete paragraph and substitute:

"Electrolyte shall be packaged and packed in accordance with Federal Specification, O-S-801, paragraphs 5.1.1 and 5.2.1 (as applicable), except that the exterior container shall conform to PPP-B-621, class 2 or PPP-B-601, overseas type. Marking shall be according to paragraph 5.3.2 or O-S-801. The packed electrolyte shall be stowed in the same location as the B11 and secured independently to permit separate removal."

PAGE 14

* Paragraph 3.5.1 - line 3 delete the word "white" and substitute the word "black".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:09Z
Check the source to verify that this is the current version before use.

PAGE 15

Paragraph 3.6, "Drive-on-drive-off capability", on line 2 after "unloading" add: "(See 6.2)".

Paragraph 3.6.2, delete entire paragraph and substitute:

"Batteries and electrolyte. Batteries shall be filled with electrolyte, fully charged, and battery cables connected (ref 3.1.9.1 and 3.1.9.2). After vehicle self-movement for loading or placement in storage, the ground cable at battery shall be disconnected and then secured to battery carrier with 3/4-inch tape conforming to Type IV of PPP-T-97. A tag bearing the following message, "Vehicle preserved for drive away condition. Before cranking, connect ground cable to battery terminal. Engine and fuel tanks not preserved", shall be located in a conspicuous place in the driver's compartment."

PAGE 16

Paragraph 6.1, "Intended use.":

Line 1 - after "548", add M548A1".

PAGE 17

Paragraph 6.2 under "Ordering data." add:

"i. If vehicle drive-on-drive-off capability is required (see 3.6)."

PAGE 36

Paragraph 20.1 "Issues of document.":

Under "SPECIFICATIONS FEDERAL", line 3, add "PPP-B-1055 - Barrier Material, Waterproofed, Flexible".

Lines 4 and 5 - delete in their entirety.

Paragraph 30.1, line 2, delete "MIL-B-13239, Type CW-2;" substitute "PPP-B-1055, Class E-2".

PAGE 37

Paragraph 30.2, line 3, delete "MIL-B-13239, Type CW-2;" substitute "PPP-B-1055, Class E-2".

PAGE 38

FIGURE 8. "Vehicle Closure;" delete in its entirety; substitute revised FIGURE 8. (See page 4 of this amendment).

Custodian:
Army - AT

Preparing Activity:
Army - AT
Project No. PACK-A309

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:09Z
Check the source to verify that this is the current version before use.