MILITARY SPECIFICATION

# TELESCOPE, ELBOW: M114E1

## 1. SCOPE

1.1 This specification covers one type of elbow telescope which provides eight power magnification and an eight degree field of view. A sliding reticle with a range marker line acts as a cursor for a combined multiple-ballistic data and range pattern. This cursor establishes the elevation setting for a particular ammunition and range. The pattern on each reticle is radioactively illuminated.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-O-13830 | Optical Components for Fire Control Instruments, General Specification Governing the Manufacture, Assembly and Inspection |
| MIL-F-13926 | Fire Control Materiel; General Specification Governing the Manufacture and Inspection |
| MIL-P-14232 | Parts, Equipment and Tools for Army Materiel, Packaging, and Packing of |
| MIL-I-45607 | Inspection Equipment, Supply and Maintenance of |

STANDARDS

Military

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-109 | Quality Assurance Terms and Definitions |

DRAWING

U.S. Army, Frankford Arsenal

| | |
|---|---|
| F11730285 | Telescope, Elbow: M114E1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET

11730285 Packaging of Telescope, Elbow: M114E1

(Copies of specifications, standards, drawings and packaging sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

DEFENSE SUPPLY AGENCY MANUAL

DSAM 4145.8 Radioactive Commodities in the DOD Supply Systems

(Copies of DSAM 4158.8 may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C.20402).

3. REQUIREMENTS

3.1 Regulations pertaining to radioactive devices. - Marking, identification, handling, and shipping of radioactive devices shall be in accordance with DSAM 4145.8.

3.2 Fabrication. - The telescope shall be manufactured in accordance with Drawing F11730285.

3.3 General specification. - The following requirements of MIL-F-13926 shall be met:

a. Order of precedence
b. Dimensions and tolerances
c. Inorganic protective surface finishes
d. Part identification and marking
e. Workmanship

3.4 Environmental.

3.4.1 Storage temperatures. - The telescope shall show no evidence of physical failure due to being thermally stabilized at -80° and +160° Fahrenheit (F).

3.4.2 Operating temperatures. - The telescope shall meet the applicable requirements of 3.9 while thermally stabilized at -40° and +150°F.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

3.5 Vibration. - The telescope shall be vibrated in a vertical plane at a constant frequency of thirty cycles per second with an amplitude of 1/16 inch (1/8 inch total excursion) for a period of five minutes plus or minus fifteen seconds. Subsequent to vibration, there shall be no evidence of physical failure.

3.6 Cleanliness. - The telescope shall meet the cleanliness requirements of MIL-O-13830 and there shall be no more than 2 particles of dirt visible on the reticle. The area of each particle shall not be in excess of the areas equivalent to a size 10 dig. There shall be no dirt on other surfaces which interferes with observation or adversely affects image quality.

3.7 Sealing. - The telescope shall show no evidence of leakage when subjected to an internal pressure of dry nitrogen at 5 psig for five minutes. The interior atmosphere of the accepted telescope shall contain nitrogen (dew point of nitrogen shall be at least as low as -25°F) at a pressure of between 0.1 and 0.25 psig.

3.8 Accuracy.

3.8.1 Orientation. - With the telescope mounted on the front mounting surface and the rear angular locating surface of the objective tube housing, the plane of the objective tube and the locating key shall be horizontal.

3.8.2 Collimation.

3.8.2.1 Reticle lens. - The extreme left and right zero graduations shall coincide with a horizontal target line 20 mils above the geometric axis of the objective tube within ±0.5 mil. The vertical line of the HExM482 ballistic data on the reticle lens shall be 36.5 mils ± 3 mils in azimuth from the boresight cross of the sliding reticle at the zero elevation position.

3.8.2.2 Sliding reticle. - With the telescope positioned as in 3.8.1 and the horizontal line of the boresight cross in coincidence with the zero graduation on the extremeright,the horizontal line shall be in coincidence with the zero graduation on the extreme left within 0.2 mil; the line of sight through the boresight cross shall be parallel in azimuth to the geometric axis of the objective tube within 0.5 mil.

3.8.3 Eyepiece focus. - The eyepiece focus shall be adjustable over the range of plus and minus four diopters as read on the diopter scale. The zero of the diopter scale shall indicate zero diopters within 0.25 diopter.

3.8.4 Reticle accuracy. - The angular values, between the zero and maximum scale graduations for each of the three scales on the reticle lens shall be as indicated on the applicable drawings within 3.0 percent.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

3.8.5 Image tilt. - With the telescope positioned as in 3.8.1, the image of a plumb line over the full field of view shall be vertical within one degree.

3.8.6 Reticle shift. - Changing the direction of rotation of the reticle knob shall not cause the horizontal line of the boresight cross to exceed the tolerance specified in 3.8.2.2; nor shall the boresight cross shift in azimuth in excess of 0.05 mil.

3.8.7 Resolution. - The resolution on the optical axis shall be five seconds of arc or less.

3.8.8 Reticle plumb travel. - With the telescope positioned as in 3.8.1, the line of sight through the boresight cross of the sliding reticle shall track a plumb line within plus or minus 0.5 mil, (total lateral spread not to exceed 0.5 mil) when the reticle is depressed by rotation over an excursion of 60 mils as read on the mil scale of the reticle lens.

3.8.9 Parallelism of reticle and image. - With the telescope positioned as in 3.8.1, the vertical line of the mil scale shall be parallel to the image of the plumb line within 30 minutes.

3.8.10 Parallax. - With the boresight cross positioned with 2.0 mils of the optical axis, parallax at the boresight cross shall not exceed 0.25 mil between 125 yards and infinity.

3.9 Operability. - The running torque required to rotate the diopter adjustment and the reticle knob shall not exceed the values specified in Table I at temperatures indicated when subjected to the requirements of 3.4.2.

TABLE I - OPERABILITY

| Control | Plus 60° to 90°F | Minus 40°F | Plus 150°F |
|---|---|---|---|
| Diopter Adjustment | 5 inch lbs | 9 inch lbs | 5 inch lbs |
| Reticle Slide Adjustment | 4 inch lbs | 8 inch lbs | 4 inch lbs |

3.10 Illumination. - The reticle markings shall be visible in ambient light conditions ranging from dusk into night. When required, the use of a mask wiht a 3/4" aperture, located on the entrance window, will be permitted to meet this requirement.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specifiedm, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions. - The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions - of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval. - The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) telescopes plus three (3) each of all items covered by SQAP . The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government tesrting. - When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing. - When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor’s inspection.

4.3 Inspection provisions.

4.3.1 Submission of product. - Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.

4.3.2.1 Components and subassemblies. - All components and subassemblies shall be inspected in accordance with the inspection provisions



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

contained in Supplementary Quality Assurance Provisions (SQAP) listed in the List of Inspection Documents (IEL), when provided with the technical data package (TDP). In the absence of SQAPS, the applicable Quality Assurance Provisions of MIL-F-13926 shall apply.

4.3.2.2 Final acceptance inspectioon. - Subsequent to first article approval, examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Table II herein. Examination and tests for Packaging, Packing and Marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Table II shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

TABLE II - CLASSIFICATION OF DEFECTS

| CLASS CHARACTERISTIC | REQUIREMENT | TEST PROCEDURE |
|---|---|---|
| CRITICAL 100% INSPECTION | | |
| 1. Sealing | 3.7 | 4.6.1.2 |
| 2. Pressure | 3.7 | 4.6.1.2 |
| MAJOR: AQL 1.0% DEFECTIVE | | |
| 101. Pre-vibration collimation | 3.8.2.1 & 3.8.2.2 | 4.6.2.2 |
| 102. Vibration | 3.5 | 4.6.2.3 |
| 103. Cleanliness | 3.6 | 4.6.2.4 |
| 104. Post-vibration | 3.5 | 4.6.2.5 |
| 105. Eyepiece focus | 3.8.3 | 4.6.2.6 |
| 106. Reticle plumb travel | 3.8.8 | 4.6.2.7 |
| 107. Reticle shift | 3.8.6 | 4.6.2.8 |
| 108. Parallax | 3.8.10 | 4.6.2.9 |
| 109. Resolution | 3.8.7 | 4.6.2.10 |
| 110. Image tilt | 3.8.5 | 4.6.2.11 |
| 111. Reticle accuracy | 3.8.4 | 4.6.2.13 |
| 112. Operability | 3.9 | 4.6.2.14 |
| 113. Illumination | 3.10 | 4.6.2.15 |
| 114. Parallelism image & reticle | 3.8.9 | 4.6.2.12 |
| MINOR: None defined | | |

4.3.3 Acceptance and rejection. - Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling.

4.4.1 General. - Three telescopes shall be selected at random as a special sampling from each 100 produced. The sample shall meert the requirements and tests in Table III.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

TABLE III

| | CHARACTERISTIC | REQUIREMENT | TEST PROCEDURE |
|---|---|---|---|
| 301. | Regulation pertaining to radioactive materials | 3.1 | Certification |
| 302. | Fabrication | 3.2 | Certification |
| 303. | General specification | 3.3 | Certification |
| 304. | Temperature storage | 3.4.1 | 4.6.1.1 |
| 305. | Temperature operating | 3.4.2 | 4.6.1.1 |
| 306. | Operability (Torque at operating temperature) | 3.9 | 4.6.2.14 |

4.4.2 Failure of sample. - Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.3.3).

4.5 inspection equipment. - Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment. - Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 government design. - Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data listed in the List of Inspection Documents when provided with the Technical Data Package (TDP).

4.5.2.2 Contractor design. - The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerance used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:23Z
Check the source to verify that this is the current version before use.

| NOMENCLATURE | DESCRIPTION |
|---|---|
| 1. Hot and cold chamber | Standard type conforming to the accuracies outlined in test facilities specified under test facilities of MIL-F-13926 |
| 2. Power supply | Standard shop type to provide a 3 VDC output, within 10% accuracy |
| 3. Torque wrench | Standard shop type accurate to within 10% of drawing tolerance |

4.6 Test methods and procedures.

4.6.1 Environmental.

4.6.1.1 Temperature test. - The telescope shall be subjected to Test Procedure I of MIL-F-13926; however, the temperatures specified in 3.4.1 and 3.4.2 shall apply. When the item under test has been stabilized at the temperature specified, the result of the specified test shall conform to the limits outlined in 3.4.1 and 3.4.2 using test procedures outlined herein.

4.6.1.2 Sealing. - This test shall be performed on a 100% inspection basis using testing equipment the accuracy of which shall conform to the accuracy depicted on Drawing F8565556. When using pressure test fixture, the fixture shall be set-up as outlined in set-up instructions shown on Drawing F8565556. The gas used shall be dry nitrogen having a dew point of -258°F. After connecting the test equipment to the unit under test, adjust the pressure to the pressure specified in 3.7 and maintain the pressure for the time specified in 3.7. Pressure to remain constant to assure compliance with 3.7. At the completion of the test, connect a dew point tester to the exit port and purge the unit under test until -25°F is recorded and seal the unit after adjusting the internal pressure in the unit to the value specified in 3.7. Record this internal pressure.

4.6.1.2.1 Internal pressure. - This test to be performed using standard shop type pressure gage and standard shop type inspection techniques. This test to be performed on a 100% inspection basis just prior to packaging. Any unit found not containing the internal pressure recorded in 4.6.1.2 shall be rejected and repressurized and retested in accordance with 4.6.1.2. All retested units shall be set aside for a minimum of 12 hours and then retested for internal pressure in accordance with 3.7. Should the unit fail the second test, the unit is to be considered rejected.

4.6.2 Performance.

4.6.2.1 Orientation. - Position Fixture F7573980 in accordance with set-up instructions outlined on the drawing and position and secure Adapter



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:23Z
Check the source to verify that this is the current version before use.

F8566269 and the unit under test to the fixture as outlined in the adapter set-up instructions. Upon completion of all set-up instructions, the unit shall be orientated as outlined in 3.8.1.

4.6.2.2 Collimation (pre-vibration). - With the unit positioned as outlined in 4.6.2.1, position the intersecting point of the boresight cross of the sliding reticle in coincidence with the horizontal reticle line of the projected reticle. Observe where this point falls with respect to the vertical limit lines of the projected reticle target. This intersecting point must fall within the limits of the pip lines to assure conformance with 3.8.2.2. Record this position. When this coincidence has been established, sight through the telescope and observe where the left and right zero range lines fall with respect to the projected target line. Both extreme zero range lines must coincide to this target line within the limit of the tolerance lines located above and below this projected target line to assure conformance with 3.8.2.1. Record this position. Also observe where the vertical line of the HEX M482 scale falls with respect to the corresponding target line. this vertical reticle line must coincide with the limits of projected reticle tolerance lines to assure conformance with 3.8.2.1. Record this position. By means of the range knob, raise the horizontal line of the boresight cross to coincide with extreme right zero range line and observe where the opposite end of this horizontal line falls with respect to the extreme left zero range line. They must coincide within the limits of 3.8.2.2. Use one half the space of the tolerance lines used when determining the locating of the extreme zero range line. Record this position.

4.6.2.3 Vibration. - This test shall be performed using devices the accuracy of which shall be equal or exceed the accuracy depicted on Drawings F7560085 and F8295974. The test is to be performed as outlined in Procedure V of MIL-F-13926, however, the frequency and duration shall be as outlined in 3.5.At the conclusion of the test, the unit under test shall be subjected to a visual and tactile examination and shall be subjected to the following test to determine conformance with 3.5.

4.6.2.4 Cleanliness. - The unit under test shall be subjected to the test procedures outlined in MIL-O-13830 for conformance to the require-ments outlined in 3.6.

4.6.2.5 Post-vibration. - Reassemble the unit to the final test fixture and repeat the test procedure outlined in 4.6.2.2. The unit under test shall not have moved from the previously recorded settings for those requirements outlined in 3.8.2.1 and 3.8.2.2.

4.6.2.6 Eyepiece focus. - This test is to be accomplished by placing a white background in front of the telescope’s window. Eyepiece focus is to be measured using a 3 power dioptometer conforming to the accuracies depicted on Drawing 7680631. Adjust the dioptometer eyepiece assembly to the dioptometer's optical axis. Next direct the dioptometer’s line of



Source: https://assist.dla.mil -- Downloaded: 202640-22T20:23Z
Check the source to verify that this is the current version before use.

sight toward a 500 feet distant target such as a smoke stack, edge of a building, or some other well defined target image. Adjust the objective assembly until parallax is removed. Parallax is defined as any apparent movement between the reticle and target image when the head is moved from side to side or up and down. Set zero diopters on the eyepiece of the unit under test and align the dioptometer's optical axis to the optical axis of the unit under test and obtain a clear sharp image of the telescope reticle on the optical axis. Make all measurements on the dioptometer by adjusting the objective assembly. Any and all adjustments to be within the limits of 3.8.3. Rotate the telescope's eyepiece assembly and observe the amount of rotation from the zero diopter reading for conformance to the requirement outlined in 3.8.3.

4.6.2.7 Teticle plumb travel. - With the telescope positioned as outlined in 4.6.2.2, observe where the intersecting point of the boresight cross of the sliding reticle falls with respect to the intersecting point of the projected reticle centerlines. By means of the range knob, activate the boresight cross from reticle's geometric axis (20 mil graduation) to each extreme of the mil scale and observe parallelism between this intersecting point and the projected reticle centerline. parallelism to be maintained with the limits of 3.8.8.

4.6.2.8 Reticle shift. - With the telescope positioned as outlined in 4.6.2.2, sight through the telescope and observe coincidence between the intersecting point boresight cross and the projected center reticle lines while rotating the range knob first in the clockwise and then counterclockwise direction. Rotation of the knob shall not shift the horizontal line of the boresight cross in excess of the limits of 3.8.6. During this rotation of the range knob, also observe that the horizontal line of the boresight cross does not shift from the zero range lines when coincidence has been established as outlined in 4.6.2.2.

4.6.2.9 Parallax. - This test may be performed with the telescope positioned as outlined in 4.6.2.2. Adjust the collimatot projector to either parallax distance specified in 3.8.10. Sight through the telescope and by means of the range knob, position the horizontal line of the boresight on the geometric axis of the telescope under test (use 20 mil graduation for location of geometric axis). Observe any apparent movement between the intersecting point of the boresight cross and the intersecting point of the projector collimator's center horizontal and vertical reticle lines. Any apparent movement between these two points when the inspector's head is moved up and down or from side to side is considered parallax. The amount of movement shall not exceed the limits specified in 3.8.10. Repeat this procedure with the projector collimator set to infinity.

4.6.2.10 Resolution. - To perform this test, a wall target containing the appropriate resolution target shall be employed. construction of the resolution target and the method of inspection shall be as outlined in MIL-O-13830. The telescope must resolve the test pattern within the



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:23Z
Check the source to verify that this is the current version before use.

limits outlined in 3.8.7. During this test, the telescope may be supported in a "V" Block. The use of packing or shims may be used to position the telescope. When making this test, use a dioptometer having a minimum of 3 power.

4.6.2.11 Image tilt. - This test may be performed with the telescope positioned as outlined in 4.6.2.2. The test is performed by sighting through the auxillary telescope and observe parallelism between the center vertical reticle line of the projector collimator and the center vertical reticle line of the auxillary telescope. They must be parallel within the limits of the angular lines of the projector collimator reticle to assure compliance with 3.8.5.

4.6.2.12 Parallelism of image and reticle. - With the telescope and fixture positioned as outlined in 4.6.2.1, sight through the telescope and observe parallelism between the mil scale vertical line and the corresponding projected reticle line. the extent of non-parallelism is to be estimated and shall not exceed the width of the mil scale to assure conformance with paragraph 3.8.9.

4.6.2.13 Reticle accuracy. - This test may be performed with the telescope positioned as outlined in 4.6.2.2. To facilitate this inspection, the telescope may be unlocked in the adapter and the zero range graduations of the reticle placed in coincidence with zero range lines of the projected target. To obtain this coincidence, shim the unit in the mount. When this coincidence has been established, observe coincidence between the maximum range line of the scales. They must be within the limit lines of the projected reticle for each scale to assure compliance with 3.8.4.

4.6.2.14 Operability. - This test will be performed at the temperature specified in 3.9 using a torque wrench and appropriate adapters. Running torque readings shall conform to the limits specified in 3.9.

4.6.2.15 Reticle illuimination. - Place the instrument in a dark room having a controlled light source. The obsever and instrumentt mustbecome dark adapted. Prior to performing the test, place a white matted surface approximately 2 feet from the telescope window. Perform the test by observing reticle pattern and determine that this pattern is clearly discernible by the means of the self-illuminating source in the dark room. Gradually raise the level of illumination to where the pattern becomes indiscernible. Place a fixed stop having an aperture as specified in 3.10 over the objective window and observe that the reticle pattern is again clearly discernible by means of the self-illuminating source, Raise ambient level of illumination to 10 foot candle, remove the fixed stop and observe the reticle pattern. It shall appear as when viewed in ambient light condition to assure conformance with 3.10.



Source: https://assist.dla.mil -- Downloaded: 202640-22T20:23Z
Check the source to verify that this is the current version before use.

## 5. PREPARATION FOR DELIVERY

5.1 packaging, packing, and marking. - Packaging, packing, and marking shall be in accordance with Packaging Data Sheet 11730285. The level if protection shall be as specified in the procurement document.

## 6. NOTES

6.1 Intended use. - The M114E1, Elbow Telescope is primarily intended to lay artillery weapons in indirect fire.

6.2 Ordering data. - Procurement documents should specify the following:

a. Title, number, and date of this specification
b. Selection of applicable levels of preservation, packaging, and packing
c. Applicable stock number

6.3 Radioactive material. - Prospective bidders should be cognizant of the need for an Atomic Energy Commission license governing the procurement and handling of radioactive material.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A214



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:23Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**OFFICIAL BUSINESS**
**PENALTY FOR PRIVATE USE $300**

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commanding Officer
Frankford Arsenal
Attn: SMUFA-N1100
Philadelphia, PA 19137

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:23Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| | |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |
| | |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:23Z
Check the source to verify that this is the current version before use.