INCH-POUND

MIL-W-63468A (AR)
AMENDMENT 4
8 June 1994
SUPERSEDING
AMENDMENT 3
16 February 1990

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, H.E.: M261

This amendment forms a part of MIL-W-63468A (AR), dated 07 October 1983, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.7: Delete in its entirety.

* 3.9: Delete "components" and substitute "major components, assemblies, and subassemblies such as: pusher plate, M73 Grenade, flat flex lead, lead tape, auto jettison retaining rings, etc."

PAGE 7

Table I, First Article Inspection: Delete Note (b) in its entirety and substitute "The first article ballistic sample with units from secured cargo (36), helicopter vibration (19), and leakage test (6) shall be rejected if two (2) or more payloads fail to eject, or thirty-four (34) more grenades fail to function."

* 4.4.1, last line: Delete "4,000." and substitute "5,000."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:57Z
Check the source to verify that this is the current version before use.

PAGE 10

* 4.4.2.2:

Delete "None defined" under Critical and substitute:

"1 Pulled arming pin (b) 100% 3.2 Gage".

Add Major 105:

"Presence of correct auto jettison retaining rings 100% 3.2 Visual (c)".

Add Notes (b) and (c):

"(b) To be performed just prior to grenade stacking.

(c) No. 9 retaining ring is different from No. 1 - No. 8 retaining rings and is color-coded. Inspection of the retaining rings shall be performed after stacking, but before insertion of grenades into the warhead case. Part count of both types of auto jettison retaining rings shall be made at the end of each shift."

PAGE 11

4.4.2.3:

Major 109: Delete and substitute:

"109	Leakage test	6	--	3.16	4.5.6
110	Ballistic test	36(a)	--	3.18	4.5.8".

Add Note (a): "(a) Sample includes 6 items from leakage test."

Add 4.4.2.4, included as Page 11a.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Grenade, General Purpose, High Explosive: M73	1 OF 1	9334143
			NEXT HIGHER ASSEMBLY: 9334122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Correct position of auto jettison retaining rings	100%	3.2	Visual
Minor				
201	Evidence of poor workmanship	0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:57Z
Check the source to verify that this is the current version before use.

* 4.5.1, second sentence: Delete and substitute:

"Verify that all major components, assemblies, and subassemblies, such as pusher plate, M73 Grenade, flat flex lead, lead tape, auto jettison retaining rings, etc., are present and properly placed; that all grenades are safe; and that no foreign material is present."

* 4.5.2, second sentence: Delete "2.75 Inch Rocket Motors" and substitute "2.75 inch MK66 rocket motors".

PAGE 14

* 4.5.2, last paragraph, line 3: Delete "intact and securely in place)." and substitute "intact and not manually removable)."

PAGE 16

* 4.5.6, second line: Delete "for first article testing only.".

End of paragraph, Add: "To inspect the cargo compartment, unthread the plug in the rear of the warhead. If one or more warheads fail to meet the requirements, the lot shall be rejected."

* 4.5.8: Delete and substitute:

"4.5.8 Ballistic test. The tactical requirement for the warhead is to provide proper delivery of M73 grenades into target areas from 1000 to 6000 meters from the launching helicopter. Performance shall be evaluated by ground launching a sample of 36 M261 warheads, assembled with M66 Mod 1 or Mod 2 motors, from any of the compatible launchers into a permanently contaminated field. Twelve warheads shall be conditioned at -50° + 5°F, 12 warheads at +70° ± 15°F, and 12 warheads at +150°- 5°F for a minimum period of 8 hours. Firing and fuze charging shall be accomplished by means of a Government-approved ballistic firing test set using appropriate fuze time settings to achieve airburst range of 1000, 3000, and 6000 meters. Time from launch to cargo ejection, and number of grenade functions, shall be detected and recorded. If three or more payloads fail to eject, or 22 or more grenades fail to function, the lot shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

* 6.3: Delete "US Army Armament Research and Development Command, Attn: DRDAR-QAF-I" and substitute "Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, Attn: SMCAR-QAF-I, Picatinny Arsenal, NJ 07806-5000".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A934)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.