INCH-POUND

MIL-DTL-28840/15D
23 October 2009
SUPERSEDING
MIL-DTL-28840/15C
20 April 2004

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, THREADED,
HIGH SHOCK, HIGH DENSITY, SHIPBOARD, DUST COVER, PLUG

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28840.



FIGURE 1. Dimensions and configurations.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:39Z
Check the source to verify that this is the current version before use.

Designator (see note 1)	A thread class 2B	B Max. dia.	C ± .006 ± .15	D ± .010 ± .25
A (11)	.750-1P-.2L-DS	1.028 (26.21)	.575 (14.60)	.765 (19.43)
B (13)	.875-1P-.2L-DS	1.141 (28.98)	.699 (17.75)	.890 (22.61)
C (15)	1.062-1P-.2L-DS	1.263 (32.08)	.871 (22.12)	1.015 (25.78)
D (17)	1.125-1P-.2L-DS	1.387 (35.23)	.941 (23.90)	1.140 (28.96)
E (19)	1.312-1P-.2L-DS	1.513 (38.43)	1.108 (28.14)	1.265 (32.13)
F (23)	1.500-1P-.2L-DS	1.703 (43.51)	1.293 (32.84)	1.453 (36.91)
G (25)	1.625-1P-.2L-DS	1.825 (46.35)	1.454 (36.93)	1.577 (40.06)
H (29)	1.812-1P-.2L-DS	2.143 (54.43)	1.620 (41.15)	1.890 (48.01)
J (33)	2.000-1P-.2L-DS	2.329 (59.16)	1.812 (46.02)	2.077 (52.76)

Inches	mm	Inches	mm
.01	.25	.450	11.43
.025	.64	.630	16.00
.03	.76	.849	21.56
.032	.81	.859	21.82
.047	1.19	.88	22.35
.115	2.92	1.00	25.40
.146	3.71	5.00	127.00
.166	4.22		

NOTES:
1. Shell sizes are provided within parentheses for information and are not a part of the designator.
2. Dimensions are in inches.
3. Metric equivalents are given for information only.
4. Dimensions apply after plating.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:39Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configurations: See figure 1.
Interface dimensions shall conform to MIL-DTL-28840.

Material

Cover: Aluminum alloy in accordance with, ASTM B85/B85M, ASTM B108/B108M, ASTM B26/B26M, ASTM B209, ASTM B211, or ASTM B221.

Corrosion resistant steel shall be in accordance with ASTM A276, ASTM A580/A580M or ASTM A473, type 316.

Gasket: Flourosilicone.

Chain and other hardware: 300 series corrosion resistant steel.

Finish

Cover: Finish shall be in accordance with MIL-DTL-28840, olive drab over electroless nickel, corrosion resistant steel, cadmium plate, black.

Chain and other hardware: Passivated in accordance with SAE-AMS2700, type 2.

Marking: The cover shall be identified with the manufacturer's name or trade-mark and the Part or Identifying Number (PIN).

PIN example:



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:39Z
Check the source to verify that this is the current version before use.

Qualification: One protective cover of each shell size for which qualification is desired shall have the following tests performed in the sequence shown:

Visual and mechanical

Magnetic permeability

Shell conductivity

Corrosion

Air leakage: Cover shall be mated to suitable connector plug and tested in accordance with test procedure EIA-364-02. The following details shall apply: The air leakage rate shall not be greater than one atmospheric cubic inch per hour ($4.55X10^{-3}$ cubic centimeter per second).

Tensile strength: Cover shall be mounted to a suitable fixture to facilitate a 25-pound pull applied at the rate of 5 pounds per second and held for a period of 5 minutes. The load shall be applied to the chain end fastener through the center line axis of the protective cover, then repeated through a perpendicular axis (90°) from the centerline axis. Chain or fastener breakage, or loosening of the rivet shall be considered failures.

Shell conductivity

Post visual and mechanical

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-DTL-28840, this document references the following:

ASTM A276
ASTM A473
ASTM A580/A580M
ASTM B26/B26M
ASTM B85/B85M
ASTM B108/B108M
ASTM B209
ASTM B211
ASTM B221
EIA-364-02
SAE-AMS2700

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:39Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Navy - EC
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2007-227)

Review activities:
Navy - OS, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:39Z
Check the source to verify that this is the current version before use.