INCH-POUND

MIL-DTL-28840/17C
26 April 2007
SUPERSEDING
MIL-C-28840/17B(EC)
16 July 1986

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, SCREW THREADS, HIGH DENSITY, HIGH SHOCK, SHIPBOARD, CRIMP CONTACTS, PLUG ASSEMBLY, OPEN WIRE, CLASSES D AND DS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28840.



FIGURE 1. Dimensions and configuration.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:40Z
Check the source to verify that this is the current version before use.

Designator (See note 3)	Assembly Part or Identifying Number (PIN) (See note 6)	Connector plug PIN (See note 6)	Backshell assembly PIN (See note 6)	B thread class 2B	F Cable entry	
					open	closed
A (11)	M28840/17*A***	M28840/16*A***	M28840/1A*	.750-.1P-.2L-D.S.	.286	.177
B (13)	M28840/17*B***	M28840/16*B***	M28840/1B*	.875-.1P-.2L-D.S.	.286	.177
C (15)	M28840/17*C***	M28840/16*C***	M28840/1C*	1.062-.1P-.2L-D.S.	.416	.250
D (17)	M28840/17*D***	M28840/16*D***	M28840/1D*	1.125-.1P-.2L-D.S.	.476	.291
E (19)	M28840/17*E***	M28840/16*E***	M28840/1E*	1.312-.1P-.2L-D.S.	.626	.348
F (23)	M28840/17*F***	M28840/16*F***	M28840/1F*	1.500-.1P-.2L-D.S.	.831	.429
G (25)	M28840/17*G***	M28840/16*G***	M28840/1G*	1.625-.1P-.2L-D.S.	.956	.523
H (29)	M28840/17*H***	M28840/16*H***	M28840/1H*	1.812-.1P-.2L-D.S.	1.081	.643
J (33)	M28840/17*J***	M28840/16*J***	M28840/1J*	2.000-.1P-.2L-D.S.	1.187	.704

FIGURE 1. Dimensions and configuration – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:40Z
Check the source to verify that this is the current version before use.

Designator (See note 3)	Assembly PIN (See note 6)	Connector plug PIN (See note 6)	Backshell assembly PIN (See note 6)	L max	Q max	Max O.D. over rear clamps
A (11)	M28840/17*A***	M28840/16*A***	M28840/1A*	2.438	1.028	.832
B (13)	M28840/17*B***	M28840/16*B***	M28840/1B*	2.438	1.141	.832
C (15)	M28840/17*C***	M28840/16*C***	M28840/1C*	2.438	1.263	.989
D (17)	M28840/17*D***	M28840/16*D***	M28840/1D*	2.688	1.387	1.094
E (19)	M28840/17*E***	M28840/16*E***	M28840/1E*	2.812	1.513	1.319
F (23)	M28840/17*F***	M28840/16*F***	M28840/1F*	2.938	1.703	1.557
G (25)	M28840/17*G***	M28840/16*G***	M28840/1G*	3.062	1.825	1.653
H (29)	M28840/17*H***	M28840/16*H***	M28840/1H*	3.188	2.143	1.819
J (33)	M28840/17*J***	M28840/16*J***	M28840/1J*	3.375	2.329	2.020

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Shell sizes are provided within parentheses for information and are not a part of the designator.
4. Dimensions apply after plating.
5. Normal mating key position shown. For alternate key positions see MIL-DTL-28840.
6. Assembly shall be made of a connector and backshell of the same material.

FIGURE 1. Dimensions and configuration – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:40Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.
Classes: D and DS.
Insert Arrangements: See the section of MIL-STD-1698 corresponding to desired shell size.
Contacts: Style P or S crimp type.
Shell polarization: 1 thru 6, key position.
Marking: PIN on shell.
Mating counterpart: Receptacle connectors in accordance with MIL-DTL-28840/10, 11, 12, 14, 20 and 21.
Installation and removal tool: In accordance with MIL-I-81969/33 and /34.
PIN's shown indicate aluminum alloy hardware. If corrosion resistant steel parts are required, the connector and accessory part numbers must be changed to designate corrosion resistant hardware.

PIN example:



Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-28840, this document references the following:

MIL-DTL-28840/10
MIL-DTL-28840/11
MIL-DTL-28840/12
MIL-DTL-28840/14
MIL-DTL-28840/20
MIL-DTL-28840/21
MIL-I-81969/33
MIL-I-81969/34
MIL-STD-1698

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:40Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Navy - EC
DLA - CC

Preparing activity:
DLA - CC

(Project 5935–2005-037)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:40Z
Check the source to verify that this is the current version before use.