INCH-POUND


MIL-DTL-28840/23C
11 January 2010
SUPERSEDING
MIL-DTL-28840/23B
20 April 2004

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, THREADED, HIGH SHOCK, HIGH DENSITY, SHIPBOARD, BACKSHELL, GLAND NUT, WIRING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28840.



Inches	mm
.032	0.81
.062	1.57
.228	5.79
.718	18.24

FIGURE 1. Dimensions and configurations.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:42Z
Check the source to verify that this is the current version before use.

Designator (see note 1)	A thread class 2B	B max dia
A (11)	.750-20 UNFF	1.028 (26.11)
B (13)	.875-20 UNEF	1.14 (26.11)
C (15)	1.000-20 UNEF	2.263 (32.08)
D (17)	1.125-18 UNEF	1.387 (35.23)
E (19)	1.250-18 UNEF	1. 513(38.43)
F (23)	1.438-18 UNEF	1.703 (43.51)
G (25)	1.562-18 UNEF	1.825 (46.35)
H (29)	1.876-16 UN	2.143 (54.43)
J (33)	2.062-16 UNS	2.329 (59.16)

NOTES:
1. Shell sizes are provided within parentheses for information and are not a part of the designator.
2. Dimensions are in inches.
3. Metric equivalents are given for information only.
4. Dimensions apply after plating.
5. These gland nuts are used with MIL-DTL-28840/10, /11, /14 and /16.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:42Z
Check the source to verify that this is the current version before use.

REQUIREIMENTS

Dimensions and configurations: See figure 1.
Interface dimensions shall conform to MIL-DTL-28840.


Material: Shall be aluminum alloy in accordance with, ASTM B85/B85M, ASTM B108/B108M, ASTM B26/B26M or ASTM B209/B209M, ASTM B211 or ASTM B221.

Corrosion resistant steel shall be in accordance with ASTM A276, ASTM A580/A580M or ASTM A473, type 316.

Finish: Aluminum components shall plated in accordance with MIL-DTL-28840. Corrosion resistant steel components shall be cadmium plate, black. The screws and washers shall be passivate in accordance with SAE-AMS2700, type 2.

Marking: Backshell shall be identified with the manufacturer's name or trademark and the Part or Identifying Number (PIN).

PIN example:



W - Aluminum, cadmium plate, olive drab over electroless nickel
D - Corrosion resistant steel, cadmium plate, black
F - Wrought aluminum, pure electrodeposited aluminum – non-reflective
L - Wrought aluminum, Nickel Fluorocarbon Polymer non-reflective
S - Wrought aluminum, zinc nickel – non-reflective

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:42Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-28840, this document references the following:

MIL-DTL-28840/10
MIL-DTL-28840/11
MIL-DTL-28840/14
MIL-DTL-28840/16
ASTM A276
ASTM A473
ASTM A580/A580M
ASTM B26/B26M
ASTM B85/B85M
ASTM B108/B108M
ASTM B209/B209M
ASTM B211
ASTM B221
SAE-AMS2700

CONCLUDING MATERIAL

Custodians:
Navy - EC
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2008-009)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:42Z
Check the source to verify that this is the current version before use.