MILITARY SPECIFICATION

TRANSCEIVER, VHF/UHF

This amendment forms a part of Military Specification MIL-T-28849(EC), dated 26 January 1979.

PAGE 2

3.2.5, line 4: Delete "and loudspeaker disable switch." and substitute ", loudspeaker disable switch, RF power select switch, and antenna connectors.".

PAGE 3

3.3.3.5, line 2: After "such as grounding," insert "shorting,".

3.3.3.5, add to end of paragraph: "The unit shall be operational when used with mismatched antenna loading up to at least a 3:1 voltage standing wave ratio (VSWR).".

3.3.5.1, line 3: Delete "with" and substitute "without".

PAGE 4

Add as paragraph 3.3.5.4:

"3.3.5.4 Remote control. The transceiver shall be able to operate by remote control at a minimum distance of 9.144 meters (m) (30 feet (ft)).".

3.5.1, line 4: Delete "23.8 volts to 29.0 volts." and substitute "22.0 volts to 30.0 volts.".

PAGE 5

3.5.2.12: Delete the text and substitute: "The signal selectivity of the IF amplifier shall have a bandwidth of ± 10 kHz minimum at 6 dB down with respect to the center frequency.".

PAGE 6

Add as paragraph 3.5.2.22:

"3.5.2.22 Frequency monitoring. A means of monitoring at least two other frequencies simultaneously with the operating frequency shall be provided. Either guard receivers or a receiver scanner shall be used. Guard receivers or scanner shall be operable on any 25 kHz channel in the frequencies listed in 1.1. Guard receivers shall have identical operating specifications with the main receiver. A scanner shall have a variable scan rate. Either shall be operatable or disabled, or both, from the front panel of the transceiver.".

3.5.3.2: Delete the text and substitute: "The unmodulated RF carrier power output shall be front-panel switchable to two levels into a 50-ohm resistive load as follows:

a. HIGH output: Shall not be less than five watts
b. LOW output: Shall not be less than 250 milliwatts (mW) (0.25 watts) and shall be no more than 500 mW (0.50 watts).".

FSC 5820

Source: https://assist.dla.mil -- Downloaded: 202610-20T19:50Z
Check the source to verify that this is the current version before use.

PAGE 7

3.5.4.2: Add "The main tuning controls shall be located on the front panel of the transceiver.".

Add as paragraph 3.5.4.3:

"3.5.4.3 Synthesizer lockup time. The synthesizer shall lockup to within specified limits of a channel frequency (see 3.5.2.18) within 100 milliseconds (ms) for any frequency change within the frequencies listed in 1.1.".

Add as paragraph 3.5.4.4:

"3.5.4.4 Synthesizer noise-to-carrier ratio. The synthesizer noise-to-carrier ratio shall not exceed -130 dBm/Hz at any of the frequencies listed in 1.1, but separated from the carrier frequency by at least ±10 MHz.".

PAGE 8

3.5.5, line 4: Delete "a 12 VDC vehicular battery, or a 24 VDC vehicular battery" and substitute "or a 12 VDC or 24 VDC vehicular battery".

3.5.5.1, lines 4 and 5: Delete "10 percent transmit with 1000 Hz, 0.5 watts audio output, and 80 percent standby." and substitute "0.5 watts audio output, at 1000 Hz, 10 percent transmit, 5.0 watts RF output at all frequencies listed in 1.1, and 80 percent standby.".

PAGE 10

TABLE I: After the "Enclosure" line, add the following in the columns shown:

	Examination or test	Requirement paragraph	Test paragraph	First article	Quality conformance Group A	B	C	
*	"Remote control	3.3.5.4	4.5.3	X	X			"

PAGE 12

* TABLE II: In the first column heading, delete "Test" and substitute "Examination or test".

* TABLE II: In the "Requirement paragraph" column, on the "Rcvr additional characteristics" line, delete "3.5.2.21" and substitute "3.5.2.22".

* TABLE II: In the "Examination or test" column, delete "Synthesizer preset" and substitute "Synthesizer characteristics".

* TABLE II: In the "Requirement paragraph" column, on the "Synthesizer characteristics" line, delete "3.5.4.2.2" and substitute "3.5.4 through 3.5.4.4".

Source: https://assist.dla.mil -- Downloaded: 202610-20T19:50Z
Check the source to verify that this is the current version before use.

* 4.5.12.2, line 5: Delete "True RMS Voltmeter" and substitute "true RMS voltmeter".

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
NAVY-EC
(Project 5820-N727)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:50Z
Check the source to verify that this is the current version before use.