MIL-B-60597(MU)
AMENDMENT 1
31 July 1968

MILITARY SPECIFICATION

BALLISTICS COMPUTER SUBASSEMBLY: 10543800
(COMPUTER UNIT)

This amendment forms a part of Military Specification MIL-B-60597(MU), dated 8 September 1967.

Paragraph 3.5.4: Delete first sentence and substitute:

"With a 250 MA ± 5% load connected across 1J26-J and D, the D.C. voltage pin J shall be 24.0 VDC ± 5%."

Add new paragraphs 3.5.6 and 3.5.6.1 as follows:

"3.5.6 Deflection amplifier outputs.

3.5.6.1 Gunner's deflection channel.- The maximum input signal required at the gunner's deflection jump jack to drive the amplifier into saturation (maximum current flow through the center tap of a 160 ohm center tapped resistive load connected across pins FF and GG of 1J26 with center tap supplied from pin CC of 1J26) shall not exceed 0.8 volt RMS with the gain control R20 full counterclockwise. All other test jacks with the exception of the amplifier input shall be grounded during the test."

Paragraph 3.5.8: Delete "neasured" and substitute "measured".

Paragraph 3.5.8, Table I: For 1,660 ohms delete "±1%" and "Commander's "E" Droop Sin C Jack" and substitute "±2%" and "Commander's "D" Droop Sin C Jack"; For 77.8 ohms delete "±1%" and substitute "±2%".

Paragraph 3.5.9, Table II: Delete and substitute

TABLE II

"RESISTANCE	TOLERANCE	FROM	TO
924.13 ohms	± 0.15%	1J25-B	1J25-C
69,645 ohms	± 5%	1J25-F (Ground Gunner's amplitude input	1J25-E and Commander's jacks)
2581.9 ohms	± 1%	1J27-F (Bridge test terminals must be connected such that the voltage at the base of transistor Q7 of the Demodulator and Ramp Generator board is	1J25-E

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

TABLE II (Continued)

RESISTANCE	TOLERANCE	FROM	TO
		negative with respect to ground. The terminal voltage shall not exceed 5 VDC.)	
28.10 ohms	± 5%	1J25-G	1J27-F
473.13 ohms	± 0.15%	1J25-M	1J26-a
1 ohm max.		1J25-G	1J25-H
1 ohm max.		1J25-P	Gunner's deflection lead jack
100,000 ohms	± 5%	1J25-R (Ground Gunner's and Commander's "E" amplitude input jacks)	1J25-E
213.35 ohms	± 0.15%	1J25-S	1J27-P
1 ohm max.		1J25-S	1J25-T
1 ohm max.		1J25-T	1J25-U
1 ohm max.		1J25-U	1J25-V
1 ohm max.		1J25-V	1J25-W
2751.95 ohms	± 0.15%	1J25-W	1J25-X
3313.71 ohms	± 0.15%	1J25-X	1J25-Y
2541.88 ohms	± 0.15%	1J25-Y	1J25-Z
1960.82 ohms	± 0.15%	1J25-Z	1J25-a
1538.95 ohms	± 0.15%	1J25-a	1J25-b
1247.63 ohms	± 0.15%	1J25-b	1J25-c
1029.50 ohms	± 0.15%	1J25-c	1J25-d
862.94 ohms	± 0.15%	1J25-d	1J25-e
732.69 ohms	± 0.15%	1J25-e	1J25-f
487.84 ohms	± 0.15%	1J25-f	1J25-G"

Paragraph 3.5.11, Table IV, Line 4: Delete

"0 volts 9.0 volts RMS PiØ .000000 ± .0010"

Paragraph 3.5.12, Table V, Line 3: Delete

"1 ohm max. 1J26-Y 1J26-u" and substitute "1 ohm max. 1J23-B 1J26-U".

Paragraph 3.5.13: Delete "Boresight-Norman Circuitry" and substitute "Boresight-Normal Circuitry".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

Paragraph 3.5.13.1: Delete and substitute:

"3.5.13.1 Relay K_1.- A 1.0 volt RMS, 400 cycle signal shall be injected at the gunner's deflection channel $\emptyset_S$ x sin C jack, the gunner's elevation channel $\emptyset_S$ COS C jack, and 1J24-g. The signal shall be present at the amplifier input jacks when K_1 is de-energized, and the signal shall be removed from the amplifier input jacks when K_1 is energized. The signal shall be present at 1J26-y when K_1 is energized, and the signal shall be removed from 1J26-y when K_1 is de-energized."

Paragraph 4.1, first sentence: Delete "otherwixe" and substitute "otherwise".

Paragraph 4.2: Delete and substitute:

"4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) computer units. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.4.3: Delete and substitute:

"4.4.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the contractor and resubmitted items have been approved (see 4.3.3)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.2.1: Delete and substitute:

"4.5.2.1 Government design.- Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications of SQAP forming a part of the contract shall be supplied by the contractor in accordance with applicable technical data listed in the technical data package (TDP)."

Paragraph 4.5.3, Table XI, Item 6 Description:

Delete "±1.0%" and substitute "±3.0%".

Paragraph 4.6.3: Delete "Figure 4" and substitute "Figures 4 and 5".

Paragraph 4.6.9.3, first sentence: Delete "D&A" and substitute "Digital to Analog".

Paragraph 4.6.11, fourth sentence: Delete and substitute "Relay K_2 shall be energized by applying 21 VDC across terminals 1J26-Y and 1J27-C, terminal Y being positive with respect to C."

Paragraph 4.6.12.1: Delete and substitute:

"4.6.12.1 Relay K_1.- To determine conformance to 3.5.13.1, the signal specified shall be applied to the appropriate jacks and to 1J24-g, and relay K_1 energized and de-energized. The amplifier input jacks and 1J26-y shall be monitored for the presence or absence of signals as specified."

Paragraph 4.6.12.2, third sentence: Delete "1J26-Y" and substitute "1J26-y".

Paragraph 4.6.14, third sentence: Delete and substitute:

"Each rate input specified in Table VII shall be checked for gyro output voltage at 1J25-j which shall be as specified."

Figure 1: Delete "Figure 1" and substitute revised "Figure 1" (attached).

Figure 3: Delete "2N605" and substitute "2N2605".

Figure 4: Delete "Figure 4" and substitute revised "Figure 4" (attached).

Add new "Figure 5" (attached).

Custodian:
Army - MU

Preparing Activity:
Army - MU

Project No. 1220-A135

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.