MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, RIGHT ANGLE, HERMAPHRODITIC CONTACT, CRIMP REMOVABLE, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by the Communications Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-55302.




FIGURE 1. Connector, plug (.100 spacing).

Ⓓ denotes changes


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

INCHES	MM	INCHES	MM	INCHES	MM
.005	.13	.062	1.57	.246	6.25
.008	.20	.085	2.16	.270	6.86
.010	.25	.100	2.54	.312	7.92
.050	1.27	.120	3.05	.375	9.52
.059	1.50	.173	4.39	.470	11.94
				.520	13.21

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Unless otherwise specified, tolerance is ±.005 (.13 mm).
4. Contacts (class A per MIL-C-55302/97-01) are shipped loose in a plastic bag with each connector unless otherwise specified. When contacts are furnished separately, the letters "WO" shall appear immediately after the military part number marking on the connector (i.e., M55302/103-02 WO).
5. For direct government procurements connectors shall be furnished with contacts in a plastic bag with each connector.
6. Connectors are supplied with open eyelets (2), which are to be rolled over after assembly to printed wiring board.
7. With connectors fully engaged the mating contacts shall have a minimum overlap of .062. As a minimum the contacts shall exhibit a wiping action through this distance.

FIGURE 1. Connector, plug (.100 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Metric equivalents are in parentheses.

FIGURE 2. Detail of P.C. card showing typical plus hole pattern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number and dimensions.

Dash number 1/	No. of contacts	*Dimensions (inches) A	B ±.010	C Ref.	D
01	18	.850 (21.59)	1.150 (29.21)	1.290 (32.77)	1.150 (29.21)
02	30	1.450 (36.83)	1.750 (44.45)	1.890 (48.01)	1.750 (44.45)
03	36	1.750 (44.45)	2.050 (52.07)	2.190 (55.63)	2.050 (52.07)
04	42	2.050 (52.07)	2.350 (59.69)	2.490 (60.96)	2.350 (59.69)
05	54	2.650 (67.31)	2.950 (59.69)	3.090 (78.49)	2.950 (74.93)
06	72	3.550 (90.17)	3.850 (97.79)	3.990 (101.35)	3.850 (97.79)

1/ See requirements for complete part number when keying pin is required.

* Metrics equivalents are in parentheses.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figures 1 and 2, and table I.

Material and finish:

Insulator: MIL-M-14, type SDG-F.

End guides: Left hand, sintered brass 90/10, clear chromate per MIL-C-5541, class 1A. Right hand, sintered brass 90/10, nickel plate 300 microinches per MIL-F-14072.

Keying pin: Aluminum alloy 2011-T3 with clear chromate per MIL-C-5541, class 1A.

Contact identification: Contact locations are identified in numerical sequence (see figure 1).

Mating and unmating: The maximum insertion force, in pounds, shall not exceed a value equal to .5 times the number of contacts, and the withdrawal force, in pounds, shall be a minimum of .11 times the number of contacts and shall not exceed the measured insertion force.

Contact retention: 6.0 pounds minimum after five insertions and withdrawals from the same connector position.

Contact resistance: The contact resistance shall not exceed 20 milliohms.

Dry circuit: Connectors shall be tested in accordance with method 3002 of MIL-STD-1344. The contact resistance shall not exceed 20 milliohms.

Dielectric withstanding voltage:

Sea level: 1,000 volts rms, 60 hertz.

High altitude: 300 volts rms, 60 hertz.

Current rating, maximum: 5 amperes.

Keying: When required, one of the following codes shall be added to the dash number:

"P" - Specifying location by contact number where keying pin shall be inserted, for example, M55302/103-01P17. (Keying pin inserted in place of contact number 17.)

"H" - Specifying location by contact number where contact shall be omitted for mating; for example, M55302/103-01H17. (Keying pin hole has contact number 17 omitted.)

Contact, crimp removable (class A or B): Shall conform to MIL-C-55302/97.

Contact removal tool: Shall conform to MIL-I-81969/4.

Contact insertion tool: Shall conform to MIL-I-81969/5.

Contact crimp tool: Shall conform to MIL-C-55302/17-02.

Mating receptacle: Shall conform to MIL-C-55302/52, MIL-C-55302/99, or MIL-C-55302/102.

Part number: M55302/103-(dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR

Review activities:
Army - AT, AV, MI
DLA - ES

User activities:
Army - AR, ME

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 5935-A228-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in *submitting comments and suggestions for improvements.* All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

HQ, CECOM
ATTN: DRSEL-ED-TO
Ft Monmouth, N.J. 07703

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:50Z
Check the source to verify that this is the current version before use.