

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: 2-ROW RECEPTACLE ASSEMBLIES, RIGHT ANGLE, 20 THROUGH 150 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.100 SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-55302.






F ±.015		Type	Type of termination 1/
Inches	mm		
.180	4.57	I	Solder post
.165	4.19	II	Solder post
.140	3.56	III	Solder post
.120	3.05	IV	Solder post

1/ Solder post shall be a .036 (0.91 mm) maximum diameter or .036 (0.91 mm) maximum across the diagonal.

FIGURE 1. Connectors, receptacle assemblies .100 (2.54 mm) spacing 20 through 150 contacts.


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.



NOTES:
1. Torque wrench must be used when fastening connector to printed circuit board.
2. Length to be determined by user.

FIGURE 1. Connectors, receptacle assemblies .100 (2.54 mm) spacing, 20 through 150 contacts - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.




Recommended circuit layout

Inches	mm
.002	0.05
.005	0.13
.006	0.15
.010	0.25
.015	0.38
.042	1.07
.043	1.09
.050	1.27
.054	1.37
.070	1.78
.080	2.03
.100	2.54
.120	3.05
.170	4.32
.180	4.57
.182	4.62
.200	5.08
.219	5.54
.234	5.94
.260	6.60
.275	6.98
.604	15.34
.719	18.26
.746	18.95

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm) on decimals and ±2° on angles.
4. These connectors mate with connectors specified in MIL-C-55302/173 and /175.
5. Location indicators embossed on surface.
6. Numbers indicating end cavities, letters indicating row closest to polarizing feature, and markings every ten positions stamped on this surface.

FIGURE 1. Connectors, receptacle assemblies .100 (2.54 mm) spacing, 20 through 150 contacts - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.



DESIGN OF TINES OPTIONAL

Inches	mm
.020	0.51
.040	1.02

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 2. Contact plating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number, number of contacts, contact type, and dimensions.

Dash no.	No. of contacts	Contact type	A	B	C	D	E	Contact ident. no.
01 02 03 04	20	I II III IV	1.750 (44.45)	1.450 (36.83)	1.024 (26.01)	9	.900 (22.86)	1-10
05 06 07 08	30	I II III IV	2.250 (57.15)	1.950 (49.53)	1.524 (38.71)	14	1.400 (35.56)	1-15
09 10 11 12	40	I II III IV	2.750 (69.85)	2.450 (62.23)	2.024 (51.41)	19	1.900 (48.26)	1-20
13 14 15 16	50	I II III IV	3.250 (82.55)	2.950 (74.93)	2.524 (64.11)	24	2.400 (60.96)	1-25
17 18 19 20	56	I II III IV	3.550 (90.17)	3.250 (82.55)	2.824 (71.73)	27	2.700 (68.58)	1-28
21 22 23 24	60	I II III IV	3.750 (95.25)	3.450 (87.63)	3.024 (76.81)	29	2.900 (73.66)	1-30
25 26 27 28	70	I II III IV	4.250 (107.95)	3.950 (100.33)	3.524 (89.51)	34	3.400 (86.36)	1-35
29 30 31 32	80	I II III IV	4.750 (120.65)	4.450 (113.03)	4.024 (102.21)	39	3.900 (99.06)	1-40
33 34 35 36	90	I II III IV	5.250 (133.35)	4.950 (125.73)	4.524 (114.91)	44	4.400 (111.76)	1-45
37 38 39 40	100	I II III IV	5.750 (146.05)	5.450 (138.43)	5.024 (127.61)	49	4.900 (124.46)	1-50

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number, number of contacts, contact type, and dimensions - Continued.

Dash no.	No. of contacts	Contact type	A	B	C	D	E	Contact ident. no.
41 42 43 44	110	I II III IV	6.250 (158.75)	5.950 (151.13)	5.524 (140.31)	54	5.400 (137.16)	1-55
45 46 47 48	120	I II III IV	6.750 (171.45)	6.450 (163.83)	6.024 (153.01)	59	5.900 (149.86)	1-60
49 50 51 52	125	I II III IV	7.050 (179.07)	6.750 (171.45)	6.324 (160.63)	62	6.200 (157.48)	1-63
53 54 55 56	130	I II III IV	7.250 (184.15)	6.950 (176.53)	6.524 (165.71)	64	6.400 (162.56)	1-65
57 58 59 60	134	I II III IV	7.450 (189.23)	7.150 (181.61)	6.724 (170.79)	66	6.600 (167.64)	
61 62 63 64	140	I II III IV	7.750 (196.85)	7.450 (189.23)	7.024 (178.41)	69	6.900 (175.26)	1-70
65 66 67 68	150	I II III IV	8.250 (209.55)	7.950 (201.93)	7.524 (191.11)	74	7.400 (187.96)	1-75

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.

TABLE II. Contact plating requirements.

Type	Finish requirement
A	Overall contact finish: Shall be gold in accordance with MIL-C-55302.
B	Localized contact finish: Contact engagement area shall have a minimum plating (see figure 2) in accordance with MIL-C-55032. Solder post area (contact type I, .195 minimum length; type II, .180 minimum length; type III, .155 minimum length; type IV, .135 minimum length) shall be tin-lead over nickel in accordance with MIL-C-55302.
C	Overall contact finish: Shall be palladium or palladium nickel alloy (80/14 ±6 percent), 50 microinches minimum thickness, with a gold flash of 3 microinches minimum, over a nickel underplate of 50 microinches minimum in accordance with QQ-N-290, and shall meet the requirements of MIL-P-45209.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1 and table I.

Material: In accordance with MIL-C-55302.

Contacts: Shall be copper-beryllium in accordance with QQ-C-530 or QQ-C-533.

Plating: See table II and figure 2.

Current rating: 3.0 amperes maximum per contact, 2.25 amperes continuous per contact at room ambient with no more than two adjacent contacts carrying this current.

Keying (see MIL-C-55302/31):

Two keys, part number MS55302/31-04, and two retaining rivets, part number M55302/31-05, are recommended. Keys and rivets shall be ordered separately.

Jackscrews (see MIL-C-55302/182):

Use M55302/182-08 or -10. Jackscrews are purchased separately.

Mating and unmating: The maximum mating force in pounds shall be the number of contacts multiplied by .094; the withdrawal force in pounds shall be a minimum of .025 times the number of contacts and shall not exceed the measured insertion force.

Contact resistance: No individual contact pair shall have a resistance exceeding .015 ohm initial and .020 ohm after testing.

Contact retention: 3 pounds, minimum.

Dielectric withstanding voltage:

Sea level: 900 volts rms.

70,000 feet: 200 volts rms.

2 milliamperes maximum leakage current.

Part number: M55302/174 (and dash number from table I and type from table II.

Example: M55302/174-01A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 17

Review activities:
Army - AR
Navy - AS, OS, SH
Air Force - 11, 85, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - MC
Air Force - 19

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5935-3542-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:55Z
Check the source to verify that this is the current version before use.