INCH-POUND

MIL-F-60044A (AR)
AMENDMENT 3
16 June 1993
SUPERSEDING
AMENDMENT 2
25 May 1979

MILITARY SPECIFICATION

FUZE, BASE DETONATING, M62A2
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-F-60044A (AR), dated 09 October 1968, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

* Denotes change from previous amendment.

PAGE 1

Paragraph 2, Specifications.

Military, add the following:

"MIL-C-45467 - Cartridge 165MM, HEP, M123A1 Loading, Assembling and Packing"

PAGE 3

Paragraph 3.9, Delete in its entirety and substitute:

"3.9, Static functioning. The fuze shall function high order as evidenced by a minimum depth depression of 0.115 inches in a steel plate when tested as specified in 4.3.7"

Add the following:

"3.9.1, First Article Inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract."

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

PAGE 4

Add the following:

"4.1.2, First Article Inspection

4.1.2.1, Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of paragraphs 4.2 and 4.3.

4.1.2.2, The First Article sample shall consist of twenty-five (25) each of all partial assemblies and twenty-five (25) assembled fuzes which shall be inspected in accordance with the applicable provision as specified in 4.2.2.

4.1.2.3, The First Article sample shall consist of one hundred ninety-five (195) assembled fuzes for use in performing the following tests.

a. Twenty-five (25) fuzes shall be tested ballistically against armor plate as specified in MIL-C-45467.

b. Twelve (12) fuzes shall be subjected to the jolt and jumble test specified in 4.3.3.

c. Eight (8) fuzes shall be subjected to the transportation vibration test as specified in 4.3.4.

d. One hundred twenty-five (125) fuzes shall be tested for functioning in accordance with 4.3.5.

e. Twenty-five (25) fuzes shall be tested for static functioning as specified in 4.3.7."

PAGE 6

4.2.2.4, Major 101, Delete the word "Concentricity" and substitute the words "True Position".

* 4.2.2.4, Major 101, delete in its entirety and substitute: "Perpendicularity of outside diameter to shoulder ...Gage ...04012."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

PAGE 7

4.2.2.5, Delete all Majors in their entirety and substitute:

"Major

101	Fuze not packed with Booster down	Visual	05009
102	Sealing Strip incomplete or badly wrinkled	Visual	05010
103	Bag torn or damaged	Visual	05011
104	Failure of Heat Seal Test	Manual/ Visual	05012"

PAGE 8

4.2.3.4.1, Delete in its entirety.

4.2.3.4.2, Delete in its entirety and substitute:

"A sample of fifty (50) fuze assemblies shall be selected from each production lot for this test in accordance with paragraph 4.3.5. If there are any premature bursts or if three (3) or more assemblies fail to function high order the lot shall be rejected."

PAGE 9

4.2.3.7, Delete the first sentence and substitute the following:

"A sample of fifteen (15) fuzes shall be randomly selected from each lot for this test subsequent to completion of the slider non-arming test. The test shall be performed as specified in 4.3.7, using test equipment specified in 4.2.4."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

4.3.7, Delete in its entirety and substitute the following:

"4.3.7, Static functioning. The slider shall be armed by inserting a plug into the slider cavity in the fuze body and reassembling the slider, slider spring and retaining screw. The firing pin assembly shall be removed and replaced by a firing pin guide plug. A hole shall be drilled through the fuze head in line with the hole in the firing pin guide plug and detonator holder to receive the firing pin. The modified fuze assembly shall be mounted in a suitable fixture with the booster end down. The firing pin, which has been equipped with a rubber 0-ring to prevent inserting it too far into the head assembly shall be placed booster end down upon a steel plate (approximately 14" x 18" x 2" in accordance with ASTM 836, Rockwell B60-80. The operator then returns to the test building and removes safety pin from the test arm, pulls the cord connecting the test arm which then falls and depresses the firing pin into the detonator. If the fuze fails to function all personnel will wait behind the barricade for a period of 30 minutes minimum prior to returning to the test sample. The fuze shall then be destroyed in place (in accordance with local safety regulations) by means of a demolition charge, taking extreme care when placing the charge, not to disturb the fuze in any way. Any fuze which fails to function high order shall be cause for rejection.

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A255)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.