INCH-POUND
MIL-PRF-55365/4F
28 February 2003
SUPERSEDING
MIL-PRF-55365/4E
3 July 1997

PERFORMANCE SPECIFICATION SHEET

* CAPACITORS, CHIP, FIXED, TANTALUM, POLARIZED
ESTABLISHED RELIABILITY AND NONESTABLISHED RELIABILITY,
STYLES CWR06 AND CWR09

This specification is approved for use by all Departments
and Agencies of the Department of Defense

The requirements for acquiring the product described herein
shall consist of this specification and MIL-PRF-55365.




FIGURE 1. Style CWR06 (conformally coated) capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.


Case size	L ± .015 (0.38)	W ±.015 (0.38)	H ±.015 (0.38)	P ±.005 (0.13)
A	.100 (2.54)	.050 (1.27)	.050 (1.27)	.030 (0.76)
B	.150 (3.81)	.050 (1.27)	.050 (1.27)	.030 (0.76)
C	.200 (5.08)	.050 (1.27)	.050 (1.27)	.030 (0.76)
D	.150 (3.81)	.100 (2.54)	.050 (1.27)	.030 (0.76)
E	.200 (5.08)	.100 (2.54)	.050 (1.27)	.030 (0.76)
F	.220 (5.59)	.135 (3.43)	.070 (1.78)	.030 (0.76)
G	.265 (6.73)	.110 (2.79)	.110 (2.79)	.050 (1.27)
H	.285 (7.24)	.150 (3.81)	.110 (2.79)	.050 (1.27)
X	.273 (6.93)	.213 (5.41)	.108 (2.74)	.047 (1.19)

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.
4. These capacitors are designed for mounting by dip soldering, thermo-compression bonding, reflow soldering, or other conventional means.
5. Cathode terminal may be epoxy coated on one surface for polarity identification.
6. Solderable surfaces are only those surfaces designated as such.
7. Anode and cathode terminals may be two-sided through five-sided, and may not be the same on some designs, but will meet all specification requirements.
8. The anode terminal shall be identified by the riser wire connection, which may extend the case size .015 (0.38 mm) maximum. The riser wire weld area is not solderable. The riser wire connection shall have a continuous weld of a minimum of 25 percent of the contact surface.
9. When solder coated terminations are required, add an additional .015 (0.38 mm) to the above listed tolerances for “L”, “W”, “H”, and “P” for each case size.

FIGURE 1. Style CWR06 (conformally coated) capacitors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.



*

Case size	L ± .015 (0.38)	W ±.015 (0.38)	H ±.015 (0.38)	P +.010 (0.25) - .005 (0.13)	W_2	H_2 min
A	.100 (2.54)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 ±.005 (1.27±.013)	.030 (0.76)
B	.150 (3.81)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 ±.005 (1.27±.013)	.030 (0.76)
C	.200 (5.08)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 ±.005 (1.27±.013)	.030 (0.76)
D	.150 (3.81)	.100 (2.54)	.050 (1.27)	.030 (0.76)	.095+.005,-.010 (2.41+0.13, -0.25)	.030 (0.76)
E	.200 (5.08)	.100 (2.54)	.050 (1.27)	.030 (0.76)	.095+.005,-.010 (2.41+0.13, -0.25)	.030 (0.76)
F	.220 (5.59)	.135 (3.43)	.070 (1.78)	.030 (0.76)	.130±.005 (3.30±0.13)	.040 (1.02)
G	.265 (6.73)	.110 (2.79)	.110 (2.79)	.050 (1.27)	.105±.005 (2.67±0.13)	.060 (1.52)
H	.285 (7.24)	.150 (3.81)	.110 (2.79)	.050 (1.27)	.145+.005. -.020 (3.68 +0.13, -0.51)	.060 (1.52)

FIGURE 2. Style CWR09 molded chip.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.
4. These capacitors are designed for mounting by dip soldering, thermo-compression bonding, reflow soldering, or other conventional means.
5. The anode (+) terminal shall be identified by a marking on the case.
6. The termination width (W_2) shall be maintained to the top of the solderable area.
7. Solderable surfaces are only those surfaces designated as such. Termination edges are not considered solderable.
* 8. When solder coated terminations are required, add an additional .015 inch (0.38 mm) to the above listed tolerances for “L”, “W”, “H”, “P”, “W_2”, and H_2 for each case size.

FIGURE 2. Style CWR09 molded chip – Continued

REQUIREMENTS:

Dimensions and configuration: See figures 1 and 2.

Termination finish: In accordance with termination finishes B, C, H, or K of MIL-PRF-55365.

DC rated voltage: See table I. Above +85°C, voltage derating is required (see MIL-PRF-55365).

Operating temperature range: -55°C to +125°C.

Product level designator: In accordance with MIL-PRF-55365.

DC leakage (DCL): See table I.

Capacitance: See table I.

Capacitance tolerance: ±5 percent (J), ±10 percent (K), or ±20 percent (M).

Dissipation factor (DF): See table I.

Equivalent series resistance (ESR) at 100 kHz: In accordance with MIL-PRF-55365 (see table I).

Resistance to soldering heat: In accordance with MIL-PRF-55365.

Stability at low and high temperatures: In accordance with MIL-PRF-55365.

Step 1 (+25°C):	DCL	- See table I.
	Capacitance	- Shall not exceed tolerance of table I value.
	DF	- See table I.
Step 2 (-55°C):	ΔCapacitance	- Shall not exceed ±10 percent of initial measurement.
	DF	- See table I.
Step 3 (+25°C):	DCL	- See table I.
	ΔCapacitance	- Shall not exceed ±5 percent of initial +25°C measurement.
	DF	- See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Step 4 (+85°C):	DCL	-	See table I.
	ΔCapacitance	-	Shall not exceed ±10 percent of initial +25°C measurement.
	DF	-	See table I.
Step 5 (+125°C):	DCL	-	See table I.
	ΔCapacitance	-	Shall not exceed ±15 percent of initial +25°C measurement.
	DF	-	See table I.
Step 6 (+25°C):	DCL	-	See table I.
	ΔCapacitance	-	Shall not exceed ±5 percent of initial +25°C measurement.
	DF	-	See table I.

Surge voltage: In accordance with MIL-PRF-55365.

DCL	-	See table I.
ΔCapacitance	-	Within ±5 percent of initial value.
DF	-	See table I.

Life: Method 108 of MIL-STD-202.

2,000 hours:

At 25°C:	DCL	-	See table I.
	ΔCapacitance	-	Shall not exceed ±5 percent of initial measured value.
	DF	-	See table I.
At 85°C:	DCL	-	See table I.
At 125°C:	DCL	-	See table I.

10,000 hours:

At 25°C:	DCL	-	200 percent of initial requirement.
	ΔCapacitance	-	Shall not exceed ±5 percent of initial measured value.
	DF	-	See table I.
At 85°C:	DCL	-	200 percent of initial requirement.
At 125°C:	DCL	-	200 percent of initial requirement.

* Solderability will be in accordance with MIL-PRF-55365 except that following steam aging, test samples may have a 30 minute bake out at 150°C prior to solder dipping.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

*

TABLE I. Styles CWR06 and CWR09 characteristics.

Part or identifying number (PIN) 1/ 2/	DC rated voltage (+85°C)	Cap. (nom)	DC Leakage (max)			Dissipation factor (max)			Max ESR 100 kHz +25°C Style CWR06	Max ESR 100 kHz +25°C Style CWR09	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C			
	Volts	µF	µA	µA	µA	%	%	%	Ohms	Ohms	
CWR0-C-225---	4	2.2	1.0	10	12	6	8	8	8.0	8.0	A
CWR0-C-475---	4	4.7	1.0	10	12	6	8	8	8.0	8.0	B
CWR0-C-685---	4	6.8	1.0	10	12	6	8	8	5.5	5.5	C
CWR0-C-106---	4	10.0	1.0	10	12	8	8	10	4.0	4.0	D
CWR0-C-156---	4	15.0	1.0	10	12	8	10	12	3.5	3.5	E
CWR0-C-336---	4	33.0	2.0	20	24	8	10	12	2.2	2.2	F
CWR0-C-686---	4	68.0	3.0	30	36	10	12	12	1.1	1.1	G
CWR0-C-107---	4	100.0	4.0	40	48	10	12	12	.9	.9	H
CWR0-D-155---	6	1.5	1.0	10	12	6	8	8	8.0	8.0	A
CWR0-D-335---	6	3.3	1.0	10	12	6	8	8	8.0	8.0	B
CWR0-D-475---	6	4.7	1.0	10	12	6	8	8	5.5	5.5	C
CWR0-D-685---	6	6.8	1.0	10	12	6	8	8	4.5	4.5	D
CWR0-D-106---	6	10.0	1.0	10	12	8	10	12	3.5	3.5	E
CWR0-D-226---	6	22.0	2.0	20	24	8	10	12	2.2	2.2	F
CWR0-D-476---	6	47.0	3.0	30	36	10	12	12	1.1	1.1	G
CWR0-D-686---	6	68.0	4.0	40	48	10	12	12	.9	.9	H
CWR0-F-105---	10	1.0	1.0	10	12	6	8	8	12.0	10.0	A
CWR0-F-225---	10	2.2	1.0	10	12	6	8	8	8.0	8.0	B
CWR0-F-335---	10	3.3	1.0	10	12	6	8	8	5.5	5.5	C
CWR0-F-475---	10	4.7	1.0	10	12	6	8	8	4.5	4.5	D
CWR0-F-685---	10	6.8	1.0	10	12	6	8	8	3.5	3.5	E
CWR0-F-156---	10	15.0	2.0	20	24	8	8	10	2.5	2.5	F
CWR0-F-336---	10	33.0	3.0	30	36	10	12	12	1.1	1.1	G
CWR0-F-476---	10	47.0	5.0	50	60	10	12	12	.9	.9	H
CWR0-H-684---	15	.68	1.0	10	12	6	8	8	12.0	12.0	A
CWR0-H-155---	15	1.5	1.0	10	12	6	8	8	8.0	8.0	B
CWR0-H-225---	15	2.2	1.0	10	12	6	8	8	5.5	5.5	C
CWR0-H-335---	15	3.3	1.0	10	12	6	8	8	5.0	5.0	D
CWR0-H-475---	15	4.7	1.0	10	12	6	8	8	4.0	4.0	E
CWR0-H-106---	15	10.0	2.0	20	24	6	8	8	2.5	2.5	F
CWR0-H-226---	15	22.0	4.0	40	48	6	8	8	1.1	1.1	G
CWR0-H-336---	15	33.0	5.0	50	60	8	8	10	.9	.9	H
CWR0-J-474---	20	.47	1.0	10	12	8	8	10	16.0	14.0	A
CWR0-J-684---	20	.68	1.0	10	12	6	8	8	14.0	10.0	B

See footnotes at the end of table

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

* TABLE I. Styles CWR06 and CWR09 characteristics - Continued.

PIN 1/ 2/	DC rated voltage (+85°C)	Cap. (nom)	DC Leakage (max)			Dissipation factor (max)			Max ESR 100 kHz +25°C Style CWR06	Max ESR 100 kHz +25°C Style CWR09	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C			
	Volts	µF	µA	µA	µA	%	%	%	Ohms	Ohms	
CWR0-J-105---	20	1.0	1.0	10	12	6	8	8	12.0	12.0	B
CWR0-J-155---	20	1.5	1.0	10	12	6	8	8	6.0	6.0	C
CWR0-J-225---	20	2.2	1.0	10	12	6	8	8	5.0	5.0	D
CWR0-J-335---	20	3.3	1.0	10	12	6	8	8	4.0	4.0	E
CWR0-J-685---	20	6.8	2.0	20	24	6	8	8	2.4	2.4	F
CWR0-J-156---	20	15.0	3.0	30	36	6	8	8	1.1	1.1	G
CWR0-J-226---	20	22.0	4.0	40	48	6	8	8	.9	.9	H
CWR0-K-334---	25	.33	1.0	10	12	6	8	8	15.0	15.0	A
CWR0-K-684---	25	.68	1.0	10	12	6	8	8	10.0	7.5	B
CWR0-K-105---	25	1.0	1.0	10	12	6	8	8	6.5	6.5	C
CWR0-K-155---	25	1.5	1.0	10	12	6	8	8	6.5	6.5	D
CWR0-K-225---	25	2.2	1.0	10	12	6	8	8	3.5	3.5	E
CWR0-K-475---	25	4.7	2.0	20	24	6	8	8	2.5	2.5	F
CWR0-K-685---	25	6.8	2.0	20	24	6	8	8	1.2	1.2	G
CWR0-K-106---	25	10.0	3.0	30	36	6	8	8	1.4	1.4	G
CWR0-K-156---	25	15.0	4.0	40	48	6	8	8	1.0	1.0	H
CWR0-M-224---	35	.22	1.0	10	12	6	8	8	24.0	18.0	A
CWR0-M-474---	35	.47	1.0	10	12	6	8	8	17.0	10.0	B
CWR0-M-684---	35	.68	1.0	10	12	6	8	8	10.0	8.0	C
CWR0-M-105---	35	1.0	1.0	10	12	6	8	8	6.5	6.5	D
CWR0-M-155---	35	1.5	1.0	10	12	6	8	8	4.5	4.5	E
CWR0-M-335---	35	3.3	1.0	10	12	6	8	8	2.5	2.5	F
CWR0-M-475---	35	4.7	2.0	20	24	6	8	8	1.5	1.5	G
CWR0-M-685---	35	6.8	3.0	30	36	6	8	8	1.3	1.3	H
CWR0-N-104---	50	.10	1.0	10	12	6	8	8	75.0	22.0	A
CWR0-N-154---	50	.15	1.0	10	12	6	8	8	25.0	17.0	A
CWR0-N-224---	50	.22	1.0	10	12	6	8	8	17.0	14.0	B
CWR0-N-334---	50	.33	1.0	10	12	6	8	8	12.0	12.0	B
CWR0-N-474---	50	.47	1.0	10	12	6	8	8	8.0	8.0	C
CWR0-N-684---	50	.68	1.0	10	12	6	8	8	7.0	7.0	D
CWR0-N-105---	50	1.0	1.0	10	12	6	8	8	6.0	6.0	E
CWR0-N-155---	50	1.5	1.0	10	12	6	8	8	4.0	4.0	F
CWR0-N-225---	50	2.2	2.0	20	24	6	8	8	2.5	2.5	F
CWR0-N-335---	50	3.3	2.0	20	24	6	8	8	2.0	2.0	G
CWR0-N-475---	50	4.7	3.0	30	36	6	8	8	1.5	1.5	H

1/ Complete PIN shall include additional symbols to indicate style, termination finish, capacitance tolerance, product level designator, and, if applicable, surge current option letter. If optional surge current is not required, the last "-" shall be deleted.

2/ Styles CWR06 and CWR09 are, with the acquiring agency approval, considered to be interchangeable, provided the size, capacitance, capacitance tolerance, failure rate level, rated voltage, maximum ESR value, and surge current option (if applicable) remain the same.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA - NA

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2184-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.