INCH-POUND

MIL-T-50595C(AR)
AMENDMENT 2
24 September 1992
SUPERSEDING
AMENDMENT 1
09 October 1987

MILITARY SPECIFICATION

TRIPOD ASSEMBLY, DEMOLITION KIT, M180,
METAL PARTS FOR AND ASSEMBLY

This amendment forms a part of MIL-T-50595C (AR), dated 01 March 1979, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 5

Table I: Change "M57 Firing Device, Modified (Dwg. 9244458)" to "Firing Device, Antipersonnel Mine, Electrical M57 (Dwg. 8800924)".

Add the following to Table I:

"Cover, Protective (Dwg. 12598668)

Examination for Defect	10	100%	3.1	4.4.2.13A"

* Delete references to "Firing Device, Antipersonnel Mine, Electrical M57" and "Cover, Protective" in their entirety.

PAGE 6

* TABLE I: Change "Strap Assembly" to "Strap Assembly, Tripod".

* Add the following to Table I:

"Strap Assembly, Tripod (Alternate) (Dwg. 9270969)

Examination for defects	10	100%	3.1	4.4.2.20A
Yield Strength	(a)	100%	3.1	4.5.2
Salt Spray Test	(a)	100%	3.1	4.5.3"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

PAGE 20

4.4.2.13: Change TITLE to "Firing Device, Antipersonnel Mine, Electrical M57"

Change DRAWING NUMBER to "8800924"

Under "Critical" Change "1 Safety pin missing or loose 100% 3.1 Visual" to "None defined".

* Delete in its entirety.

PAGE 20A

4.4.2.13A: Add new 4.4.2.13A included.

* Delete in its entirety

PAGE 27

* 4.4.2.20: Change TITLE to "Strap Assembly, Tripod"

PAGE 27A

* 4.4.20A: Add new 4.4.2.20A included.

PAGE 29

4.4.2.22: Add the following under "Critical":

"1 M57 Protective Cover missing 100% 3.1 Visual"

Add the following under "Major"

"109 Bail visible (1) 100% 3.1 Visual"

Add the following under NOTES:

"(1) If bail is visible, the protective cover should be removed, the bail placed in the safe/vertical position and the cover reinstalled."

* Delete "Critical Defect 1", "Major Defect 109", and "NOTE 1" in their entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13A	Cover, Protective	1 OF 1	12598668
			NEXT HIGHER ASSEMBLY: 9244403

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest height		0.40%	3.1	Gage
102	Top width		0.40%	3.1	Gage
103	Angle between top and largest height		0.40%	3.1	Gage
104	Angle between top and slanted side		0.40%	3.1	Gage
105	Height from top to bottom of rivet tabs		0.40%	3.1	Gage
106	Height of top lip		0.40%	3.1	Gage
107	True position of bolt slots		0.40%	3.1	Gage
108	True position of rivet holes		0.40%	3.1	Gage
109	Inside depth		0.40%	3.1	Gage
110	Material thickness		0.40%	3.1	Gage
111	Presence of rivets		0.40%	3.1	Visual
112	Markings present & properly located		0.40%	3.1	Visual
Minor					
201	Protective finish missing or incomplete		0.65%	3.1	Visual
202	Poor workmanship		1.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.20A	Strap Assembly, Tripod (Alternate)	1	1	9270969
				NEXT HIGHER ASSEMBLY 9244434

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Part missing		0.40%	3.1	Visual
102	Part damaged (Cracked or deformed)		0.40%	3.1	Visual
103	Spot weld missing or defective (material separating, etc.)		0.40%	3.1	Visual
104	Yield strength	4.5.2	-	3.1	4.5.2
Minor					
201	Large inside radius		0.65%	3.1	Gage
202	Inside length (2 places)		0.65%	3.1	Gage
203	Inside diameter of loop (2 places)		0.65%	3.1	Gage
204	Width of strap (2 places)		0.65%	3.1	Gage
205	Inside length between loops		0.65%	3.1	Gage
206	Length of strap overlap		0.65%	3.1	Gage
207	Bolt threads damaged		0.65%	3.1	Visual
208	Poor workmanship		1.00%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

* 4.5.2: Delete the following:

"Yield strength of strap assembly (Dwg. 9329696) major defect. Ten(10) assemblies shall be selected from each lot for this test.

And replace with:

"Yield strength. Ten(10) strap assemblies (Dwg. 9329696) or twenty (20) alternate strap assemblies (Dwg. 9270969) shall be selected from each lot for this test."

4.5.4: Change "(Dwg. 9244458)" to "(Dwg. 8800924)"

* Delete in its entirety.

The margins of this amendment are marked with an ansterisk or vertical lines to indicate where changes (additions, modification, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A489)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.