NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/259C(IH)
10 July 2025
SUPERSEDING
MIL-DTL-11484/259B(IH)
8 September 2020

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, CHAIRMAN'S AWARD, CHEMICAL SAFETY AND HAZARD INVESTIGATION BOARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
STAR BURST: Silver Plated, Oxidized, Relived, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 15.
SEAL (Including outside rim): 24K Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER (Circumscribed point to point): 3/4 inch (REF)
THICKNESS (Overall): 0.077 inch ± 0.005 inch

ATACHING DEVICE:
1. Attaching device shall be prong with pick and flat ball type clutches.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTE:

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:40Z
Check the source to verify that this is the current version before use.

The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2025-192)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:40Z
Check the source to verify that this is the current version before use.