INCH-POUND

MIL-DTL-11484/266
2 June 2000

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, KOSOVO CAMPAIGN

Inactive for new design after 2 June 2000.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Gilding Metal

FINISH: Hard Enameled, Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip number 6.

DIMENSIONS:
HEIGHT (overall): 9/64 inch (REF)
WIDTH (overall): 21/32 inch (REF)
THICKNESS (at edge): 0.065 inch ± 0.005 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The colors shall conform to TIOH Hard Enamel Color Chip numbers listed below:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:42Z
Check the source to verify that this is the current version before use.

COLOR	CHIP NO
Red	1
Ultramarine Blue	18
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used, the material requirement shall be gilding metal or red brass.

4. Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
DLA - CT

(Project No. 8455-0016)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:42Z
Check the source to verify that this is the current version before use.