INCH-POUND

MIL-DTL-11484/267A
24 November 2015
SUPERSEDING
MIL-DTL-11484/267
16 August 2000

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, JOINT CIVILIAN SERVICE COMMENDATION AWARD, CHAIRMAN OF THE JOINT CHIEFS OF STAFF

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.

MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230) or Nickel Silver 65/35 (UNS Alloy No. C-752)

FINISH: Nickel Plated (C-230 only) Silver Plated, Oxidized, Relieved, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 15.

DIMENSIONS:
HEIGHT: 5/8 inch (REF)
WIDTH: 5/8 (REF)
THICKNESS (At thickest point): 0.090 inch ± 0.005 inch

ATACHING DEVICE:
1. Attaching device shall be prong with pick and flat ball type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:42Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2016-028)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:42Z
Check the source to verify that this is the current version before use.