INCH-POUND
MIL-PRF-39007/12E
3 July 1997
SUPERSEDING
MIL-R-39007/12D
20 February 1990

PERFORMANCE SPECIFICATION

RESISTOR, FIXED, WIRE-WOUND (POWER TYPE), NONESTABLISHED RELIABILITY, ESTABLISHED RELIABILITY, AND SPACE LEVEL STYLE RWR82

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the associated requirements for style RWR82, nonestablished reliability, established reliability, and space level, power type, wire-wound, fixed resistor. These resistors are available with terminal types "S" (solderable, inductively wound), "W" (weldable, inductively wound), "N" (solderable, noninductively wound), and "Z" (weldable, noninductively wound).

1.2 Part or Identifying Number (PIN). Resistors covered by this specification are identified by a PIN which consists of the style designation, terminal and winding, coded resistive value, tolerance, and product level designator. The PIN is derived in accordance with MIL-PRF-39007 and is in the following form:

RWR82	S	1000	F	S
Style	Terminal wire and winding	Coded resistance	Resistance tolerance	Product level designator

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Communications - Electronics Command, ATTN: AMSEL-LC-LEO-E-EP, Fort Monmouth, NJ 07703-5023 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5905
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:26Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in section 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document user are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-39007 - Resistors, Fixed, Wire-Wound (Power Type), NonEstablished Reliability, Established Reliability, and Space Level, General Specification for.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Defense Printing Service Detachment Office, Building 4D, Customer Service, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-39007.

3.2 Interface and physical dimension. The resistor shall meet the interface and physical dimensions specified on figure 1.

3.2.1 Noninductive windings. Noninductively wound resistors shall be identified by terminal designation N to indicate a solderable terminal and Z to indicate a weldable terminal.

3.3 Minimum resistance value for all terminations (S, W, N, Z). For inductively wound resistors and noninductively wound resistors, the minimum resistance value shall be 0.1 ohm. For resistance tolerance B (.1 percent), minimum resistance value shall be .499 ohm.

3.4 Maximum resistance value for S and W type resistors. For resistors having inductive characteristic S and W designator, the maximum resistance shall be 1,300 ohms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:26Z
Check the source to verify that this is the current version before use.

3.4.1 Maximum resistance value for N and Z type resistors. For resistors having noninductive characteristic N and Z designation, the maximum resistance value shall be 649 ohms.

3.5 Power rating. The power rating shall be 1.5 watts at +25°C.

3.6 Weight. The maximum weight shall be .00662 pound (3 grams).

3.7 Terminal lead types. This style resistor is available in both solderable (S) and weldable (W) leads.

3.8 Marking. Due to size limitation, this style resistor shall be marked with the minimum marking as specified.

W82S: Partial style and terminal designator.

49R9: Resistance.

FMJ: Tolerance, failure rate, JAN marking.

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-39007.

4.2 Short-time overload. The duration of applied voltage shall be 5 seconds. Voltage applied shall be equivalent to 5 times rated wattage.

4.3 Dielectric withstanding voltage.

4.3.1 Atmospheric pressure. The magnitude of test voltage shall be 500 volts rms.

4.3.2 Barometric pressure (reduced). The test voltage shall be 100 volts rms.

4.4 Terminal strength. The applied force shall be 5 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:26Z
Check the source to verify that this is the current version before use.



Inches	mm
.002	0.05
.016	0.41
.020	0.51
.031	0.79
.062	1.57
.078	1.98
.312	7.92
1.500	38.10

Standard style	Dimensions			
	A +.016, -.031	B min	C ±.002	D ±.016
RWR82	.312	1.500	.020	.085

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Dimension A is clean lead to clean lead.
4. Lead length for tape and reel packaging shall be 1 inch minimum.
5. Lead concentric tolerance is to be measured at the point of lead egress from the resistor body to be within .016 TIR.

FIGURE 1. Style RWR82 resistor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:26Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-PRF-39007 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, date of the specification, and complete PIN.

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

c. Packaging requirements (see 5.1).

6.3 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - AS, CG, MC, OS
Air Force - 17, 19, 80

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5905-1440-09)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:26Z
Check the source to verify that this is the current version before use.