[INCH-POUND]

MIL-R-39007/6F
AMENDMENT 1
4 October 1990

MILITARY SPECIFICATION

RESISTOR, FIXED, WIRE-WOUND (POWER TYPE),
ESTABLISHED RELIABILITY
STYLE RWR74

This amendment forms a part of MIL-R-39007/6F, dated 20 February 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, third line following "(solderable, inductively wound)": Add "and terminal "N" (solderable, noninductively wound)".

PAGE 2

3.3, delete first sentence and substitute:

"For inductively wound and noninductively wound resistors, the minimum resistance value shall be 0.1 ohm."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR
Navy - AS, OS
Air Force - 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - CG, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1238)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:23Z
Check the source to verify that this is the current version before use.