MILITARY SPECIFICATION

COMPRESSORS, RECIPROCATING, ROTARY AND DIAPHRAGM POWER DRIVEN, AIR, (PAINT SPRAY TYPE)

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers portable, single and multistage air compressors driven either by a gasoline engine or an electric motor.

1.2 Classification. The compressors shall be of the following types, styles, groups, and sizes, as specified (see 6.2):

Type I - Reciprocating.
Type II - Rotary.
Type III - Diaphragm.

Style A - Electric-motor-driven.
Style B - Gasoline-engine-driven.

Group A - Single stage.
Group B - Multistage.

Size 1 - 1.5 cubic feet per minute (cfm), 40 pound-force per square inch (psi).
Size 1A - 2.7 cfm, 80 psi.
Size 1B - 6 cfm, 40 psi.
Size 2 - 15 cfm, 80 psi.
Size 3 - 30 cfm, 80 psi.
Size 4 - 75 cfm, 80 psi.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-C-3600 - Compressors, Rotary, Power Driven; and Compressors, Reciprocating, Power Driven: Air and Gas (except Oxygen and Refrigerant), Packaging of.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF LABOR
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402).

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as Department of Defense adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code Section VIII - Pressure Vessels, Division 1.
Performance Test Code, PTC 9 - Displacement Compressors, Vacuum Pumps and Blowers.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

ICS 70 - Industrial Controls and Systems.
WD 1 - General Purpose Wiring Devices.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

No. 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096).

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The compressors shall include controls and accessories as specified herein. Each unit shall be mounted on a frame that shall support the entire assembly without permanent deformation. The unit shall be furnished, ready for service, shall be equipped with a suitable driver as specified herein, and shall be readily portable. Each compressor shall be rated in accordance with the provisions of ASME PTC 9.

3.1.1 Standard commercial product. The compressors shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the compressors being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.2 First article. When specified (see 6.2), the contractor shall furnish a compressor for first article inspection and approval (see 4.2.1 and 6.4).

3.3 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using

Source: https://assist.dla.mil -- Downloaded: 202640-16T22:12Z
Check the source to verify that this is the currentversion before use.

materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.4 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5 Design. Each compressor shall be designed to provide the rated capacity at the specified pressure in accordance with the requirements of 3.6. Air receivers shall be designed and constructed in accordance with the ASME Code for Pressure Vessels. Controls and motors shall be NEMA rated and installed in accordance with NFPA No. 70. Engines and alternating current motors, shall be in accordance with the referenced specifications. The compressor design shall be such as to prevent conditions hazardous to personnel or deleterious to equipment. The compressor unit shall be readily accessible for maintenance and service in the field. The compressor shall be mounted on an unified skid base arranged for easy portability. When specified (see 6.2), the unit shall be wheel-mounted on a two-wheel, rubber-tired cart or have a wheelbarrow-type mounting. Size 1, 1A, and 1B units shall be base mounted and provided with carrying handles when wheel mounting and receivers are not specified. The compressor shall comply with OSHA regulations in effect at the time of manufacture.

3.6 Performance. The compressor unit shall be capable of compressing and delivering not less than the applicable volume of free air specified in table I at the specified receiver pressure. The compressors shall be designed to produce at least the working pressure specified in table I.

TABLE I. Compressor performance.

Size	Free air, cfm	Discharge pressure, psig	Compressor working pressure psig
1	1.5	40	80
1A	2.7	80	100
1B	6	40	100
2	15	80	100
3	30	80	100
4	75	80	100

3.7 Construction. Compressor units shall be constructed to withstand strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service. Exposed, electrically-energized compressor parts shall be insulated. When specified (see 6.2), size 1 compressor shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

direct coupled drive. Moving parts or parts subject to high operating temperatures and located so as to be hazardous to operating personnel, shall be fully enclosed or properly guarded. Protective devices shall not impair operating functions. Cover plates for access openings shall be oiltight and dusttight. When specified (see 6.2), the compressor shall be explosion proof.

3.7.1 Type I. Type I compressors shall be the reciprocating type, air-cooled, single-stage for the size 1, 1A, and size 1B units and either single-stage or multistage at the option of the manufacturer for sizes 2, 3, and 4, unless otherwise specified in the contract (see 6.2). The multistage compressor shall have a relief valve installed between the stages to prevent excessive pressure in the low-pressure cylinder. An intercooler shall also be installed between stages. The compressor air intake shall be fitted with an air filter, sized to prevent excessive restriction of the airflow. The filter shall be of the oil-wetted type or a dry type having equivalent efficiency and shall be removable for cleaning or replacement.

3.7.1.1 Bearings. Compressor bearings shall be of the precision insert type, or antifriction ball or roller type.

3.7.2 Type II. The type II compressors shall be of the rotary, single or multistage positive displacement, air-cooled type. Means shall be provided to remove and recover the oil from the discharge air. When a filter-type separator is used, it shall be accessible for examination, cleaning, or replacement without removal of other parts or components. Means shall also be provided in the stator assembly to allow accumulated oil to pass directly into the sump upon starting, thereby avoiding a hydraulic lock. The rotors, stators, and blades shall be interchangeable for each size compressor. A means shall be furnished to prevent reverse flow of air from the receiver when the compressor is stopped. The compressor shall not exceed the manufacturer's recommended continuous operating speed.

3.7.3 Type III. The type III compressors shall be of the diaphragm, single-stage, air-cooled type.

3.8 Controls. Motor control equipment shall conform to NEMA ICS 70. The control equipment shall be designed to protect the motor and motor starter under all conditions of operation. When required, the motor control equipment shall provide overload protection of either the thermal or electromagnetic relay type and low-voltage protection with automatic or electromagnetic relay type and low-voltage protection with automatic and manual reset provisions. When air receivers are supplied an automatic pressure release device shall be provided to automatically unload the compressor upon shut-down and protect the unit from starting against pressure. Gasoline-engine drive units, shall be equipped with an adjustable, pressure actuated, mechanical control to permit the engine to run at constant speed during unloaded periods.

3.9 Power.

3.9.1 Electric motor - style A. Style A compressor motors shall either be open type subject to an allowable temperature rise of 40 degrees Celsius (^{o}C), or totally enclosed, subject to an allowable temperature rise of

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

55°C, and shall have the electrical characteristics specified (see 6.2). Motors shall be rated for continuous duty, and shall have minimum horsepower (hp) ratings of 1/3, 1/2, 1, 3, 7-1/2, and 20 for sizes 1, 1A, 1B, 2, 3, and 4 respectively. The hp ratings shall be adequate for operation of the compressors at full load without exceeding the maximum specified temperature rise.

3.9.2 Engine - style B. The style B compressor engine shall be an air-cooled, 4-cycle type gasoline engine, having hp, torque, and speed characteristics to satisfactorily meet all performance requirements specified herein. When specified (see 6.2), the gasoline engine shall be furnished by the Government. Gasoline engines shall include a fuel tank of sufficient capacity for not less than 4 hours of operation. Unless otherwise specified (see 6.2), an electric cranking system with a 5-ampere generator shall be supplied for the size 3 and size 4 compressors. When specified (see 6.2), a clutch shall be supplied and installed by the contractor for the sizes 2, 3, and 4 compressors.

3.10 Accessories. When specified (see 6.2), compressor units shall be furnished with a receiver and pressure gage.

3.10.1 Receivers. Unless otherwise specified (see 6.2), air receivers shall be not less than 7-1/2 gallons for size 1, 1A, or 1B compressors, not less than 60 gallons for size 2 compressors, not less than 80 gallons for size 3 compressors, and not less than 120 gallons for size 4 compressors. When wheel mountings are specified for gasoline-engine driven compressors, the size of the receiver shall be as specified (see 6.2). The receivers shall be constructed in accordance with the ASME Code for Pressure Vessels, section VIII, division 1. Receivers shall be designed for a maximum allowable working pressure at least 10 psi, more than the specified maximum working pressure of the compressor for which the receiver is furnished. Receivers shall be fitted with a safety valve designed and rated to prevent receiver pressure from rising more than 10 percent above the maximum allowable working pressure of the receiver. The receiver shall also be fitted with a drain valve, inspection ports (when required by the ASME Code) and a stand for mounting the receiver. The receiver shall be mounted in a vertical or horizontal position at the option of the contractor unless either position is definitely specified (see 6.2). Unless otherwise specified (see 6.2), a pulsation chamber sized to minimize pressure surges shall be provided when an air receiver is not furnished. The pulsation chambers shall be capable of withstanding 80 psi for size 1 units and 100 psi for sizes 1A, 1B, 2, 3, and 4. The pulsation chamber shall be fitted with a drain cock and safety valve. The safety valve may be located on the chamber or between the chamber and the compressor. The valve shall be set to relieve size 1 units at 80 psi and sizes 1a, 1b, 2, 3, and 4 at 100 psi.

3.10.2 Gage. A dial gage ranging from 0 to 200 psi shall be provided to indicate the pressure produced. The gage shall be located at the compressor outlet or directly on the receiver, as specified (see 6.2).

3.11 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 psi or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.12 Treatment and painting. Unless otherwise specified (see 6.2), the compressor shall be treated and painted in accordance with the manufacturer's standard practice. All surfaces of the compressor other than corrosion resisting steel shall be protected against corrosion and present a neat appearance.

3.13 Wiring. Wiring on style A compressors shall be complete up to the point of the plug connection for the power supply cord. All wiring and circuit devices shall conform to and be installed in accordance with NFPA No. 70.

3.13.1 Power cord. A hard-service, oil resistant, flexible, power cord, NEMA type S, SO, or SJ, shall be furnished with each style A compressor. When 3-phase motors are furnished, the cord shall be 4-conductor, equipped with two 3-phase, 3-pole, 4-wire grounding type connectors conforming to figure 15-20 of NEMA WD 1, a male connector to one end and a female connector to the other end. The compressor shall be equipped with a matching, weather-proof male connector suitable for exterior applications. When single-phase motors are furnished, the cord shall be 3-conductor, permanently connected to the compressor and shall be equipped with a single-phase, 2-pole, 3-wire grounding type male connector conforming to figure 5-15 of NEMA WD 1. A start-stop switch shall be provided either on the cord or on the compressor.

3.14 Identification marking. Identification shall be permanently and legibly marked directly on the compressor or on a corrosion-resisting metal plate securely attached to the compressor at the source of manufacturer. Identification shall include the manufacturer's model and serial number, name and trademark to be readily identifiable to the manufacturer.

3.15 Valves. Valves for compressors shall be removable for inspection and replacement without the use of special tools.

3.16 Lifting attachments. When specified (see 6.2), permanently affixed attachments that enable the sizes 2, 3, and 4, paint spray compressors to be lifted in the normal travel position shall be provided. Each attachment shall withstand, without damage to any part of the compressor, 2-1/2 times the resultant vertical force imposed when the compressor is suspended by the lifting attachment. Attachments for multiple slings shall be so located that: (a) slings will converge at no more than 19 feet above the lowest extremity of the compressor; and (b) not less than 1-inch clearance will be maintained between the slings and the compressor. The inside diameter of the attachment eye shall be not less than 3 inches.

3.17 Tiedown attachments. Unless otherwise specified (see 6.2), permanently affixed attachments that permit fastening the sizes 2, 3, and 4

Source: https://assist.dla.mil -- Downloaded: 202610-16T22:12Z
Check the source to verify that this is the current version before use.

paint spray compressors to the floor or deck of a transportation medium shall be provided. Each attachment shall withstand, without damage to the compressor, its proportion of the following static loads: 8-G forward, 8-G rearward, 2-1/4 G upward, 1-1/2 G sideward, where G equals cargo weight of the compressor. Attachments shall be rounded and beveled to prevent cutting of the tiedown material. Tiedown attachments may also be used as lifting attachments when such attachments meet the requirements specified in 3.16.

3.18 Workmanship.

3.18.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.18.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.18.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.18.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.18.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-16T22:12Z
Check the source to verify that this is the currentversion before use.

* 4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one compressor when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3, the tests of 4.4, and, when specified, the preproduction pack inspection of 4.5 (see 4.5 and 6.2). The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4.4, and the packaging inspection of 4.5.

4.3 Examination. Each compressor shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests.

4.4.1 Test Conditions. Prior to the tests specified herein which require the compressor(s) to be operated, the unit(s) shall be serviced with oils and greases recommended by the manufacturer for use in ambient temperature at the test location. Batteries used for test purposes shall be supplied by the manufacturer in lieu of the dry charge batteries to be shipped with the unit.

4.4.2 Performance test. The compressor shall be tested to determine capacity and power consumption in accordance with the rules, procedures, and instrumentation specified in the ASME PTC-9. The duration of the test shall be sufficient to record all data required under Report of Test of PTC-9, but in no case shall the test duration be less than 1 hour. Prior to the actual performance test, preliminary tests shall be run, as required, to verify that the compressor and associated systems are in suitable condition, that required speed controls have been properly adjusted, and that gages and instruments are

Source: https://assist.dla.mil -- Downloaded: 202610-16T22:12Z
Check the source to verify that this is the currentversion before use.

functioning properly. Inability of the compressor to meet the performance requirements of this specification or to operate satisfactorily shall be cause for rejection.

4.4.3 Functional test. The air compressor shall be operated continuously for a period of not less than 4 hours for sizes 2, 3, and 4, and 2 hours for sizes 1, 1A, and 1B, during which time a log shall be maintained for the capacity, discharge pressure, and operating speed. For a 1-hour period during the test, the air discharge valve shall be alternately opened and closed so as to operate the compressor through the complete loading cycle (from zero to full rated capaity to zero capacity) not less than once every 5 minutes. The compressor shall operate at zero capacity for not more than 1 minute between cycles. Cycling operation for style B units shall be observed to determine if, when the air discharge valve is closed, the engine speed reduces from full-rated-capacity speed to an idle speed not greater than that recommended by the engine manufacturer. Failure of the compressor to meet the performance requirements of 3.6 or malfunction or failure of any parts, components, or controls shall be cause for rejection.

4.4.4 Operational test. Each compressor, excluding first article samples and initial production units, shall be tested for a period of not less than 15 minutes to verify satisfactory operation of the compressor and all controls. During the test all necessary adjustments in controls shall be made as required to insure that performance requirements relating to compressor output and regulation and engine speeds will be met.

4.5 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-C-3600. The inspection shall consist of the quality conformance inspection; and, when specified (sec 6.2), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2).

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-C-3600 with the level of preservation and the level of packing as specified (see 6.2).

6. NOTES

6.1 Intended use. The compressors are intended as portable sources of compressed air for paint spray outfits. Each compressor with driver is a self-contained unit readily movable and suitable for field service.

* 6.2 Ordering data. Aquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type, styles, and size required (see 1.2), and group if either a single or multistage compressor is required (see 1.2 and 3.7.1).
c. Specifications and standards (see 2.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

d. When a first article is required for inspection and approval (see 3.2, 4.2.1, and 6.4).
e. When wheel mounting is required and whether wheelbarrow or cart mounting shall be furnished (see 3.5).
f. When direct drive is required on size 1 compressor (see 3.7).
g. When explosion proof is required (see 3.7).
h. When single-stage or multistage only is required for sizes 2, 3, or 4 (see 3.7.1).
i. Whether the motor shall be of the open type or totally enclosed and electrical characteristics required (alternating current or direct current voltage, frequency, single or 3-phase) (see 3.9.1).
j. When engine is to be Government-furnished (see 3.9.2).
k. When an electric cranking system with a 5-ampere generator will not be supplied for the size 3 or size 4 compressor (see 3.9.2).
l. When a clutch is required for size 2, 3, or 4 compressors (see 3.9.2).
m. When a receiver and gage are required (see 3.10, 3.10.1, and 3.10.2).
n. Size of receivers for wheel-mounted, style B units; when either horizontal or vertical mounting for receivers is required (see 3.10.1).
o. When a pulsation chamber is not required for compressors being furnished without receivers (i.e., if compressor is procured for use with an existing receiver) (see 3.10.1).
p. Location of pressure gage, when furnished (see 3.10.2).
q. When means for lubrication shall be other than the manufactures standard practice (see 3.11).
r. When painting shall be other than manufacturer's standard (see 3.12).
s. When lifting attachments are required (see 3.16).
t. When permanently affixed tiedown attachments are not required for sizes 2, 3, and 4 compressors (see 3.17).
u. When a first article pack inspection is required and time frame required for submission (see 4.2.1 and 4.5).
v. Level of preservation and level of packing required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 Contract Data Requirements List (CDRL) and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

* 6.4 First article. When a first article inspection is required (see 3.2 and 6.2), the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one complete unit. The contracting officer should include specific instructions in acquisition

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

documents regarding arrangements for examination, test, and approval of the first article.

* 6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Navy - YD

Preparing activity:

Navy - YD

(Project 4310-0167)

Review activities:

Army - ME
DLA - CS

User activities:

Army - AR, CE
Navy - MC, CG

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:12Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Facilities Engineering Command (04M2)
200 Stovall Street
Alexandria, VA 22332

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer, (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 202610-16T22:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-3925G	COMPRESSORS, RECIPROCATING, ROTARY AND DIAPHRAGM POWER DRIVEN, AIR, (PAINT SPRAY TYPE)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T22:12Z
Check the source to verify that this is the current version before use.