INCH-POUND


MIL-DTL-3922/67C
22 June 2004
SUPERSEDING
MIL-F-3922/67B
17 December 1975

DETAIL SPECIFICATION SHEET

FLANGES, WAVEGUIDE (CONTACT) (ROUND, 4 HOLE) (MILLIMETER)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the flanges described herein shall consist of this specification sheet and MIL-DTL-3922.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are for general information only (1 inch = 25.4 mm).
3. This requirement is not applicable to dash numbers 001, 002, or 003.
4. See table I for lettered dimensions.

Inches	mm
.001	0.03
.002	0.05
.004	0.10
.005	0.13
.006	0.15
.010	0.25
.030	0.76
.112	2.84
.140	3.56

FIGURE 1. Flange.


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.

TABLE I. Flange dimensions.

PIN M3922/67-			PIN M3922/67-			Dimensions 1/								
Dash no. 2/	Used with		Dash no. 3/	Used with		A +.002 (+ 0.05) -.000	B +.002 (+ 0.05) -.000	C + 0.00 -.002 (- 0.05)	D ± .005 (± 0.13)	E ± .005 (± 0.13)	F BSC	G ± .005 (±0.13)	H ± .005 (±0.13)	J
	Waveguide	Mating flange		Waveguide	Mating flange									
001	M85/3-010 (RG-97/U), 011, 012 (RG-272/U)	M3922/67-001	---	---	---	.309 (7.85)	.197 (5.00)	1.125 (28.58)	.406 (10.31)	.406 (10.31)	.9375 (23.812)	.268 (6.81)	.042 (1.07)	.156 (3.96) ±.005 (0.13)
002	M85/3-017(RG-98/U), 018, 019 (RG-273/U)	M3922/67-002	---	---	---	.233 (5.92)	.159 (4.04)	.750 (19.05)	.328 (8.33)	.328 (8.33)	.5625 (14.288)	.268 (6.81)	.030 (0.76)	.156 (3.96) ±.005 (0.13)
003	M85/3-020(RG-99/U), 021, 022 (RG-274/U)	M3922/67-003	---	---	---	.207 (5.26)	.146 (3.71)	.750 (19.05)	.296 (7.52)	.296 (7.52)	.5625 (14.288)	.268 (6.81)	.030 (0.76)	.156 (3.96) ±.005 (0.13)
004	M85/1-100,102(RG-53/U), 106 (RG-66/U)	M3922/67-004	011	M85/1-103 (RG-121/U), 104	M3922/67-011	.502 (12.75)	.252 (6.40)	1.125 (28.58)	.625 (15.88)	.625 (15.88)	.9375 (23.812)	.250 (6.35)	.032 (0.81)	.160 (4.06) +.005 (.13) -.002 (.05)
005	M85/3-006(RG-96/U), 007, 008 (RG-271/U)	M3922/67-005	012	M85/3-009	M3922/67-012	.362 (9.19)	.222 (5.64)	1.125 (28.58)	.500 (12.70)	.468 (11.89)	.9375 (23.812)	.250 (6.35)	.032 (0.81)	.160 (4.06) +.005 (.13) -.002 (.05)
006	M85/3-010(RG-97/U), 011, 012 (RG-272/U)	M3922/67-006	013	M85/3-013	M3922/67-013	.306 (7.77)	.194 (4.93)	1.125 (28.58)	.500 (12.70)	.468 (11.89)	.9375 (23.812)	.250 (6.35)	.032 (0.81)	.160 (4.06) +.005 (.13) -.002 (.05)
007	M85/3-014, 015, 016 (RG-358/U)	M3922/67-007	---	---	---	.270 (6.86)	.176 (4.47)	1.125 (28.58)	.500 (12.70)	.468 (11.89)	.9375 (23.812)	.250 (6.35)	.032 (0.81)	.160 (4.06) +.005 (.13) -.002 (.05)
008	M85/3-017 (RG-98/U), 018, 019 (RG-273/U)	M3922/67-008	---	---	---	.230 (5.84)	.156 (3.96)	.750 (19.05)	.375 (9.53)	.312 (7.92)	.5625 (14.288)	.250 (6.35)	.032 (0.81)	.160 (4.06) +.005 (.13) -.002 (.05)
009	M85/3-020 (RG-99/U), 021, 022 (RG-274/U)	M3922/67-009	---	---	---	.204 (5.18)	.143 (3.63)	.750 (19.05)	.375 (9.53)	.312 (7.92)	.5625 (14.288)	.250 (6.35)	.032 (0.81)	.160 (4.06) +.005 (.13) -.002 (.05)
010	M85/3-023, 024, 025 (RG-359/U)	M3922/67-010	---	---	---	.182 (4.62)	.132 (3.35))	.750 (19.05)	.375 (9.53)	.312 (7.92)	.5625 (14.288)	.250 (6.35)	.032 (0.81)	.160 (4.06) +.005 (.13) -.002 (.05)

1/ Metric equivalents are in parentheses.
2/ Material shall be copper alloy.
3/ Material shall be aluminum alloy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.



Inches	mm
.002	0.05
.005	0.13
.010	0.25
.078	1.98
.110	2.79
.112	2.84
.180	4.57
.300	7.62
.400	10.16

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are for general information only (1.00 inch = 25.4 mm).

FIGURE 2. Socket-head cap screw.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Material:

Flange: See table I.

Cap screw: Corrosion resistant steel in accordance with SAE-AMS-QQ-S-763, type 302 or 304.

Marking: See figure 1.

Part or Identifying Number (PIN): M3922/67-(dash number from table I).


Material supplied with flange: Four socket-head cap screws as specified in figure 2.

ENGINEERING INFORMATION:

Finished flange and waveguide assembly (dash numbers 004 through 013 only). See figure 3 and table II.

Cross reference and supersession data, frequency range, and return loss data: See table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm
.0005	0.013	.015	0.38	.130	3.30
.001	0.03	.030	0.76	.140	3.56
.002	0.05	.0595	1.571	.156	3.96
.003	0.08	.0615	1.562	.160	4.06
.004	0.10	.067	1.70	.250	6.35
.005	0.13	.112	2.84	.312	7.92

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only based upon 1.00 inch = 25.4 mm.
3. See table II for lettered dimensions.

FIGURE 3. Finished flange and waveguide assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.

TABLE II. Finished flange and waveguide assembly dimensions (004 through 013 only).

PIN M3922/67-	Dimensions 1/					
	K ±.0015 (0.038)	L ±.0015 (0.038)	M +.000 -.002 -0.05	N BSC	T ±.005 (0.13)	U ±.005 (0.13)
004, 011	.4200 (10.668)	.1700 (4.318)	1.125 (28.58)	.9375 (23.812)	.625 (15.88)	.625 (15.88)
005, 012	.2800 (7.112)	.1400 (3.556)	1.125 (28.58)	.9375 (23.812)	.500 (12.70)	.468 (11.89)
006, 013	.2240 (5.690)	.1120 (2.845)	1.125 (28.58)	.9375 (23.812)	.500 (12.70)	.468 (11.89)
007	.1880 (4.775)	.0940 (2.388))	1.125 (28.58)	.9375 (23.812)	.500 (12.70)	.468 (11.89)
008	.1480 (3.759)	.0740 (1.880)	.750 (19.05)	.5625 (14.288)	.375 (9.53)	.312 (7.92)
009	.1220 (3.099)	.0610 (1.549)	.750 (19.05)	.5625 (14.288)	.375 (9.53)	.312 (7.92)
010	.1000 (2.540)	.0500 (1.270)	.750 (19.05)	.5625 (14.288)	.375 (9.53)	.312 (7.92)

1/ Metric equivalents are in parentheses.

TABLE III. Suggested frequency range, cross reference, supersession data, and return loss data.

PIN M3922/67-	AN nomenclature	Frequency range	Worst case return loss (dB)	
			Lowest frequency	Highest frequency
		GHz		
001	UG-383/U	33.0 - 50.0	-29.6	-36.3
002	UG-385/U	50.0 - 75.0	-22.4	-28.9
003	UG-387/U	60.0 - 90.0	-18.8	-25.4
004	---	18.0 - 26.5	-55.1	-61.2
005	---	26.5 - 40.0	-48.7	-54.2
006 1/	---	33.0 - 50.0	-43.7	-50.3
007 2/	---	40.0 - 60.0	-41.4	-47.4
008	---	50.0 - 75.0	-36.5	-43.0
009	---	60.0 - 90.0	-32.9	-39.5
010	---	75.0 - 110.0	-30.1	-36.1
011	---	18.0 - 26.5	-55.1	-61.2
012	---	26.5 - 40.0	-48.7	-54.2
013	---	33.0 - 50.0	-43.7	-50.3

1/ Supersedes M3922/65-001.
2/ Supersedes M3922/65-002.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.

NOTES:

References. In addition to MIL-DTL-3922, this specification sheet also references: MIL-DTL-85/1, SAE-AMS-QQ-S-763 and MIL-DTL-85/3

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5985-1261-01)

Review activities:
Army - AR, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.