
MILITARY SPECIFICATION SHEET

FLANGES, WAVEGUIDE (MINIATURE, UNPRESSURIZED CONTACT)

(4 HOLE AND 8 HOLE)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The complete requirements for procuring the flanges described herein shall consist of this document and the latest issue of Specification MIL-F-3922.



INCHES	MM
.001	03
.003	.08
.004	.10
.015	.38
.125	3 18
.250	6.35

NOTES.
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Roughness of mating surfaces shall not exceed 63 microinches in accordance with ANSI - B46 1 - 1962, except that flaws shall be included in the roughness height measurement
4 For lettered dimensions, see table I

FIGURE 1 Flange configuration for part numbers 001 through 008.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.


TABLE I. Dash numbers and dimensions.

Part No. M3922/63-						Dimensions 1/				
	Used with			Used with						
Dash No. 2/	Waveguide M85/1-	Mating flange M3922/63-	Dash No. 3/	Waveguide M85/1-	Mating flange M3922/63-	A	B	C	D BSC.	E BSC.
001	051 055	001	005	053 054 174	005	2.002 ±.003 (50.85) (.08)	1.002 ±.003 (25.45) (.08)	2.781 ±.015 (70.64) (.38)	.468 (11.89)	.715 (18.16)
002	063 067	002	006	065 066 176	006	1.503 ±.003 (38.18) (.08)	.753 ±.003 (19.13) (.08)	2.281 ±.015 (57.94) (.38)	.343 (8.71)	.590 (14.99)
003	069 073	003	007	071 072 177	007	1.253 ±.003 (31.83) (.08)	.628 ±.003 (15.95) (.08)	2.016 ±.015 (51.21) (.38)	.280 (7.11)	.517 (13.13)
004	075 079	004	008	077 078 178	008	1.003 ±.003 (25.48) (.08)	.502 ±.003 (12.75) (.08)	1.766 ±.015 (44.86) (.38)	.225 (5.72)	.455 (11.56)
009	107 109	009	010	110 111 183	010	.425 ±.001 (10.80) (.03)	.255 ±.001 (6.48) (.03)	.875 ±.005 (22.23) (.13)	.335 (8.51)	.320 (8.13)

Dash No. 2/	Dash No. 3/	F BSC.	G BSC.	H Max	J	K ±.015 (.38)	P +.003 (.08) -.002 (.05)	Q
001	005	.405 (10.29)	.810 (20.57)	.010 (.25)	.225 ±.025 (5.72) (.64)	.892 (22.66)	.147 (3.73)	(No. 6) .138-32 UNC-2B
002	006	.322 (8.18)	.643 (16.33)	.010 (.25)	.225 ±.025 (5.72) (.64)	.767 (19.48)	.147 (3.73)	(No. 6) .138-32 UNC-2B
003	007	.277 (7.04)	.553 (14.05)	.010 (.25)	.225 ±.025 (5.72) (.64)	.694 (17.63)	.147 (3.73)	(No. 6) .138-32 UNC-2B
004	008	.235 (5.97)	.470 (11.94)	.010 (.25)	.225 ±.025 (5.72) (.64)	.632 (16.05)	.147 (3.73)	(No. 6) .138-32 UNC-2B
009	010	---	---	---	.187 ±.005 (4.75) (.13)	---	---	---

1/ Metric equivalents are in parentheses.
2/ Copper alloy.
3/ Aluminum alloy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM
.001	03	.046	1.17
002	.05	.112	2 84
004	10	.116	2 95
005	.13	.125	3.18
.016	.41	.138	3.51
025	.64	.187	4 75
031	.79	.50	12.70

NOTES
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm
3. These surfaces to be parallel within .0005 (.01 mm) to facilitate the use of quick disconnect couplings covered by MIL-C-39004
4. Roughness of mating surfaces shall not exceed 63 microinches in accordance with ANSI - B46.1 - 1962, except that flaws shall be included in the roughness height measurement.
5. For lettered dimensions, see table I.

FIGURE 2. Flange configuration for part numbers 009 and 010.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration: See figures 1 and 2, and table I.

Material. Metallic alloy as specified in table I.

Marking. See figures 1 and 2.
Part number. M3922/63- (and dash number from table I).

Items supplied with flange: See table II.

TABLE II. Items supplied with flange.

Item	M3922/63-001, 002, 003, 004, 005, 006, 007, 008	M3922/63-009, 010
Hex head cap screw	(No 6) 138-32 UNC-2A .50 inch long (4 EACH)	(No. 4) .112-40 UNC-2A .50 inch long (2 EACH)
Hex nut	(No 6) .138-32 UNC-2B (4 EACH)	(No. 4) .112-40 UNC-2B (2 EACH)
Spring lockwasher	.138 x .031 (4 EACH)	.112 x .025 (2 EACH)

TABLE III Cross-reference of part numbers/AN nomenclature and engineering data.

Part No M3922/ 63	AN nomenclature	Frequency range
		GHz
001	UG-1475/U	3 95 - 5 85
002	UG-1476/U	5.85 - 8.20
003	UG-1477/U	7.05 -10.0
004	UG-1478/U	8.20 -12.40
005	UG-1480/U	3.95 - 5.85
006	UG-1481/U	5.85 - 8 20
007	UG-1482/U	7.05 -10.0
008	UG-1483/U	8.20 -12.40
009	UG-1530/U	22.0 -33.0
010	---	22.0 -33.0

Custodians
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - MI, MU, SG, EL
Navy - None
Air Force - 11, 85, 80
DSA - ES

User activities.
Army - AV
Navy - AS, OS, MC, SH, CG
Air Force - 14, 19

Preparing activity
Navy - EC

Agent
DSA - ES

(Project 5985-0822-3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commander
Naval Electronic Systems Command
Defense Standardization Program Branch
Department of the Navy
Washington DC 20360

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation.

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:08Z
Check the source to verify that this is the current version before use.