FEDERAL SPECIFICATION

BEDSPREAD, COTTON OR COTTON/RAYON BLEND

This amendment which forms a part of Federal Specification DDD–B–151e, dated January 25, 1966, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Paragraph 1.2, second line—delete "types and sizes" and substitute "types, styles, and sizes".

PAGE 2

Table I—delete "Type IV Corded" in its entirety, and substitute the following:

Type	Size of finished bedspread (after laundering)	Weight of finished bedspreads	Minimum		Minimum	
	Minimum	Minimum	Warp	Filling	Warp	Filling
	Inches	Ounces			Pounds	Pounds
IV Corded						
Style A						
Bedspreads with four square cut corners.						
Size 1	63 by 103	38.0	65	32	85	70
Size 2	76 by 103	46.0	including			
Size 3	76 by 113	49.0	the cotton			
Size 4	90 by 113	57.0	cords			
Style B						
Bedspreads with two square cut corners at one end, and two round corners at the opposite end.						
Size 1	63 by 103	37.0	65	32	85	70
Size 2	76 by 103	45.0	including			
Size 3	76 by 113	48.0	the cotton			
Size 4	90 by 113	56.0	cords			

PAGE 3

Paragraph 3.4, second sentence—delete in its entirety and substitute: "The ends of the bedspread shall be hemmed. The four corners of the bedspread shall be square cut, except for type IV bedspreads, which shall have either four square cut corners, or two square cut corners at one end, and two round corners at the opposite end (see table I and 6.2)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.

Paragraph 3.4.2—delete in its entirety and substitute:

"3.4.2 Hems. The finished hems for the four square cut corner bedspreads shall be not less than ¾ inch wide, with the raw edges turned under not less than ¼ inch, using stitch type EFb–1. The finished hems for bedspreads with two square cut corners at one end and two round corners at the opposite end shall be not less than 5/16 inch wide, with the raw edges turned under not less than 3/16 inch, using stitch type EFb–1. All hems shall be stitched with not less than 5, nor more than 8 stitches per inch, using stitch type 301. The stitching shall be 1/16 to ⅛ inch from the turned edge. Selvages shall be straight woven and not hemmed."

PAGE 4

Paragraph 3.7.4—add the following subparagraph:

"3.7.4.3 Round corners. When specified (see 6.2), the round corners for style B bedspreads shall be made as follows: An arc 20 inches in radius shall be swung from the midpoint of the intersection of two straight lines of a 20-inch square, formed at the corners to be shaped round."

PAGE 5

Paragraph 4.3.2.1.1—under "Hem" after "¼ inch" add "(except for type IV, style B)"; also, insert the following:

"Varies in width by more than ⅛ inch for type IV, style B"; also, add "X" under "Classification —Minor" for the defect.

PAGE 6

Paragraph 4.3.2.3—under "Defect" for "Hem" and "Turn under" delete:

"Less than ¾ inch" and "Less than ¼ inch," and substitute: "Less than specified" for each.

PAGE 8

Paragraph 5.2.1.1, line 2—after "type", insert "style".

PAGE 9

Paragraph 5.2.2.1, line 2—after "type", insert "style".

Table V, type I—under "Total number of items in each shipping container" delete "30", and substitute "32".

PAGE 10

Paragraph 6.2—Add the following subparagraph:

"(k) Whether style A or style B shall be specified for type IV bedspreads (see 3.4 and table I)."

CUSTODIANS:
Navy—SA
Air Force—82

Review activities:
Navy—MS
Air Force—82, 85
Defense Supply Agency—DM

User activities:
Navy—MS, CG, YD

Preparing activity:
Navy—SA

CIVIL AGENCIES INTEREST:
HEW
COM
VA
GSA
FAA

Review and user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DOD Standardization Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.