FEDERAL SPECIFICATION


NAILS, BRADS, STAPLES AND SPIKES:
WIRE, CUT AND WROUGHT

This amendment, which forms a part of Federal Specification FF-N-105B, dated March 17, 1971, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 9

Add the following new paragraph:

3.6.5.1 Type II, style 4 - Box nails. Steel wire, flat head, diamond point, round smooth shank, cement coated.



S	L	D	H	NO./LB	S	L	D	H	NO./LB
2d	1	0.058	0.172	1,252	7d	2-1/8	0.086	0.250	280
3d	1-1/8	.062	.188	978	8d	2-3/8	.099	.266	190
4d	1-3/8	.067	.203	680	9d	2-5/8	.099	.266	172
5d	1-5/8	.072	.219	510	10d	2-7/8	.113	.297	119
6d	1-7/8	.086	.250	315					

PAGE 11

Paragraph 3.6.11.1: Delete in its entirety and substitute the following:

3.6.11.1 Type II, style 10-Common nails. Copper wire, flat head, diamond point, round smooth shank.

L	D	H	NO./LB	L	D	H	NO./LB
5/8	0.065	0.156	1,380	2	0.120	0.266	130
3/4	.065	.156	1,160	2	.134	.281	106
3/4	.072	.172	956	2-1/2	.134	.281	86
7/8	.072	.172	808	3	.148	.312	56
1	.072	.172	704	3-1/2	.165	.344	40
1-1/4	.083	.203	424	4	.203	.406	23
1-1/2	.109	.250	208	4-1/2	.220	.438	18
1-3/4	.109	.250	180	5	.238	.469	14
1-3/4	.120	.266	144	6	.284	.531	8

Source: https://assist.dla.mil -- Downloaded: 20260-26111:442
Check the source to verify that this is the current version before use.

Add the following to Table IV-B:

CROWN WIDTH	0.435 ± .015				0.180 ± .015			
WIRE** SIZE	0.020T X .030W		0.020T X .040W		0.020T X .030W		0.020T X .040W	
LEG LENGTH	3/16 1/4 5/16 3/8 1/2	+1/32 -1/64	1/4 5/16 3/8 1/2	+1/32 -1/64	3/8 1/2 9/16 5/8 3/4 7/8	+1/32 -1/64	3/8 1/2 9/16 5/8 3/4 7/8 1 1-1/8	+1/32 -1/64

MILITARY CUSTODIANS:
Army - WC
Navy - YD
Air Force - 82

Reviewer activities:
Army - GL
Navy - SA
Air Force - None
DSA - IS, GS
NSA

User activities:
Army - AV, CE, ME, MI
Navy - AS, MC, SH
Air Force - None

Preparing activity:
Army - WC

CIVIL AGENCIES INTEREST:
GSA
DC
JUS
AGR

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.